



**PUBLIC AGENDA
EXECUTIVE COMMITTEE**

**Wednesday, February 11, 2015, 1:00 p.m.
Council Chamber, City Hall**

Pages

1. CALL TO ORDER
2. CONFIRMATION OF AGENDA
3. DECLARATION OF PECUNIARY INTEREST
4. ADOPTION OF MINUTES
 - 4.1 Minutes of regular meeting of Executive Committee held on January 19, 2015.
5. UNFINISHED BUSINESS
6. COMMUNICATIONS (requiring the direction of the Committee)
 - 6.1 Delegated Authority Matters
 - 6.1.1 Brent Penner, Executive Director, The Partnership - Board Members Resignation and Current Composition (File No. CK. 175-48) 4 - 4

Recommendation
That the information be received.
 - 6.2 Matters Requiring Direction
 - 6.2.1 Darlene Walker, Executive Assistant, Mendel Art Gallery - Notice of Annual General Meeting - The Saskatoon Gallery and Conservatory Corporation (File No. CK. 175-27) 5 - 6

Recommendation
That the City of Saskatoon, being a member of The Saskatoon Gallery and Conservatory Corporation, appoint Donald Atchison, or in his absence, Tiffany Paulsen or Charlie Clark of the City of Saskatoon, in the Province of Saskatchewan, as its proxy to vote for it on its behalf at the Annual General Meeting of the members of The Saskatoon Gallery and Conservatory Corporation, to be held on the 17th day of March, 2015, or at any adjournment or adjournments thereof.

6.2.2	Darlene Walker, Executive Assistant, Mendel Art Gallery - Notice of Annual General Meeting - The Art Gallery of Saskatchewan Inc. (File No. CK. 175-27)	7 - 8
--------------	--	--------------

Recommendation

That the City of Saskatoon, being a member of The Art Gallery of Saskatchewan Inc., appoint Donald Atchison, or in his absence, Tiffany Paulsen or Charlie Clark of the City of Saskatoon, in the Province of Saskatchewan, as its proxy to vote for it on its behalf at the Annual General Meeting of the members of The Art Gallery of Saskatchewan Inc., to be held on the 17th day of March, 2015, or at any adjournments or adjournments thereof.

6.3 Requests to Speak (new matters)

7. REPORTS FROM ADMINISTRATION

7.1 Delegated Authority Matters

7.1.1	River Landing Parkade Update (File No. CK. 620-5)	9 - 11
--------------	--	---------------

Recommendation

That the information be received.

7.1.2	Remai Modern Art Gallery of Saskatchewan Update	12 - 14
--------------	--	----------------

Recommendation

That the information be received.

7.2 Matters Requiring Direction

7.2.1	Strategic Plan: Proposed Performance Measures and Targets (File No. CK. 116-1)	15 - 101
--------------	---	-----------------

Recommendation

That the report of the General Manager, Corporate Performance Department dated February 11, 2015, be forwarded to City Council recommending:

1. That the information be received; and
2. That the Administration proceed with public engagement and consultation on the performance targets as outlined in the report of the General Manager, Corporate Performance Department dated February 11, 2015.

7.2.2	Nutana Slope Stability Update (File No. CK. 4000-1)	102 - 418
--------------	--	------------------

Recommendation

That the report of the General Manager, Transportation and Utilities Department dated February 11, 2015, be forwarded to City Council for information.

8. LEGISLATIVE REPORTS


8.1 Delegated Authority Matters

8.2 Matters Requiring Direction

9. URGENT BUSINESS

10. ADJOURNMENT

To: Sproule, Joanne (Clerks)
Subject: RE: Board Member Resignation - The Partnership



From: Brent Penner [mailto:ed@downtownsaskatoon.com]
Sent: Wednesday, January 14, 2015 9:27 AM
To: Sproule, Joanne (Clerks)
Subject: Board Member Resignation - The Partnership

Hi Joanne,

At the January 13, 2015 Board of Management Meeting for The Partnership, Mr. Shea Ferster announced he was resigning from the Board. Mr. Ferster was a past Chair of the Board and served the Downtown Business Improvement District since June, 2004.

I anticipate the Board will look to fill his vacancy in the coming months. Currently, the composition of the Board of Management includes the following people with the year they joined the Board listed after their name:


- Mr. Dave Denny, Chair (2008)
- Mr. Chris Ryder (2012)
- Ms. Roxanne Woodley (2012)
- Mr. Derrek Fahl (2012)
- Mr. Chris Beavis (2013)
- Ms. Tamara Bowman (2013)
- Ms. Jacqueline Gallagher (2013)
- Ms. Della Keen (2013) & Mr. Terry Napper (2013) – shared position
- Mr. Kevin Johnson (2015)
- Councillor Troy Davies (2015)

Please let me know if you require any additional information.

Thanks,

Brent

Brent Penner | Executive Director
The Partnership | Saskatoon Downtown Business Improvement District
t: 306-664-0709 | f: 306-664-2245
downtownsaskatoon.com | @DowntownStoon | 242 Third Avenue South Saskatoon, SK S7K1L9



February 3, 2015

To: His Worship the Mayor and City Council,
 c/o Office of the City Clerk
 Alain Gaucher, Q.C., Chair
 Darrell Bell
 Cheryl Carver
 Councillor Charlie Clark
 Danielle Favreau
 Lynda Haverstock
 Ineke Knight
 Keitha McClocklin
 Councillor Tiffany Paulsen, Q.C.
 Ken Smith
 Peter Stoicheff
 Alexander Sokalski
 Michelle Wildeman
 Gregory Burke, Executive Director & CEO
 Angie Larson, Director, Finance & Operations
 PricewaterhouseCoopers LLP, Corporate Auditors
 MacPherson Leslie & Tyerman LLP, Corporate Solicitors

From: Darlene Walker, Executive Assistant

**NOTICE OF ANNUAL GENERAL MEETING
 THE SASKATOON GALLERY AND CONSERVATORY CORPORATION**

The Annual General Meeting of the Members of The Saskatoon Gallery and Conservatory Corporation will take place on **Tuesday, March 17, 2015, at 7:00 p.m.** The meeting will be held at the Saskatoon Club, 417 - 21st Street East, Saskatoon.

And further take notice that at this meeting an item of special business dealing with the removal of class members and resignation of trustees appointed by that class will be considered.

The agenda for the meeting is attached.

Please confirm your attendance with Darlene Walker by email dwalker@mendel.ca or phone 975-7669.

Thank you.


AGENDA

**ANNUAL GENERAL MEETING OF THE MEMBERS
THE SASKATOON GALLERY AND CONSERVATORY CORPORATION
Saskatoon Club, 417 – 21st Street East, Saskatoon, SK**

Tuesday, March 17, 2015, at 7:00 a.m.

- I. ROLL CALL
- II. APPOINTMENT OF SECRETARY
- III. NOTICE OF WAIVER OF IRREGULARITIES
- IV. APPROVAL OF AGENDA
- V. APPROVAL OF MINUTES
 - Annual General Meeting – March 25, 2014
 - Special General Meeting – January 7, 2014
 - Special General Meeting – June 17, 2014
- VI. INSTRUMENT OF PROXY
- VII. ANNUAL REPORTS
 1. Annual Report of the Chair & President
 2. Annual Report of the Executive Director & CEO
 3. Annual Report of the Treasurer
 - a. Review and approval of financial statements
- VIII. SPECIAL BUSINESS - REMOVAL OF CLASS MEMBERS AND RESIGNATION OF TRUSTEES APPOINTED BY THAT CLASS
- IX. APPOINTMENT TO BOARD OF TRUSTEES
- X. APPOINTMENT OF AUDITORS
- XI. RECOGNITION OF RETIRING TRUSTEES
- XII. VOTE OF THANKS
- XIII. ADJOURNMENT

February 3, 2015



To: His Worship the Mayor and City Council,
c/o Office of the City Clerk
Alain Gaucher, Q.C., Chair
Darrell Bell
Cheryl Carver
Councillor Charlie Clark
Danielle Favreau
Lynda Haverstock
Ineke Knight
Keitha McClocklin
Councillor Tiffany Paulsen, Q.C.
Ken Smith
Peter Stoicheff
Alexander Sokalski
Michelle Wildeman
Gregory Burke, Executive Director & CEO
Angie Larson, Director, Finance & Operations
PricewaterhouseCoopers LLP, Corporate Auditors
MacPherson Leslie & Tyerman LLP, Corporate Solicitors

From: Darlene Walker, Executive Assistant

**NOTICE OF ANNUAL GENERAL MEETING
THE ART GALLERY OF SASKATCHEWAN INC.**

The Annual General Meeting of the Member of The Art Gallery of Saskatchewan Inc. will take place on **Tuesday, March 17, 2015, at approximately 7:30 p.m. (immediately following adjournment of the Annual General Meeting of The Saskatoon Gallery and Conservatory Corporation)**. The meeting will be held at the Saskatoon Club, 417 - 21st Street East, Saskatoon.

The agenda for the meeting is attached.

Please confirm your attendance with Darlene Walker by email dwalker@mendel.ca or phone 975-7669.

Thank you.

AGENDA

ANNUAL GENERAL MEETING OF THE MEMBERS THE ART GALLERY OF SASKATCHEWAN INC.

Saskatoon Club, 417 - 21st Street East, Saskatoon, SK

Tuesday, March 17, 2015, at approximately 7:30 p.m.

**(immediately following adjournment of the Annual General Meeting of
The Saskatoon Gallery and Conservatory Corporation)**

- I. ROLL CALL
- II. APPOINTMENT OF SECRETARY
- III. NOTICE OF WAIVER OF IRREGULARITIES
- IV. APPROVAL OF AGENDA
- V. APPROVAL OF MINUTES
 - Annual General Meeting - March 25, 2014
 - Special General Meeting - June 17, 2014
- VI. INSTRUMENT OF PROXY
- VII. ANNUAL REPORTS
 1. Annual Report of the Chair & President
 2. Annual Report of the Treasurer
 - a. Review and approval of financial statements
- VIII. APPOINTMENT TO BOARD OF TRUSTEES
- IX. APPOINTMENT OF AUDITORS
- X. APPOINTMENT OF OFFICERS
- X1. ADJOURNMENT

River Landing Parkade Update

Recommendation

That the information be received.

Topic and Purpose

The purpose of this report is to provide the Executive Committee with an update on the River Landing Parkade Project.

Report Highlights

1. Work on the parkade is largely complete.
2. The Contractor is projecting total performance of their work by May 14, 2016, which is the date prescribed by the Contract.
3. The parkade will be available for commissioning by the River Landing Project after total performance of the construction contract.

Strategic Goals

This project supports the Quality of Life Strategic Goal relating to the implementation of the Municipal Culture Plan. It supports the Four Year Priority to enhance the quality of life in Saskatoon by directing expenditures toward amenities in neighbourhoods to enhance and protect property values and encourage private investment.

Background

The construction contract was awarded in March 2013, with a target for completion in 2016.

Report

Construction on the River Landing Parkade is largely complete. The project occupies the same site as the Remai Modern Art Gallery of Saskatchewan. As such, the parkade will be available for commissioning by the River Landing Project after total performance of the entire construction contract.

Financial Implications

Capital Project # 1814 River Landing Parkade has been approved for funding in the amount of \$19,469,000. The budget has not changed since City Council approved the contract award and funding of the project on March 18, 2013.

The funding is made up of the following components:

\$12,100,000 – City Contribution (Mill Rate and Parking Revenue)
\$ 369,000 – Provincial Funding – Building Canada

River Landing Parkade Update

\$ 7,000,000 – City Contribution (Reallocated City Capital Fund, from reassigning fully funded project dollars from other Capital Projects backfilled by other external funding)
\$19,469,000 – Total

In addition to the capital project approved by City Council on March 18, 2013:

- i) Land costs of \$468,000 were excluded from the total project costs as the City would be required to borrow additional funds and pay the River Landing Project who developed and assembled the land.
- ii) That Persephone Theatre funded an additional \$662,577 worth of total construction for the Remai Arts Centre portion of the construction contract part of which is in the Gallery portion of the contract, and part of which is in the parkade portion of the contract.

In addition to the construction costs, land costs and Persephone work, the River Landing Parkade will install a revenue collection system, and will commission, and operate the parkade. Currently, these costs are being planned and estimated in 2015 and will be funded by the River Landing Project as part of their annual operating and capital budgets.

Public and/or Stakeholder Involvement

No public and/or stakeholder involvement would be required.

Communication Plan

All public project reports and updates are being posted to the City's Website.

Environmental Implications

Construction of a parkade will have a negative short and long term GHG impact. The City strives to balance all forms of transportation in the City, and the need for additional downtown parking has been demonstrated.

Other Considerations/Implications

There are no policy, privacy, or CPTED implications.

Due Date for Follow-up and/or Project Completion

The next project update will be brought to the Executive Committee in mid-2015.

Public Notice

Public Notice pursuant to Section 3 of Policy No. C01-021, Public Notice Policy, is not required.

Report Approval

Written by: Mike Gutek, Director of Major Projects
Reviewed by: Mike Gutek, Director of Major Projects

River Landing Parkade Update

Approved by: Jeff Jorgenson, General Manager, Transportation & Utilities
Department

Approved by: Murray Totland, City Manager

Exec MG – River Landing Parkade Update

Remai Modern Art Gallery of Saskatchewan Update

Recommendation

That the information be received.

Topic and Purpose

The purpose of this report is to provide the Executive Committee with an update on the Remai Modern Art Gallery of Saskatchewan (Remai Modern AGS).

Report Highlights

1. The Contractor is projecting total performance of their work by May 14, 2016, which is the date prescribed by the Contract.
2. The Project has had schedule impacts due to the 2013 increased river levels, site soil conditions, the winter temperatures of 2013/14, delay claims associated with structural steel and impacts due to changes and additions.
3. The largest immediate challenge to the project will be for the Contractor to keep the City informed of its completion dates and the status of the work.

Strategic Goals

This project supports the Quality of Life Strategic Goal relating to the implementation of the Municipal Culture Plan. It supports the Four-Year Priority to enhance the quality of life in Saskatoon by directing expenditures toward amenities in neighbourhoods to enhance and protect property values and encourage private investment.

Background

The Remai Modern AGS construction contract was awarded in March 2013, with a target for completion in 2016.

Report

The Contractor is continuing to progress on the gallery construction contract. There have been schedule impacts and the status of their schedule is updated monthly. The Contractor is projecting total performance of their work by May 14, 2016, which is the date prescribed by the Contract. The contractual consequence for failure to meet that date are essentially the City's out of pocket damages.

The contract is being administered by the Architect team hired by the City in June 2010, with overall project oversight provided by the Major Projects division since 2014.

The Remai Modern AGS is planning the move and transition and opening of the gallery which will occur after total performance of the contract.

Financial Implications

Capital Project # 1813 Remai Modern AGS has been approved for funding in the amount of \$81,834,160. This number includes \$1.6 million of deferred items that were added to the project and funded by Gallery fundraising as well as \$6 million approved as part of the 2015 Capital Budget.

The funding is made up of the following components:

\$22,095,160 – Remai Gallery Pre & Post 2013 Fundraising
\$29,487,000 – City Contribution (Borrowing for 25 Years, \$1.3 million annual repayment) and Major Recreational and Cultural Facilities Mill Rate Funding Plan
\$ 488,000 – Remai Board Loan from City for Kitchen Equipment
\$ 4,093,000 – Provincial Funding – Building Communities
\$12,651,000 – Provincial Funding – Building Canada
\$13,020,000 – Federal Funding – Building Canada
\$81,834,160 – Total

In addition to the capital project approved by City Council on March 18, 2013:

- i) Land costs of \$1,890,000 were excluded from the total project costs as the City would be required to borrow additional funds and pay the River Landing Project who developed and assembled the land.
- ii) That Persephone Theater funded an additional \$662,577 of construction for the Remai Arts Centre portion of the construction contract.

In addition to the construction costs, land costs and Persephone work, the Remai Modern Art Gallery is funding transition and implementation costs associated with becoming the Remai Modern AGS. The Gallery has informed the Administration that the \$1.6 million of deferred items have now been funded.

The Remai Modern is also proceeding to industry to obtain a proponent to fit out and run the restaurant and the catering kitchen.

Public and/or Stakeholder Involvement

No public and/or stakeholder involvement would be required.

Communication Plan

All public project reports and updates are being posted to the City's Website.

Environmental Implications

As a LEED® building, the Remai Modern AGS will be designed, constructed and operated to optimize energy efficiency and indoor air quality. Construction and operation will result in the consumption of non-renewable resources and the generation

Remai Modern Art Gallery of Saskatchewan Update

of GHG emissions; however, meeting the performance requirements of LEED® will result in a net decrease in GHG emissions when compared to a non-LEED® building.

Other Considerations/Implications

There are no policy, privacy, or CPTED implications.

Due Date for Follow-up and/or Project Completion

The next project update will be brought to the Executive Committee in mid-2015.

Public Notice

Public Notice pursuant to Section 3 of Policy No. C01-021, Public Notice Policy, is not required.

Report Approval

Written by: Mike Gutek, Director of Major Projects

Reviewed by: Mike Gutek, Director of Major Projects

Approved by: Jeff Jorgenson, General Manager, Transportation & Utilities
Department

Approved by: Murray Totland, City Manager

Exec MG – Remai Modern Art Gallery of Sask Update

Strategic Plan: Proposed Performance Measures and Targets

Recommendation

1. That the information be received; and
2. That the Administration proceed with public engagement and consultation on the performance targets as outlined in this report.

Topic and Purpose

The purpose of this report is to provide information on proposed performance measures and targets for the seven Strategic Goals within the City of Saskatoon (City) *Strategic Plan 2013 – 2023* in an effort to be more accountable, transparent and effective.

Report Highlights

1. Performance measures are a way of monitoring the progress toward achieving the City's Strategic Goals, and providing information to make well-informed decisions that will be reflected in the annual Business Plan and Budget.
2. A consistent process has been used in determining the indicators and targets including trends for Saskatoon and comparative cities, high level benefits and costs, and risks that could impact progress.
3. Citizens and stakeholders are being asked to provide input on the measures. A summary of the consultations will be provided to City Council to use as part of their deliberations when approving the targets and indicators.

Strategic Goal

A robust performance measurement program will contribute to the City's strategic goal of "Continuous Improvement" and becoming the best-managed city in Canada. Clear targets and indicators of success for the City's seven strategic goals will help the City focus efforts on achieving results in areas identified as important, measure progress, and take corrective action as needed.

Background

City Council adopted the Strategic Plan: 2013 - 2023 in 2013 which includes a vision and seven strategic goals, along with Strategies for the Long-Term and Priorities for the Short-Term. The Strategic Plan also outlines Success Drivers and examples of performance measures that could be used. This report is a follow-up to a report to City Council on June 23, 2014 which provided examples of potential performance measures and indicators. The Administration subsequently conducted a more thorough assessment of proposed performance targets and indicators which is presented in the following report.

Report

Performance Measures

Performance measures are a way of monitoring progress toward achieving the City's Strategic Goals and assessing whether investments are achieving results at a corporate or community level. Benefits to having performance measures and targets include:

- providing a communication tool that can contribute to success when used to quantify results and expectations;
- tracking progress toward goals and targets;
- ensuring the Administration is working toward the City's vision;
- providing a balance between risk and controls;
- assisting in managing the work being done throughout the organization;
- leading to overall performance improvement; and
- aligning budget decisions with planning decisions.

Process

The Administration has proposed 19 performance targets to assist in measuring progress toward achieving the City's Vision and the Strategic Goals, based on the following process:

1. Determine what to measure – confirm that the success drivers in the Strategic Plan continue to be what is important for the organization to measure.
 - For example, sufficient, appropriate, and attainable housing is a success driver and something that is important to measure progress toward achieving the Quality of Life Strategic Goal.
2. How to measure – determine the best way of measuring success.
 - For example, the number of new attainable housing units and vacancy rates for rental housing contribute to sufficient, appropriate, and affordable housing.
3. Set targets that are specific, measurable, achievable, realistic, and time-bound.
 - For example, set an annual target of 500 new units across the attainable housing continuum and an average vacancy rate of 3%.

In addition, seven performance indicators of success are proposed as measures which will be regularly monitored for changes in trends.

Attachment 1 provides a summary by Strategic Goal of the indicators and targets. Attachment 2, *Talking about Targets: Measuring the Success of our 2013-2023 Strategic Plan* provides more detailed information on the targets and indicators including Saskatoon trends, benchmarking information where possible, high level benefits and costs, and risks that could impact progress towards each target.

Next Steps

Over the course of the next few weeks, our citizens and stakeholders will be provided with an opportunity to provide input. In the second quarter, the Administration will provide City Council with the results of the public consultations as well as

recommendations for the performance targets and indicators. After City Council approves the performance targets, these targets will be used to inform the annual business plan and budget, and progress will be reported.

Communication Plan

On the *Shaping Saskatoon* website, which will be available mid-February, citizens will be able to view the following:

1. A summary of the proposed indicators and targets
2. Additional information on trends and benchmarks
3. A more detailed report including high level benefits and costs, and risks that could impact progress towards each target

Citizens and stakeholders will be invited to provide feedback on the website about the proposed targets and what is needed to achieve them. The process will be promoted through a public service announcement, City Pages notice, and social media. E-mails inviting feedback also will be sent to the City's advisory committees and stakeholders.

Other Considerations/Implications

There are no policy, financial, environmental, privacy, or CPTED implications or considerations.

Due Date for Follow-up

Results of consultations and recommended targets and indicators will be presented to City Council in second quarter, 2015.

Public Notice

Public Notice pursuant to Section 3 of Policy No. C01-021, Public Notice Policy, is not required.

Attachments

1. Summary of Proposed Indicators and Targets
2. Talking about Targets: Measuring the Success of Our 2013-2023 Strategic Plan

Report Approval

Written by: Angela Schmidt, Performance Measurement Consultant,
Strategic and Business Planning
Reviewed by: Kim Matheson, Director, Strategic and Business Planning
Approved by: Catherine Gryba, General Manager, Corporate Performance
Department
Murray Totland, City Manager

Summary of Proposed Indicators and Targets

City of Saskatoon Strategic Plan 2013-2023

Vision: Saskatoon is a great place to live, where sustainable growth enables the community to invest for the benefit of all.

Strategic Goals	Indicators of Success	Annual Business Plans and Budgets
Continuous Improvement	<ul style="list-style-type: none"> ➤ Satisfaction with Civic Services 	
Asset and Financial Sustainability	<ul style="list-style-type: none"> ➤ Municipal Property Tax Per Capita ➤ Municipal Property Tax as a Percentage of Total Municipal Revenues 	
Quality of Life	<ul style="list-style-type: none"> ➤ Perceived Quality of Life in Saskatoon 	
Sustainable Growth	<ul style="list-style-type: none"> ➤ Population Growth 	
Economic Diversity & Prosperity	<ul style="list-style-type: none"> ➤ Building Activity ➤ Retail Space per Capita 	

City of Saskatoon Strategic Plan 2013-2023

Vision: Saskatoon is a great place to live, where sustainable growth enables the community to invest for the benefit of all.

Strategic Goals	Targets for Success
Continuous Improvement	<ul style="list-style-type: none"> ✓ The City of Saskatoon's workforce represents the diversity of Saskatoon's population ✓ Zero lost time incidents
Asset and Financial Sustainability	<ul style="list-style-type: none"> ✓ Annual municipal property tax increase equal to or less than Municipal Price Index (MPI) ✓ Maximum long-term tax-supported debt per capita of \$1,750 ✓ Maintain key civic infrastructure at annual "B Service Level"
Quality of Life	<ul style="list-style-type: none"> ✓ 500 new units annually across the attainable housing continuum ✓ Maintain an average rental housing vacancy rate of 3% ✓ Increase visits to City recreation & culture facilities to 6,600 visits/1,000 residents ✓ Decrease overall crime rates by 5.0% annually over the previous five-year average ✓ Respond to fire calls within six minutes and 20 seconds at least 90% of the time
Environmental Leadership	<ul style="list-style-type: none"> ✓ Divert 70% of waste from the Saskatoon landfill ✓ Reduce the City of Saskatoon's greenhouse gas emissions by 30% from 2006 levels
Sustainable Growth	<ul style="list-style-type: none"> ✓ At least 25% five-year rolling average of residential development is in infill neighbourhoods ✓ An 8% increase in residential development density within infill neighbourhoods
Moving Around	<ul style="list-style-type: none"> ✓ Increase transit ridership to 62 rides per capita ✓ 20% of people use cycling, walking or transit to get to work ✓ Increase the amount of cycling-specific infrastructure by 10% ✓ Decrease traffic collisions by 5% annually
Economic Diversity & Prosperity	<ul style="list-style-type: none"> ✓ A one-year inventory of land for single family units, a two-year inventory of land for multi-family units and a two-year inventory of industrial land

Annual Business Plans and Budgets

Talking about Targets

Measuring the Success of Our 2013-2023 Strategic Plan

January, 2015



Talking about Targets

Measuring the Success of Our 2013-2023 Strategic Plan

Contents

Introduction	4
Continuous Improvement	8
Overall Satisfaction with Civic Services	9
Workforce Diversity.....	11
Frequency of Lost Time Injuries	16
Asset and Financial Sustainability	19
Municipal Property Tax per Capita	20
Municipal Property Tax as a Percentage of Total Revenues.....	22
Annual Municipal Property Tax Increase.....	24
Long-Term Tax-Supported Debt per Capita.....	26
Key Civic Infrastructure Status	28
Quality of Life	31
Perceived Quality of Life.....	32
Number of New Attainable Housing Units.....	34
Vacancy Rates for Rental Housing	37
Participation Rates for City Recreation and Cultural Facilities	40
Crime Rates	43
Fire Response Time.....	45
Environmental Leadership	48
Waste Diverted From the Landfill	49
Reduction of Greenhouse Gas Emissions	52
Sustainable Growth	55
Population Growth and Rate of Change.....	56
Residential Infill Development	58
Residential Development Density in Established Areas	61
Moving Around.....	64
Transit Rides Per Capita.....	65
Kilometres of Cycling-Specific Infrastructure	68

Transportation Choices..... 70

Traffic Collisions..... 72

Economic Diversity and Prosperity..... 75

Amount and Value of Building Activities..... 76

Retail Space per Capita..... 78

Supply of Residential and Industrial Land..... 80

“Talking about Targets”

Measuring the Success of Our 2013-2023 Strategic Plan

Introduction

The City of Saskatoon’s *Strategic Plan 2013-2023* was developed with the input of more than 10,000 citizens. Seven strategic goals were identified by the community and City Council to realize our vision for the future.

The next step is to set targets which measure our success in achieving each of our goals. Nineteen targets have been proposed as measures of success to guide our programs, policies and investments over the next ten years. Most targets are to be achieved by 2023, some targets are to be achieved annually, and three are longer – term targets.

The following background is provided for the proposed targets (in some cases not all information was available):

- Target description
- How we’ve been doing over the last five years
- How other cities are doing
- What we need to do to achieve our target
- Benefits of achieving our target
- What risks may impact our success in achieving our target

Seven additional indicators are proposed to track progress towards our goals. Trends and comparisons with other cities also are shown for each indicator.

Citizens are being invited to provide comments on the targets and indicators as measures of success. Saskatoon City Council will consider citizens’ feedback when finalizing the targets. Annual business plans and budgets will be developed to align with the targets in support of the City’s strategic goals. On an annual basis, we will report out on how we are progressing towards each target.

A short summary of the targets and indicators follows.

Continuous Improvement

“Overall satisfaction with civic services” is a proposed indicator of citizen perceptions about city services and is measured through the *City of Saskatoon Annual Civic Services Survey*.

“The City of Saskatoon’s workforce represents the diversity of Saskatoon’s population” is proposed as a long-term target. The proposed target measures the percentage of City of Saskatoon employees in four groups: females, Aboriginal people, people with disabilities, and visible minorities.

“Zero lost time incidents” measures our success in making health and safety a top priority. The proposed target is to eliminate incidents and causes of injuries which result in lost time from work.

Asset and Financial Sustainability

“Municipal property tax per capita” is a proposed indicator that tracks the average amount of municipal property tax for each person in Saskatoon.

“Municipal property tax as a percentage of total revenues” is a proposed indicator that will monitor the percentage of property tax paid relative to all revenue collected by the City of Saskatoon.

“Annual municipal property tax increase equal to or less than the Municipal Price Index (MPI)” is a proposed target to keep annual property tax increases less than the annual inflation rate for city costs. The target measures success in controlling costs.

“Maximum long-term tax-supported debt per capita of \$1,750” is a proposed maximum debt level and represents each resident’s average share of the City’s debt. The intent is not to meet the maximum, but to have it in place so the debt remains affordable for taxpayers.

“Maintain key civic infrastructure at annual “B Service Level” is a proposed target to measure success in maintaining our bridges, structures, roads, sidewalks, water, and sewer infrastructure. With a “B Service Level”, the asset condition is “getting better” and the backlog of required maintenance declines slowly.

Quality of Life

“Perceived quality of life” is a proposed indicator of citizen perceptions about well-being in the city. Perceptions are measured through the *City of Saskatoon Annual Civic Services Survey*.

“500 new units annually across the attainable housing continuum” is a proposed target to measure the City’s success in developing a mix of affordable housing for ownership and rental throughout Saskatoon to address basic needs.

“Maintain an average rental housing vacancy rate of 3%” is a proposed target to measure success in maintaining a generally acceptable level of rental accommodation.

“Increase visits to City of Saskatoon recreation and culture facilities to 6,600 visits for every 1,000 residents” is a proposed target to measure our success in growing and maintaining participation in City-owned and managed recreation and culture facilities and programs.

“Decrease overall crime rates by 5.0% annually over the previous five-year average” is a proposed target to measure success in increasing public safety in our homes, on our streets, and in our overall community.

“Respond to fire calls within six minutes and 20 seconds at least 90% of the time” is a proposed target to measure our success in minimizing loss of life and property due to fire.

Environmental Leadership

“Divert 70% of waste from the Saskatoon landfill” measures our success in environmental stewardship. The proposed target means that more of Saskatoon’s waste will be recycled, reused, or composted instead of going to the landfill.

“Reduce the City of Saskatoon’s greenhouse gas emissions by 30% from 2006 levels” is proposed as a target to measure our success as an organization in reducing our impact on climate change by lowering greenhouse gas emissions.

Sustainable Growth

“Population growth and growth rate” are proposed as indicators of sustainable growth. Population growth is a fundamental driver of the City’s business plan and budget planning process.

“At least 25% five-year rolling average of residential development is in infill neighbourhoods” is proposed as a target to measure success in reducing requirements for new infrastructure and ongoing maintenance costs. This target supports the overall strategic direction of many major corporate initiatives.

“An 8% increase in overall residential development density within infill neighbourhoods” is proposed as a target to measure our success in increasing residential density within the established area of the city. This target is a measure of the overall sustainability for urban development.

Moving Around

“Increase transit ridership to 62 rides per capita” is a proposed longer-term target to measure our success in making our transit system a more efficient option for people to move around in Saskatoon.

“Increase the amount of cycling-specific infrastructure by 10%” is a proposed target to measure success in improving the ease with which cyclists move around the city. A 10% increase requires approximately 1.5 km’s of additional cycling infrastructure annually.

“20% of people use cycling, walking or transit to get to work” is a proposed longer-term target to measure our success in significantly increasing the proportion of transit users and cyclists and decreasing the proportion of people who drive to work.

“Decrease traffic collisions by 5% annually” is a proposed target to measure success in increasing public safety on our streets.

Economic Diversity and Prosperity

“The number and value of building permits” are proposed indicators of economic growth and prosperity. Increased investment and construction activity are influenced by our success in creating a business environment with competitive taxes, quality infrastructure, and policies encouraging growth.

“Retail space per capita” is proposed as an indicator of a healthy and diverse economy. The City influences the amount of retail space through city planning and zoning while demand and supply is determined by retailers and the market.

“A one-year inventory of land for single family units, a two-year inventory of land for multi-family units and a two-year inventory of industrial land” are proposed as targets to support building demand. The target includes inventory held by the City and by private sector builders and developers.

Talking about Targets

Continuous Improvement

- Overall Satisfaction with Civic Services
 - Workforce Diversity
 - Frequency of Lost Time Injuries


Overall Satisfaction with Civic Services

Proposed Indicator: “Overall satisfaction with civic services”

Description: “Overall satisfaction with civic services” is an indication of citizen perceptions about city services and is measured through the *City of Saskatoon Annual Civic Services Survey*. The survey asks, “Generally speaking, how satisfied are you with the overall level of services provided by the City of Saskatoon?”

How are we doing?


In 2014, 86% of 500 telephone respondents and 79% of 801 online respondents said they were satisfied or very satisfied with the level of civic services. Average satisfaction increased from 2013 to 2014.



Source: *City of Saskatoon Annual Civic Services Survey*

How are other cities doing?

Surveys indicate that people in Saskatoon are more satisfied with their civic services than people in Regina. Calgary residents are most satisfied with their civic services.



Sources: *The City of Saskatoon Annual Civic Services Survey (2014)* and surveys conducted adapted to comparable format: *City of Regina Citizen Survey Base Report (March 2012)*; *Winnipeg Citizen's Perspective 2013 Citizen Survey*; *The City of Calgary 2013 Citizen Satisfaction Survey*; *City of Edmonton Citizen Perception Survey (Draft Report, 2014)*

Notes: Some cities do not undertake surveys annually. The graph reports the most recent survey results available.

Workforce Diversity


Proposed Long-Term Target: The City of Saskatoon’s workforce represents the diversity of Saskatoon’s population

Description: The workplace diversity target will measure the percentage of City of Saskatoon employees in four groups: females, Aboriginal people, people with disabilities, and visible minorities. The City’s numbers do not include fire, police association, library, or exempt staff from boards. The Saskatchewan Human Rights Commission (SHRC) has identified targets based on 2006 populations in the provincial labour force.


The workforce diversity target measures our success in offering an inclusive workplace that embraces diverse backgrounds under our goal for “Continuous Improvement”.

How are we doing?

In 2014, the City of Saskatoon had a gap in employment of females, Aboriginal people, and people with disabilities relative to SHRC targets.




Sources: City of Saskatoon, Saskatchewan Human Rights Commission, Statistics Canada




Overall, the percentage of City of Saskatoon employees who are members of Equity Groups has been increasing.

Source: City of Saskatoon




Over the last five years, the proportion of female employees has remained relatively constant at 39.5%. Most of the City's female employees work in traditional female jobs and are underrepresented in the management and trades positions. The SHRC goal is for females working in underrepresented occupations.

Sources: City of Saskatoon, Saskatchewan Human Rights Commission, Statistics Canada




Over the last five years, the percentage of the City of Saskatoon's Aboriginal employees has increased. Most Aboriginal employees work in labour and service positions with many of these being seasonal jobs.

Sources: City of Saskatoon, Saskatchewan Human Rights Commission, Statistics Canada



The City has surpassed the SHRC target for visible minority employees. Immigration has brought many more skilled visible minority people to Saskatoon since the SHRC goals were set based on 2006 populations.

Sources: City of Saskatoon, Saskatchewan Human Rights Commission, Statistics Canada



The proportion of self-declared employees with a disability employed by the City increased in 2011 and 2012 but subsequently decreased to close to the 2010 level.

Sources: City of Saskatoon, Saskatchewan Human Rights Commission, Statistics Canada

Current benchmarks with comparative municipalities are not available.

What do we need to do to achieve this target?

- Maintain a dedicated person to manage the diversity programs and policies.
- Maintain a dedicated person to manage Aboriginal affairs and build relationships with Aboriginal communities.
- Increase training opportunities for employees at all levels of the organization to increase intercultural skills.
- Invest in measurement tools such as the Inter-developmental Inventory and the Employee Engagement Survey.
- Improve workplace spaces to increase accessibility for people with disabilities.

What are the benefits of achieving the target?

- A representative workplace draws from a larger labour pool which can result in a variety of skills and experience, cultures and language which represent the clients that the City serves.

What are the risks?

- Using the SHRC goals as the only measure of success has some shortcomings:
 - The goals were last changed in 2006 based on the Statistics Canada census survey and Saskatoon's population has changed significantly since then.
 - Stats Canada notes that "the Aboriginal people may be underrepresented in census surveys."
 - SHRC's are population numbers for ages 15 to 74 and may not reflect those who are working or want to work.
 - SHRC goals specify women in under-represented occupations but do not consider types of jobs for other equity groups.
- City of Saskatoon employment that relies on self-reported information may appear lower if people choose not to self-identify or if their situation changes over time (e.g. some people acquire a disability while employed).
- Competition is strong from other organizations who are recruiting talented employees to meet diversity targets or other employment objectives.
- Expected turnover rates will impact the ability to achieve some SHRC goals within ten years.

Frequency of Lost Time Injuries

Proposed 10 Year Target: Zero lost time incidents


Description: “Lost Time Injury Frequency” (LTIF) measures our success in making health and safety a top priority under our goal for “Continuous Improvement”. The target is to eliminate incidents and causes of injuries which result in lost time from work.

$$\text{LTIF} = \frac{\text{Number of lost time injuries} \times 200,000}{\text{Number of employee labour hours worked}}$$

Note: 200,000 is the base for 100 full-time equivalent workers (working 40 hours per week, 50 weeks per year).

How are we doing?


Lost work time due to injuries relative to the number of hours employees worked has been on a downward trend but increased in 2014.



Source: City of Saskatoon

How are other cities doing?

Saskatoon's lost time is similar to the average lost time in other Saskatchewan municipalities but is higher than the overall Saskatchewan industry average. As the largest municipal employer in the province, Saskatoon's lost time has a significant influence on the average for all Saskatchewan municipalities.



Sources: City of Saskatoon and Workers Compensation Board

What do we need to do to achieve this target?

An integrated Health and Safety Management System is being implemented to make health and safety a top priority. Culture change will be influenced by increasing safety awareness to reduce injuries through:

- Regular safety and toolbox meetings
- Regular Occupational Health and Safety (OHS) Committee meetings
- Inspections
- Incident investigations
- Ergonomic assessments and adaptations
- Enhanced training, particularly for new equipment operators

Over the longer term, safety can be improved through implementing an online health and safety management software system to provide quick collection of more comprehensive information so that timely corrective action can be undertaken to prevent future similar injuries.

What are the benefits of achieving the target?

- Positive impact on employees' personal lives and daily living activities
- Reduced pain and suffering for employees
- Positive impact on productivity and employee morale
- Lower Workers Compensation Board (WCB) rates as expenses associated with medical treatment, rehabilitation, and pension costs for long-term claims are reduced

What are the risks?

- "Lost time" may not be interpreted the same by those reporting on the measure, thereby reducing the value of comparative information.
- Anticipating and preventing all sources of accidental injury may not be achievable or practical in some cases where risk is small. Risk versus benefits need to be considered when making investments.
- Sometimes incidents occur when situations interact in unexpected ways.

Talking about Targets

Asset and Financial Sustainability

- **Municipal Property Tax per Capita**
- **Municipal Property Tax as a Percentage of Total Revenues**
 - **Annual Municipal Property Tax Increase**
 - **Long-Term Tax-Supported Debt per Capita**
 - **Key Civic Infrastructure Status**

Municipal Property Tax per Capita

Proposed Indicator: Municipal Property Tax per Capita


Description: The proposed indicator will track the average amount of municipal property tax for each person in Saskatoon.

$$\text{Municipal Property Tax per Capita} = \frac{\text{Total Municipal Property Taxes}}{\text{Population of Saskatoon}}$$

“Total Municipal Property Taxes” is from the City of Saskatoon’s annual approved budget. The Saskatoon Public Library Tax and the Education Tax are not included in the municipal property taxes. The city’s population is estimated as of December 31 for each year by the City of Saskatoon Planning and Development Division.

How are we doing?

The City of Saskatoon’s municipal property tax per capita has increased over the last five years. The graph below does not include public library or education property taxes.




Sources: City of Saskatoon

Note: Does not include Saskatoon Public Library Tax or Education Tax

How are other cities doing?

The City of Saskatoon's municipal property tax per capita is quite favourable compared to other major cities in Western Canada, partly because more of Saskatoon's budget is funded through other self-generated revenues. The graph below, with comparative numbers published by the City of Calgary, includes library taxes.



Source: City of Calgary *Residential Property Taxes and Utility Charges Survey (2012)*

Note: *The Residential Property Taxes and Utility Charges Survey* does not include education taxes but includes library taxes as part of the municipal property taxes for comparability with jurisdictions that do not charge a separate library levy. The graph does not include additional business taxes applied by Winnipeg (\$82 per capita) and Calgary (\$195 per capita).

Municipal Property Tax as a Percentage of Total Revenues

Proposed Indicator: Municipal Property Tax as a Percentage of Total Revenues


Description: The proposed indicator will monitor the percentage of municipal property taxes paid relative to all revenue collected by the City of Saskatoon:

$$\frac{\text{Total Municipal Property Taxes}}{\text{Total Municipal Revenues}}$$

“Total Municipal Property Taxes” includes the budgeted “property levy”. Some examples of revenue sources included in total municipal revenues are water and power utilities, user fees for recreation and transit, permits and licenses, land development, and interest.

How are we doing?


Currently, the percentage of municipal property tax to total municipal revenues is 43.6%. The percentage of municipal property tax could increase to more than 45% as the City moves towards fully funding approved service levels for core civic services like roads and bridges unless other funding sources are identified.



Source: City of Saskatoon

How are other cities doing?

Comparing other cities is challenging because of differences in how revenues are calculated. While not directly comparable, measures from these municipalities are helpful as representations of municipal property tax as a percentage of total municipal revenue. Currently, the City of Saskatoon's percentage is quite favourable. A contributing factor to this favourable indicator is that the City of Saskatoon has a higher level of self-generated revenues that enables less reliance on property taxes to fund its annual budgets. Saskatoon also may not be funding to the same service level as other cities.



Source: City of Saskatoon *Annual Municipal Operations Benchmark Report*

Notes: The *Annual Municipal Operations Benchmark Report* includes Saskatoon property taxes resulting from supplementary assessment (from properties that are assessed throughout the year, therefore not included in the initial property tax roll). Winnipeg operates its transit as a utility and does not include transit revenues in its total.

Annual Municipal Property Tax Increase


Proposed 10-Year Target: Annual municipal property tax increase equal to or less than the Municipal Price Index (MPI)

Description: The proposed target is to keep annual municipal property tax increases less than the annual inflation rate for city costs (MPI) and measures success in controlling costs. Setting a target for a maximum municipal property tax increase provides specific direction to City Council and the Administration during the budget preparation and budget deliberations.

The MPI is calculated annually based on inflation rate for municipal costs such as labour and fuel.

How are we doing?


The 2013 municipal property tax increase was 3.74% plus a 1.25% increase dedicated to the Roadways Infrastructure Reserve (total of 4.99%). The 2014 municipal property tax increase was 3.14% and two dedicated taxes were introduced: one for roads (2.92%) and one for increased service levels related to snow removal, street sweeping, and sidewalks (1.37%) for a total of 7.43%.



Source: City of Saskatoon

How are other cities doing?

Other Western Canadian cities had 2014 municipal property tax increases ranging from 2.95% to 7.29%.



Sources: Cities of Saskatoon, Regina, Winnipeg, Calgary, Edmonton

Note: The City of Edmonton increased their municipal property tax by 4.92% and allocated an additional 2.37% in provincial education property “tax room” to arterial road rehabilitation.

What do we need to do to achieve this target?

- The City is undertaking continuous improvement to identify and implement efficiencies and cost savings without reducing the level of service for citizens.

What are the benefits of achieving the target?

- A target based on inflation ensures the annual property tax increases remain affordable to citizens.

What are the risks?

- The City will need to fund growth-related expenses which occur prior to receiving related revenue. Limiting property tax increases to inflation means that the City will need to diversify its revenue streams.
- Increases in service levels or fully funding approved service levels for core civic services may require a tax increase in excess of the MPI.

Long-Term Tax-Supported Debt per Capita

Proposed Maximum Long-Term Debt: Maximum long-term tax-supported debt per capita of \$1,750

A maximum debt level is recommended rather than a target. The intent is not to meet the maximum, but to have it in place so the debt remains affordable for taxpayers.


Description: The measure represents each resident's average share of the City's long-term tax-supported debt. Debt per capita helps to communicate City's debt levels.

Long-Term Tax-Supported Debt Per Capita = $\frac{\text{Actual Borrowing including P3 Financing}}{\text{Population of Saskatoon}}$

The city's population is estimated as of December 31 for each year by the City of Saskatoon Planning and Development Division.

Long-term tax-supported debt includes Public Private Partnership (P3) financing in addition to debt repaid by property taxes and federal gas taxes but excludes utility debt.


How are we doing?



Average long-term tax-supported debt has increased to support the City's growth.

Source: City of Saskatoon

How are other cities doing?



Saskatoon's long-term debt is lower than debt in most other major cities in Western Canada.

Source: City of Saskatoon's *Annual Municipal Operations Benchmark Report*

Note: The *Annual Municipal Operations Benchmark Report* used the 2011 Census population for all municipalities. Long-term tax-supported debt per capita using more recent estimated populations would be lower.

What are the benefits of achieving the target?

- Long-term public infrastructure like bridges and roads is needed to support economic growth and quality of life for citizens.
- Debt is an important part of any city's funding strategy for long-term infrastructure.
- The maximum debt per capita ensures debt levels are controlled based on the population.
- Although not considered directly by credit rating agencies, the measure contributes to a strong credit rating which keeps interest rates lower.

What are the risks?

- As the City grows, there is more need to expand infrastructure which will require more debt financing.
- Increased debt payments influence the tax rate.

Key Civic Infrastructure Status

Proposed 10-Year Target: Maintain key civic infrastructure at annual “B Service Level”

Description: An annual “B Service Level” requires funding for an “acceptable” level of service to citizens and a slow improvement to the overall condition of the asset. With a “B Service Level”, the backlog of required maintenance declines slowly and once the backlog is eliminated, the asset condition is maintained. Adequate funding is needed to both meet the public’s current expectations and maintain the assets with minimum long-term costs (lowest life cycle costs).

Key Civic Infrastructure includes bridges, structures, roads, sidewalks, water, and sewer infrastructure.

The following table describes service levels:

Asset Service Levels

Level of Service	Asset Condition	Description
A	Getting Better Quickly	Sufficient expenditures to maintain and keep assets in optimal condition. Asset condition/value improves to optimal levels, eliminating any backlog.
B	Getting Better	Sufficient expenditures to increase asset condition/value and decrease backlog slowly over time. Once backlog is eliminated, the funding is sufficient to maintain condition without a backlog.
C	Maintained	Sufficient expenditures to keep assets in constant condition over time. The backlog remains constant.
D	Maintain Assets that are in Very Poor Condition	Sufficient expenditures to replace assets when they completely fail. Insufficient funding to treat all segments requiring preservation and restoration work, and the backlog will slowly increase with time.
E	Getting Worse	Insufficient expenditures to maintain asset condition. Asset condition deteriorates annually. Some assets may need to be closed or removed from service.
F	Getting Worse Quickly	Asset condition/value decreases rapidly. Assets are frequently removed from service due to deterioration as insufficient funding exists to replace all completely failed segments.

How are we doing?

Funding has been increasing to maintain key infrastructure, particularly “roads and sidewalks” but a significant funding increase is needed to meet B Service Levels in the future.

Funding for bridges and structures has not kept up with what is needed to maintain bridges and structures at their lowest lifecycle cost. With “B Service Level” funding, the current maintenance backlog is expected to be eliminated by 2023 and funding can be stabilized to maintain conditions without a backlog. The timing for specific projects will affect how much of the backlog is eliminated each year.

How are other cities doing?

Infrastructure service levels are difficult to compare across jurisdictions because of differences in definitions and reporting on infrastructure service levels and investments.

What do we need to do to achieve this target?

A long-term strategy for key infrastructure is needed to identify:

- Inventory of key infrastructure
- Condition of key infrastructure
- Investment needed to improve the infrastructure
- Funding strategy to eliminate the current investment gap

What are the benefits of achieving the target?

Investing required funding levels to achieve the target “B Service Level” will have many benefits:

- Infrastructure will meet the needs of the growing population and economy.
- Assets will last longer.
- Long-term overall infrastructure costs will be minimized (least life cycle costs).
- The overall condition of the road and sidewalk network will be improved.
- The backlog of roads requiring repair and upgrading will be reduced.
- Fewer water main breaks or sewer backups will occur.
- Bridges and structures can be maintained to last indefinitely.
- Travel will be safer.
- Citizens will be more satisfied with the core infrastructure.

What are the risks?

- The main risk to achieving service levels and maintaining assets is that required funding may not be approved. If required funding is not approved, assets will deteriorate over time, the backlog of maintenance will continue to grow, and long-term costs will increase exponentially.
- If the shortfall in funding for bridges and structures continues over the next five years, rehabilitation options will change and costs will be higher.
- Continued deterioration of bridges and structures could result in closures to protect public safety.

Talking about Targets

Quality of Life

- **Perceived Quality of Life**
- **Number of New Attainable Housing Units**
 - **Vacancy Rates for Rental Housing**
- **Participation Rates for City Recreation and Cultural Facilities**
 - **Crime Rates**
 - **Fire Response Time**

Perceived Quality of Life


Proposed Indicator: Perceived Quality of Life

Description: The percentage of people rating “Quality of Life” in Saskatoon as “good” or “very good” measures how people feel about well-being in the city. Quality of life is influenced by factors such as access to good jobs, housing, opportunities for leisure activities, transportation, access to appropriate services, and feelings of safety.

City initiatives such as sports, culture, and recreation programs, efficient transportation networks, housing programs, quality infrastructure, and effective policing can influence perceptions of quality of life.

How are we doing?


The City of Saskatoon Annual Civic Services Survey asks people to rate quality of life in Saskatoon as very poor, poor, fair, good, or very good. In 2014, 86% of individuals surveyed rated the quality of life in Saskatoon as good or very good, slightly lower than in recent years.



Source: *The City of Saskatoon Annual Civic Services Survey*

How are other cities doing?

Perceived quality of life in Saskatoon compares favourably to perceptions in other western cities.



Sources: *The City of Saskatoon Annual Civic Services Survey (2014)* and surveys conducted adapted to comparable format: *City of Regina Citizen Survey Base Report (March 2012)*; *Winnipeg Citizen's Perspective 2013 Citizen Survey*; *The City of Calgary 2013 Citizen Satisfaction Survey*; *City of Edmonton Citizen Perception Survey (Draft Report, 2014)*

Note: Some cities do not undertake surveys annually. The graph reports the most recent survey results available.

Number of New Attainable Housing Units

Proposed 10-Year Target: 500 new units annually across the attainable housing continuum


Description: The proposed target measures the City’s success in developing a mix of affordable housing for ownership and rental throughout Saskatoon to address basic needs. Affordable, appropriate, and secure housing contributes to healthy and economically viable communities.

The target includes a mix of the following:

- Affordable rental and secondary suites
- Purpose-built rental units
- Affordable-ownership units
- Entry-level ownership units


How are we doing?

The City of Saskatoon has supported an average of 654 units of attainable housing annually over the last five years.



Source: City of Saskatoon

How are other cities doing?



Sources: City of Saskatoon, City of Regina

Comparisons between cities are difficult because of differences in programs and definitions cities use for attainable housing. Regina adopted a new strategy in 2013 to increase its housing supply.

What do we need to do to achieve this target?

The City has a ten-year *Housing Business Plan* to support 500 units annually across the attainable housing continuum. Achieving the target requires an annual optimal investment of approximately \$2 million which leverages additional funding from the federal and provincial governments, Aboriginal groups, non-profit housing providers, faith groups, and private builders. The annual investment may be less in years when the housing providers are focusing on providing smaller units with a lower cost per unit.

The City's average costs per attainable housing unit are as follows:

Attainable Housing Average Unit Costs			
	Cash Grant	Foregone Tax Revenue	Total
Affordable Rental	\$18,186	\$2,545	\$20,731
Affordable Ownership	\$3,920	\$3,262	\$7,182
Purpose Built Rental		\$2,324	\$2,324
Secondary Suites	\$498		\$498
Entry Level	Under the Equity Building Program, down payments are available from the City's investment funds, repayable over five years at 3.5% interest. There is no expense to the City.		

What are the benefits of achieving the target?

Implementation of the City's housing program will result in more affordable and appropriate housing choices for Saskatoon residents, helping them to contribute to our community and economy. Groups that directly benefit from achieving the target include the following:

- Métis and Off-reserve First Nations people
- New immigrants to the city
- Single parents
- Young people entering the workforce
- Post-secondary students
- Low and moderate income individuals and families

When people have appropriate housing, everyone benefits and the quality of life in Saskatoon remains high.

What are the risks?

Several factors influence the city's ability to achieve this target:

- Funding commitments from other levels of government which together contribute significantly more than the City of Saskatoon to attainable housing in Saskatoon.
- The willingness of non-profit housing providers and private home builders to create new attainable housing units.
- The availability of suitable land for housing projects.
- Economic factors such as interest rates, mortgage and lending rules, the availability of skilled labour, and demand and supply for rental housing.

Vacancy Rates for Rental Housing


Proposed 10-Year Target: Maintain an average rental housing vacancy rate of 3%

Description: The proposed target measures success in maintaining a generally acceptable level of rental accommodation. Vacancy rates below 3.0% generally indicate a limited supply of rental housing and can lead to rising costs for renters. Affordable, appropriate, and secure housing contributes to healthy and economically viable communities.

Vacancy rates = $\frac{\text{Total number of vacant rental units}}{\text{Total number of rental units available}}$

How are we doing?


In 2007, in response to a 0.6% vacancy rate, City Council committed to a five-year *Housing Business Plan*. The plan's implementation increased the housing supply and contributed to consistent vacancy rates of about 2.6%. In 2013, a ten-year plan was adopted to support a target of 500 affordable housing units annually across the attainable housing continuum. In 2014, the rental vacancy rate increased to its highest level since 2005.



Source: Canadian Mortgage and Housing Corporation

How are other cities doing?

Saskatoon's Fall 2014 vacancy rate was higher than the rate in other western Canadian cities and higher than the 2.7% national average of Canada's 35 largest cities.



Source: Canadian Mortgage and Housing Corporation

What do we need to do to achieve this target?

The City will influence a healthy vacancy rate by

- Permitting the creation of new and legalizing existing secondary suites that meet required standards
- Implementing the infill strategy which allows garage and garden suites
- Achieving the target of 500 units annually under the *Housing Business Plan* with a cost of approximately \$2 million annually

What are the benefits of achieving the target?

Through achieving a healthy vacancy rate, residents will have access to more variety of appropriate and affordable housing thereby facilitating the opportunity for them to contribute to our community and economy. Groups that directly benefit from the achievement of this target include the following:

- Temporary workers
- Métis and Off-reserve First Nations people
- New immigrants to the city
- Single parents
- Young people entering the workforce
- Post-secondary students
- Low and moderate income individuals and families

When people have appropriate housing, everyone benefits and the quality of life in Saskatoon remains high.

What are the risks?

Several factors influence the city's ability to achieve this target:

- Funding commitments from other levels of government for housing programs
- The willingness of non-profit housing providers and private home builders to create new rental properties
- Higher economic growth and more migration into the City than expected
- Other economic factors such as interest rates, mortgage and lending rules, the supply of skilled labour, and demand for rental housing
- Slower economic and population growth can result in an oversupply relative to demand

Participation Rates for City Recreation and Cultural Facilities

Proposed 10-Year Target: Increase visits to City of Saskatoon recreation and culture facilities to 6,600 visits per 1,000 people

Description: The target measures our success in growing and maintaining participation in City-owned and managed recreation and culture facilities and programs which contribute to quality of life of residents. The measure includes number of visits to leisure centres (including registered programs), the Forestry Farm Park and Zoo, outdoor pools, municipal golf courses, playground programs, youth programs, youth centres, Mendel Art Gallery, and Rемаi Modern Art Gallery of Saskatchewan.


While the City also provides financial and staff support to community-based organizations that offer a variety of sports, culture and recreation activities, attendance at third party facilities, events and programs are not included in the target.

Participation =
$$\frac{\text{Number of visits to city managed recreation and culture facilities}}{\text{Population of Saskatoon / 1,000}}$$

The target represents an increase of about 500,000 visits to two million visits by 2023 based on a 2% annual population growth rate.

How are we doing?

In 2013, City-managed recreation facilities and programs attracted about 1,490,000 visits or an average of almost 6,000 visits per 1,000 residents. Attendance is influenced by availability and types of programs, price, other recreation options, and weather. Overall attendance fell in 2013 due to poor spring golfing weather and increased opportunities to participate in recreation through private fitness centres and community-based organizations.



Source: City of Saskatoon

Attendance at City of Saskatoon Recreation Facilities		
Admissions and Attendance	2013	2012 to 2013 Percent Change
Indoor Leisure Centres	757,421	-9.5%
Forestry Farm Park & Zoo	142,440	9.6%
Playground Programs	115,680	12.3%
Outdoor Pools	87,915	2.2%
Municipal Golf Courses	45,395	-7.4%
Youth Centres, Youth Events & Youth Programs	10,684	5.0%
Registered Programs (Average 8 visits per registration)	161,392	1.3%
Mendel Art Gallery	168,972	-4.8%
Total Admissions	1,489,899	-4.0%

Information from other jurisdictions is not directly comparable because of different types of recreation facilities and different ways of counting visits.

What do we need to do to achieve this target?

- New recreation programs and art exhibits to respond to changing demands, attract new users and continue to attract repeat visits
- New fee options to stay competitive
- Effective new marketing and promotions to increase awareness and attendance at facilities and programs
- Facility upgrades, enhancements or new facilities including the new Remai Modern Art Gallery of Saskatchewan to address aging infrastructure, reflect changing trends, respond to the growing population, and attract new users

What are the benefits of achieving the target?

- Saskatoon residents, regardless of their income, will have access to leisure activities in their neighbourhood.
- Participation in sports and recreation improves health and fitness. Healthier people are more productive and have a higher quality of life.
- Recreation programs provide Saskatoon with a competitive edge in being a city of choice when families are considering Saskatoon as a place to live, work, or vacation.
- Youth participation in recreation activities can help to reduce crime and mischief and the related costs to society.

What are the risks?

- Private fitness facilities and community organization programs that are conveniently located and meet specific interests may reduce attendance at City recreation facilities.
- Adverse weather has an impact on visits to golf courses, outdoor pools and playground programs.
- Social, cultural and demographic changes influence how people spend their leisure time.



Crime Rates

Proposed 5-Year Target: Decrease overall crime rates by 5.0% annually over the previous five-year average

Description: Decreasing crime rates indicate success in increasing public safety in our homes, on our streets, and in our overall community. People have a higher quality of life when they feel safe. Crime rates decrease when people are working and have recreation and leisure opportunities.

How are we doing?

Saskatoon’s crime rates for both property crime and violent crime have been steadily decreasing since 2009.



Even though Saskatoon’s crime rates have decreased, our crime rates are higher than in other western cities.

Source: Saskatoon Police Service (both graphs)

What do we need to do to achieve this target?

- The Saskatoon Police Service (SPS) is decreasing crime as one of four priority areas in their *2015–2019 Business Plan* to create a safe and secure community. Reducing robberies, thefts, and mischief will be emphasized to reduce overall crime.

What are the benefits of achieving the target?

Less crime means fewer victims and an increase in the sense of public safety. Less crime reduces costs associated with the following:

- Stolen and damaged property
- Medical system usage due to drug use and violent crime
- Criminal justice costs for courts, prosecution, prisons, etc.
- Productivity losses including lost wages
- Intangible costs including pain and suffering

What are the risks?

- Saskatoon has a large marginalized population facing poverty, poor housing, and non-inclusion which contribute to street and gang activity such as robbery, assault, theft, and vandalism. Underlying issues must also be addressed to reduce crime.
- Rapid population growth contributes to more crime and social disorder. Physical and population growth is straining the City's funding capacity while increasing pressure on human resources.

Fire Response Time

Proposed 10 Year Target: Respond to fire calls within six minutes and 20 seconds at least 90% of the time


Description:

“Fire Response Time” measures total response time from when dispatch receives a call for a fire emergency until the first unit arrives at the fire scene. Total response time includes dispatch (communication), turnout (reaction) and travel time.

The National Fire Protection Association (NFPA), a body of professionals that develops best practice models for fire services, recommends the following response times for emergency fire calls in urban settings, to be achieved 90% of the time:


- 60 seconds to receive and process the call
- 80 seconds for responders to don protective clothing, and
- 240 seconds (4 minutes) for travel time for the first arriving unit to arrive at the incident after leaving the station
- Eight minutes travel response time to have a full complement of at least 16 firefighters on-site

How are we doing?



In 2014, the Saskatoon Fire Department responded within six minutes and 20 seconds to 82.5% of the 5,312 fire calls they responded to. The average total response time in 2014 for the first fire unit to arrive on-site was five minutes and 10 seconds.

Source: Saskatoon Fire Department



The map shows the present location and coverage of the nine fire stations and the travel time required to respond to a fire in the service area.

How are other cities doing?

Cities have different goals for response times and different ways of reporting, therefore making direct comparisons difficult. Calgary and Edmonton have targets for total response time for fire calls of seven minutes 90% of the time. In 2013, Calgary achieved their target 66.4% of the time and Edmonton 82.9% of the time.

What do we need to do to achieve this target?

Strategically located fire stations which maximize the service area that can be reached within a four minute travel time are key to meeting the response time target. New fire stations, with appropriate funding plans, must be incorporated in long-term planning strategies. Minimizing overlap of service areas will increase operating efficiencies while continuing to provide effective coverage.

What are the benefits of achieving the target?

- Due to the dynamics of fire growth, seconds count in saving lives and property.
- Increased densification, new building and insulation materials, and modern furnishings which contribute to quicker fire spread and release of toxic chemicals make a timely response even more important to protecting citizens and their property.
- By achieving timely response time targets, “quality of life” is enhanced by the knowledge that life and property have a reasonable, quantified chance of success.
- Fire protection levels are a key driver in the establishment of insurance rates within the service area. Quicker response times can lower insurance costs.

What are the risks?

Meeting targeted response times may be negatively impacted by the following:

- The construction of houses in new neighbourhoods which are further from fire stations
- Increased neighbourhood densification and resulting traffic congestion
- More train traffic through the city
- Lack of appropriate funding plans for the development of strategically located fire stations

Talking about Targets

Environmental Leadership

- **Waste Diverted From the Landfill**
- **Reduction of Greenhouse Gas Emissions**

Waste Diverted From the Landfill


Proposed 10-Year Target: Divert 70% of waste from the Saskatoon landfill

Description: The target will measure our success in environmental stewardship through increasing the percentage of waste that is recycled, reused, or composted.

$$\text{Waste Diversion Rate} = \frac{\text{Total waste diverted}}{\text{Total waste (diverted + landfill)}}$$

How are we doing?


In 2013, 17.8% of waste not including the City’s waste soil and 39.5% including soil went somewhere other than the Saskatoon landfill. The total waste diversion rates for 2009 to 2013 in the graph below include soil from City construction and other City projects that went to the landfill but was subsequently reused. With the new *Soils Handling Strategy*, City soil will not go into the waste system and will not be included in the waste diversion numbers. This lowers future expected waste diversion rates.



Source: City of Saskatoon

How are other cities doing?

Saskatoon currently diverts more of its waste than most other Western Canadian cities when the City's waste soil is included. If the City's waste soil is not included, Saskatoon diverts the same percentage of waste as Regina and less than Winnipeg, Calgary or Edmonton. Waste soil is not included in other cities' diversion rates. Other cities have set waste diversion targets ranging from 50% to 90% with 2020 being a common target date.



Sources: City of Saskatoon (2013), City of Regina (2014), City of Calgary (2012), City of Edmonton (2013) and City of Winnipeg (2014)

Notes: Not all cities report annually. Data is based on most recent data available.

What do we need to do to achieve this target?

In 2023, approximately 200,300 tonnes of waste are expected. To reduce the amount going to the landfill to 60,000, the following is required:

- Current programs including multi-unit recycling will divert 66,300 tonnes or approximately 33% of waste by 2023.
- Proposed new programs will divert an additional 52,000 tonnes or 26% of total waste when fully implemented.
- Additional programs need to be identified to divert another 22,000 tonnes or 11% of waste to reach 70%.

Current Programs	Tonnes Diverted in 2013	Potential Tonnes Diverted by 2023
Curbside Recycling (single family)	8,034	16,800
Multi-Unit Recycling	-	3,500
Compost Depot	21,088	20,000
Green Cart (Leaves & Grass) Program	832	3,500
Recycling Depots	3,773	2,000
Household Hazardous Waste Days	52	300
Soil Re-Use	42,189	20,000
Outgoing Recyclable Material from Landfill	800	
Public Space Recycling	14	200
Total	76,782	66,300

Proposed New Programs	Potential Tonnes Diverted by 2023
Recovery Park	22,000
Food Waste Program	12,000
Industrial, Commercial and Institutional Recycling	8,500
Industrial, Commercial and Institutional Food Waste	9,500
New Programs to be Determined	22,000
Total	74,000

What are the benefits of achieving the target?

Waste diversion provides economic, environmental, and social benefits:

- Significant future costs to build a new landfill will be postponed or avoided. If waste is not diverted, a new landfill will be necessary within 50 years at an estimated cost of \$180 million.
- Landfill operating costs and the market value for land are \$90 per cubic meter or approximately \$4 million per year (2009 valuation).
- Recycling conserves raw materials.
- Recycling saves energy.
- A tonne of recycled aluminum cans saves 6.5 tonnes of greenhouse gas (CO_{2e}).
- A tonne of recycled newspapers saves 2.8 tonnes of CO_{2e}.
- A tonne of recycled plastic saves 2.3 to 3.6 tonnes of CO_{2e}.
- The City's current waste diversion programs reduce CO_{2e} by approximately 97,000 tonnes annually (equivalent to removing 19,000 vehicles from our roadways each year).
- Waste diversion programs create local jobs and provide skills and learning opportunities for more than 400 adults with intellectual disabilities.

What are the risks?

- Achieving the target will require changes in what people send to the landfill. Changing attitudes and habits towards waste disposal may take more time.

Reduction of Greenhouse Gas Emissions


Proposed 10-Year Target: Reduce the City of Saskatoon’s greenhouse gas emissions by 30% from 2006 levels

Description: The target will measure our success as an organization in reducing our impact on climate change by lowering greenhouse gas emissions and diversifying to more renewable energy sources.

A 30% reduction from 2006 levels means the City of Saskatoon (corporate) must reduce greenhouse gas emissions to 75,000 tonnes. Considering growth, 67,770 tonnes of CO₂e must be eliminated to reach the target.

How are we doing?

In 2013, the City of Saskatoon (corporate) emitted an estimated 117,100 tonnes of greenhouse gas (CO₂e), an increase from 2006 levels.



Source: City of Saskatoon

How are other cities doing?

Other municipalities report GHG reductions relative to different years making comparisons challenging. The following is a sample of other cities' corporate greenhouse gas targets and current status:

City	Corporate Reduction Targets	Current Status
Regina	20% below 1990 by 2005 & 1% each year following until 2012	No status available
Winnipeg	20% below 2006 by 2019	20.2% below 2006 (2007)
Calgary	20% below 2005 by 2020 80% below 2005 by 2050	46% below 2005 (2012) and 100% of corporate electricity offset by renewable electricity certificates (mostly wind power)
Edmonton	20% below 1990 by 2020 50% below 1990 by 2050	No status available

What do we need to do to achieve this target?

Continued operational changes and investments in energy efficiency are needed to reduce greenhouse gases. Several measures have been implemented through the *2009 Energy and Greenhouse Gas Management Plan* with costs ranging from \$6 to \$1,500 per tonne of greenhouse gas saved. Operational changes have been as simple as introducing set-back thermostats to reduce energy for heating to complex initiatives like installing solar heating at indoor pools and producing electricity from landfill gas.

Current initiatives shown below will contribute to achieving the target.

Initiative	Estimated Tonnes of GHG Reduction
Civic Building Energy Efficiency through Energy Performance Contracting	8,000
Compressed Natural Gas Garbage Fleet	570
Water and Waste Water Plants	300
Garbage Service Verification	300
Innovation (Green) Teams	4,500
Sustainable Procurement	Unavailable
CHP at Shaw and Lakewood (produces heat and power in one efficient process)	900
Landfill Gas	45,000
Recovery Park	8,200
Totals	67,770

What are the benefits of achieving the target?

- Almost all greenhouse gas reduction activities reduce utility costs (savings today) or help defer major capital costs (future savings).
- Conventional non-renewable energy is replaced with renewable sources that generate a new revenue stream for the City.
- Reducing greenhouse gases can also reduce air pollutants.
- Future legislation mandating emissions reduction is anticipated. By reducing emissions now, the City will avoid making deeper cuts in greenhouse gases in the future to comply with regulations.

What are the risks?

- The City's greenhouse gas emissions have been rising as a result of increased activity to respond to citizen expectations and growth. Future growth will contribute to more emissions as City vehicles travel greater distances.

Talking about Targets

Sustainable Growth

- **Population Growth and Rate of Change**
 - **Residential Infill Development**
- **Residential Development Density in Established Areas**

Population Growth and Rate of Change


Proposed Indicators: Population growth and rate of change

Description: Population growth and growth rate are proposed as indicators of sustainable growth and community success. The overall vision of the City of Saskatoon’s *Strategic Plan 2013-2023* is to continue to grow and prosper. Population growth is necessary to provide sufficient labour for Saskatoon’s continued economic growth. Population growth also provides opportunity for other aspects of the community to grow and diversify including business, education, culture, recreation, and overall financial stability.

Population growth is a fundamental driver of the City’s business plan and budget planning process. City infrastructure investments are based on population growth. The return on those investments often depends on further growth.

How are we doing?


Saskatoon’s population grew by an average annual rate of 2.9% from 2009 to 2013. Referencing recent Statistics Canada’s population estimates for Canadian municipalities, our annual growth rate for 2014 was 3.7%. Over the last five years, the City’s opportunities for employment, education, services, and a high quality of life attracted people from around Saskatchewan, Canada and internationally.



Source: City of Saskatoon

How are other cities doing?

Between 2009 and 2013, Saskatoon's population grew faster than other major western Canadian cities. The strength in the resource sector, particularly mining, and related employment opportunities has contributed to Saskatoon's higher growth rate.




Source: Statistics Canada

Residential Infill Development

Proposed 10-Year Target: At least 25% five-year rolling average of residential development is in infill neighbourhoods by 2023

Description: Residential infill development measures the City’s success in reducing requirements for new infrastructure and ongoing maintenance costs. The City’s *Growth Plan to Half a Million* has an infill target of 30% of the next 250,000 people over the next 30 years. Current infill levels are below 30% and many significant infill projects are several years away. A five-year rolling average is used because of large annual fluctuations in development.

The target =
$$\frac{\text{Number of new housing units in infill neighbourhoods over five years}}{\text{Total new housing units over five years}}$$




The target supports the success drivers of sustainable growth, neighbourhood quality, balanced land use, multiple transportation options, and it can contribute significantly to

the availability of land for development. This target supports the overall strategic direction being set by many major corporate initiatives such as the *Growth Plan to Half a Million*, *North Downtown Plan*, *City Centre Plan*, *Neighbourhood Infill Guidelines Study*, *Civic Operations Centre Plan*, *University's 2057 Plan*, and Vacant Lot Development Incentive Program.

How are we doing?

Over the past 10 years, almost 20% of total dwellings constructed in Saskatoon were infill development. The infill ratio varied from a low of 13% in 2009 and 2013 to a high of 44% in 2004.



Source: City of Saskatoon

How are other cities doing?

Many cities have infill development as a high priority to facilitate sustainable growth and have targets for new units or population living in infill neighbourhoods. Meaningful comparisons are a challenge since each city defines infill differently and uses different data for the calculations. The following benchmarks were identified:

- In Edmonton, 15.3% of new residential units were infill (downtown, mature neighbourhoods and near LRT stations) in 2013.
- In Calgary, 16% of new population lived in infill neighbourhoods between 2006 and 2014.
- In Regina, 25% of new residential units were infill and 30% of new population lived in infill neighbourhoods between 2006 and 2011.

What do we need to do to achieve this target?

- The ‘growth near major corridors’ component of the “*Growing Forward! Shaping Saskatoon*” initiative will have recommendations for infill along major corridors such as Idylwyld Drive and 8th Street and at key locations.
- With a projected build-out population of 7,650, the *North Downtown Plan* will increase infill development. However, it is currently planned to be implemented over 30 years, meaning that the impact on the infill target is unlikely to be significant within the next 10 years. The City could influence this by advancing the implementation timeframe.
- Saskatoon Land has a mandate to generate revenue for the City, primarily through development in new suburban areas. The City could alter Saskatoon Land’s mandate to include infill development. This would help achieve the target and set a strong example for private developers by demonstrating feasibility.
- The University of Saskatchewan’s *Vision 2057* plan for its endowment lands forms the single largest potential component of the City’s infill strategy. Impacts will likely be realized in the medium and long-term.
- Offsite levies are considered as “owing” on many existing sites within the City’s infill neighbourhoods. The offsite levy structure could be reviewed with a goal of encouraging infill development through, for instance, reducing or offsetting the levies, or replacing them with re-development levies to provide more direct benefits to re-development areas.

What are the benefits of achieving the target?

- Increases cost-effective and efficient transportation
- Reduces the overall cost of infrastructure
- Supports services and amenities in and near the city centre
- Enhances neighbourhood quality by the development of vacant sites and redevelopment of neglected buildings
- Adds population to support neighbourhood amenities like schools and services
- Supports City Centre population growth
- Avoids requirements to develop and service approximately 1,700 hectares (over 4,000 acres) in new suburban areas.

What are the risks?

- New buildings that do not fit with existing character or too much density in one location, may detract from neighbourhood quality and raise opposition among residents, so infill policy requires sensitivity at the local level.
- In periods of high growth, there is a tendency for developers to “do what they know best” and there may be resistance to taking substantive steps to change the current suburb-focused development model to more infill development.
- A major factor in achieving the target is *Vision 2057* which is dependent on the University of Saskatchewan’s developments over the next ten years.
- Much of the required development activity is out of the City’s direct control and is dependent on continued economic success for Saskatoon and region.

Residential Development Density in Established Areas


Proposed 10-Year Target: An 8% increase in residential development density within infill neighbourhoods

Description: This target measures our success in increasing residential density within the established area of the city and is another means to monitor the progress of infill development. Achieving the target will increase density in established areas to 11.1 units/hectare. This target is a useful measure of the overall sustainability for urban development. This measure is also tracked on a neighbourhood basis which provides value by characterizing how existing neighbourhoods are progressing over time, and how our new neighbourhoods are increasing in overall design densities.

Targeting density in infill neighbourhoods will track a consistent area and avoid problems with including new neighbourhoods while development is in progress. The City regulates a minimum development density for new neighbourhoods which is higher than the target density for infill neighbourhoods and is consistently exceeded. For example, the recently approved plan for the new neighbourhood of Aspen Ridge will make it the densest neighbourhood in Saskatoon. Density in new areas will be tracked separately.

How are we doing?

In 2014, the gross dwelling unit density in infill neighbourhoods was 10.31 units/hectare (4.2 units/acre) up 2.9% over five years and 4.7% over ten years.



Source: City of Saskatoon

How are other cities doing?

Most cities track dwelling unit density as measures of sustainability. Comparisons, however, are not meaningful since the precise methods for calculating density vary by community.

None of the cities surveyed (Calgary, Edmonton, Regina and Winnipeg) have a target for dwelling unit density for existing areas of the city. Calgary has a city-wide target to increase population density by 35% over 60 years.

What do we need to do to achieve this target?

- Offsite levies are considered as “owing” on many existing sites within the City’s infill neighbourhoods. The offsite levy structure could be reviewed with a goal of encouraging infill development through, for instance, reducing or offsetting the levies, or replacing them with re-development levies to provide more direct benefits to re-development areas.
- The ‘growth near major corridors’ component of the “*Growing Forward! Shaping Saskatoon*” initiative is expected to contain medium and long-range recommendations to achieve “intermediate” infill along major corridors and at key locations.
- With a projected build-out population of 7,650, the *North Downtown Plan* has potential to positively impact the share of infill development. However, it is currently planned to be implemented over 30 years, meaning that the impact on the infill target is unlikely to be significant within the next 10 years. The City could influence this by advancing the implementation timeframe and increasing investment earlier on.
- Saskatoon Land currently has a mandate to generate revenue for the City, primarily through the development of new suburban areas. The City could alter Saskatoon Land’s mandate to include infill development. This would help achieve the above target and would also set a strong example for private developers to follow, in part by demonstrating feasibility.
- The University of Saskatchewan’s *Vision 2057* plan for its endowment lands forms the single largest potential component of the City’s infill strategy. It will require coordination of planning efforts between the City and University administrations. This is a long-term component with impacts more likely to be realized in the medium and long-term. However, the City should begin discussions with the University about how to achieve *Vision 2057*.

What are the benefits of achieving the target?

- More infill development will increase cost-effective and efficient transportation options, reduce the overall cost of infrastructure, and support services and amenities in and near the city centre.
- Neighbourhood quality is supported by the development of vacant sites and redevelopment of neglected buildings, as well as by adding diversity and population growth to support neighbourhood amenities like schools and services.
- Infill development supports City Centre population growth and helps to balance population growth near the City Centre.
- Achieving this target will allow the City to avoid developing and servicing approximately 1,700 hectares (over 4,000 acres) of new suburban areas.

What are the risks?

- On its own, density is not inherently positive or negative. Other factors, such as the form of development, and the distribution of density play a critical role in overall outcomes.
- New buildings that do not fit with existing character or too much density in one location, may detract from neighbourhood quality and raise opposition among residents, so infill policy requires sensitivity at the local level.
- In periods of high growth, there is a tendency for developers to “do what they know best” meaning that there may be resistance to taking substantive steps to change the current greenfield-focused development model to more infill development.
- A major factor in achieving the target is the completion of *Vision 2057*, meaning that much of the success is dependent on the actions of the University of Saskatchewan.
- Much of the required development activity is out of the City’s direct control and is dependent on continued economic success for Saskatoon and region.

Talking about Targets

Moving Around

- Transit Rides Per Capita
- Kilometres of Cycling-Specific Infrastructure
 - Transportation Choices
 - Traffic Collisions

Transit Rides Per Capita

Proposed Long-Term Target: Increase transit ridership to 62 rides per capita


Description: The target measures our success in making our transit system a more efficient option for people to move around in Saskatoon. Achieving this target means that more people are using transit for their travel needs, thereby reducing road congestion. Higher transit use provides the movement of more people rather than more cars, particularly along key corridors.

Bus ridership will be measured using electronic pass swipes.

The transit target is consistent with the transit rides per capita target identified in the “*Growing Forward! Shaping Saskatoon*” strategy for a population in 30 to 40 years that is twice the size of Saskatoon’s current population.

How are we doing?

In 2011, electronic bus passes were introduced. In 2013, based on electronic pass swipes, total bus ridership was 9.4 million rides or 37.8 rides per capita.



Source: City of Saskatoon Transit

How are other cities doing?

Saskatoon has higher per capita bus ridership than Regina and has mid-range ridership relative to other medium-sized cities with similar transit systems. Regina uses an electronic method similar to Saskatoon in counting ridership. Other cities, however, may calculate ridership differently.



Source: Canadian Urban Transit Association (CUTA)

What do we need to do to achieve this target?

To significantly increase ridership, transit needs to be more convenient and reliable. Increased operating and capital investments will be needed to make transit a reliable and convenient transportation alternative. In addition to making improvements in scheduling, routing and service hours, investing in the following five key areas will attract new ridership through decreasing travel time and improving the transit experience:

1. Increase bus frequency:
 - Add more direct routes (16 current limited stop express service routes) to high congestion and high ridership areas.
 - Increase bus frequency on regular routes and offer new routes as the city grows.

2. Improve reliability and on-time performance:
 - Implement Intelligent Transit System (ITS) providing improved efficiency through more detailed route analysis. ITS will allow fleet resources to be appropriately focused on problematic areas so that schedules are more closely adhered to, ultimately increasing the reliability of the service.
 - Decrease average fleet age from 14 years to 9 years through the purchase of new buses. This will reduce downtime due to major maintenance requirements.
 - Decrease the bus/mechanic ratio from 15:1 to approximately 7:1 through hiring more mechanics.
3. Enhance comfort:
 - Provide cleaner buses and shelters to offer a more comfortable, enjoyable ride.
 - Convert high volume shelters to heated shelters.
 - Install shelters in more locations.
4. Improve customer service:
 - Provide more customer focused training to build customer-centered service skills.
 - Increase the quantity and quality of the information that customers receive. By dedicating staff to this area, Transit will be able to communicate up-to-date information through multiple communication channels (Transit's website, social media, and public service announcements).
5. Implement Bus Rapid Transit (BRT)
 - Develop a Bus Rapid Transit (BRT) plan to implement rapid transit corridors throughout Saskatoon, increasing frequency, reliability and commuting options.

What are the benefits of achieving the target?

- Fewer private vehicles on the road results in lower greenhouse gas emissions, a decrease in congestion, and a healthier environment.
- An easier commute means a higher quality of life for Saskatoon citizens.

What are the risks?

- The greatest barriers to encouraging new ridership are time, convenience and reliability. As congestion increases, the ability to commute by personal vehicle will become more difficult and public transportation will become a more attractive option. With funding allocations going to decrease congestion, Saskatoon Transit's current services will be a less attractive option than driving.
- A primary risk to achieving this target is insufficient funding invested to make transit a more attractive transportation option. Higher frequencies, newer buses and a more comfortable commute require increases in both capital and operating budgets.

Kilometres of Cycling-Specific Infrastructure


Proposed 10-Year Target: Increase the amount of cycling-specific infrastructure by 10%

Description: The proposed target measures the City's success in making it easier for cyclists to move around. Cycling-specific infrastructure includes pathways, multi-use trails, cycle tracks, bicycle boulevards, and bike lanes.

A 10% increase is approximately 1.5 km's of additional cycling infrastructure annually.

How are we doing?

Saskatoon currently has 155.9 kilometres of cycling-specific infrastructure.



Source: City of Saskatoon (Draft numbers)

The City's total cycling infrastructure includes cycling-specific facilities and the general roadway network available for cycling. Saskatoon has a total of 1,142 km of cycling facilities of which 80% are suitable for novice cyclists, 10% for intermediate cycling skills, and the remaining 10% are suitable only for expert cyclists (high volume roads).

What do we need to do to achieve this target?

- A new growth plan is needed to prioritize cycling infrastructure projects and programs to make cycling a more accessible transportation option for more people.
- Costs for new cycling-friendly paths range from \$500K per km in unconstrained locations to \$3M per km in fully developed urban locations.

What are the benefits of achieving the target?

- Many residents use their bicycle for their daily transportation needs. Cycling initiatives are intended to increase the ability of Saskatonian's to use their bicycles as an alternative to automobiles.
- Increasing accessible cycling infrastructure will provide more opportunities for people to use their bicycles for recreation purposes.
- Cycling has a positive impact on reducing energy consumption and greenhouse gas production.

What are the risks?

- The historical level of investment for cycling infrastructure will not be sufficient to meet these targets. If a funding plan is not approved, the target will not be met.
- Efforts to create more cycling infrastructure through converting parking stalls or driving lanes to cycling lanes may be opposed by other road users.

Transportation Choices


Proposed Long-Term Target: 20% of people use cycling, walking or transit to get to work

Description: The proposed target measures our success in significantly increasing the proportion of transit users and cyclists and decreasing the proportion of people who drive to work.

The target uses census data from the *National Household Survey* and reflects only trips to work. The Transportation Division will work towards providing an alternative indicator to estimate what mode of transportation people use to cross the river.

How are we doing?


In 2011, approximately 11.5% of Saskatoon residents used cycling, walking or transit to get to work.



Source: Statistics Canada, 2011 National Household Survey

How are other cities doing?

An average of 10.2% of people in cities with a population of 150,000 to 350,000 used cycling, walking or transit to get to work in 2011. More people in Saskatoon cycle or take transit to work than the average in other mid-size cities.



Source: Statistics Canada, 2011 Census, National Household Survey

What do we need to do to achieve this target?

- Achieving this type of change will require priority for transit infrastructure investments including development of rapid transit corridors.
- Increased investments are needed to make cycling a more accessible transportation option for more people.

What are the benefits of achieving the target?

Fewer people driving and more people cycling, walking and taking transit to work have many benefits for the community:

- Less energy consumption and greenhouse gas production
- Less road congestion
- Reduced need and costs for road and bridge infrastructure
- Healthier people
- More cost-effective transit system

What are the risks?


- People like the flexibility, convenience and time savings driving to work offers. More people will drive to work if sufficient investments are not made to make transit and cycling more attractive transportation options.

Traffic Collisions

Proposed 5-Year Target: Decrease traffic collisions by 5% annually

Description: Decreasing traffic collisions indicates success in increasing public safety on our streets.


How are we doing?



Saskatoon's traffic collisions have increased as the population and related traffic congestion has increased.

Source: Saskatoon Police Service

How are other cities doing?



Traffic collisions in Saskatoon are higher than in other Western cities.

Source: Saskatoon Police Service

What do we need to do to achieve this target?

Saskatoon Police Service is working to reduce traffic accidents as one of four priority areas in their *2015–2019 Business Plan* to create a safe and secure community. The addition of a new integrated traffic section with the RCMP, funded by SGI, will enforce traffic laws and reduce accidents.

The City of Saskatoon's 2014 *Traffic Safety Action Plan (TSAP)* will focus on reducing accidents associated with the following:

- Aggressive driving
- Distracted driving
- Impaired driving
- Intersections
- Older drivers
- Young drivers
- Vulnerable road users (e.g. pedestrians, bikers)

What are the benefits of achieving the target?

A reduction in vehicle collisions means

- Fewer fatalities and injuries
- Less property damage
- Smoother traffic flow
- Increased productivity (less time off for injuries and dealing with damaged vehicles)

The TSAP identified the direct cost of collisions to be \$57.52 million per year and societal costs to be \$261.2 million per year in Saskatoon. A 5% reduction in collisions means a \$2.9 million savings in direct costs and a \$13.1 million savings in societal costs.

What are the risks?

- Unusually bad weather conditions increase traffic collisions.
- More vehicles and road infrastructure congestion increase traffic violations and collisions.

Talking about Targets

Economic Diversity and Prosperity

- **Amount and Value of Building Activities**
 - **Retail Space per Capita**
- **Supply of Residential and Industrial Land**

Amount and Value of Building Activities


Proposed Indicators: Number and value of building permits

Description: The number and value of building permits are indicators of economic growth and prosperity. They are often used in understanding trends in the local business cycle and can assist in predicting future real estate supply levels. Investment and construction activity are influenced by a business environment with competitive taxes, quality infrastructure, and policies encouraging growth.

Saskatoon’s higher than average construction activity signifies investor confidence in our economy. Higher construction levels also reflect Saskatoon’s significant population growth. Building activity has created well-paying employment opportunities in the construction industry and in businesses that support the industry, contributing to higher quality of life.

How are we doing?


The number of building permits issued by the City of Saskatoon has doubled in the last ten years and the value increased more than three times. In 2012 and 2013, the City issued over 5,000 building permits with over \$1 billion in annual construction value. In 2014, the number of permits decreased slightly and the value decreased by 19.3%.



Source: City of Saskatoon

How are other cities doing?

Between 2009 and 2013, Saskatoon's \$3,880 per capita average annual construction was close to the average in Edmonton and Calgary and significantly more than in Regina and Winnipeg.



Sources: City of Saskatoon, Statistics Canada's 2011 Census.

*Edmonton construction value is average of four years (2010 to 2013).

What are the risks?

- The number and value of building permits are influenced by local economic factors, world commodity prices, population growth, and changes in interest rates.

Retail Space per Capita


Proposed Indicator: Retail space per capita

Description: “Retail space per capita” is proposed as an indicator of a healthy and diverse economy. The City influences the amount of retail space through city planning and zoning while demand and supply are determined by retailers and the market.

Retail space per capita = $\frac{\text{Retail square footage inventory}}{\text{Population of Saskatoon}}$

How are we doing?

Saskatoon has approximately 51 ft² per capita of retail space. Benchmark comparisons are imprecise because the definition of what constitutes retail space varies from city to city. In 2013, Colliers reported that Edmonton and Calgary had 32 ft² and 34 ft² per capita of retail space respectively.



Sources: City of Saskatoon population estimates for December 31, *Colliers International Total Retail Inventory*

What do we need to do?

Retail demand in Saskatoon remains strong due to population and economic growth in the city and the rural areas that Saskatoon retailers serve. The *Official Community Plan* guides commercial land-use development to provide adequate access and availability of retail space to meet the city's future needs. Rezoning of some areas is sometimes necessary to re-develop existing sites.

What are the benefits?

- Through planning for adequate appropriate space for retailers, the City of Saskatoon encourages the amenities and services that support the growing population.
- Saskatoon residents benefit from more choices for products and lower prices when there is a healthy competitive retail market.
- An appropriate balance of retail space per capita also supports employment growth through facilitating a business-friendly environment.

What are the risks?

- Retail space is mainly determined by market-driven and tenant-driven demand and supply.
- Increasing trends in internet shopping could reduce the demand for retail space.

Supply of Residential and Industrial Land

Proposed 10-Year Targets:

- A one-year inventory of land for single family units
- A two-year inventory of land for multi-family units
- A two-year inventory of industrial land


Description: The targets will measure success in maintaining an adequate supply of serviced land to meet building demand.

The target for single family lots is equivalent to a one-year supply held by Saskatoon Land and private-sector home builders and developers. In setting yearly servicing goals for single family lots, the City aims to have enough land completely serviced by year-end to satisfy the City’s share of market demand in the next year. The target for serviced land for multi-family units accommodates a two-year demand. A multi-family project typically requires a longer time to design and construct.

The target for industrial serviced land supports two years of demand for industrial building. The inventory target provides a healthy supply of land to accommodate business and employment growth.


The annual target for serviced residential land is based on past building permits, projected population growth and projected demand for single family lots and multi-units in the upcoming year. The annual target for industrial land is based on the average of the previous five years of industrial land sales by Saskatoon Land.

How are we doing?



The supply of land for single and multi-unit residential housing has met or exceeded targets over the last four years.

Source: City of Saskatoon



The supply of land for industrial development has met or exceeded targets over the last four years.

Source: City of Saskatoon

What do we need to do to achieve this target?

Over the next three years Saskatoon developers are planning to service enough land to accommodate over 16,000 dwelling units. Actual servicing levels will vary depending on contractor performance, weather, and market conditions.

Land Use	2014	2015	2016	2017	Total
Single Family	1,724	1,970	2,098	1,866	7,658
Multi-family	2,320	2,329	1,684	2,388	8,721
Total	4,044	4,299	3,782	4,254	16,379

Investment required by the City and private land developers to achieve the targets is not measured. The City's investment required to meet inventory targets is quantified in the annual Land Development Capital Budget. Over the past three years the City's annual land development capital budget has increased from \$70.73 million to over \$170 million.

What are the benefits of achieving the target?

- Meeting the inventory target for residential land supply ensures there is a sufficient amount of serviced lots to accommodate demand for housing in the Saskatoon market.
- The one-year supply of single family and two-year supply of multi-family land ensures a balanced market exists that is not subject to significant price swings due to land shortage or oversupply.
- Measuring inventory levels to ensure the targets are being met informs investment decisions and ensures carrying costs are not unreasonably high.

What are the risks?

- Due to the significant capital expenditure land development has inherent risk. In achieving the target inventory levels, changing market conditions that are beyond the City's control can have significant impacts on achieving the targets.
- Above average precipitation and contractor performance can have a significant impact on the City's ability to influence the target.
- Much of the risk in achieving the target arises from the dependence on the investment decisions of private developers. As a land developer the City strives to achieve the above noted targets, however it is the land development industry as a whole that ultimately achieves the set inventory goals.

Nutana Slope Stability Update

Recommendation

That the report of the General Manager, Transportation & Utilities Department dated February 11, 2015, be forwarded to City Council for information.

Topic and Purpose

This report is intended to present the results of the in-depth geotechnical investigation of the Nutana Slope Failure, including causes, potential remediation options and relative remediation costs. The report also provides an update on the current situation with the riverbank slope failure occurring in Nutana between 11th Street East & Saskatchewan Crescent East.

Report Highlights

1. The river bank slope between Saskatchewan Crescent East & 11th Street has moved as much as 2.7 meters over the past two and a half years.
2. An in-depth geotechnical investigation of the slope failure was conducted by Golder Associates including causes of failure and conceptual remediation options.
3. The extensive geotechnical investigation revealed that the cause of the failure was natural and due to three key geological features – geometry; geology; and groundwater.
4. Public safety remains a paramount focus of the City. The slope has been monitored regularly by appropriate civic staff as well as consultants, and information has been provided to residents on a regular basis.
5. There have been slope remediation projects conducted at different sites in Saskatoon where the failure is primarily on public property.

Strategic Goals

The investment in monitoring the slope and site for safety concerns supports the City's Quality of Life Strategic Goal.

Background

In June 2012, a slope failure occurred on the river bank between 11th Street East and Saskatchewan Crescent East. This failure directly impacted the backyards of two properties. This was known as the west slide area. A temporary evacuation was issued for these properties due to concerns with a gas line in the lane. This gas line has since been removed. In response to the slope failure, the City initiated an investigation and monitoring program within the lane (Cherry Lane) between the private properties. Golder Associates was retained to provide this geotechnical expertise and the investigation led to a report that recommended actions that could be taken to stabilize the slope. The scope of this study was contained to the lane. Monitoring of the lane continued on a monthly basis throughout 2012 and into the spring of 2013, showing

negligible movement of the slope. Following initial movement, the west slide area recorded approximately 140 millimeters of movement throughout 2012.

In June 2013, a new slide area to the east of the first location was reported. Monitoring was expanded, and throughout 2013 this new east slide area moved over 1200 millimeters, which is significant. The west slide also continued moving for a total of 500 millimeters in 2013. This situation prompted the City to declare a voluntary evacuation and initiate an extensive study with Golder Associates with the scope of the study involving a complete investigation of the entire slope area, analysis of the failure and evaluation of conceptual remediation options.

Report

Slope Movement

The Nutana slope failure is comprised of two distinct slide areas; west slide and east slide. These areas are represented in Attachment 1. Following the initial sudden movement reported in backyards in June 2012, the following table documents the recorded horizontal movement progression of the slope.

West Slide		East Slide	
Initial failure	<i>Not recorded</i>		
2012	140 millimeters		
2013	500 millimeters	2013	1,200 millimeters
2014	400 millimeters	2014	1,500 millimeters
TOTAL	1,040 millimeters (3' 5")	TOTAL	2,700 millimeters (8' 10")

Golder Associates Study

In the fall of 2013, the Administration received the final draft report from Golder Associates, outlining the causes of the failure and possible solutions for the remediation.

The extensive geotechnical investigation revealed that the cause of the failure was natural and due to three key geological features. The first is due to the geometry of the slope referring to its steepness and tendency to be pulled down. The second is due to the geology referring to weak soil formations existing deep within the slope that are not sufficient to hold the slope up. The third feature causing failure is groundwater. Water tables throughout Saskatoon have risen over the past decade due to unprecedented amounts of rainfall. This high water table leads to a buoyancy force within the slope that causes it to lift and facilitate movement.

This study identified two possible high level options for remediation. The first option is the removal of 8 - 10 homes along 11th Street East and Saskatchewan Crescent East and re-grading the slope including groundwater lowering. Once re-graded, this slope would not be developed again. The cost of this option would be in the order of \$10M plus the value of the homes and lots which could total another \$10M. Attachment 2 provides an overview of the affected area of Option 1. The second option would result

in the homes remaining intact by constructing a stabilization zone in the midpoint of the slope along the lane. This option would be complex and require specialized contractors. The initial conceptual costs for this would be in the order of \$20M. Attachment 3 provides an overview of the affected area of Option 2.

The Administration commissioned Clifton Associates to conduct a third-party review of this work. The Clifton Associates analysis presents a bleaker picture than the Golder Associates report, and suggests that soil shear strengths could be even lower. In either case, the severity of the situation and the options to remediate are of the same general nature.

The City provided the consulting reports to the residents affected, and has been providing weekly updates to residents during all but the winter months. These updates have repeatedly reminded homeowners that there is a voluntary evacuation notice in effect, and that it is their responsibility to consult with their own engineers on the stability of their property.

A copy of the Golder Associates Report is included as Attachment 4.

Public Safety

In this situation, safety is paramount for residents and anybody else that may be near this area. The approach that has and will continue to be taken includes monitoring, providing the monitoring information to residents, and regular evaluation of the site and situation. If at any point, the City's engineers or the Saskatoon Fire Department decide that safety is at an elevated risk, a mandatory evacuation notice will be issued. The Emergency Measures Organization has developed a response plan for catastrophic slope failure and will implement it if required. The City will continue to provide information to residents as it becomes available, and will continue to remind residents of the voluntary evacuation notice due to the known instability of the slope. A sudden failure could also occur at any time, and affected homeowners have been made aware of this risk.

On June 3, 2014, an evacuation alert was issued to three properties immediately affected by the slope movement. This was triggered by a rapid increase in movement rate as high as 40mm/day. On June 24, 2014, further movement prompted an expansion of the evacuation alert to include eight properties in total.

The evacuation alert was issued on the recommendation of the Saskatoon Emergency Measures Organization. The purpose of the alert was to warn affected residents of the risk of sudden property movement and failure including a recommendation to evacuate. The alert also drew attention to the necessity of each homeowner to be vigilant about the stability of their property, seek professional advice and make decisions regarding their own comfort level in their home.

Monitoring of the slope movement has occurred on a weekly, bi-weekly and monthly basis as required through the summer of 2014. Since late July, insignificant movement has been recorded. The situation has not reached a stable state and remains a critical

matter, but given the decreased movement and the onset of winter, the evacuation alert was rescinded on October 31, 2014. This recommendation was again made by the Saskatoon Emergency Measures Organization.

Ongoing Monitoring

A detailed monitoring program remains in place for the Nutana slope. Due to the lack of movement, the frequency of monitoring is currently scaled back and will be increased as movement resumes in the spring of 2015. This monitoring will provide residents with up-to-date information on the slope status. This will help enable them to make informed decisions about their own safety, and the information may be an input to remediation activities they choose to undertake to protect their properties.

Past Slope Remediation Projects

There have been three notable slope stability projects in the past 15 years:

1. Rotary Park at the Broadway Bridge south abutment;
2. Cosmopolitan Park near the University Bridge east abutment; and
3. 17th Street & Saskatchewan Crescent East.

Each of these failures occurred exclusively on public right of way. The City funded these repairs because the affected areas were on public right of way and because further failure would impact public infrastructure.

Next Steps

City Council may choose from a wide number of possible roles for the City at this site. They range from the current approach, which is to monitor the slope movement and provide information to residents, to participating in remediation and contributing financially. The City typically does not contribute financially to remediation or restitution on private property.

There is a wide range of legal and associated risk consequences to the City related to this location. These will be reported to Executive Committee In-Camera, and are of the following nature:

1. Current approach, which is to monitor the site and provide detailed information to adjacent property owners and residents.
2. Offer mediation services, with or without participation by the City.
3. Become actively involved with property owners in the remediation approach.
4. Provide some level of grant or financial aid to property owners.

Public and/or Stakeholder Involvement

Since the initial movement in June 2012, the residents affected have been kept fully informed on the status of the slope and its recorded movements. These updates have been delivered via print and email. Meetings with affected residents have been held in July 2013, May 2014, and June 2014 to discuss, in detail, the extent of the problem and the nature of the evacuation recommendations. Homeowners have also been corresponding with Administration in small groups and one-on-one. The City will continue to keep affected residents informed of the situation in this manner.

Communication Plan

Communication will continue with the residents by providing print and email updates of the monitoring results. Administration will also continue to provide City Council with similar updates as the residents receive them.

Financial Implications

This project and all East Riverbank Stabilization initiatives have been funded by the Storm Water Utility, Capital Project #1493 – TU East Riverbank Stabilization. To date, nearly \$700,000 has been spent on geotechnical engineering to install instrumentation, monitor and analyse the Nutana slope failure. It is anticipated that approximately \$80,000 per year will be required to fund the necessary monitoring for public safety as long as the slope is unstable and moving at the rates that have been seen in the previous two seasons.

Sufficient budget has been allocated in 2015 to manage this.

Due Date for Follow-up and/or Project Completion

Administration will continue its current course of action of monitoring slope movement and informing residents of new information as it is available. Further reports on the updated status of the slope situation will be presented to the Standing Policy Committee on Environment, Utilities and Corporate Services as required.

Public Notice

Public Notice pursuant to Section 3 of Policy No. C01-021, Public Notice Policy, is not required.

Attachments

1. Nutana Slope Failure Overview
2. Conceptual Area Affected by Re-Grading
3. Conceptual Area Affected by Shear Zone Modification
4. Golder Associates Report – Geotechnical Investigation and Evaluation of Conceptual Remedial Options


Report Approval

Written by: Andrew Hildebrandt, Director of Community Standards
Reviewed by: Mike Gutek, Director of Major Projects
Approved by: Jeff Jorgenson, General Manager, Transportation & Utilities
Department
Approved by: Murray Totland, City Manager

Exec AH - Nutana Slope Stability Update-Feb 11-15

Nutana Slope Failure Overview





LEGEND

- BENCHMARK LOCATION (OTHERS)
- ⊕ BENCHMARK LOCATION (GOLDER)
- ⊕ 3015 PANEL BENCHMARKS (GOLDER)
- ⊕ POWER POLE
- ⊕ CANCH BARN
- MANHOLE
- OVERHEAD POWER LINE
- 303 LOT NUMBER

REFERENCE
 AERIAL PHOTOGRAPH PROVIDED BY CITY OF SASKATOON, MAY 15, 2011
 CITY OF SASKATOON/DATA/IM

DRAFT

10 0 10
 SCALE: 1:600 METRES


PROJECT
 City of Saskatoon
 CHERRY LANE
 SLOPE INSTABILITY

CONCEPTUAL AREA AFFECTED BY RE-GRADING

FIGURE: 1

PROJECT	11-1362-0057	DATE	2013
REVISION	001	DATE	2013
CHECKED		DATE	
APPROVED		DATE	

FIGURE: 1



LEGEND

- BOREHOLE LOCATION (OTHERS)
- BOREHOLE LOCATION (CO-CORR)
- 2013 HAZEL BOREHOLE (S1 (OIL/URN))
- POWER POLE
- CATCH BASIN
- MANHOLE
- OVERHEAD POWERLINE
- 303 LOT NUMBERS

REFERENCE
 AERIAL PHOTOGRAPHS PROVIDED BY CITY OF SASKATOON, JAN 15, 2011
 CITY OF SASKATOON DATA

DRAFT

10
0
10
SCALE 1:800
METRES

City of Saskatchewan
CHERRY LANE SLOPE INSTABILITY

CONCEPTUAL AREA AFFECTED BY SHEAR ZONE MODIFICATION

PROJECT	11-1362-0057	DATE	2007 Remedial Ops
DESIGNER	Goldier Associates	SCALE	AS SHOWN
CHECK	WES	NOV	2
DATE	06/11/13		

FIGURE: 2



May 2014

CHERRY LANE SLOPE MOVEMENT, SASKATOON, SK

Geotechnical Investigation and Evaluation of Conceptual Remedial Options

Submitted to:

City of Saskatoon
Infrastructure Services
222 - 3rd Avenue North
Saskatoon, SK S7K 0J5

Attention: Mr. Andrew Hildebrandt

REPORT



Report Number: 11-1362-0057/5100

Distribution:

2 Copies - City of Saskatoon, Saskatoon, SK
2 Copies - Golder Associates Ltd., Saskatoon, SK





Executive Summary

Golder Associates Ltd. was retained by the City of Saskatoon to conduct a geotechnical investigation and evaluation of conceptual remedial options for the slope instability located in the area of Cherry Lane (back alley), the 200 to 300 blocks between the 11th Street East and the Saskatchewan Crescent East, Saskatoon (the Site).

Two slope failures recently occurred in this area, affecting approximately a 120 metre long section of Cherry Lane and the backyards of several houses and buildings. The first failure (referred to as the West Failure) occurred on June 20, 2012. The second failure (referred to as the East Failure) occurred sometime between June 20 and June 24, 2013. The West Failure impacted a slope area approximately 70 metre section of Cherry Lane and 40 metres from the head scarp to the toe; it was most pronounced in the backyards of 229, 231, 233/235 and 237/239 11th Street East, through Cherry Lane, and into the backyard of 222 Saskatchewan Crescent East. The West Failure resulted in the disruption and interference with the Electrical Utility Services, requiring repairs and adjustment, and disruption of the geometry and stability of the public right-of-way land, requiring closure of Cherry Lane. The East Failure affected a slope area approximately 30 metre section of Cherry Lane and 45 metres from the head scarp to the toe; it was most pronounced in the backyard of 303, 305 and 307 11th Street East, through Cherry Lane, and into the backyard of 306 Saskatchewan Crescent East. The West Failure and East Failure were separated by two residential houses/apartment building, 241 11th Street East and 230 Saskatchewan Crescent East. No obvious cracking or slope movement was observed in this slope section between the two failure areas to date (May 2014).

Soil investigation and instrumentation installation were carried out to determine stratigraphy, location of the failure plane, rate of landslide movement and groundwater conditions; which are required for the development of conceptual remedial option. Monitoring of slope movements has been conducted since the West Failure occurred. The slope failures along Cherry Lane are most likely a result of a combination of the geology of the area along the riverbank, the heavy and prolonged precipitation in the spring of 2012 and 2013 that resulted in increased groundwater levels, and changes to the geometry as a result of landscaping of the slope.

The following conceptual remedial options have been evaluated for the Site:

- Option 1: Do nothing option;
- Option 2: Installation of a sub-drainage system;
- Option 3: Slope flattening with the installation of a sub-drainage system; and
- Option 4: Modification of shear zone with installation of a sub-drainage system.

As this Site poses a high risk to the public, infrastructure, and property in the area; a minimum slope factor of safety of 1.5 is recommended as the criteria for the evaluation of conceptual remedial options.



CHERRY LANE GEOTECHNICAL INVESTIGATION AND EVALUATION

Based on the results of the option evaluation, Option 4 is recommended as a potential remedial option for the Site. The conceptual Option 4 involves the shear zone modification along Cherry Lane and the installation of a sub-drainage system (one section along 11th Street East and another along Cherry Lane). The approximate extent of the conceptual shear zone modification area is approximately 120 metres long and 4 to 13 metres wide. The construction cost estimate for this Option is in the range of 10 to 20 million dollars. While the conceptual cost of this option is estimated to be higher than the other three options, this option will result in the least disturbance to the surrounding properties (e.g., the majority of the remedial work can be confined to the area surrounding Cherry Lane), and can achieve the recommended minimum factor of safety of 1.5 for the remedial slope.



Table of Contents

1.0 INTRODUCTION.....	1
2.0 OBJECTIVE AND SCOPE OF WORK	3
3.0 BACKGROUND.....	3
3.1 Riverbank Instability History.....	3
3.2 Historical Slope Stability Condition of the Site	4
3.3 Aerial Photos	6
3.4 Previous Geotechnical Studies	6
3.5 Summary of Existing Foundation Plans	8
3.6 Precipitation Data and Changes in Groundwater Table.....	9
4.0 SITE RECONNAISSANCE	14
5.0 TOPOGRAPHIC SURVEY, GEOTECHNICAL INVESTIGATION AND INSTRUMENTATION INSTALLATION	17
5.1 Topographic Survey.....	17
5.2 Geotechnical Investigation and Instrumentation Installation	17
5.3 Summary of Installed Instrumentation	22
5.3.1 Slope Inclinometers.....	22
5.3.2 Piezometers	22
5.3.3 Survey Pins	23
5.3.4 Tell-Tale Crack Monitors	27
5.3.5 Tilt Plates	27
5.3.6 Settlement Points	27
6.0 TOPOGRAPHY AND STRATIGRAPHY	28
7.0 GROUNDWATER CONDITION	33
8.0 LABORATORY TESTING	35
9.0 INSTRUMENTATION MONITORING RESULTS.....	39
9.1 Slope Inclinometer Results	39
9.2 Piezometers.....	40
9.3 Survey Pin Monitoring.....	43
9.3.1 June 21 to June 28, 2012.....	43
9.3.2 June 28, 2012 to Jun 4, 2013 (100 series pins)	43



Table of Contents (continued)

9.3.3	June 28, 2012 to June 28, 2013 (100 series pins)	43
9.3.4	June 25, 2013 to September 11, 2013	48
9.3.5	September 11, 2013 to October 31, 2013 (300 series pins).....	51
9.4	Monitoring of Structures.....	51
9.4.1	Tell-Tale Crack Monitors	51
9.4.2	Tilt Plates	51
9.4.3	Settlement Points	51
10.0	SLOPE STABILITY ANALYSIS	53
10.1	General	53
10.2	Method of Analysis	53
10.3	Material Properties.....	53
10.4	Uncertainty of Input Parameters	54
10.5	Recommended Factor of Safety	54
10.6	Back-Analysis of Failure Slope	55
10.7	Conceptual Remedial Options	58
10.7.1	Option 1 – Do Nothing.....	58
10.7.2	Option 2 – Installation of Sub-Drainage System	59
10.7.3	Option 3 – Site Re-grading.....	66
10.7.4	Option 4 – Shear Zone Modification.....	70
11.0	SUMMARY.....	74
12.0	CLOSURE.....	76



Table of Contents (continued)

TABLES

Table 1:	Summary of Historical Reports Reviewed.....	7
Table 2:	Summary of Building Foundations in Building Permits	8
Table 3:	Summary of Installed Downhole Instrumentation.....	19
Table 4:	Slope Inclinator Casing Summary Table.....	22
Table 5:	Piezometer Summary Table	23
Table 6:	Atterberg Limit Test Results.....	36
Table 7:	Grain-size Analysis Results	37
Table 8:	Dry Density Test Results	38
Table 9:	Direct Shear Test Results.....	39
Table 10:	Shear Strength Parameters for the Preliminary Slope Stability Analysis	53
Table 11:	Calculated Factor of Safety for Remedial Options	58
Table 12:	Average Slope Gradient for Conceptual Option 3 – Re-grading.....	66
Table 13:	Shear Zone Modification Dimensions for Conceptual Option 4.....	70
Table 14:	Risk/Benefit Summary of Conceptual Remediation Options.....	75

FIGURES

Figure 1:	Site Location Plan.....	2
Figure 2:	Borehole and Cross-Section Location Plan	5
Figure 3:	Saskatoon Area Annual Precipitation (1996 to 2013).....	10
Figure 4:	Saskatoon Area Total Monthly Precipitation (1908 to 2013).....	11
Figure 5:	Saskatoon Area Daily and Cumulative Precipitation (2012)	12
Figure 6:	Saskatoon Area Daily and Cumulative Precipitation (2013)	13
Figure 7:	Topographic Survey Plan (2013)	18
Figure 8:	Instrumentation Location Plan	21
Figure 9:	Cherry Lane Survey Pin Location Plan - 100 Series Pins (2012).....	24
Figure 10:	Cherry Lane Survey Pin Location Plan - 200 Series Pins (2013).....	25
Figure 11:	Cherry Lane Survey Pin Location Plan - 300 Series Pins (2013).....	26
Figure 12:	Cross-Section A-A' (West Failure).....	29
Figure 13:	Cross-Section B-B' (East Failure)	30
Figure 14:	Longitudinal Section C-C' (along Cherry Lane).....	31
Figure 15:	Longitudinal Section D-D' (along 11 th Street).....	32



Table of Contents (continued)

Figure 16:	Historical Groundwater Levels	34
Figure 17:	Monitored Piezometric Levels (2012-2013)	41
Figure 18:	Total Head Measured on October 30, 2013	42
Figure 19:	Monitoring Pin Location Plan for the Period of June 22-24, 2012	44
Figure 20:	Horizontal Slope Movements for 100 Series Pins (from June 28, 2012 to June 4, 2013)	45
Figure 21:	Rate of Horizontal Movement Versus Time for Selected 100 Series Pins	46
Figure 22:	Horizontal Slope Movement for 100 Series Pins (June 28, 2012 to June 27, 2013)	47
Figure 23:	Horizontal Slope Movements for 200 Series Pins (from June 25, 2013 to September 11, 2013)	49
Figure 24:	Rates of Horizontal Movement Versus Time for 200 Series Pins	50
Figure 25:	Results of Tilt Monitoring	52
Figure 26:	Back Analysis - Cross-Section A-A', West Failure	56
Figure 27:	Back Analysis - Cross-Section B-B', East Failure	57
Figure 28:	Slope Stability Analysis for Cross-Section A-A', Do Nothing Option With Low Water Table	60
Figure 29:	Slope Stability Analysis for Cross-Section B-B', Do Nothing Option With Low Water Table	61
Figure 30:	Slope Stability Analysis for Cross-Section A-A, Do Nothing Option With High Water Table	62
Figure 31:	Slope Stability Analysis for Cross-Section B-B', Do Nothing Option With High Water Table	63
Figure 32:	Slope Stability Analysis for Cross-Section A-A', Drainage Option	64
Figure 33:	Slope Stability Analysis for Cross-Section B-B', Drainage Option	65
Figure 34:	Slope Stability Analysis for Cross-Section A-A', Site Re-grading	67
Figure 35:	Slope Stability Analysis for Cross-Section B-B', Site Re-grading	68
Figure 36:	Conceptual Area Affected by Site Re-grading	69
Figure 37:	Slope Stability Analysis for Cross-Section A-A', Shear Zone Modification	71
Figure 38:	Slope Stability Analysis for Cross-Section B-B', Shear Zone Modification	72
Figure 39:	Conceptual Area Affected by Shear Zone Modification Option	73



Table of Contents (continued)

APPENDICES

APPENDIX A

Information and Limitations of this Report

APPENDIX B

Aerial Photographs

APPENDIX C

Field Inspection Photographs

APPENDIX D

Topographic Survey Plan

APPENDIX E

Records of Boreholes

APPENDIX F

Monitoring Data

APPENDIX G

Laboratory Test Results

APPENDIX H

Cost Estimates for Conceptual Remediation Options



1.0 INTRODUCTION

Golder Associates Ltd. (Golder) was retained by the City of Saskatoon (the City) to conduct a geotechnical investigation and evaluation of conceptual remedial options for the slope instability located in the area of Cherry Lane (back alley), the 200 to 300 blocks between the 11th Street East and the Saskatchewan Crescent East, Saskatoon (the Site).

Two slope failures recently occurred in this area, affecting approximately a 120 metre (m) long section of Cherry Lane and the backyards of several houses and buildings. The first failure (referred to as the West Failure) occurred on June 20, 2012. The second failure (referred to as the East Failure) occurred sometime between June 20 and June 24, 2013. Site location, locations of the slope failures and civic addresses of residential properties are shown in Figure 1.

The West Failure impacted a slope area approximately 70 m section of Cherry Lane and 40 m from the head scarp to the toe; it was most pronounced in the backyards of 229, 231, 233/235 and 237/239 11th Street East, through Cherry lane, and into the backyard of 222 Saskatchewan Crescent East. The West Failure resulted in the disruption and interference with the Electrical Utility Services, requiring repairs and adjustment, and disruption of the geometry and stability of the public right-of-way (ROW) land, requiring closure of Cherry Lane. The East Failure affected a slope area approximately 30 m section of Cherry Lane and 45 m from the head scarp to the toe; it was most pronounced in the backyard of 303, 305 and 307 11th Street East, through Cherry Lane, and into the backyard of 306 Saskatchewan Crescent East. The West Failure and East Failure were separated by two residential houses/apartment building, 241 11th Street East and 230 Saskatchewan Crescent East. No obvious cracking or slope movement was observed in this slope section between the two failure areas.

This report presents a summary of field observations, the results of field investigation and monitoring program, assessment of slope stability conditions, and conceptual slope remediation options for the Site.

This report should be read in conjunction with “Information and Limitations of the Report”, included in Appendix A. The reader is specifically directed to this information as it is essential for the proper interpretation and usage of this report.

G:\2011\136211-1362-0057 COS East Riverbank\Figures\Phase 5100 Cherry Lane Remediation\Task 700011-1362-0057 Site Loc Plan.dwg 5/2/2014 9:31 AM



LEGEND

- CRACK LOCATION (APPROXIMATE)
- TOE OF SLUMP (APPROXIMATE)
- 303 LOT NUMBER

REFERENCE

AERIAL PHOTOGRAPH PROVIDED BY CITY OF SASKATOON, MAY 15, 2011



PROJECT		CHERRY LANE SLOPE INSTABILITY	
TITLE			
SITE LOCATION PLAN			
PROJECT		11-1362-0057	FILE No.
DESIGN	LM	08/05/14	SCALE AS SHOWN REV.
CADD	BDS/JDS	08/05/14	FIGURE: 1
CHECK	HV	08/05/14	
REVIEW	PGB	08/05/14	





2.0 OBJECTIVE AND SCOPE OF WORK

The objective of this work was to develop a conceptual remediation plan for the Site (i.e., the West Failure, the East Failure, and the section of Cherry Lane between the two existing failures).

The scope of work for this study, as presented in our work plan dated July 12, 2013 includes:

- project management and meetings;
- geotechnical information review and compilation;
- structural engineering support;
- installation of survey control network and topographic survey;
- development of soil investigation program and monitoring system;
- soil investigation and instrumentation installation;
- soil laboratory testing;
- field monitoring;
- geotechnical analysis;
- development and evaluation of conceptual remediation options; and
- preparation of this engineering report.

Site reconnaissance, slope movement monitoring, and meetings with the City began when the slope movement occurred in June 2012, as part of the emergency response to the slope movement. Prior to July 2013, site reconnaissance and monitoring conducted by Golder was restricted to a portion of the Site owned by the City (i.e., Cherry Lane). Recent site reconnaissance and monitoring have been conducted for the entire Site, which is partially-owned by the City and partially-owned properties of private landowners. These tasks have been continued to date (May 2014); the results of our field observations and monitoring program have been provided to the City following each monitoring visit.

3.0 BACKGROUND

3.1 Riverbank Instability History

The topography of Saskatoon is a generally level plain of low relief dissected by the valley of the South Saskatchewan River. The South Saskatchewan River within Saskatoon runs through glacial till underlying surficial stratified deposits (SSD) of lacustrine clays, silts, and sands. The river is a discharge receptor for many of the aquifer systems in this geographic region. Slope instability along the east riverbank in the City has been an ongoing problem since 1913 (Clifton et al. 1981). Clifton et al. (1981), Clifton (1985), Eckel et al. (2002) and Golder (2008a) provide a detailed review of the geology, hydrogeology, historical slope instability activities and remedial works for the east river bank.



There is an increasing level of slope instability along the riverbank in recent years. High annual precipitation and heavy and prolonged precipitation events occurring in the last few years have increased piezometric levels in soils and contributed to slope instability.

3.2 Historical Slope Stability Condition of the Site

Riverbank instability occurs as a result of shear failure within the soil mass. Slope stability conditions depend on the site stratigraphy, soil materials, slope geometry, groundwater conditions and time. Most of the slope failures occur as shear within the lacustrine clay of the SSD at the contact with the till. The stability of a slope can be negatively affected by a number of activities (Clifton 1985), including: i) adding weight to the slope (such as fills on the slope and snow dumps); ii) increase in the elevation of the water table (resulting from lawn watering, leaking water mains, sewers and storm water lines, surface runoff directed towards the slope, blockage of the zone of seepage by placed fill, and the reduction in evapotranspiration through removal of vegetation, covering the slope with a membrane, or covering the slope with gravel); iii) excavation of the slope face (e.g., for road cuts and basement excavations); iv) removing natural vegetation (e.g., mature trees that tend to stabilize the slope); v) erosion of toe of the slope; and vi) vibrations (e.g., pile driving and explosives).

P. Machibroda Engineering Ltd. (PMEL) (1997) suggested the following primary mechanisms contributing to instability:


- prolonged periods of precipitation and/or spring snowmelt resulting in induced surface infiltration;
- toe erosion at the lower reach of the riverbank; and
- influences from upslope or down slope development including site grading, groundwater discharge or recharge and/or building development.

Clifton (1985) highlights the Cherry Lane area as an area where “existing landslides potentially threaten structures or improvements placed on or near the top of the slopes” and states that “the effects of movement can be seen on several parcels of private property and on several structures”. The report also states that new improvements would require detailed slope stability analysis with particular consideration to sites that “lie on a landform, such as the old head scarps landward from Cherry Lane, where shear strain, however slow, can be expected”.

Following the findings of the Clifton (1985) report, an agreement between Meewasin Valley Authority (MVA) and the City was signed on October 7, 1985 (City of Saskatoon 1985). This agreement outlined the responsibilities of each party in monitoring 17 inclinometers mentioned in the agreement, as well as any additional instrumentation that may be installed pursuant to the agreement. The 17 inclinometers that form the basis of the monitoring program were installed in 1984 and 1985. This agreement recommended monitoring the inclinometers in the spring and fall of each year, with more frequent monitoring during unusually heavy precipitation periods, and at locations where large displacements were observed.

Two inclinometers, designated as SI84-1CL and 85-511 with locations presented on Figure 2 were installed and monitored in Cherry Lane. However Inclinometer SI84-1CL was blocked in 2004 and inclinometer 85-511 was bent in 2006. Inclinometer SI-84 ICL recorded approximately 20 millimetres (mm) of total movement for the period from November 1992 to October 2001. Inclinometer 85-511 recorded approximately 32 mm of total movement for the period from August 1985 to October 2005.

G:\2011\136211-1362-0057 COS East Riverbank\Figures\Phase 5100 Cherry Lane Remediation\Task 700011-1362-0057 Borehole Loc Plan.dwg 5/8/2014 11:25 AM



- REFERENCES**
- GE76 - GOLDER ENGINEERING LTD. APR. 9, 1976. GEOTECHNICAL INVESTIGATION 216, 218 AND 220 SASKATCHEWAN CRESCENT
 - GE77 - GOLDER ENGINEERING LTD. JULY 4, 1977. GEOTECHNICAL SITE INVESTIGATION PROPOSED HOUSING COMPLEX, SASKATCHEWAN CRESCENT
 - PMEL81 - P. MACHIBRODA ENGINEERING LTD. JUNE 17, 1981. GEOTECHNICAL INVESTIGATION PROPOSED APARTMENT BUILDING SASKATCHEWAN CRESCENT, SASKATOON, SASKATCHEWAN
 - CLIF83 - CLIFTON ASSOCIATES LTD. AUG. 17, 1983. GEOTECHNICAL STUDIES PROPOSED PARK TERRACE CONDOMINIUMS 222 SASKATCHEWAN CRESCENT EAST SASKATOON, SK.
 - GAL85 - GOLDER ASSOCIATES LTD. MAY 1985. PROGRESS REPORT NO. 1 SLOPE MONITORING PROGRAM, PARK TERRACE CONDOMINIUMS, 222 SASKATCHEWAN CRESCENT EAST, SASKATOON, SASKATCHEWAN
 - PMEL97 - P. MACHIBRODA ENGINEERING LTD. SEPT. 15, 1997. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED RESIDENTIAL DEVELOPMENT, 237-11TH STREET EAST, SASKATOON, SASKATCHEWAN
 - PMEL03A - P. MACHIBRODA ENGINEERING LTD. SEPTEMBER 11, 2003. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED GARAGE, 306 SASKATCHEWAN CRESCENT EAST, SASKATOON, SASKATCHEWAN, PMEL FILE NO. S03-4869
 - PMEL03B - P. MACHIBRODA ENGINEERING LTD. OCTOBER 31, 2003. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED RESIDENCE, 313-11TH STREET EAST, SASKATOON, SASKATCHEWAN, PMEL FILE NO. S03-4925
 - AMEC05 - AMEC EARTH & ENVIRONMENTAL. JULY 27, 2005. REVISED SLOPE STABILITY ASSESSMENT PROPOSED CONDOMINIUM DEVELOPMENT, 316 SASKATCHEWAN CRESCENT, SASKATOON, SASKATCHEWAN
 - PMEL06 - P. MACHIBRODA ENGINEERING LTD. JULY 14, 2006. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED CONDOMINIUM 316 - SASKATCHEWAN CRESCENT EAST, SASKATOON, SK
 - PMEL07 - P. MACHIBRODA ENGINEERING LTD. JUNE 12, 2007. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED RESIDENCES, 221 & 225 - 11TH STREET EAST, SASKATOON, SK
 - PMEL08 - P. MACHIBRODA ENGINEERING LTD. JULY 8, 2008. PROPOSED COMMERCIAL/RESIDENTIAL DEVELOPMENT 328 SASKATCHEWAN CRESCENT EAST, SASKATOON, SK
 - GAL12 - GOLDER ASSOCIATES LTD. MAY 2013. ASSESSMENT OF SLOPE INSTABILITY AT 200 BLOCK, 11TH STREET EAST.
 - PMEL13 - P. MACHIBRODA ENGINEERING LTD. JULY 18, 2013. SLOPE INSTABILITY 230/306 SASKATCHEWAN CRESCENT SASKATOON, SK. DRAWING NO S13-8517-1 TO 7

- LEGEND**
- ◉ BOREHOLE LOCATION (OTHERS)
 - ◉ BOREHOLE LOCATION (GOLDER)
 - ◉ 2013 & 2012 BOREHOLES LOCATION (GOLDER)
 - POWER POLE
 - CATCH BASIN
 - MANHOLE
 - O/H — OVERHEAD POWER LINE
 - 303 LOT NUMBER

REFERENCE
 AERIAL PHOTOGRAPH PROVIDED BY CITY OF SASKATOON, MAY 15, 2011
 CITY OF SASKATOON DATUM



CITY OF SASKATOON		CHERRY LANE SLOPE INSTABILITY	
BOREHOLE AND CROSS SECTION LOCATION PLAN			
PROJECT	11-1362-0057	FILE No.	
DESIGN	LM 08/05/14	SCALE	AS SHOWN REV. 0
CADD	JDS 08/05/14		
CHECK	HV 08/05/14		
REVIEW	PGB 08/05/14		
Golder Associates <small>Saskatoon, Saskatchewan</small>		FIGURE: 2	



As part of the City's site reconnaissance program for the east riverbank; site reconnaissance for Cherry Lane was conducted yearly by Golder since 2006. The 2012 site reconnaissance was conducted on April 26, 2012. As noted during these inspections, deflected curbs and fences, drops in the pavement and tension cracks were present; however, no noticeable slope movement was observed at the time of inspection.

The City noted that during surveys and inspections in 2012, there was no evidence of leaking water mains, storm drains or sewers in the vicinity of the study area.

3.3 Aerial Photos

Aerial photos covering the City area, including the Site were taken in 1939, 1958, 1961, 1970, 1974, 1977, 1987, 1997, 2001, 2006 and 2011 and are included Appendix B. The site is located in a meander bend of the South Saskatchewan River, where river erosion may affect the stability of the slope. Rotary Park and the fill area immediately north of Saskatchewan Crescent East were constructed in the 1960s. Apartment building 328 on Saskatchewan Crescent East was constructed before a portion of the river immediately north of Saskatchewan Crescent East (now Rotary Park) was filled in in the 1960s. Apartment buildings 222 and 230 on Saskatchewan Crescent East were constructed before 1987. Construction of 233/235 and 237/239 11th Street East and some landscaping work was completed before 2001. The landscaping in the backyards of 233/235 and 237/239 11th Street East was completed before 2006. Construction of 303 11th Street East and landscaping of this property was completed before 2011.

3.4 Previous Geotechnical Studies

A large amount of background information is available on the geology, hydrogeology, slope conditions and soil properties for the east riverbank within the City in general and at the Site. General background information related to slope stability assessment for the east riverbank includes various geologic and hydrogeologic data published in the physical environment of Saskatoon (Christiansen 1968, 1970, 1979, Sauer 1975, Haug et al. 1977, Clifton et al. 1981); riverbank instability study reports prepared for the MVA and the City (Clifton 1985, Golder 2008a, 2013a); and riverbank site reconnaissance and monitoring reports (Eckel et al. 2002, Golder 2013b, AMEC 2005a to 2010, 2013).

Available geotechnical information and documents for the area surrounding the Cherry Lane slope movement include geotechnical and riverbank assessment reports and aerial imagery provided by the City, the MVA and local landowners for the 200 to 300 block of 11th Street East and the 200 to 300 block of Saskatchewan Crescent East in Saskatoon. Table 1 shows a summary of the site specific reports for the Site. These reports were mainly prepared for residential development at various times.



CHERRY LANE GEOTECHNICAL INVESTIGATION AND EVALUATION

Table 1: Summary of Historical Reports Reviewed

Title (Abbreviation)	Author	Year	Location
Geotechnical Investigation 216, 218 and 220 Saskatchewan Crescent (GE76)	Ground Engineering Ltd.	Apr. 9, 1976	222 Saskatchewan Crescent East
Geotechnical Site Investigation Proposed Housing Complex, Saskatchewan Crescent (GE77)	Ground Engineering Ltd.	Jul. 4, 1977	222 Saskatchewan Crescent East
Geotechnical Investigation Proposed Apartment Building Saskatchewan Crescent, Saskatoon, Saskatchewan (PMEL81)	P. Machibroda Engineering Ltd.	Jun. 17, 1981	222 Saskatchewan Crescent East
Geotechnical Studies, Proposed Park Terrace Condominiums 222 Saskatchewan Crescent East Saskatoon, SK (CLIF83)	Clifton Associates Ltd.	Aug. 17, 1983	222 Saskatchewan Crescent East
Progress Report No. 1 Slope Monitoring Program, Park Terrace Condominiums, 222 Saskatchewan Crescent East, Saskatoon, Saskatchewan (GAL85)	Golder Associates Ltd.	May 1985	222 Saskatchewan Crescent East
Slope Instability Study, South Saskatchewan River Bank Saskatoon, Saskatchewan (CLIF85)	Clifton Associates Ltd.	Dec. 23, 1985	East Riverbank
Feasibility of Horizontal Drains for Slope Stabilization East Bank – South Saskatoon, Saskatchewan (GAL89)	Golder Associates Ltd.	Apr. 1989	East Riverbank
Geotechnical Investigation and Slope Stability Study, Proposed Residential Development, 237-11 th Street East, Saskatoon, Saskatchewan (PMEL97)	P. Machibroda Engineering Ltd.	Sept. 15, 1997	237 – 11 th Street East
Geotechnical Investigation and Slope Stability Study, Proposed Garage, 306 Saskatchewan Crescent East, Saskatoon, Saskatchewan, PMEL File No. S03-4869 (PMEL03A)	P. Machibroda Engineering Ltd.	Sept. 11, 2003	306 Saskatchewan Crescent East
Geotechnical Investigation and Slope Stability Study, Proposed Residence, 313-11 th Street East, Saskatoon, Saskatchewan, PMEL File No. S03-4925 (PMEL03B)	P. Machibroda Engineering Ltd.	Oct. 31, 2003	313 – 11 th Street East
Revised Slope Stability Assessment, Proposed Condominium Development, 316 Saskatchewan Crescent, Saskatoon, Saskatchewan (AMEC05)	AMEC Earth & Environmental	Jul. 27, 2005	316 Saskatchewan Crescent East
Geotechnical Investigation, Proposed Idylwyld Lift Station Saskatoon, Saskatchewan (GAL06)	Golder Associates Ltd.	Feb. 2006	East of Sid Buckwold Bridge
Geotechnical Investigation and Slope Stability Study, Proposed Condominium 316 - Saskatchewan Crescent East, Saskatoon, SK (PMEL06)	P. Machibroda Engineering Ltd.	Jul. 14, 2006	316 Saskatchewan Crescent East
Geotechnical Investigation and Slope Stability Study, Proposed Residences, 221 & 225 - 11 th Street East, Saskatoon, SK (PMEL07)	P. Machibroda Engineering Ltd.	Jun. 12, 2007	221 and 225 – 11 th Street East
Proposed Commercial/Residential Development, 328 Saskatchewan Crescent East, Saskatoon, SK (PMEL08)	P. Machibroda Engineering Ltd.	Jul. 8, 2008	328 Saskatchewan Crescent East
Storm Sewer Preservation, East River Bank Slope Stabilization, City of Saskatoon File No. PW 8250-4/IS 7821-3 (GAL08)	Golder Associates Ltd.	Jul. 28, 2008	East Riverbank
Supplementary Comments and Visual Review and Groundwater Monitoring Results, Proposed Condominium 316-Saskatchewan Crescent East Saskatoon, Saskatchewan, PMEL File No. S09-5722.1 (PMEL09)	P. Machibroda Engineering Ltd.	Nov. 16, 2009	316 Saskatchewan Crescent East
Assessment of Slope Instability at 200 to 300 block, 11 th Street East (GAL12)	Golder Associates Ltd.	May 2013a	200 to 300 block, 11 th Street East



In addition to the geotechnical reports listed above, Golder also reviewed building permit information provided by the City for 222 and 230 Saskatchewan Crescent East and 229, 233-236, 239, 241, and 303 – 11th Street East.

3.5 Summary of Existing Foundation Plans

Foundation plans provided to the City as part of the building permit process were reviewed to determine the type and depths of foundation for those buildings located near the Cherry Lane slope failure, and are summarized in Table 2. It is not known if the installed foundations match the proposed building plans provided for review.

Table 2: Summary of Building Foundations in Building Permits

Location	Foundation Type	Foundation Size
222 Saskatchewan Crescent East	cast-in-place concrete piles	23 – 305 mm diameter, 6 m long 88 – 406 mm diameter, 6 m to 14 m long 20 – 600 mm diameter, 10 m to 14 m long
	battered concrete piles	5 – 406 mm diameter, 8 m to 10 m long
230 Saskatchewan Crescent East	cast-in-place concrete piles	2 – 500 mm diameter, 7.6 m long 25 – 406 mm diameter, 6.1 m to 7.9 m long 17 – 406 mm diameter, 3.0 m to 5.8 m long 8 – 406 mm diameter, 0.6 m to 2.7 m long
306 Saskatchewan Crescent East	cast-in-place concrete piles	2 – 254 mm diameter, 3.0 m deep (garage) 1 – 203 mm diameter, 3.0 m deep (garage)
	concrete footings	610 mm square, 203 mm thick and 1,372 mm square, 229 mm thick, step down (ground floor)
229 – 11 th Street East	cast-in-place concrete piles	10 – 305 mm diameter, 6.1 m long
	concrete footings	610 mm square, 203 mm thick, step down, minimum 1.2 m deep
231 – 11 th Street East	Demolished	N/A
233/235 – 11 th Street East	cast-in-place concrete piles	5 – 305 mm diameter, 6.1 m long 15 – 406 mm diameter, 6.1 m to 9.1 m long 15 – 406 mm diameter, 10.7 m to 13.7 m long
237/239 – 11 th Street East	cast-in-place concrete piles	1 – 305 mm diameter, 6.1 m long 17 – 406 mm diameter, 7.6 m to 9.1 m long 14 – 406 mm diameter, 10.7 m to 12.2 m long
241 – 11 th Street East	concrete footings	610 mm strip, 305 mm thick
303 – 11 th Street East	cast-in-place concrete piles	44 – 305 mm diameter, 4.9 m to 5.8 m long 8 – 406 mm diameter, 5.8 m to 7.0 m long
305 – 11 th Street East	cast-in-place concrete piles	8 – 305 mm diameter, 3.7 m long (rear addition)
307 – 11 th Street East	cast-in-place concrete piles	10 – 254 mm diameter, 6.1 m long (back porch) 1 – 203 mm diameter, 2.4 m long (2 nd floor addition)
	concrete footings	610 mm square, 305 mm thick (front veranda)

mm = millimetre; m = metre

Buildings located along Saskatchewan Crescent East are founded on piles and/or strip footings. Foundation elevations of the buildings at 222 and 306 Saskatchewan Crescent East appeared to be below the till/clay contact (i.e., shear zone) and likely have an insignificant effect on the slope movement. The retaining wall and foundation system of 230 Saskatchewan Crescent East, which extended further upslope, appears to have a positive effect to the stability of the upper slope south of this building. However, it is unknown to what degree this retaining wall and foundation system can sustain slope movement.



3.6 Precipitation Data and Changes in Groundwater Table

Groundwater levels in the SSD, especially in the clay layer overlying till, have a significant influence on slope stability at the Site. Increases in groundwater elevation decrease the stability of the slope. In general, groundwater levels vary in response to the amount of water available at the ground surface and the amount of discharge or recharge potential of the soil profile, which are dependent on the variation of precipitation.


The 105 year daily total precipitation record for Saskatoon was analysed by Golder to determine the climatic conditions that may have influenced slope stability at the Site. The record was based on observations from the Environment Canada Reference Climate Station (EC 2013) for the years 1908 to 2007 and the Saskatchewan Research Council Climate Reference Station (SRC-CRS) (SRC 2013) from 2008 to present.



Saskatoon has experienced a wet cycle over the past ten years. Following a severe drought from 1997-2003, precipitation was above average between 2004 and 2006 (Figure 3) with 2005 and 2006 being the fourth and fifth wettest years on record, respectively. Although precipitation was below average between 2007 and 2009, the wettest year on record occurred in 2010 when 708 mm fell, almost double the historic average. High precipitation in 2010 created the antecedent conditions that led to flooding throughout the Prairie Provinces during 2011.


Although low through the winter of 2011-2012, precipitation was above normal during the spring and summer of 2012, particularly May and June (Figure 4). Several rain events between 10 and 25 mm led to a total precipitation of 129.8 mm in May 2012, making it the third wettest year observed between 1908 and 2012 and more than three times the median value of 31.5 mm: 69.6 mm of rain fell in the first week of May with 61.2 mm concentrated on May 5 and 6, 2012. On May 22 and 23, 2012, 33.6 mm of rain fell.

Rainfall in June 2012 was 104.4 mm, making it almost twice the median June precipitation of 54.6 mm (Figure 4). Sustained daily rainfall between June 9 and June 19, 2012 amounted to 81mm with 47.6 mm concentrated on June 9 and 10, 2012 (Figure 5). An additional 18.6 mm fell between June 24 and June 27, 2012.


The 2012-2013 winter snowpack leading up to the spring runoff was high. Cumulative winter precipitation from November 1, 2012 to March 4, 2013 exceeded 200% of average in Saskatoon (WSA 2013). There was below normal precipitation during April and May of 2013 (Figure 5). However, total June precipitation was approximately twice the median with 131.4 mm total precipitation of which 101.6 mm fell between June 13, 2013 and June 23, 2013 (Figure 6).




 City of Saskatoon		CHERRY LANE SLOPE INSTABILITY	
TITLE SASKATOON AREA ANNUAL PRECIPITATION (1996 - 2013)			
 Golder Associates Saskatoon, Saskatchewan		PROJECT 11-1362-0057 DESIGN LNM 08/05/14 CADD CHECK PGB 08/05/14 REVIEW HQV 08/05/14	FILE No. SCALE N/A REV.
			FIGURE: 3



		CHERRY LANE SLOPE INSTABILITY	
TITLE SASKATOON AREA TOTAL PRECIPITATION (1908 - 2013)			
		PROJECT 11-1362-0057 DESIGN LNM 08/05/14 CADD CHECK PGB 08/05/14 REVIEW HQV 08/05/14	FILE No. SCALE N/A REV.
FIGURE: 4			



		CHERRY LANE SLOPE INSTABILITY	
TITLE SASKATOON AREA DAILY AND CUMULATIVE PRECIPITATION (2012)			
	PROJECT 11-1362-0057 DESIGN LNM 08/05/14 CADD CHECK PGB 08/05/14 REVIEW HQV 08/05/14	FILE No. SCALE N/A REV.	FIGURE: 5



		CHERRY LANE SLOPE INSTABILITY	
TITLE SASKATOON AREA DAILY AND CUMULATIVE PRECIPITATION (2013)			
		PROJECT 11-1362-0057 DESIGN LNM 08/05/14 CADD CHECK PGB 08/05/14 REVIEW HQV 08/05/14	FILE No. SCALE N/A REV.
			FIGURE: 6



4.0 SITE RECONNAISSANCE

Visual inspection of the Site has been conducted yearly since 2006; more frequent inspection was conducted after the West Slide Failure in June 2012. Observations during the inspections are presented in Golder (2008a, 2008b, 2009, 2010, 2011, 2013a, 2013b). A summary of key observations and events from visual monitoring across the site has been broken down into a timeline, as follows. Photographs taken during the inspections are presented in Appendix C:

■ 2006 to June 20, 2012

The site had experienced deformation and some movement prior to the West Failure event on June 20, 2012. During the annual site reconnaissance conducted by Golder, active land development (e.g., new house/building construction and landscaping work) was noted; deflected curbs and fences, drops in pavement and tension cracks were observed, as shown in Photos C.1, C.2, and C.3. However, no noticeable slope failure was observed. The toe of the upper slope, along Cherry Lane, prior to the West Failure event is shown in Photo C.4.

■ June 21, 2012

Golder was notified by the City that a slope failure (i.e., the West Failure) had occurred at Cherry Lane. During the site inspection conducted by Golder and the City, the following observations were noted:

- The failure was predominately in the backyards of 229, 231, 233/235 and 237/239 - 11th Street East, through Cherry Lane, and into the backyard of 222 Saskatchewan Crescent East.
- The head scarp of the slide crossed through the backyard of 233/235 - 11th Street East (Photo C.5).
- The toe of the slide crossed through the lane into the backyard of 222 Saskatchewan Crescent East (Photos C.6 and C.7).
- There was cracking behind and displacement of the bricks along the retaining wall in the backyard of 237/239 - 11th Street East (Photos C.8 and C.9).
- There was tension cracking along the lane, behind 237/239 - 11th Street East (Photo C.10).
- There was cracking along the head scarp of the East Failure location (behind 303 and 305 - 11th Street East, Photo C.11).

■ After June 21, 2012

Subsequent to the West Failure, the following activities and observations were made in the summer of 2012. Field inspection and slope monitoring was restricted to portion of the Site owned by the City (i.e., Cherry Lane).

- The SaskEnergy gas line that runs along Cherry Lane was shut off and relocated to reduce the public safety hazard.
- Subsequent to the West Failure event, Golder initiated a slope monitoring program along the lane. The monitoring program included the installation of slope movement and groundwater monitoring equipment.



- Homeowners affected by the slide were advised to seek independent geotechnical advice on their residences.
- Golder continued to conduct visual inspections approximately every other day throughout July 2012. The frequency of site inspections decreased as the rate of slope movement decreased in the fall and winter seasons.
- No significant slope movement was recorded east of 230 Saskatchewan Crescent East along Cherry Lane in 2012.

■ June 24, 2013

Golder was notified by the City that a second slide had occurred at Cherry Lane (i.e., the East Failure); predominantly in the backyards of 303 and 305 - 11th Street East, through Cherry Lane, and into the backyard of 306 Saskatchewan Crescent East. During the site inspection conducted by Golder and the City, the following observations were noted:

- The head scarp of the slide crossed through the backyards of 303 and 305 - 11th Street East; the ground surface had dropped approximately 0.6 m to 0.9 m (Photos C.12 and C.13).
- The toe of the slide was located in the backyard of 306 Saskatchewan Crescent East (Photo C.14).
- There was severe cracking along the lane behind 305 - 11th Street East; the ground surface had dropped approximately 0.5 m (Photo C.15).
- There was tension cracking along the lane behind 303 - 11th Street East (Photo C.16).
- Damage to the retaining wall in the backyard of 237/239 - 11th Street East, in the West Slide area, was also noted to be more extensive during the site inspection on June 24, 2013, compared to the observations noted on June 4 and 20, 2013 (Photos C.17, C.18, and C.19).

■ July to August 2013

Site reconnaissance and monitoring had been conducted for the entire Site. Subsequent to the East Failure, the following activities and observations were made in the summer of 2013.

- Golder conducted daily site inspections for the remainder of June 2013 and the majority of July 2013. Additional slope movement and groundwater monitoring equipment was installed in July and August 2013.
- Homeowners affected by the slide were advised to seek independent geotechnical advice on their residences.
- Cracking along Cherry Lane, between 303 and 305 - 11th Street East and 306 Saskatchewan Crescent East became more severe in the weeks following the East Failure. The drop in the pavement observed behind 305 - 11th Street East increased to approximately 0.5 m by June 4, 2013 (Photo C.20).
- On July 5 and 6, 2013, the City's Public Works was on site to seal tension cracking along the lane and re-grade the section of Cherry Lane behind 305 - 11th Street East (Photo C.21). That night there was a rainfall event that continued into the following morning. That afternoon (July 6, 2013), Golder and the City were notified by the owners of 306 Saskatchewan Crescent East that runoff was flowing from the



parking lot of the apartment building at 328 Saskatchewan Crescent East, along the lane and into the backyard of 306 Saskatchewan Crescent East. The runoff was causing erosion along the lane (Photo C.22) and washing the cold patch material that had been used to re-grade the section of the lane behind 305 - 11th Street East into the backyard of 306 Saskatchewan Crescent East. The City subsequently re-graded the eroded area and constructed a soil berm along the north edge of the lane, adjacent to the backyard of 306 Saskatchewan Crescent East (Photo C.23).

■ July 7, 2013

During the site inspection the following observations were noted:

- A trench was being excavated, by one of the residents, along the east side of the concrete retaining wall between 230 and 306 Saskatchewan Crescent East (Photo C.24). The retaining wall had been flexing and cracking under the loading of the adjacent soil on the lower slope (Photo C.25 and C.26).
- New tension cracks had appeared along the section of lane that had been re-graded, behind 305-11th Street East (Photo C.27). The City's Public Works returned to site to re-grade the lane and seal tension cracks again on July 12 and 21, 2013.

■ July 12, 2013

The City implemented a voluntary evacuation notice due to the accelerated rate of movement that was observed at that time.

■ July 17, 2013

It was noted that the trench that had been excavated along the east side of the concrete retaining wall between 230 and 306 Saskatchewan Crescent East had been partially backfilled with soil (Photo C.28).

■ August 18, 2013

The City Public Works constructed an asphalt berm on the north edge of Cherry Lane, between 303 and 305 - 11th Street East and 306 Saskatchewan Crescent East. A V-shaped berm was installed on the lane, behind 311 - 11th Street East to capture runoff from the parking lot of 328 - 11th Street East and direct the water to a 200 mm diameter pipe on the surface of the lane (Photo C.29).

■ Fall 2013

The frequency of site inspections decreased as slope movement decreased in the fall and winter seasons.



5.0 TOPOGRAPHIC SURVEY, GEOTECHNICAL INVESTIGATION AND INSTRUMENTATION INSTALLATION

5.1 Topographic Survey

Topographic survey was conducted for the West Failure by the City and Golder in 2012 (Golder 2013a) after the West Failure occurred, and then for the entire Site (including 219 to 313 – 11th Street East, 212 to 316 Saskatchewan Crescent East, and Cherry Lane) by Meridian Surveys Ltd. of Saskatoon during the period from July 16 to July 25, 2013, after the East Slide occurred. The survey included the property outlines, roads and landslide features surrounding Cherry Lane. An additional survey of installed instrumentation was completed on September 4, 2013. The surface feature elevations in 2013 were tied to the City Benchmark D1-008 (Orthometric Elevation 499.033 masl), located at the southwest abutment of the Broadway Bridge. The survey is referenced to the NAD 83 Universal Transverse Mercator coordinate system. Figure 7 shows the plan view of the survey area contours and survey features completed in 2013. Locations and co-ordinates of control points and Bench Mark used by Meridian Survey are shown in Appendix D.

5.2 Geotechnical Investigation and Instrumentation Installation

Geotechnical investigation and instrumentation installation for the slope failure study of the Site were completed in 2012 for the West Failure, and in 2013 for both the West Failure and East Failure area. The site investigation was conducted, to supplement the historical site investigation programs, to provide information for assessing soil stratigraphy, soil properties, groundwater, and slope stability conditions for the Site.

A representative of Golder was on site during the field investigation to monitor the borehole drilling, install instrumentation, and collect samples for further laboratory testing. Borehole locations were selected in advance of drilling to determine whether conflicts with utilities or site access existed. Boreholes were drilled through the pavement, surficial stratified deposits, and into glacial till to depths of up to 7.6 metres below ground surface (mbgs) during the 2012 drilling and up to 16.8 mbgs during the 2013 drilling.

Disturbed samples and Shelby Tube samples were collected from each borehole and returned to Golder's Saskatoon Laboratory for further testing and analysis. Disturbed samples were collected from the auger flights at the intervals noted on the Record of Borehole sheets. Shelby tube samples were collected to provide undisturbed samples for further testing. Groundwater conditions at the time of drilling were noted and the boreholes were backfilled with a bentonite-cement grout mixture to ground surface upon the completion of drilling.

G:\2011\136211-1362-0057 COS East Riverbank\Figures\Phase 5100 Cherry Lane Remediation\Task 700011-1362-0057 Topographic Survey Plan.dwg 5/2/2014 10:14 AM





LEGEND

- CONTOURS (MAJOR / MINOR)
- 303 LOT NUMBER

REFERENCE

CONTOURS PROVIDED BY MERIDIAN SURVEYS, AUGUST 2013
 CONTOURS SHOWN AT 0.5m INTERVALS
 AERIAL PHOTOGRAPH PROVIDED BY CITY OF SASKATOON, MAY 15, 2011



PROJECT		 CHERRY LANE SLOPE INSTABILITY	
TITLE			
TOPOGRAPHIC SURVEY PLAN (2013)			
 Golder Associates Saskatoon, Saskatchewan	PROJECT	11-1362-0057	FILE No.
	DESIGN	LM 08/05/14	SCALE AS SHOWN REV.
	CADD	BDS/JDS 08/05/14	FIGURE: 7
	CHECK	HV 08/05/14	
REVIEW	PGB 08/05/14		



CHERRY LANE GEOTECHNICAL INVESTIGATION AND EVALUATION

Downhole instrumentation included slope inclinometer to measure slope movement, and vibrating wire and/or standpipe piezometers to monitor pore water pressure. Vibrating wire piezometers were attached to the slope inclinometer casing or installed in a separate borehole, and the boreholes were backfilled with a bentonite-cement grout mixture to ground surface upon the completion of drilling. The standpipe piezometers installed by Golder consisted of a 50 mm (2 inch) polyvinyl chloride pipe with a 1.5 m (5 ft) slotted screen which were covered with commercial filter sand and then backfilled with a bentonite-cement grout mixture to ground surface. In general, a flush mount casing was installed over the piezometer/slope inclinometer location to protect it from damage. Borehole locations were located in the field by Golder in 2012 and by Meridian Surveys Ltd. in 2013.

A field log was prepared for the boreholes to record the description and relative position of the soil strata, the location of samples, and the instrumentation installation details, in addition to other drilling notes. The Record of Borehole sheets are included in Appendix E.

In addition, six boreholes were drilled and standpipe piezometers installed by PMEL in the area of the East Slide, these piezometers are designated as TH13-1 to TH13-6. A cone penetration test (CPT) was conducted by PMEL at TH13-1 location.

Table 3 provides a summary of installed downhole instrumentation, locations of boreholes are shown in Figure 2, and locations of installed instrumentation are shown in Figure 8. Borehole records and instrumentation installation details are provided in Appendix E.

A Health and Safety Plan was developed prior to the start of drilling activities. All workers involved in the field investigation conducted a daily field hazard level assessment and toolbox meeting prior to starting work in order to identify potential site hazards and to address health and safety concerns.

Table 3: Summary of Installed Downhole Instrumentation

Borehole No.	Slope Inclinometer	VW Piezometer	Standpipe Piezometer	Location	Date of Installation
11-0057-BH1	SI1	VW11192	---	behind 241-11 th Street East on Cherry Lane	23-Jun-12
11-0057-BH2	SI2	VW11200	---	behind 233/235-11 th Street East on Cherry Lane	23-Jun-12
11-0057-BH3	SI3	VW11984	---	behind 231-11 th Street East on Cherry Lane	23-Jun-12
COS-13-001B	COS-13-001B	VW25927	---	behind 305-11 th Street East on Cherry Lane	26-Jul-13
COS-13-002	COS-13-002	VW25400 VW25399	---	front yard of 307-11 th Street East	25-Jul-13
COS-13-003	---	---	COS-13-003	Saskatchewan Crescent East	26-Jul-13
COS-13-004	COS-13-004	VW26020 VW25397	---	backyard of 307-11 th Street East	19-Aug-13



CHERRY LANE GEOTECHNICAL INVESTIGATION AND EVALUATION

Table 3: Summary of Installed Downhole Instrumentation (continued)



Borehole No.	Slope Incliner	VW Piezometer	Standpipe Piezometer	Location	Date of Installation
COS-13-005	COS-13-005	VW25926 VW26019 VW25401	---	empty lot 316 Saskatchewan Crescent East	20-Aug-13
COS-13-006	COS-13-006	VW26018 VW25398	---	empty lot 231-11 th Street East	21-Aug-13
COS-13-007	---	---	COS-13-007	empty lot 231-11 th Street East	21-Aug-13
TH 13-1	---	---	TH 13-1	backyard of 306 Saskatchewan Crescent East	17-Jul-13
TH 13-2	---	---	TH 13-2	backyard of 306 Saskatchewan Crescent East	17-Jul-13
TH 13-3	---	---	TH 13-3	backyard of 306 Saskatchewan Crescent East	17-Jul-13
TH 13-4	---	---	TH 13-4	backyard of 306 Saskatchewan Crescent East	17-Jul-13
TH 13-5	---	---	TH 13-5	backyard of 307-11 th Street East	18-Jul-13
TH 13-6	---	---	TH 13-6	backyard of 30311 th Street East	18-Jul-13

VW = vibrating wire

The 2012 soil investigation and instrumentation installation program was completed on June 23, 2012. Boreholes were drilled on Cherry Lane using Solid Stem Augers through the pavement, surficial stratified deposits, and into glacial till. The drilling was conducted by Paddock Drilling Ltd. with Acker MP-5 drill rig and monitored by Golder. The 2012 field program consisted of five (5) boreholes drilled to the depth ranging between 3.4 to 7.6 mbgs; three (3) slope inclinometers (in boreholes 11-0057-BH1, 11-0057-BH2 and 11-0057-BH3); and three (3) vibrating wire piezometers (in boreholes 11-0057-BH1P, 11-0057-BH2P and 11-0057-BH3).

The 2013 soil investigation and instrumentation installation program was completed using hollow and solid stem augers. The 2013 drilling program consisted of three phases: 1) on July 25 and 26, 2013 with a CME75 truck mounted drill rig operated by Boss Drilling Ltd. of Saskatoon, SK; 2) on August 19, 2013 with an MC4T track mounted drill rig operated by Mobile Augers and Research Ltd. of Saskatoon, SK; and 3) on August 20 and 21, 2013 with an M10 truck mounted drill rig operated by Mobile Augers and Research Ltd. of Saskatoon, SK. The 2013 field program conducted by Golder consisted of eight (8) boreholes drilled to depths ranging between 9.1 m and 16.8 m below ground surface (mbgs); five (5) slope inclinometer casings were installed to depths ranging between 7.5 and 15.5 mbgs (in boreholes COS-13-001B, COS-13-002, and COS-13-004 to COS-13-006); ten (10) vibrating wire piezometers installed to depths ranging between 5.7 mbgs and 16.1 mbgs (in boreholes COS-13-001B, COS-13-002, and COS-13-004 to COS-13-006); and two (2) standpipe piezometers installed to depths of 7.6 mbgs and 4.1 mbgs (in boreholes COS-13-003 and COS 13-007). Six standpipe piezometers installed by PMEL in the area of the East Failure are designated as TH13-1 to TH13-6.

G:\2011\136211-1362-0057 COS East Riverbank\Figures\Phase 5100 Cherry Lane Remediation\Task 700011-1362-0057 Instrument Loc Plan.dwg 5/5/2014 4:31 PM



CONTROL POINTS				
COORDINATE TABLE NAD 83 (CSRS)		UTM ZONE 13		
POINT	NORTHING (m)	EASTING (m)	ORTHOMETRIC ELEVATION (m) HTv2.0	DESCRIPTION
CP-1	5,775,701.84	385,897.84	477.97	24" REBAR WITH PLASTIC CAP
CP-2	5,775,680.32	386,022.25	478.99	24" REBAR WITH PLASTIC CAP
CP-3	5,775,693.72	386,071.10	479.49	24" REBAR WITH PLASTIC CAP
CP-4	5,775,692.40	385,951.67	477.95	GPS CONTROL POINT
TP-4	5,775,565.50	386,118.76	499.32	X IN CONCRETE
TP-5	5,775,549.79	386,001.87	498.05	X IN NORTH RIM CATCH BASIN
TP-7	5,775,566.48	385,909.52	491.32	X IN SOUTH RIM MANHOLE
TP-8	5,775,560.37	385,809.26	484.62	X IN WEST RIM MANHOLE
D1-008	5,775,775.85	386,467.62	499.033	CONTROL TABLET

- LEGEND**
- ⊖ SETTLEMENT POINT LOCATION
 - △ TELL-TALE CRACK LOCATION MONITOR
 - ⊕ TILT PLATE LOCATION
 - ▲ SI & VIBRATING WIRE PIEZOMETER LOCATION
 - STANDPIPE PIEZOMETER LOCATION
 - 303 LOT NUMBER
- REFERENCE**
- LOT LOCATIONS PROVIDED BY CITY OF SASKATOON
CITY OF SASKATOON DATUM



		CHERRY LANE SLOPE INSTABILITY	
INSTRUMENTATION LOCATION PLAN			
PROJECT	11-1362-0057	FILE No.	
DESIGN	LM 08/05/14	SCALE	AS SHOWN REV. 0
CADD	JDS/BDS 08/05/14		
CHECK	HV 08/05/14		
REVIEW	PGB 08/05/14		
		FIGURE: 8	



5.3 Summary of Installed Instrumentation

In addition to the downhole instrumentation (e.g., slope inclinometers, vibrating wire piezometers and standpipe piezometers) other instrumentation was also installed on the ground surface (e.g., survey pins) to monitor ground surface movement, and on the house/building structures (e.g., tilt plate, settlement points, and tell-tale crack monitors) to monitor potential tilt, vertical movement and cracks of the structures.

The following sections summarize the instrumentation installed by Golder to investigate and evaluate slope stability conditions near Cherry Lane. Monitoring data for the instrumentation is included in Appendix F of this report.

5.3.1 Slope Inclinometers

Slope inclinometers are used to determine the magnitude, rate, direction, depth, and type of slope movement. Inclinometer casings were installed in boreholes, in 2012 and 2013, at depths shown in Table 4 to serve as an access tube to guide an inclinometer probe down the borehole. Slope inclinometers were installed 3 m or more into the till (i.e., below the expected zone of movement). The 70 mm diameter glue and snap inclinometer casings were supplied by RST Instruments.

Table 4: Slope Inclinometer Casing Summary Table

Borehole No.	Date of Base Reading	Ground Elevation (masl)	Clay/Till Contact Elevation (masl)
11-0057-BH1P	25-Jun-12	488.25	484.64
11-0057-BH2P	25-Jun-12	485.87	483
11-0057-BH3	25-Jun-12	484.06	N/A
COS-13-001B	27-Jul-13	489.34	482.79
COS-13-002	30-Jul-13	498.48	484.46
COS-13-004	28-Aug-13	491.74	483.05
COS-13-005	28-Aug-13	494.48	482.14
COS-13-006	28-Aug-13	494.77	484.25

masl = metres above sea level

5.3.2 Piezometers

Both vibrating wire type and standpipe type piezometers were installed. Vibrating wire piezometers consist of a pressure transducer, which outputs a frequency signal, and an integral thermistor, which measures the temperature of the transducer and its surroundings. The frequency output and temperature reading are used to calculate piezometric levels in the soil. The installed vibrating wire piezometers were supplied by RST Instruments. The vibrating wire piezometers were equipped with data loggers programmed to record measurements every eight hours. The data was downloaded periodically to evaluate fluctuations in pore-water conditions with time.

Standpipe piezometers consist of slotted and solid sections of polyvinyl chloride (PVC) pipe, and were installed to monitor groundwater elevations within the area. The area around the section of slotted PVC pipe (the intake zone) was backfilled with sand, allowing pore-water to flow into the standpipe. The groundwater elevation near the intake zone was determined by measuring the water elevation in the standpipe.



CHERRY LANE GEOTECHNICAL INVESTIGATION AND EVALUATION

Table 5 summarizes the piezometers installed near Cherry Lane by Golder in 2012 and 2013, including six standpipe piezometers installed by PMEL. The targeted piezometer completion depths were at the Clay/Till contact, in the SSD and in the Till. Locations of piezometers are shown in Figure 8.

Table 5: Piezometer Summary Table



Piezometer Serial No.	Borehole No.	Type	Ground Elevation (masl)	Clay/Till Contact Elevation (masl)	Tip Elevation (masl)	Water Level (Oct 30)	Material at Tip Elevation
VW11192	11-0057-BH1P	VW	488.25	484.64	485.05	485.98	Clay
VW11200	11-0057-BH2P	VW	485.87	483.0	483.43	483.84	Clay
VW11984	11-0057-BH3	VW	484.06	-	482.84	dry	Clay
VW25927	COS-13-001B	VW	489.34	482.79	483.53	485.91	Clay
VW25400	COS-13-002	VW	498.48	484.46	485.38	490.80	Clay
VW25399	COS-13-002	VW	498.48	484.46	482.33	490.12	Till
-	COS-13-003	Standpipe	480.34	-	471.20	473.65	Gravel
VW26020	COS-13-004	VW	491.74	483.05	483.38	486.86	Clay
VW25397	COS-13-004	VW	491.74	483.05	481.50	485.08	Till
VW25926	COS-13-005	VW	494.48	482.14	487.30	dry	Sand
VW26019	COS-13-005	VW	494.48	482.14	482.73	485.93	Clay
VW25401	COS-13-005	VW	494.48	482.14	479.68	484.30	Till
VW26018	COS-13-006	VW	494.77	484.25	484.56	dry	Clay
VW25398	COS-13-006	VW	494.77	484.25	481.51	dry	Till
-	COS-13-007	Standpipe	494.80	-	489.21	dry	Clay
-	TH 13-1	Standpipe	486.55	483.5	482.7	482.73	Till
-	TH 13-2	Standpipe	487.84	484.0	482.0	483.53	Till
-	TH 13-3	Standpipe	487.85	482.8	482.0	483.07	Clay/Till
-	TH 13-4	Standpipe	488.60	483.3	482.2	483.59	Sand and Gravel/Till
-	TH 13-5	Standpipe	491.39	484.2	482.5	484.79	Till
-	TH 13-6	Standpipe	492.73	484.4	484.1	489.83	Clay/Till

masl = metres above sea level

5.3.3 Survey Pins

Three series of pins; 100, 200 and 300 series, were installed for monitoring of ground movement (primarily downslope, horizontal movement) along Cherry Lane. The pins were intended to be surveyed at regular intervals with reference to a reference line and a stable reference mark on Remai Arts Centre building. Pins were replaced in series over time as old pins were damaged or covered over, and to improve the monitoring accuracy. Survey markers were installed for the 300 series of survey pins. Figure 9, Figure 10 and Figure 11 show the location of survey pins of 100 series, 200 series, and 300 series installed by Golder along Cherry Lane, respectively. Survey pins consisted of nails driven into the surface of Cherry Lane. Survey markers consisted of square topped steel pins driven into the surface of Cherry Lane.

G:\2011\136211-1362-0057 COS East Riverbank\Figures\Phase 5100 Cherry Lane Remediation\Task 700011-1362-0057 2012 Series 100 Pins.dwg 5/8/2014 11:31 AM





LEGEND
 ● PIN LOCATION
 303 LOT NUMBER

NOTE
 PINS 100-142 INSTALLED JUNE 28, 2012.

REFERENCE
 AERIAL PHOTOGRAPH PROVIDED BY CITY OF SASKATOON, MAY 15, 2011
 CITY OF SASKATOON DATUM

		CHERRY LANE SLOPE INSTABILITY	
CHERRY LANE SURVEY PIN LOCATION PLAN - 100 SERIES PINS (2012)			
	PROJECT	11-1362-0057	FILE No.
	DESIGN	LM 08/05/14	SCALE AS SHOWN REV. 0
	CADD	JDS 08/05/14	
	CHECK	HV 08/05/14	
	REVIEW	PGB 08/05/14	
FIGURE: 9			

G:\2011\136211-1362-0057 COS East Riverbank\Figures\Phase 5100 Cherry Lane Remediation\Task 700011-1362-0057 2013 Series 200 Pins.dwg 5/8/2014 11:32 AM




LEGEND
 ● PIN LOCATION
 303 LOT NUMBER

NOTE
 PINS 200-216 INSTALLED JUNE 4, 2013
 PINS 217-228 INSTALLED JUNE 25, 2013

REFERENCE
 AERIAL PHOTOGRAPH PROVIDED BY CITY OF SASKATOON, MAY 15, 2011
 CITY OF SASKATOON DATUM

PROJECT		CHERRY LANE SLOPE INSTABILITY	
TITLE			
CHERRY LANE SURVEY PIN LOCATION PLAN - 200 SERIES PINS (2013)			
PROJECT		11-1362-0057	FILE No.
DESIGN	LM	08/05/14	SCALE AS SHOWN REV. 0
CADD	JDS	08/05/14	FIGURE: 10
CHECK	HV	08/05/14	
REVIEW	PGB	08/05/14	

G:\2011\136211-1362-0057 COS East Riverbank\Figures\Phase 5100 Cherry Lane Remediation\Task 700011-1362-0057 2013 Series 300 Pins.dwg 5/8/2014 11:35 AM



LEGEND
 ● PIN LOCATION
 303 LOT NUMBER

NOTE
 PINS INSTALLED SEPTEMBER 13, 2013

REFERENCE
 AERIAL PHOTOGRAPH PROVIDED BY CITY OF SASKATOON, MAY 15, 2011
 CITY OF SASKATOON DATUM

		CHERRY LANE SLOPE INSTABILITY	
CHERRY LANE SURVEY PIN LOCATION PLAN - 300 SERIES PINS (2013)			
	PROJECT	11-1362-0057	FILE No.
	DESIGN	LM 08/05/14	SCALE AS SHOWN REV. 0
	CADD	BDS/JDS 08/05/14	
	CHECK	HV 08/05/14	
	REVIEW	PGB 08/05/14	
			FIGURE: 11



5.3.4 Tell-Tale Crack Monitors

Crack monitors were installed on selected retaining walls where there was an existing crack. The crack monitors consisted of two plates, which were installed to overlap for part of their length, and move relative to each other as a crack opened or closed. Standard Tell-Tale crack monitors were used on flat surfaces, to monitor movement across cracks in vertical and horizontal directions.

Crack monitors were installed at the following locations (Figure 8):

- north face of the retaining wall behind 306 Saskatchewan Crescent East;
- east face of the retaining wall between 230 and 306 Saskatchewan Crescent East; and
- west face of the retaining wall between 230 and 306 Saskatchewan Crescent East.

5.3.5 Tilt Plates

Stainless steel tilt plates were installed on selected external house foundations and retaining walls. Changes in the tilt of the structure were measured using a tilt meter, which allows the tilt of a structure to be monitored on a vertical plane. Measurements were taken periodically, and cover plates were placed on the tilt plates to protect them between readings.

Tilt plates were installed at the following locations (Figure 8):

- North-south retaining wall between 230 and 306 Saskatchewan Crescent East;
- East-west retaining wall at 306 Saskatchewan Crescent East;
- North side of house at 303 – 11th Street East;
- West side of house at 303 – 11th Street East;
- North side of house at 241 – 11th Street East; and
- West side of house at 237 – 11th Street East.

5.3.6 Settlement Points

Building settlement points were installed at selected locations to monitor long term vertical movement of the structure. The settlement points were monitored using precise leveling equipment. Point S14, installed in the southwest corner of 328 Saskatchewan Crescent East, is used as a local temporary bench mark for the settlement monitoring. Elevation of Point S14 has been referenced to the COS D1-008 benchmark elevation. The building settlement surveys are conducted by precise levelling method using Leica DN03 precise digital level equipment. Settlement points were installed at the locations shown on Figure 8.



6.0 TOPOGRAPHY AND STRATIGRAPHY

Borehole information from the various geotechnical reports listed in Section 3.3 was compiled to construct a physical model of the soils at the Site. The boreholes used to construct all cross-sections were obtained from many different studies, and have likely been located using various coordinate systems and survey datums. Efforts were made to reconcile the different elevation datums; however, there may still be some discrepancies in the elevation data due to the use of unknown or older elevation datums, or slope movement. Soil descriptions and laboratory test results were also reviewed and interpreted according to Golder's classification system to provide a more consistent classification of the soils. Two cross-sections, A-A' and B-B' were selected as representative cross-sections for the West Failure and East Failure, respectively. Stratigraphic cross-sections A-A' and B-B' are shown in Figure 12 and Figure 13, respectively. Soil stratigraphic conditions along Cherry Lane and 11th Street East are shown in Figure 14 (longitudinal stratigraphic section C-C') and Figure 15 (longitudinal stratigraphic section D-D'), respectively. Locations of cross sections and longitudinal sections are shown in Figure 2.


In general, the soil profile from 11th Street East to Saskatchewan Crescent East at this location consists of, in descending order: topsoil and/or fill, silty clay or clay of surficial stratified deposits (SSD), and glacial till. The ground elevation varies from approximately 496 m above sea level (masl) to 498 masl along 11th Street East, 481 to 486 masl along Cherry Lane and 474 to 479 masl along Saskatchewan Crescent East. The till/clay contact, at the failure area, is at elevation ranging from 482.8 to 484.6 masl. The silty clay and clay layer overlying till is up to 14 m thick. The topography of the area generally slopes downward to the northwest and the South Saskatchewan River. The river water elevation is at approximately 472 masl.

Topsoil thicknesses were generally less than 0.15 m at the borehole locations, and asphalt and fill up to 3 m deep were noted in various locations. The SSD at TH 97-3 location consist of less than 1 m of poorly graded sands and silty sands, less than 1 m of silt and clayey silt, 1 m to 2 m of poorly graded sands and silty sands, up to 2 m of silts and silty clay, and up to 5 m of highly plastic clay, in descending order.

The highly plastic clay unit is encountered above the till along the 11th Street East (Figure 14) and east portion of the Cherry Lane from TH101 (Figure 15). The contact between this highly plastic clay unit and till is at elevation approximately 485 masl along the 11th Street East, and at elevation approximately from 483 to 487 masl along the Cherry Lane. Extent of this highly plastic clay unit in the northwest portion of the West Failure was not known.


Much of the upper soil profile has been classified as fill in this report due to the unknown extent of slope modification and soil mixing caused by landscaping and slope movement. The layer thicknesses vary across the site, generally decreasing in thickness and daylighting in the lower slope between Cherry Lane and Saskatchewan Crescent East. The deposits of sand, silt and clay are present at the bottom of the slope, in addition to fill which was placed for landscaping and building construction.

The sand layers within the SSD were typically described as wet in the borehole logs reviewed. High sand content and layers of cobbles were noted in the silty clay till material at elevation approximately 467 masl below the SSD (at the TH 101 location).



A
2
CROSS SECTION A-A

LEGEND




STRATIGRAPHIC COLOUR LEGEND


- UNDIFFERENTIATED FILL / SURFICIAL STRATIFIED DEPOSITS
- SURFICIAL STRATIFIED DEPOSITS, SAND AND GRAVEL
- SURFICIAL STRATIFIED DEPOSITS (SSD), SILT, SAND, CLAY
- SURFICIAL STRATIFIED DEPOSITS (SSD), CLAY
- TILL
- GLACIAL SANDS AND GRAVELS
- XXXX COBBLE

REFERENCES

- GE77 - GROUND ENGINEERING LTD. JULY 4, 1977. GEOTECHNICAL SITE INVESTIGATION PROPOSED HOUSING COMPLEX, SASKATCHEWAN CRESCENT
- PMEL97 - P. MACHIBRODA ENGINEERING LTD. SEPT. 15, 1997. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED RESIDENTIAL DEVELOPMENT, 237-11TH STREET EAST, SASKATOON, SASKATCHEWAN




CHERRY LANE SLOPE INSTABILITY																
CROSS SECTION A-A (WEST FAILURE)																
	FIGURE: 12															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>PROJECT</th> <th>11-1362-0057</th> <th>FILE No.</th> </tr> </thead> <tbody> <tr> <td>DESIGN</td> <td>LM 08/05/14</td> <td>SCALE AS SHOWN REV. 0</td> </tr> <tr> <td>CADD</td> <td>BDS/JDS 08/05/14</td> <td></td> </tr> <tr> <td>CHECK</td> <td>HV 08/05/14</td> <td></td> </tr> <tr> <td>REVIEW</td> <td>PGB 08/05/14</td> <td></td> </tr> </tbody> </table>	PROJECT	11-1362-0057	FILE No.	DESIGN	LM 08/05/14	SCALE AS SHOWN REV. 0	CADD	BDS/JDS 08/05/14		CHECK	HV 08/05/14		REVIEW	PGB 08/05/14		
PROJECT	11-1362-0057	FILE No.														
DESIGN	LM 08/05/14	SCALE AS SHOWN REV. 0														
CADD	BDS/JDS 08/05/14															
CHECK	HV 08/05/14															
REVIEW	PGB 08/05/14															



B
2
CROSS SECTION B-B

LEGEND




STRATIGRAPHIC COLOUR LEGEND


- UNDIFFERENTIATED FILL / SURFICIAL STRATIFIED DEPOSITS
- SURFICIAL STRATIFIED DEPOSITS, SAND AND GRAVEL
- SURFICIAL STRATIFIED DEPOSITS (SSD), SILT, SAND, CLAY
- SURFICIAL STRATIFIED DEPOSITS (SSD), CLAY
- TILL
- GLACIAL SANDS AND GRAVELS
- XXXX COBBLE

REFERENCES

- PMEL03A - P. MACHIBRODA ENGINEERING LTD. SEPTEMBER 11, 2003. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED GARAGE, 306 SASKATCHEWAN CRESCENT EAST, SASKATOON, SASKATCHEWAN, PMEL FILE NO. S03-4869
- AMEC05 - AMEC EARTH & ENVIRONMENTAL. JULY 27, 2005. REVISED SLOPE STABILITY ASSESSMENT PROPOSED CONDOMINIUM DEVELOPMENT, 316 SASKATCHEWAN CRESCENT, SASKATOON, SASKATCHEWAN
- PMEL13 - P. MACHIBRODA ENGINEERING LTD. JULY 18, 2013. SLOPE INSTABILITY 230/306 SASKATCHEWAN CRESCENT SASKATOON, SK. DRAWING NO S13-8517-1 TO 7




		CHERRY LANE SLOPE INSTABILITY	
CROSS SECTION B-B (EAST FAILURE)			
		PROJECT 11-1362-0057	FILE No.
DESIGN	LM	08/05/14	SCALE AS SHOWN REV. 0
CADD	BDS/JDS	08/05/14	
CHECK	HV	08/05/14	
REVIEW	PGB	08/05/14	
FIGURE: 13			



C
2
CROSS SECTION C-C

LEGEND



STRATIGRAPHIC COLOUR LEGEND

- UNDIFFERENTIATED FILL / SURFICIAL STRATIFIED DEPOSITS
- SURFICIAL STRATIFIED DEPOSITS, SAND AND GRAVEL
- SURFICIAL STRATIFIED DEPOSITS (SSD), SILT, SAND, CLAY
- SURFICIAL STRATIFIED DEPOSITS (SSD), CLAY
- TILL
- GLACIAL SANDS AND GRAVELS
- XXXX COBBLE


REFERENCES

- CLIF83 - CLIFTON ASSOCIATES LTD. AUG. 17, 1983. GEOTECHNICAL STUDIES PROPOSED PARK TERRACE CONDOMINIUMS 222 SASKATCHEWAN CRESCENT EAST SASKATOON, SK.
- PMEL97 - P. MACHIBRODA ENGINEERING LTD. SEPT. 15, 1997. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED RESIDENTIAL DEVELOPMENT, 237-11TH STREET EAST, SASKATOON, SASKATCHEWAN
- PMEL03A - P. MACHIBRODA ENGINEERING LTD. SEPTEMBER 11, 2003. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED GARAGE, 306 SASKATCHEWAN CRESCENT EAST, SASKATOON, SASKATCHEWAN, PMEL FILE NO. S03-4869
- PMEL03B - P. MACHIBRODA ENGINEERING LTD. OCTOBER 31, 2003. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED RESIDENCE, 313-11TH STREET EAST, SASKATOON, SASKATCHEWAN, PMEL FILE NO. S03-4925
- AMEC05 - AMEC EARTH & ENVIRONMENTAL. JULY 27, 2005. REVISED SLOPE STABILITY ASSESSMENT PROPOSED CONDOMINIUM DEVELOPMENT, 316 SASKATCHEWAN CRESCENT, SASKATOON, SASKATCHEWAN
- PMEL07 - P. MACHIBRODA ENGINEERING LTD. JUNE 12, 2007. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED RESIDENCES, 221 & 225 - 11TH STREET EAST, SASKATOON, SK
- GAL12 - GOLDER ASSOCIATES LTD. MAY 2013. ASSESSMENT OF SLOPE INSTABILITY AT 200 BLOCK, 11TH STREET EAST.




		CHERRY LANE SLOPE INSTABILITY	
LONGITUDINAL CROSS SECTION C-C (ALONG CHERRY LANE)			
		PROJECT 11-1362-0057	FILE No.
DESIGN	LM	08/05/14	SCALE AS SHOWN
CADD	BDS/JDS	08/05/14	REV. 0
CHECK	HV	08/05/14	FIGURE: 14
REVIEW	PGB	08/05/14	

G:\2011\136211-1362-0057 COS East Riverbank\Figures\Phase 5100 Cherry Lane Remediation\Task 700011-1362-0057 Cross Sections.dwg 5/8/2014 11:39 AM



D
2
CROSS SECTION D-D

LEGEND




STRATIGRAPHIC COLOUR LEGEND

- UNDIFFERENTIATED FILL / SURFICIAL STRATIFIED DEPOSITS
- SURFICIAL STRATIFIED DEPOSITS, SAND AND GRAVEL
- SURFICIAL STRATIFIED DEPOSITS (SSD), SILT, SAND, CLAY
- SURFICIAL STRATIFIED DEPOSITS (SSD), CLAY
- TILL
- GLACIAL SANDS AND GRAVELS
- XXXX COBBLE

REFERENCES

- PMEL97 - P. MACHIBRODA ENGINEERING LTD. SEPT. 15, 1997. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED RESIDENTIAL DEVELOPMENT, 237-11TH STREET EAST, SASKATOON, SASKATCHEWAN
- PMEL03B - P. MACHIBRODA ENGINEERING LTD. OCTOBER 31, 2003. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED RESIDENCE, 313-11TH STREET EAST, SASKATOON, SASKATCHEWAN, PMEL FILE NO. S03-4925
- PMEL07 - P. MACHIBRODA ENGINEERING LTD. JUNE 12, 2007. GEOTECHNICAL INVESTIGATION AND SLOPE STABILITY STUDY PROPOSED RESIDENCES, 221 & 225 - 11TH STREET EAST, SASKATOON, SK



		CHERRY LANE SLOPE INSTABILITY	
LONGITUDINAL CROSS SECTION D-D (ALONG 11TH STREET)			
	PROJECT 11-1362-0057		FILE No.
	DESIGN LM	08/05/14	SCALE AS SHOWN
	CADD BDS/JDS	08/05/14	REV. 0
	CHECK HV	08/05/14	
	REVIEW PGB	08/05/14	
FIGURE: 15			



7.0 GROUNDWATER CONDITION

Groundwater levels in the surficial stratified deposits (SSD), particularly in the clay above the till, and in the intertill sand and gravel have significant influence on slope stability in the east riverbank geologic setting. High water levels in the soil can be expected immediately following spring thaw, following intensive irrigation, or after prolonged precipitation. The minimum water table condition is reached during winter when there is minimum recharge. Most slope instability occurs following spring thaw, or after periods of prolonged precipitation (Clifton 1985).


Hamilton and Tao (1977) reported the results of groundwater level measurements in SSD, spanning from six to fourteen years in three study areas in Saskatoon. Groundwater levels vary depending on annual weather cycles, the season of the year, and depending on rainfall and surface runoff conditions. It was reported that groundwater level rises of 6.1 m are reasonable, and 3.0 to 3.7 m might be considered average in clay soils for the typically semi-arid climatic conditions of Saskatoon. It was also reported that annual variation in groundwater levels can range from 0.6 m to more than 2.4 m, depending on many variables related to soil and weather conditions.

Historical groundwater levels (i.e., total head) in the area of Cherry Lane were compiled from data provided in the geotechnical reports reviewed and the East River Bank Monitoring Program reports provided by AMEC (2005b, 2009, 2013), PMEL (1994) and Ireland (2000) and are summarized in Figure 16. The groundwater table slopes downwards across the site from 11th Street to the river. Adjacent to 11th Street, the water table measured in September 1997 in TH07-2 was at about elevation 489.2, approximately 7 m below the ground surface. It should be noted that all groundwater elevations taken from the PMEL (1997) report have been converted from a local elevation presented in the report to be consistent with the surveyed elevations of the slope. It was noted that seepage was encountered during the August 5, 1997 investigation from sand layer at 490.3 masl in TH97-2, located in the front yard of 233/235 11th Street East.

With the exception of the data from piezometer P-84 (Figure 16), which was monitored on an annual basis from 1987 to 2012, there is insufficient data to interpret historical groundwater levels in this area. The highest groundwater elevation measured in P-84 was at 485.9 masl, or approximately 0.3 m below ground surface. It was recorded at this location in May 2012 prior to the occurrence of the West Failure. It should be noted that groundwater levels for this piezometer were generally monitored in fall or winter (October to December), when there is little recharge on ground surface and groundwater levels are expected to be at the lowest. High water table condition can be expected following spring thaw, or after heavy, prolonged precipitation during the summer.

During site walkovers immediately after the West Failure in 2012, water was observed in tension crack at the backyard of house 231 on June 21, 2012 which was approximately 0.5 mbgs. There was also seepage on the slope at the interface between Cherry Lane and Lot 231 immediately after the West Failure; the seepage was lessening since the West Failure occurred.

Groundwater levels recorded from the piezometers installed in 2012 and 2013 are presented and discussed in Section 9.2.



		CHERRY LANE SLOPE INSTABILITY	
HISTORICAL GROUNDWATER LEVELS			
	PROJECT 11-1362-0057 DESIGN LNM 08/05/14 CADD CHECK HQV 08/05/14 REVIEW PGB 08/05/14	FILE No. SCALE N/A REV.	FIGURE: 16



8.0 LABORATORY TESTING

Laboratory tests conducted on representative soil samples included visual classification, water content, Atterberg limits, unit weight, specific gravity, grain size analysis, and direct shear tests. The test results are presented in Appendix G.

Table 6 presents the results of water content tests and Atterberg limit tests for the selected samples. The samples were obtained from the field investigation conducted in 2012 and 2013 along Cherry Lane. Grain size analysis was completed using both the mechanical method (for cohesionless soils) and the hydrometer method (for cohesive soils) for soil classification.

Table 7 presents the results of grain-size analysis. Specific gravity and dry density tests were completed to assess the volume and density relationships of the soil. Dry density tests were completed on select undisturbed samples, the results of which are shown in Table 8.

Direct Shear tests were completed on select undisturbed samples to provide additional material property information for slope stability modelling, the results of which are shown in Table 9.

The silty clay was medium plastic. Measured water contents varied from 23 percent (%) to 35%. Atterberg limit tests for three samples of silty clay indicated that the plastic limit varied from 13% to 25%, liquid limit varied from 31% to 49%, and plasticity index varied from 12% to 29%. Dry density values of 1,371 and 1,306 kilograms per cubic metre (kg/m^3) were determined for sample BH1P-1 and COS-13-005-9, respectively.

The clay was high plastic. Measured water contents varied from 25% to 36%. Atterberg limit tests for four samples of clay indicated that the plastic limit varied from 18% to 27%, liquid limit varied from 50% to 74%, and plasticity index varied from 29% to 50%. Dry density values determined for BH1P-3 and BH2P-2 were $1,405 \text{ kg/m}^3$ and $1,415 \text{ kg/m}^3$, respectively.

The glacial till consisted of a silty clay matrix with some sand and gravel. Measured water contents varied from 8% to 16%. Atterberg limits for sample BH2-5 indicated the till was low plasticity with a plastic limit of 12%, liquid limit of 18% and plasticity index of 6%.



CHERRY LANE GEOTECHNICAL INVESTIGATION AND EVALUATION

Table 6: Atterberg Limit Test Results

Borehole	Material	Sample Number	Sample Elevation (masl)	Water Content (%)	Plastic Limit (%)	Liquid Limit (%)	Plastic Index
COS-13-005	Silty clay	005-5	488.9	23.2	20	49	29
COS-13-005	Silty clay	005-8	486.6	29.5	22	38	16
11-0057-BH1P	Silty clay	BH1P-1	486.4	34.6	21	43	22
11-0057-BH1	Silty clay	BH1-3	486.0	33.9	20	39	19
COS-13-006	Silty clay	006-10	486.0	29.5	13	41	28
COS-13-004	Silty clay	004-8	484.4	33.7	21	46	25
COS-13-005	Silty clay	005-12	483.5	28.7	21	33	12
11-0057-BH2	Silty Clay	BH2-4	483.3	30.4	25	48	23
COS-13-005	Silty clay	005-13	482.8	29.3	19	34	15
11-0057-BH3	Silty clay	BH3-2	482.7	24.3	17	31	14
COS-13-005	Silty clay	005-14	482.2	29.4	14	40	26
COS-13-005	Clayey sand	005-4	490.3	11.5	15	35	20
11-0057-BH3	Clayey sand	BH3-3	482.1	28.4	18	28	10
COS-13-005	Sandy, clayey silt	005-10	485.0	28.2	25	32	7
COS-13-006	Clay	006-3	492.9	25.3	22	65	43
COS-13-006	Clay	006-8	488.4	34.0	23	72	49
COS-13-004	Clay	004-5	487.2	33.6	24	74	50
11-0057-BH1P	Clay	BH1P-3	485.2	35.0	21	50	29
COS-13-002	Clay	002-17	485.2	32.7	21	69	48
COS-13-001	Clay	001-6	484.3	33.9	18	56	38
11-0057-BH1	Clay	BH1-5	484.7	36.3	22	62	40



CHERRY LANE GEOTECHNICAL INVESTIGATION AND EVALUATION

Table 6: Atterberg Limit Test Results (continued)

Borehole	Material	Sample Number	Sample Elevation (masl)	Water Content (%)	Plastic Limit (%)	Liquid Limit (%)	Plastic Index
11-0057-BH2P	Clay	BH2P-2	483.4	34.5	27	72	45
11-0057-BH2	Clay	BH2-2	484.5	31.8	24	55	31
COS-13-003	Clay	003-5	475.4	32.3	19	57	38
11-0057-BH2	Till	BH2-5	482.4	12.9	12	18	6
COS-13-001B	Till	001B-3	482.4	11.0	11	23	12
COS-13-004	Till	004-11	481.8	10.8	12	19	7

masl = metres above sea level; % = percent

Table 7: Grain-size Analysis Results

Borehole	Material	Sample Number	Sample Elevation (masl)	Percent Sand (%)	Percent Silt (%)	Percent Clay (%)
COS-13-004	Silty clay	004-2	491.3	1	68	31
COS-13-002	Silty clay	002-13	488.6	12	69	17
COS-13-005	Silty clay	005-8	486.6	1	72	25
11-0057-BH1P	Silty clay	BH1P-1	486.4	3	69	28
COS-13-006	Silty clay	006-10	486.0	1	66	33
COS-13-005	Silty clay	005-12	483.5	7	74	19
COS-13-005	Silty sand	005-1	494.3	66	23	11
COS-13-006	Silty sand	006-13	482.5	59	31	10
COS-13-001	Silty sand	001-9	481.3	51	41	8
COS-13-005	Sandy, clayey silt	005-10	485.0	14	68	18
COS-13-005	Sandy, clayey silt	005-11	484.3	12	73	15
11-0057-BH3	Clayey sand	BH3-3	482.1	39	47	14



CHERRY LANE GEOTECHNICAL INVESTIGATION AND EVALUATION

Table 7: Grain-size Analysis Results (continued)

Borehole	Material	Sample Number	Sample Elevation (masl)	Percent Sand (%)	Percent Silt (%)	Percent Clay (%)
11-0057-BH1P	Clay	BH1P-3	485.2	1	62	37
11-0057-BH1	Clay	BH1-5	484.7	3	62	35
COS-13-001	Clay	001-6	484.3	3	51	46
11-0057-BH2P	Clay	BH2P-2	483.4	1	47	52
COS-13-001B	Till	001B-3	482.4	44	36	18
COS-13-004	Till	004-11	481.8	49	36	12

masl = metres above sea level; % = percent

Table 8: Dry Density Test Results

Borehole	Material	Sample Number	Sample Elevation (masl)	Water Content (%)	Dry Density (kg/m ³)	Specific Gravity
11-0057-BH1P	Silty clay	BH1P-1	486.4	34.6	1,371	-
COS-13-004	Silty clay	004-7	485.8	30.1	1,699	2.61
COS-13-005	Silty clay	005-9	485.8	23.9	1,306	2.59
11-0057-BH1P	Clay	BH1P-3	485.2	35.0	1,405	-
COS-13-002	Clay	002-17	485.2	32.7	-	2.63
COS-13-001	Clay	001-6	484.3	33.9	-	2.63
11-0057-BH2P	Clay	BH2P-2	483.4	34.5	1,415	-
COS-13-001B	Till	001B-3	482.4	11.0	2,057	-

kg/m³ = kilogram per cubic metre; m = metre; % = percent



Table 9: Direct Shear Test Results

Borehole	Material	Sample Number	Sample Elevation (masl)	Peak		Residual	
				Friction Angle (°)	Cohesion (kPa)	Friction Angle (°)	Cohesion (kPa)
COS-13-004	Silty Clay	004-8	484.4	14.2	32	11.4	0
COS-13-005	Silty Clay	005-13	482.7	31.3	9	31.3	0
11-0057-BH2P	Clay	BH2P-2	483.4	23.7	18	22.0	0
11-0057-BH1P	Clay	BH1P-3	485.2	30.0	0	11.4	0
COS-13-001B	Clay	001B-1	483.8	26.6	12	21.7	0

mbgs = metres below ground surface; kPa = kiloPascal; ° = degrees; % = percent

9.0 INSTRUMENTATION MONITORING RESULTS

9.1 Slope inclinometer Results

The monitoring results for the slope inclinometers are included in Appendix F. Location of historical inclinometers (i.e., SI84-1CL and SI85-511) are shown in Figure 2. Location of inclinometers installed by Golder in 2012 and 2013 are shown on Figure 8.

SI84-1CL: This inclinometer was blocked in 2004. A cumulative movement of 20 mm was recorded between November 2, 1992 and October 12, 2001, approximately 15 mm of which occurred for the period from October 31, 2000 to October 12, 2001.

SI85-511: This inclinometer was bent and not in service since 2006. Approximately 32 mm of cumulative movement was recorded for the period from August 1985 to October 2005. This inclinometer shows a zone of movement at approximately 2.5 mbgs.

11-0057-BH1: Less than 5 mm of cumulative movement was measured between June 25, 2012 and October 30, 2013.

11-0057-BH2: This inclinometer sheared off in June, 2013. A cumulative movement of 30 mm was recorded between June 25 and June 26, 2012. An approximate movement rate of 22 mm/day was recorded before it sheared off. This inclinometer shows a zone of movement at the clay/till interface at approximately elevation 483 masl (about 3.7 mbgs).

11-0057-BH3: Approximately 10 mm of cumulative movement was recorded between June 25, 2012 and October 30, 2013.

COS-13-001B: This inclinometer sheared off sometime between August and October, 2013. A cumulative movement of approximately 65 mm was recorded between July 27 and August 28, 2013. This inclinometer shows a consistent zone of movement at the clay/till interface at approximately elevation 482.8 masl (about 6.5 mbgs).

COS-13-002: Less than 5 mm of movement was recorded between July 30 and October 30, 2013.

COS-13-004: Less than 5 mm of movement was measured in the inclinometer installed in borehole COS-13-004 between August 28 and November 1, 2013.



COS-13-005: Less than 5 mm of movement was recorded between August 28 and October 30, 2013.


COS-13-006: Less than 5 mm of movement was recorded between August 28 and October 30, 2013.

9.2 Piezometers

The results of historical piezometer monitoring are presented and discussed in Section 7.0. Groundwater levels collected from the piezometers installed in 2012 and 2013 is included in Figure 17 for both types of piezometers (e.g., vibrating wire and standpipe). Piezometric levels recorded on October 30, 2013 are presented in Table 5, with the ground surface and till/clay contact elevation, and graphically presented in Figure 18, cross-sections A-A', B-B', and longitudinal sections C-C' and D-D'.


The vibrating wire piezometers installed in boreholes 11-1362-0057 BH1, BH2, and BH3 were installed during a period of high groundwater levels (June 2012); groundwater levels decreased approximately 0.5 m to 1.0 m during the fall and winter seasons. The trends in these vibrating wire piezometers throughout 2013 were as follows:



- Groundwater levels measured on October 30, 2013 show strong downward gradients at the piezometer nests, e.g., a gradient of 0.22 at COS-13-004, 0.53 at COS-13-005 and up to 0.95 at COS 13-004.
- Data collected from the vibrating wire piezometers revealed an increasing trend in groundwater levels starting around April 3, 2013 (at boreholes 11-1362-0057 BH1 and BH2).
- Measured annual variation in groundwater levels in 2013 was 0.86 m at 11-0057 BH3 and 1.93 m at 11-0057 BH2.
- The highest groundwater level recorded at borehole 11-1362-0057 BH1 was 487.3 masl (about 1.0 mbgs) on May 4, 2013.
- High groundwater levels recorded at borehole 11-1362-0057 BH2 were 485.3 masl (about 0.6 mbgs) and 485.4 masl (about 0.5 mbgs), recorded on April 27 and June 14, 2013, respectively.
- The highest groundwater level recorded in borehole 11-1362-0057 BH3 was 483.7 masl (about 0.4 mbgs) on May 8, 2013.
- Groundwater levels recorded at 11-0057 BH1 and BH2 started to decrease early in July 2013.



Notes:
 1) Dashed lines indicate negative pore water pressures.
 2) Piezometer TH13-1 to TH13-6 were installed by P.Machibroda Engineering Ltd. (PMEL) in July 2013.

		CHERRY LANE SLOPE INSTABILITY	
MONITORED PIEZOMETRIC LEVELS (2012-2013)			
	PROJECT	11-1362-0057	FILE No.
	DESIGN	LNK 08/05/14	SCALE N/A
	CADD		REV.
	CHECK	PGB 08/05/14	FIGURE: 17
REVIEW	HQV 08/05/14		



PROJECT		 City of Saskatoon		CHERRY LANE SLOPE INSTABILITY	
TITLE					
TOTAL HEAD MEASURED ON OCTOBER 30, 2013					
PROJECT		11-1362-0057		FILE No.	
DESIGN	LNLM	08/05/14	SCALE	N/A	REV.
CADD					
CHECK	PGB	08/05/14	FIGURE: 18		
REVIEW	HQV	08/05/14			
 Golder Associates Saskatoon, Saskatchewan					



9.3 Survey Pin Monitoring

9.3.1 June 21 to June 28, 2012

A network of survey pins was installed within the West Failure area and monitored daily for the period from June 21 to June 28, 2012, immediately after the West Failure occurred using a Total Station. Figure 19 presents locations of the survey pins installed for this monitoring period and horizontal movement vectors for selected survey pins. The horizontal movement vectors were determined for the period from June 22 to June 24, 2012. A summary of the results of ground movement monitoring for this period is as follows:

- Cherry Lane behind 233-11th Street East (Pin 18 location) moved 260 mm down slope and pushed up 0.05 m for the monitoring period from June 22 to 28. The rate of movement reduced from 110 mm/day from June 22 to June 23, to approximately 27 mm/day from June 24 to June 28, 2012.
- Cherry Lane behind 237-11th Street East (Pin 34) moved 220 mm down slope and dropped 30 mm for the monitoring period from June 22 to 28.
- The toe of the failure in the backyard of 222 Saskatchewan Crescent East (Pin 31) moved 150 mm from June 22 to June 24, 2012.

9.3.2 June 28, 2012 to Jun 4, 2013 (100 series pins)

Survey Pins 100 to 142 (Figure 9) were installed on June 28, 2012, along Cherry Lane at approximately 5 m intervals, to monitor the slope movement along the lane using a survey line. This series of pins was surveyed from July 4, 2012 to June 4, 2013. Horizontal movement of this series of survey pins was monitored every third day from June 28 to August 2, 2012; the rate of movement then reduced, and the frequency of monitoring was reduced to weekly. Cumulative horizontal movements and rates of movement between June 28, 2012 and June 4, 2013 are shown in Figure 20 and Figure 21, respectively.

A summary of the results of ground movement monitoring for this series of survey pins is as follows:

- Monitoring results show that a 45 m section of Cherry Lane, from Pin 112 to Pin 125, was impacted. No significant movement was measured east of Pin 112 or west of Pin 125.
- Total horizontal movement of 115 mm was measured behind 233/235 – 11th Street East (Pin 120 location) from June 28 to September 13, 2012.
- Recorded rate of movement reduced significantly from 12 mm/day at the start of monitoring (June 28, 2012) to less than 1 mm/day in early September 2012. Less than 5 mm of movement was monitored between February 4 and June 4, 2013

9.3.3 June 28, 2012 to June 28, 2013 (100 series pins)

Figure 22 presents the results of GPS survey of the 100 series pins between June 28, 2012 and June 27, 2013 for the Cherry Lane at the East Failure. The results show 765 mm of horizontal movement for Pin 106, 555 mm for Pin 107, and 366 mm for Pin 108. Most of these movements occurred in June 2013 because less than 5 mm of movement was measured by line survey for this location up to June 4, 2013 (Figure 20).

G:\2011\136211-1362-0057 COS East Riverbank\Figures\Phase 5100 Cherry Lane Remediation\Task 700011-1362-0057 Monitoring Pin Vectors.dwg 5/2/2014 2:38 PM




PIN MOVEMENT (BETWEEN JUNE 22-24, 2012)	
PIN NUMBER	RECORDED MOVEMENT (mm)
PIN13	20
PIN14	70
PIN15	91
PIN16	81
PIN17	90
PIN18	150
PIN19	76
PIN21	73
PIN22	91
PIN23	30
PIN29	112
PIN30	41
PIN31	150
PIN32	81
PIN33	89
PIN34	100
PIN35	110
PIN37	36

LEGEND


- PIN MOVEMENT VECTOR
- CRACK LOCATION
- TOE OF SLUMP

REFERENCE

AERIAL PHOTOGRAPH PROVIDED BY CITY OF SASKATOON




		CHERRY LANE SLOPE INSTABILITY	
MONITORING PIN LOCATION PLAN FOR THE PERIOD OF JUNE 22-24, 2012			
	PROJECT 11-1362-0057 DESIGN CADD JDS 02/05/14 CHECK REVIEW	FILE No. SCALE AS SHOWN REV.	FIGURE: 19






- Notes:
- 1) Positive values indicate down slope movement.
 - 2) Pins 100 to 142 were installed June 28, 2012.

		CHERRY LANE SLOPE INSTABILITY	
HORIZONTAL SLOPE MOVEMENT, 100 SERIES PINS (June 28, 2012 to June 4, 2013)			
	PROJECT	11-1362-0057	FILE No.
	DESIGN	LNLM	08/05/14
	CADD		
	CHECK	HQV	08/05/14
REVIEW	PGB	08/05/14	SCALE N/A REV.
			FIGURE: 20



- Notes:
- 1) Positive values indicate down slope movement.
 - 2) Pins 117 to 123 were installed June 28, 2012.

PROJECT		 CHERRY LANE SLOPE INSTABILITY	
TITLE			
RATE OF MOVEMENT vs TIME FOR SELECTED 100 SERIES PINS			
 Golder Associates Saskatoon, Saskatchewan	PROJECT	11-1362-0057	FILE No.
	DESIGN	LNLM	08/05/14
	CADD		
	CHECK	HQV	08/05/14
REVIEW	PGB	08/05/14	SCALE N/A REV.
			FIGURE: 21



Notes:
 1) Positive values indicate down slope movement.
 2) Pins 100 to 142 were installed June 28, 2012.

		CHERRY LANE SLOPE INSTABILITY	
HORIZONTAL SLOPE MOVEMENT, 100 SERIES PINS (June 28, 2012 to June 27, 2013)			
	PROJECT	11-1362-0057	FILE No.
	DESIGN	LMN 08/05/14	SCALE N/A REV.
	CADD		
	CHECK	HQV 08/05/14	
	REVIEW	PGB 08/05/14	
			FIGURE: 22




9.3.4 June 25, 2013 to September 11, 2013

The 100 series pins were replaced with Survey Pins 200 to 228 (Figure 10) to monitor horizontal slope movement along the Cherry Lane. This series of pins was surveyed from June 25 to September 11, 2013. Cumulative horizontal movements and rates of movement during this period are shown in Figure 23 and Figure 24, respectively. A summary of the ground movement monitoring for this series of survey pins is as follows:


- Monitoring results show that a 45 m section of Cherry Lane, from Pin 202 to Pin 213, was impacted within the West Failure area and a 35 m section of Cherry Lane, from Pin 218 to Pin 226, was impacted within the East Failure area.
- West Failure:
 - Rate of movement of approximately 1.8 mm/day was measured behind 233/235 and 237/239 - 11th Street East (Pin 205 to 210 locations) between June 4 and 25, 2013.
 - Rate of movement of approximately 63 mm/day was measured behind 237/239 - 11th Street East (Pin 211 location) between June 25 and 30, 2013; the rate of movement at this location decreased to approximately 13 mm/day, between June 30 and July 2, 2013.
 - Rate of movement of approximately 41 mm/day measured behind 233/235 - 11th Street East (Pin 206 location) between June 30 and July 2, 2013.
 - Movement between zero and 7.5 mm/day was measured within the West Failure area between July 2 and September 11, 2013; except for behind 233/235 - 11th Street East (Pin 207 location) where a rate of movement of 12.5 mm/day was measured between July 12 and 14, 2013.
- East Failure:
 - Rate of movement measured behind 303, 305, and 307 - 11th Street East (Pin 220 to 224 location) was approximately 50 mm/day to 75 mm/day between June 25 and 30, 2013; the rate of movement at this location decreased to approximately 8 mm/day to 33 mm/day between June 30 and July 5, 2013; rate of movement at this location then increased to approximately 13 mm/day to 92 mm/day between July 5 and 8, 2013.
 - Rate of movement behind 305 - 11th Street East (Pin 223) increased from approximately 13 mm/day, during the June 5 to 8, 2013 monitoring period, to 195 mm/day, during the June 8 to 10, 2013 monitoring period.
 - Rate of movement generally decreased after July 10, 2013; movements between zero and 12 mm/day were measured after July 24, 2013.

The rate of movement for the 200 series of pins has been less than 5 mm since July 2013 at the West Failure and since August 2013 at the East Failure.





- Notes:
- 1) Positive values indicate down slope movement.
 - 2) Pins 200 to 216 were installed June 4, 2013.
 - 3) Pins 217 to 228 were installed June 25, 2013.

		CHERRY LANE SLOPE INSTABILITY	
HORIZONTAL SLOPE MOVEMENT, 200 SERIES PINS (June 25, 2013 to Sept. 11, 2013)			
	PROJECT	11-1362-0057	FILE No.
	DESIGN	LNLM 08/05/14	SCALE N/A
	CADD		REV.
	CHECK	HQV 08/05/14	FIGURE: 23
REVIEW	PGB 08/05/14		



Notes:
 1) Positive values indicate down slope movement.
 2) Pins 206 to 211 were installed June 4, 2013.

PROJECT		 CHERRY LANE SLOPE INSTABILITY	
TITLE			
RATE OF MOVEMENT vs TIME FOR SELECTED 200 SERIES PINS			
 Golder Associates Saskatoon, Saskatchewan	PROJECT	11-1362-0057	FILE No.
	DESIGN	LNLM	08/05/14
	CADD		SCALE N/A
	CHECK	HQV	08/05/14
REVIEW	PGB	08/05/14	REV.
			FIGURE: 24



9.3.5 September 11, 2013 to October 31, 2013 (300 series pins)

More permanent survey markers, numbered 303 to 327 were installed on September 13, 2013 to monitor slope movement along Cherry Lane, and will continue to be monitored over time. Locations of these survey markers are shown in Figure 11. The 300 series pins were surveyed on September 16, September 25 and October 31, 2013. Less than 5 mm of movements, which are in a range of measurement accuracy, were measured between September 13 and October 31, 2013.

9.4 Monitoring of Structures

9.4.1 Tell-Tale Crack Monitors

Tell-tale cracks monitors were monitored approximately every 10 days from August 7 to October 30, 2013. No noticeable crack developments were noticed for this monitoring period. Photographs of the crack monitors are included in Appendix F.


9.4.2 Tilt Plates

Tilt plates were monitored approximately every 10 days from August 13 to October 30, 2013. The results of tilt plate measurement are shown in Figure 25. During the monitoring period, a tilt of approximately 0.065 degrees towards the west direction was measured at the tilt plate located on the north-south retaining wall between 230 and 306 Saskatchewan Crescent East. The tilt plate located at 241 – 11th Street has measured a steady increase in tilt angle to 0.024 degrees; however total tilt is near the expected range of measurement accuracy and movement for this structure. Monitoring of the remaining tilt plates have measured variable results which were within the expected range of movement for most structures depending on time of day, weather and other factors.

A tilt plate was installed on the north side of the building at 1721 – 8th Street E. (Golder Associates Ltd.) to provide a check of the expected range of tilt of building due to climate and temperature changes. During the monitoring period, the angle of tilt at this location ranged from 0 to -0.009 degrees.

9.4.3 Settlement Points

Settlement Points were monitored on August 28 and 29, September 18, and November 28 and 29, 2013. The results of settlement monitoring from August 28 to November 29 are presented in Appendix F. The results of the settlement data analysis indicate that no noticeable differential settlement of the structures have been measured to date (November 2013).



Note: Positive changes in tilt indicate tilting toward the monitoring structure.

		CHERRY LANE SLOPE INSTABILITY			
RESULTS OF TILT MONITORING					
		PROJECT 11-1362-0057 DESIGN LNM 08/05/14 CADD CHECK PGB 08/05/14 REVIEW HQV 08/05/14	FILE No. SCALE N/A REV.01	FIGURE: 25	



10.0 SLOPE STABILITY ANALYSIS

10.1 General

Stability analyses of the Cherry Lane site were performed in order to identify failure mechanisms at the site and to evaluate conceptual remedial options.

The following information was used to model the riverbank slope at the Site:

- Ground surface topography was obtained from the topographic survey completed by Meridian in July 2013.
- Stratigraphy was inferred from review of available geotechnical reports and field investigations by Golder.
- Groundwater conditions were inferred from existing piezometric data.
- Geometry of the slip surface was inferred from observed landslide features, inclinometer data and site stratigraphy.
- Soil parameters used in this report were based on site specific laboratory test results, back-analysed values, or based on typical values reported in the literature.

10.2 Method of Analysis

The slope stability analysis was performed using the computer software SLOPE/W, marketed by Geo-Slope International Ltd. (2007). Two-dimensional analyses were conducted using the Morgenstern-Price limit equilibrium method.

10.3 Material Properties

Material properties for the slope stability analysis were selected based upon current and historical laboratory testing results for the Cherry Lane area and Saskatoon region. Table 10 shows the shear strength properties used for the slope stability analysis. Shear strength parameters for the shear zone are back-analyzed values. Effective cohesion value of 10 kiloPascals (kPa) was used for the silty clay, and clay materials to account for the contribution from soil suction to the unsaturated shear strength of these materials. Assumed material properties of fill or modified soils for several conceptual remediation options are also included, based on typical values.

Table 10: Shear Strength Parameters for the Preliminary Slope Stability Analysis

Material	Unit Weight (kN/m ³)	Effective Cohesion (kPa)	Effective Friction Angle (degrees)
Fill	19	5	22
Silty Clay	19	10	25
Clay	19	10	22
Shear Zone	19	0	12*
Till	impenetrable	-	-
Shear Zone Modification	20	0	30

*Back analysed value; kN/m³ = kiloNewtons per cubic metre; kPa = kiloPascal



10.4 Uncertainty of Input Parameters

There is uncertainty in the input data (e.g., till/clay contact, soil properties and piezometric conditions) for the analysis. A sensitivity analysis, where the influence of variations in each input variable is isolated, can be conducted to evaluate the implications of uncertainty in the results. A probabilistic analysis can be used for assessing the reliability of the slope stability conditions. Sensitivity analysis and probabilistic analysis were not conducted at this stage of the study where a conceptual remediation is being developed. Further soil investigation and laboratory tests, sensitivity analysis and probabilistic analysis may be recommended for detailed design if one of the remediation options is to be constructed.

10.5 Recommended Factor of Safety

The stability condition of the slope is evaluated in terms of a calculated factor of safety, which is the ratio of the resisting forces/moments to the driving forces/moments. The factor of safety of a slope can be calculated in terms of all the forces and moments acting on the slope. Based on the limit equilibrium analysis, a computed factor of safety of 1.0 means the available resisting forces (e.g., the available shear strength of the soil along the sliding plane) have been mobilized and a condition of equilibrium exists and failure occurs. A computed factor of safety of greater than 1.0 means that the resisting forces are more than are required for a condition of limiting equilibrium and the slope is in a stable condition.

Determination of a minimum acceptable factor of safety (FS) for a slope stability model depends on several factors, including: i) the assumptions necessary to complete the analysis; ii) the reliability of the input data, particularly shear strength and pore-water pressure conditions; and iii) the consequence of failure. For the Cherry Lane area, potential changes in the slope geometry, additional structural loads and piezometric conditions can occur through unknown future development and landscaping work, therefore these potential unknown changes should be considered.

The consequence of failure (or risk) is an important factor to take into consideration when determining an acceptable factor of safety for design purposes. A lower factors of safety would be accepted on a slope where movement would result in little property damage or pose little hazard to public safety. A higher FS is typically required when risk to public safety and economic loss are involved.

Golder reviewed existing geotechnical reports for the site, the MVA policy (MVA 2004), and policies of other municipalities or government agencies that have high risk slope development. Existing geotechnical reports for the area specified a minimum FS of 1.3 to 1.5 depending on the site studied. In a slope instability study of the east riverbank conducted for MVA, Clifton (1985) recommended a desirable FS of 1.5 for slope improvement involving substantial risk of economic loss and some public safety considerations; and a minimum FS of 1.3 with monitoring was recommended. The MVA policy does not specify a minimum FS, with the caveat that any construction should not increase the instability of the slope, before or after construction.

As this Site poses a high risk to the people and structures on the 200 to 300 blocks of 11th Street East and Saskatchewan Crescent East, difficulties in maintaining a monitoring program in the residential properties, and uncertainty associated with future development, a FS of 1.5 is recommended for the design criteria for the Site under consideration.



10.6 Back-Analysis of Failure Slope

As the slope has already failed, a stability back-analysis can be conducted. The back-analysis method models the geometry, soil, and groundwater conditions at failure, indicated by a factor of safety (FS) of 1.0. Back-analysis is shown in Figure 26 for the West Failure and Figure 27 for the East Failure.


The condition modelled for back-analysis was for a time after the initial failure when the topography was surveyed, but when the slope was still actively moving. As such, groundwater levels shown in the model may be lower than those at the time of initial failure; but they are higher than those measured in the fall or winter months (Figure 17). Effective shear strength parameters of the clay at shear zone were expected to be near or at residual (i.e., having undergone movement).

Loading was not applied to any part of the slope within the stability analyses as it is understood that the houses within this area are founded on piles and therefore their associated vertical loads are distributed to a founding layer outside of the sliding mass. The retaining walls and large boulders present within the backyards of Lots 233/235 and 235/237 were modelled as soil within the stability analysis due to unknown geometries of these features. Retaining walls for the residences along Saskatchewan Crescent East were modelled as gravity walls and were based upon the geometry provided in the building permit plans. The slope stability analyses assume that the existing reinforced concrete wall and slab system of the basement structure of 222 Saskatchewan Crescent East (cross-section A-A'), and retaining wall behind 306 Saskatchewan Crescent East (cross-section B-B') were impenetrable. To date, no noticeable movements were observed at these two structures. The resistance of these structures against landslide activity in the future is currently unknown.

The slip surface of the sliding soil mass is in surficial stratified deposits at the contact between the clay and the underlying till. Therefore, a composite slope failure along a slip surface at the interface between the clay and till was considered in the analyses.

Cross-sections A-A and B-B were selected as the primary section for analysis for the West Failure and East Failure, respectively. The location of the cross-sections is shown on Figure 2. Figure 12 and Figure 13 show the inferred stratigraphic soil profiles along each cross-section. Both the West Failure and East Failure were back-analysed to determine the residual (or large strain) shear strength parameters corresponding to failure or a FS of 1.0.


Name: Fill Unit Weight: 19 kN/m³ Cohesion: 5 kPa Phi: 22 °
 Name: Silty Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 25 °
 Name: Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 22 °
 Name: Shear zone Unit Weight: 19 kN/m³ Cohesion: 0 kPa Phi: 12 °
 Name: Till





Cross Section: A-A' (West Failure)
 File Name: AA Back Analysis_v2.gsz

		CHERRY LANE SLOPE INSTABILITY	
BACK ANALYSIS - CROSS SECTION A-A' WEST FAILURE			
	PROJECT	11-1362-0057	FILE No.
	DESIGN	LNLM 08/05/14	SCALE N/A REV.
	CADD	HQV 08/05/14	FIGURE: 26
	REVIEW	PGB 08/05/14	

Name: Fill Unit Weight: 19 kN/m³ Cohesion: 5 kPa Phi: 22 °
 Name: Silty Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 25 °
 Name: Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 22 °
 Name: Shear zone Unit Weight: 19 kN/m³ Cohesion: 0 kPa Phi: 12 °
 Name: Till
 Name: Retaining wall



PROJECT		 CHERRY LANE SLOPE INSTABILITY	
TITLE			
BACK ANALYSIS - CROSS SECTION B-B' EAST FAILURE			
 Golder Associates Saskatoon, Saskatchewan	PROJECT	11-1362-0057	FILE No.
	DESIGN	LNLM 08/05/14	SCALE N/A
	CADD		REV.
	CHECK	PGB 08/05/14	
REVIEW	HQV 08/05/14		
			FIGURE: 27



10.7 Conceptual Remedial Options

A number of conceptual remedial options were considered for the remediation of the slope, including:

- do nothing;
- installation of sub-drainage system to lower groundwater tables;
- re-grading of existing slope; and
- modification of the shear zone to increase shear strength.

It was understood that the primary focus of the slope remediation was to preserve existing residences along 11th Street East and Saskatchewan Crescent East, and maintain vehicle access along Cherry Lane. As discussed in Section 10.5, the required slope factor of safety for the conceptual remedial options was at least 1.5. Constructability and cost effectiveness were also considered in the process of evaluating conceptual remedial options.

Options evaluated are conceptual in nature, meaning specific design details such as detailed geometry, method of construction, sourcing and supply of materials, coordination of activities, etc. have not been considered.

Table 11 summarizes the calculated factor of safety (FS) for a number of conceptual remedial options, which is discussed in detail in the following sections.

Table 11: Calculated Factor of Safety for Remedial Options

Analysed Scenarios	Cross-section	Calculated FS	Figure
Back analysis	A-A'	1.00	26
	B-B'	1.00	27
Option 1: Do nothing, low groundwater table	A-A'	1.03	28
	B-B'	1.09	29
Option 1: Do nothing, high groundwater table	A-A'	0.89	30
	B-B'	0.87	31
Option 2: Installation of sub-drainage system	A-A'	1.03	32
	B-B'	1.26	33
Option 3: Site regrading with sub-drainage system	A-A'	1.51	34
	B-B'	1.50	35
Option 4: Shear zone modification with sub-drainage system	A-A'	1.51	37
	B-B'	1.51	38

FS = Factor of Safety

10.7.1 Option 1 – Do Nothing

The first remedial option considered was leaving the slope in its existing condition. Based on the slope stability analysis conducted, it is likely that the slope at the East and West Failure locations will continue to move, likely on a seasonal basis with higher rates of movement in the spring when groundwater levels in the area are high. Rates of movement are expected to be low in the winter months and in dry years where the groundwater table is at or near the contact surface between the glacial till and surficial stratified deposits. As noted in Sections 3.6 and 7.0, groundwater level fluctuations of up to 2 m during a year and up to 6 m in the long term are measured.



Figure 28 and Figure 29 show the stability analyses for the do nothing option, with the piezometric levels approximately 1 m lower than those used on the back-analysis to represent slope instability conditions. The calculated factors of safety are 1.03 and 1.09 for cross-sections A-A' and B-B', respectively, for the case where nothing is done other than lowering the groundwater table.

Figure 30 and Figure 31 show the stability analyses for the do nothing option, with the piezometric level elevated approximately 1.5 m above those used in the back-analysis to represent slope instability. The calculated factor of safety is 0.89 for cross-section A-A' and 0.87 for cross-section B-B' when the raised groundwater level is used in the analysis. There is also a significant potential for additional sloughing of the material at the scarps of the failure areas, where there is up to 2 m of vertical drop. There is also a buildup of material at the toe and the slope has reached a flatter angle. Advancement of the failure toward 11th Street East will result in undermining of existing building foundations. Additionally, properties located below 11th Street East may experience damage from debris or additional soil loading as material collects at the toe of the sliding zone. It is expected that there will continue to be slope movement along Cherry Lane as the slope failure progresses, disrupting traffic access and power service along the lane.

10.7.2 Option 2 – Installation of Sub-Drainage System


Pore-water pressures in surficial stratified deposits, especially in the highly plastic clay overlying the till, have significant influence on slope stability as indicated by the occurrence of the East and West Failures when groundwater levels were above average in both 2012 and 2013. Installation of sub-drainage system to lower groundwater levels and maintain it at low levels will result in an increase in the factor of safety of the slope and minimize the effect of seasonal and long term groundwater level variation.

Drainage systems installed in 11th Street East can be used to intercept groundwater prior to entering the slope, however the drains will not account for pore-water pressures that are generated from surface infiltration downslope of 11th Street East. A second or alternate drainage system could be installed along Cherry Lane to reduce the pore-water pressures near the middle of the slope. Drainage systems will have to be designed to reduce pore-water pressures over the entire area of potential slope instability to prevent mounding and increased instability between individual locations. Drainage systems would require regular maintenance to ensure that blockages do not occur, and to ensure that the system is effectively draining the slope.

For the slope stability analysis, groundwater conditions where drainage systems were installed along 11th Street East approximately 10 mbgs and along Cherry Lane between 3 mbgs and 8 mbgs were considered. Installation of drainage systems in both locations for the existing slope will be more effective than a single drainage system. For the West Failure (cross-section A-A'), the post-failure pore-water conditions along 11th Street East were already near the clay and till interface, resulting in marginal increase to FS when the level was lowered, however lowering the pore-water pressures along the East Failure (cross-section B-B') resulted in an approximate 20% increase in FS. It should be noted that this increase in slope FOS will not be achieved immediately after the sub-drainage system construction because pore-water pressure in clay slope may take several years to dissipate.

Figure 32 and Figure 33 show the stability analyses for this conceptual remedial option for the West Failure and East Failure, respectively. Installation of a drainage system in 11th Street East will require a minimum length of 135 m and a depth ranging between 8.6 m and 12.5 m. Installation of a drainage system in Cherry Lane will require a length of 135 m at a depth between 3.6 m and 8 m. Detailed design will refine the overall dimensions of this option.


Name: Fill Unit Weight: 19 kN/m³ Cohesion: 5 kPa Phi: 22 °
 Name: Silty Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 25 °
 Name: Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 22 °
 Name: Shear zone Unit Weight: 19 kN/m³ Cohesion: 0 kPa Phi: 12 °
 Name: Till



Cross Section: A-A' (West Failure)
 File Name: AA Do Nothing Low WT_v2.gsz


		CHERRY LANE SLOPE INSTABILITY	
SLOPE STABILITY ANALYSIS CROSS SECTION A-A' DO NOTHING OPTION WITH LOW WATER TABLE			
	PROJECT	11-1362-0057	FILE No.
	DESIGN	LNМ	08/05/14
	CADD	HQV	08/05/14
	CHECK	PGB	08/05/14
		SCALE	N/A
		REV.	
			FIGURE: 28

Name: Fill Unit Weight: 19 kN/m³ Cohesion: 5 kPa Phi: 22 °
 Name: Silty Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 25 °
 Name: Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 22 °
 Name: Shear zone Unit Weight: 19 kN/m³ Cohesion: 0 kPa Phi: 12 °
 Name: Till
 Name: Retaining wall



		CHERRY LANE SLOPE INSTABILITY		
SLOPE STABILITY ANALYSIS CROSS SECTION B-B' DO NOTHING OPTION WITH LOW WATER TABLE				
PROJECT	11-1362-0057	FILE No.		
DESIGN	LNLM	08/05/14	SCALE	N/A
CADD				REV.
CHECK	PGB	08/05/14	FIGURE: 29	
REVIEW	HQV	08/05/14		


Name: Fill Unit Weight: 19 kN/m³ Cohesion: 5 kPa Phi: 22 °
 Name: Silty Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 25 °
 Name: Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 22 °
 Name: Shear zone Unit Weight: 19 kN/m³ Cohesion: 0 kPa Phi: 12 °
 Name: Till



Cross Section: A-A' (West Failure)
 File Name: AA Do Nothing HighWT_v2.gsz

		CHERRY LANE SLOPE INSTABILITY		
SLOPE STABILITY ANALYSIS CROSS SECTION A-A' DO NOTHING OPTION WITH HIGH WATER TABLE				
	PROJECT	11-1362-0057	FILE No.	
	DESIGN	LNK	08/05/14	SCALE N/A REV.
	CADD	HQV	08/05/14	FIGURE: 30
	CHECK	PGB	08/05/14	


Name: Fill Unit Weight: 19 kN/m³ Cohesion: 5 kPa Phi: 22 °
 Name: Silty Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 25 °
 Name: Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 22 °
 Name: Shear zone Unit Weight: 19 kN/m³ Cohesion: 0 kPa Phi: 12 °
 Name: Till
 Name: Retaining wall



		CHERRY LANE SLOPE INSTABILITY	
SLOPE STABILITY ANALYSIS CROSS SECTION B-B' DO NOTHING OPTION WITH HIGH WATER TABLE			
PROJECT	11-1362-0057	FILE No.	
DESIGN	LNLM	08/05/14	SCALE N/A REV.
CADD			
CHECK	PGB	08/05/14	FIGURE: 31
REVIEW	HQV	08/05/14	

Saskatoon, Saskatchewan


Name: Fill Unit Weight: 19 kN/m³ Cohesion: 5 kPa Phi: 22 °
 Name: Silty Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 25 °
 Name: Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 22 °
 Name: Shear zone Unit Weight: 19 kN/m³ Cohesion: 0 kPa Phi: 12 °
 Name: Till




Cross Section: A-A' (West Failure)
 File Name: AA SubDrainage System_v2.gsz

		CHERRY LANE SLOPE INSTABILITY	
SLOPE STABILITY ANALYSIS CROSS SECTION A-A' DRAINAGE OPTION			
	PROJECT	11-1362-0057	FILE No.
	DESIGN	LNLM	08/05/14
	CADD	HQV	08/05/14
	CHECK	PGB	08/05/14
			FIGURE: 32

Name: Fill Unit Weight: 19 kN/m³ Cohesion: 5 kPa Phi: 22 °
 Name: Silty Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 25 °
 Name: Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 22 °
 Name: Shear zone Unit Weight: 19 kN/m³ Cohesion: 0 kPa Phi: 12 °
 Name: Till
 Name: Retaining wall



PROJECT		 CHERRY LANE SLOPE INSTABILITY	
TITLE			
SLOPE STABILITY ANALYSIS CROSS SECTION B-B' DRAINAGE OPTION			
PROJECT		11-1362-0057	FILE No.
DESIGN	LNLM	08/05/14	SCALE N/A REV.
CADD			
CHECK	PGB	08/05/14	FIGURE: 33
REVIEW	HQV	08/05/14	



Installation of a sub-drainage system would require disturbance to roadways (11th Street East and Cherry Lane) and underground utilities in the area, but would result in only localized disturbance to the residences in this area and pose little additional risk for slope instability during construction. Construction of the drainage outlet would require connection to the sewer system or construction of a new drainage outlet downslope.

10.7.3 Option 3 – Site Re-grading

Site re-grading (e.g., slope flattening) reduces material weight at the top of the slope and, in some cases, increases weight at the toe of the slope; therefore improves the slope stability condition.

Review of the upper slope topography shows that the current slope has an average slope of 2.5H:1V along cross-section A-A' (West Failure), and 1.9H:1V along cross-section B-B' (East Failure).

Slope stability analyses for cross-section A-A' and B-B' were conducted to determine the required level of slope flattening (conceptual slope geometry) of the site to obtain a minimum FS = 1.5, as shown in Table 12. It is assumed that installation of a drainage system along Cherry Lane will be required in conjunction with the slope re-grading in order to maintain pore-water pressures at or below the till contact.

Table 12: Average Slope Gradient for Conceptual Option 3 – Re-grading


Cross Section	Average Slope Gradient	
	Upper Slope	Lower Slope
West Failure	4.4H:1V	4.8H:1V
East Failure	3.9H:1V	2.5H:1V

Figure 34 and Figure 35 show the stability analyses for this conceptual remedial slope flattening option. Figure 36 shows the plan view of the estimated extents of slope re-grading required to re-establish the slope to a minimum FS = 1.5. The approximate dimension of the conceptual slope re-grading is an area approximately 135 m long by 17 m to 67 m wide. Detailed design will refine the overall dimensions of this option.

Implementation of this option will cause significant disruption to residences along 11th Street East and Saskatchewan Crescent East, as well as the above ground power lines and landscaping in the area. Site access will be limited and large volumes of fill and debris will need to be hauled from site. Access to 11th Street East and Cherry Lane will be restricted during construction, but should not be affected in the long term.

Installation of a drainage system will be required along 11th Street East and Cherry Lane in order to maintain long term stability of the slope with this option.


Name: Fill Unit Weight: 19 kN/m³ Cohesion: 5 kPa Phi: 22 °
 Name: Silty Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 25 °
 Name: Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 22 °
 Name: Shear zone Unit Weight: 19 kN/m³ Cohesion: 0 kPa Phi: 12 °
 Name: Till



Cross Section: A-A' (West Failure)
 File Name: AA Regrading_v2.gsz


		CHERRY LANE SLOPE INSTABILITY	
SLOPE STABILITY ANALYSIS CROSS SECTION A-A' SITE REGRADING OPTION			
	PROJECT	11-1362-0057	FILE No.
	DESIGN	LNLM 08/05/14	SCALE N/A REV.
	CADD	HQV 08/05/14	FIGURE: 34
	CHECK	PGB 08/05/14	

Name: Fill Unit Weight: 19 kN/m³ Cohesion: 5 kPa Phi: 22 °
 Name: Silty Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 25 °
 Name: Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 22 °
 Name: Shear zone Unit Weight: 19 kN/m³ Cohesion: 0 kPa Phi: 12 °
 Name: Till
 Name: Retaining wall



		CHERRY LANE SLOPE INSTABILITY	
SLOPE STABILITY ANALYSIS CROSS SECTION B-B' SITE REGRADING OPTION			
		PROJECT 11-1362-0057 DESIGN LNM 08/05/14 CADD CHECK PGB 08/05/14 REVIEW HQV 08/05/14	FILE No. SCALE N/A REV.
			FIGURE: 35

G:\2011\136211-1362-0057 COS East Riverbank\Figures\Phase 5100 Cherry Lane Remediation\Task 700011-1362-0057 Remedial Options.dwg 5/2/2014 2:50 PM



LEGEND

- POWER POLE
- CATCH BASIN
- MANHOLE
- O/H — OVERHEAD POWER LINE
- 303 LOT NUMBER

REFERENCE

AERIAL PHOTOGRAPH PROVIDED BY CITY OF SASKATOON, MAY 15, 2011
CITY OF SASKATOON DATUM



City of Saskatoon		CHERRY LANE SLOPE INSTABILITY																					
TITLE CONCEPTUAL AREA AFFECTED BY SITE RE-GRADING																							
Golder Associates <small>Saskatoon, Saskatchewan</small>		<table border="1" style="width: 100%; border-collapse: collapse; font-size: 0.8em;"> <tr> <td colspan="2">PROJECT</td> <td>11-1326-0057</td> <td>FILE No.</td> </tr> <tr> <td>DESIGN</td> <td>LM</td> <td>08/05/14</td> <td>SCALE AS SHOWN</td> </tr> <tr> <td>CADD</td> <td>BDS/JDS</td> <td>08/05/14</td> <td>REV. 0</td> </tr> <tr> <td>CHECK</td> <td>HV</td> <td>08/05/14</td> <td></td> </tr> <tr> <td>REVIEW</td> <td>PGB</td> <td>08/05/14</td> <td></td> </tr> </table>	PROJECT		11-1326-0057	FILE No.	DESIGN	LM	08/05/14	SCALE AS SHOWN	CADD	BDS/JDS	08/05/14	REV. 0	CHECK	HV	08/05/14		REVIEW	PGB	08/05/14		FIGURE: 36
PROJECT		11-1326-0057	FILE No.																				
DESIGN	LM	08/05/14	SCALE AS SHOWN																				
CADD	BDS/JDS	08/05/14	REV. 0																				
CHECK	HV	08/05/14																					
REVIEW	PGB	08/05/14																					



10.7.4 Option 4 – Shear Zone Modification

Shear zone modification, such as the installation of shear key, stone column, concrete or steel piles, or using a cutter soil mixing (CSM) method, can be undertaken to improve the shear strength of the shear zone, thus improving slope stability conditions.

Slope stability analyses were conducted to evaluate the extent of the shear zone modification required to obtain a minimum FS = 1.5, as shown in Table 13. A material with an equivalent 30 degree effective friction angle and zero cohesion was assumed for the modified shear zone area. It is assumed that a dewatering system has been installed upslope of the shear zone modification in order to maintain the pore-water pressures at or below the till contact.

Table 13: Shear Zone Modification Dimensions for Conceptual Option 4

Cross Section	Shear Zone Dimensions		Comments
	Width (m)	Depth (mbgs)	
West Failure	13	7	Modification in Cherry Lane extending up and down slope
East Failure	4	7	Modification in Cherry Lane


m = metre; mbgs = metres below ground surface

Figure 37 and Figure 38 show the stability analyses for this conceptual remedial option. Figure 39 shows the plan view of the estimated extent of shear zone modification required along Cherry Lane to achieve a minimum FS = 1.5. The approximate extent of the conceptual shear zone modification area is approximately 120 m long and 4 to 13 m wide. Detailed design will refine the overall dimensions of this option.

Implementation of this option will cause significant disruption to access and services along Cherry Lane, as well as the backyards of the residences along 11th Street East. Due to the unstable nature of this slope, the use of an open excavation method would not be acceptable. Construction methods where limited excavation is necessary would be required, such as stone columns, *in situ* cutter soil mixing, etc. Site access will be limited and large volumes of fill and debris will need to be hauled from site. Access to Cherry Lane will be restricted during construction.

Installation of a drainage system will be required along 11th Street East and Cherry Lane in order to maintain long term stability of the slope with this option.


Name: Fill Unit Weight: 19 kN/m³ Cohesion: 5 kPa Phi: 22 °
 Name: Silty Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 25 °
 Name: Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 22 °
 Name: Shear zone Unit Weight: 19 kN/m³ Cohesion: 0 kPa Phi: 12 °
 Name: Till
 Name: Shear zone modification Unit Weight: 20 kN/m³ Cohesion: 0 kPa Phi: 30 °





Cross Section: A-A' (West Failure)
 File Name: AA Shear Zone Modification_v2.gsz


		CHERRY LANE SLOPE INSTABILITY		
SLOPE STABILITY ANALYSIS CROSS SECTION A-A' SHEAR ZONE MODIFICATION OPTION				
	PROJECT	11-1362-0057	FILE No.	
	DESIGN	LNLM	08/05/14	SCALE N/A REV.
	CADD			
	CHECK	HQV	08/05/14	FIGURE: 37
REVIEW	PGB	08/05/14		

Name: Fill Unit Weight: 19 kN/m³ Cohesion: 5 kPa Phi: 22 °
 Name: Silty Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 25 °
 Name: Clay Unit Weight: 19 kN/m³ Cohesion: 10 kPa Phi: 22 °
 Name: Shear zone Unit Weight: 19 kN/m³ Cohesion: 0 kPa Phi: 12 °
 Name: Till
 Name: Shear zone modification Unit Weight: 20 kN/m³ Cohesion: 0 kPa Phi: 30 °
 Name: Retaining wall



Cross Section: B-B' (East Failure)
File Name: BB Shear Zone Modification_v2.gsz

PROJECT		 CHERRY LANE SLOPE INSTABILITY	
TITLE			
SLOPE STABILITY ANALYSIS CROSS SECTION B-B' SHEAR ZONE MODIFICATION OPTION			
PROJECT		FILE No.	
DESIGN	LNLM 08/05/14	SCALE	N/A
CADD		REV.	
CHECK	PGB 08/05/14	FIGURE: 38	
REVIEW	HQV 08/05/14		
 Golder Associates Saskatoon, Saskatchewan			



LEGEND

- POWER POLE
- CATCH BASIN
- MANHOLE
- O/H — OVERHEAD POWER LINE
- 303 LOT NUMBER

REFERENCE

AERIAL PHOTOGRAPH PROVIDED BY CITY OF SASKATOON, MAY 15, 2011
CITY OF SASKATOON DATUM



PROJECT 	CHERRY LANE SLOPE INSTABILITY																				
TITLE CONCEPTUAL AREA AFFECTED BY SHEAR ZONE MODIFICATION																					
	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">PROJECT</td> <td style="width: 15%;">11-1326-0057</td> <td style="width: 15%;">FILE No.</td> <td style="width: 15%;"></td> </tr> <tr> <td>DESIGN</td> <td>LM 08/05/14</td> <td>SCALE</td> <td>AS SHOWN REV. 0</td> </tr> <tr> <td>CADD</td> <td>BDS/JDS 08/05/14</td> <td></td> <td></td> </tr> <tr> <td>CHECK</td> <td>HV 08/05/14</td> <td></td> <td></td> </tr> <tr> <td>REVIEW</td> <td>PGB 08/05/14</td> <td></td> <td></td> </tr> </table>	PROJECT	11-1326-0057	FILE No.		DESIGN	LM 08/05/14	SCALE	AS SHOWN REV. 0	CADD	BDS/JDS 08/05/14			CHECK	HV 08/05/14			REVIEW	PGB 08/05/14		
PROJECT	11-1326-0057	FILE No.																			
DESIGN	LM 08/05/14	SCALE	AS SHOWN REV. 0																		
CADD	BDS/JDS 08/05/14																				
CHECK	HV 08/05/14																				
REVIEW	PGB 08/05/14																				
FIGURE: 39																					



11.0 SUMMARY

The slope failures along Cherry Lane are most likely the result of a combination of the natural geology of the soils along the riverbank, the heavy and prolonged precipitation in the spring of 2012 and 2013 that resulted in increased groundwater levels, and changes to the geometry and landscaping of the slope. As such, this section of the riverbank is at a high risk of continuing slope failure. Action should be taken to reduce the risk to the public, infrastructure, and property in the area.

Conceptual slope remediation options were developed for the Site. Table 14 provides a summary of cost estimates, risks, and benefits associated with each of the conceptual options.

The conceptual cost estimate, shown in Table 14, was prepared by comparing the conceptual remedial options to similar projects conducted in and around the City of Saskatoon and scaling the costs to suit the estimated size and scope of the remedial option. A contingency of 50% has been added to the estimated costs to account for variations that will be generated from a more detailed analysis of the conceptual options. Similar projects include: shear key construction at Cosmopolitan Park in 2011, lightweight fill placement at 17th Street and Saskatchewan Crescent in 2013; and typical rates for CSM construction provided by Golder Construction. Costs associated with contractor mobilization, engineering design and support, and construction monitoring have been included. A more detailed breakdown of the costs for the conceptual estimates is provided in Appendix H.

It is recommended that shear zone modification with the installation of a sub-drainage system be considered as a remedial option for the properties affected by the slope movement at the Site. While the conceptual cost of the shear zone modification with drainage option is higher than the other options considered, this option will result in the least permanent disturbance to the surrounding properties, depending on the specific method of shear zone modification selected, and will achieve the required factor of safety for the remedial slope. Additionally, depending on the method selected, the majority of the remedial work can be confined to the area surrounding Cherry Lane, increasing accessibility for construction.



CHERRY LANE GEOTECHNICAL INVESTIGATION AND EVALUATION

Table 14: Risk/Benefit Summary of Conceptual Remediation Options

Conceptual Remediation Option	Estimated Cost ^(a)	Benefit/Advantage	Risk/Disadvantage
Option 1 – Do nothing	<\$500,000	<ul style="list-style-type: none"> ■ Low cost 	<ul style="list-style-type: none"> ■ High risk of continued failure, additional sloughing of the material at the scarps of the failure areas, and for buildup of material at the toe until the slope has reached a flatter angle. ■ Failure likely to retrogress toward 11th Street East may affect building foundations along 11th Street East, and may cause movement of the structures. ■ Properties located below 11th Street East may experience damage from debris or additional soil loading as material collects at the toe of the failure. ■ Ongoing cracking and movement along Cherry Lane as the slope movement progress, disrupting traffic access and power service along the lane.
Option 2 – Installation of Sub- Drainage System	\$4,500,000	<ul style="list-style-type: none"> ■ The FS for the slope increases for the existing failure areas. ■ Decreasing and maintaining the pore-water pressures along the slope will decrease the risk of additional slope movement during high precipitation years. ■ Little additional risk for slope instability during construction. ■ Only localized disturbance to the residences in this area. 	<ul style="list-style-type: none"> ■ Does not improve the Factor of Safety for the slope to target 1.5. ■ It may take several years for the remediation to be effective because dissipation of pore-water pressure in clay takes time. ■ Installation of a drainage system will require disturbance to roadways (11th Street East and Cherry Lane) and underground utilities in the area. ■ Construction of the drainage outlet would require connection to the sewer system or construction of a new drainage outlet downslope which will affect properties along Saskatchewan Crescent East. ■ Cross drains connecting between 11th Street East and Cherry Lane may require some disturbance in the yards of the residences on the 200 to 300 block of 11th Street East. ■ Long term maintenance and monitoring of the drainage system is required.
Option 3- Slope Re-grading and Installation of Sub-Drainage System	\$6,500,000	<ul style="list-style-type: none"> ■ Target Factor of Safety of 1.5 for the slope in this area is achievable. ■ Reduced risk of shallow failures in the upper slope due to the flatter grade. ■ Decreasing and maintaining the pore-water pressures along the slope will decrease the risk of additional slope movement during high precipitation years. ■ Access to 11th Street East and Cherry Lane should not be affected in the long term. 	<ul style="list-style-type: none"> ■ Construction will cause significant disruption to residences along 11th Street East and Saskatchewan Crescent East, as well as the above ground power lines and landscaping in the area. ■ Site access will be limited and large volumes of fill and debris will need to be hauled from site. ■ Access to 11th Street East and Cherry Lane will be restricted during construction. ■ Installation of a drainage system will require disturbance to roadways (11th Street East and Cherry Lane) and underground utilities in the area. ■ Construction of the drainage outlet would require connection to the sewer system or construction of a new drainage outlet downslope which will affect properties along Saskatchewan Crescent East. ■ Cross drains connecting between 11th Street East and Cherry Lane may require some disturbance in the yards of the residences on the 200 to 300 block of 11th Street East. ■ Long term maintenance and monitoring of the drainage system is required.
Option 4 - Shear Zone Modification and Installation of Sub- Drainage System	\$10,500,000	<ul style="list-style-type: none"> ■ Target Factor of Safety of 1.5 for the slope in this area is achievable. ■ Majority of work can be confined to Cherry Lane, resulting in less disruption to residences along 11th Street East and Saskatchewan Crescent East. ■ Decreasing and maintaining the pore-water pressures along the slope will decrease the risk of additional slope movement during high precipitation years. ■ Access to 11th Street East and Cherry Lane should not be affected in the long term. 	<ul style="list-style-type: none"> ■ Construction will cause significant disruption to Cherry Lane and the backyards and power line along Cherry Lane. ■ Temporary slope stabilization methods will need to be installed above Cherry Lane to reduce the risk of instability during construction. ■ Access to 11th Street East and Cherry Lane will be restricted during construction. ■ Installation of a drainage system will require disturbance to roadways (11th Street East and Cherry Lane) and underground utilities in the area. ■ Construction of the drainage outlet would require connection to the sewer system or construction of a new drainage outlet downslope which will affect properties along Saskatchewan Crescent East. ■ Cross drains connecting between 11th Street East and Cherry Lane may require some disturbance in the yards of the residences on the 200 to 300 block of 11th Street East. ■ Long term maintenance and monitoring of the drainage system is required.

^(a) Costs for alterations to existing properties, including removal of debris and landscaping, removal of structures, property purchase, and changes to existing utilities have not been considered in this estimate. Costs have been rounded to the nearest \$500,000.



12.0 CLOSURE

The findings of this report are based upon the results of field and laboratory investigations conducted by Golder. If conditions encountered at the surface or at depth during construction appear to be different than indicated in the report, or if the stated assumptions are not consistent with design, this office should be notified for review and adjustment of recommendations, if necessary.

Soil conditions are, by nature, are highly variable across a construction site. The placement of fill and prior construction activities can contribute to variables in the near-surface conditions. A contingency should be included in any construction budget to allow for the possibility of variation of soil conditions that may result in modification of design and construction procedures.

This report was prepared for the City of Saskatoon for the proposed works described in the text. The data and recommendations should not be used for any other purpose, or by any other parties, without written consent from Golder Associates Ltd. The findings and recommendations of this report were prepared in accordance with generally accepted professional engineering principles and practice. No other warranty, expressed or implied, is given.



Report Signature Page

GOLDER ASSOCIATES LTD.




Laurie McEachern, B.Sc.
Engineer in Training



Lisa Nehring, P.Eng.
Geotechnical Engineer



Hung Vu, Ph.D., P.Eng.
Associate, Senior Geotechnical Engineer



Phil Bruch, M.Sc., P.Eng.
Principal, Senior Geotechnical Engineer



Greg Misfeldt, M.Sc., P.Eng.
Principal, Senior Geotechnical Engineer
LDN/GAM/HV/PB/DF/jlb/pls

Golder, Golder Associates and the GA globe design are trademarks of Golder Associates Corporation.

n:\active\2011\1362\11-1362-0057 cos east riverbank\5100 cherry lane remediation\7000 report\11-1362-0057-5100 rpt 14 jan 27 cherry lane report final.docx

Association of Professional Engineers & Geoscientists of Saskatchewan		
CERTIFICATE OF AUTHORIZATION		
Golder Associates Ltd.		
Number C0230		
Permission to Consult held by:		
Discipline	Sk. Reg. No.	Signature
Geotechnical	12797	



REFERENCES

- AMEC (AMEC Earth & Environmental.) 2005a. Revised Slope Stability Assessment, Proposed Condominium Development, 316 Saskatchewan Crescent, Saskatoon, Saskatchewan. Report prepared for Ehrenburg Homes Ltd., File No. SX01965, dated July 27, 2005.
- AMEC. 2005b. 2005 East River Bank Monitoring Program, Fall Monitoring Event, City of Saskatoon, Saskatchewan. Report prepared for the City of Saskatoon, AMEC Project No. SX-028507, dated December 19, 2005.
- AMEC. 2009. 2008 Fall East River Bank Monitoring Program, City of Saskatoon, Saskatchewan. Report prepared for the City of Saskatoon, Project No. SX0258510, dated March 2, 2019.
- AMEC. 2010. 2009 East River Bank Monitoring Program Fall Monitoring Event, City of Saskatoon, Saskatchewan. Report prepared for the City of Saskatoon, Project No. SX0258511, dated April 6, 2010.
- AMEC. 2013. 2013 East River Bank Monitoring Program, City of Saskatoon, Saskatchewan. Project No. SX02585.2013, report dated July 30, 2013.
- Christiansen, E.A. 1968. Pleistocene stratigraphy of the Saskatoon area, Saskatchewan. Canadian Journal of Earth Sciences, 5: 1167-1173.
- Christiansen, E.A. 1970. Physical Environment of Saskatoon, Canada. Ottawa: Saskatchewan Research Council in co-operation with The National Research Council of Canada.
- Christiansen, E.A. 1979. The Wisconsinan deglaciation of southern Saskatchewan and adjacent areas. Canadian Journal of Earth Sciences, 16:913-938.
- City of Saskatoon. 1985. Agreement for Monitoring Slope Instability, Meewasin Valley Authority/City of Saskatoon. File No. CK. 4205-5, dated October 7, 1985.
- Clifton Associates Ltd. 1983. Geotechnical Studies, Proposed Park Terrace Condominiums, 222 Saskatchewan Crescent East Saskatoon, SK. Report prepared for Starport Investments Ltd., dated August 17, 1983.
- Clifton Associates Ltd. 1985. Slope Instability Study, South Saskatchewan River Banks. Report prepared for Meewasin Valley Authority, file S134, dated December 23, 1985.
- Clifton, A.W., Krahn, J., and Fredlund, D.G. 1981. Riverbank Instability and Development Control in Saskatoon. Canadian Geotechnical Journal, 18: 95-105.
- EC (Environment Canada – Meteorological Service of Canada). Climate Data Online. Available at: <http://climate.weather.gc.ca/climateData>. Accessed August 22, 2013.
- Eckel, B., Christiansen, E., Richardson, N., Schreiner, B. 2002. Trip B7: Riverbank instability in the city of Saskatoon, Saskatchewan, Canada. Geological Association of Canada, Mineralogical Association of Canada, Joint Annual Meeting, Saskatoon, Saskatchewan, Canada. GAC-MAC Saskatoon 2002 Local Organizing Committee.



- Golder Associates (Western Canada) Ltd. 1985. Progress Report No. 1 Slope Monitoring Program, Park Terrace Condominiums, 222 Saskatchewan Crescent East, Saskatoon, Saskatchewan. Project Number 852-6010, dated December 23, 1985.
- Golder (Golder Associates Ltd.) 1989. Feasibility of Horizontal Drains for Slope Stabilization, East Bank – South Saskatoon, Saskatchewan. Report prepared for the Meewasin Valley Authority, Project Number 592-6905, dated April 1989. Golder Associates Ltd. 2006. Geotechnical Investigation, Proposed Idylwyld Lift Station Saskatoon, Saskatchewan. Report prepared for Earth Tech (Canada) Inc., Project Number 05-1362-209, dated February, 2006.
- Golder. 2008a. Storm Sewer Preservation, East River Bank Slope Stabilization, City of Saskatoon, File No. PW 8250-4/IS 7821-3. Report prepared for the City of Saskatoon, Project Number 06-1362-304, dated July 2008.
- Golder. 2008b. Spring 2008 Site Reconnaissance – High Priority Sites along the East Riverbank of the South Saskatchewan River, Saskatoon, Saskatchewan. Report prepared for the City of Saskatoon, Report Number 06-1362-304, dated July 2008.
- Golder. 2008c. Slope Instability Investigation, Landslide South of the University Bridge, Saskatoon, Saskatchewan. Report prepared for the City of Saskatoon, Report number 06-1362-304/7000, dated December 2008.
- Golder. 2009. Spring 2009 Site Reconnaissance – East Riverbank of the South Saskatchewan River. Report prepared for the City of Saskatoon, Report Number 06-1362-304/3002, dated October 2009.
- Golder. 2010. Spring 2010 Site Reconnaissance – East Riverbank of the South Saskatchewan River. Report prepared for the City of Saskatoon, Report Number 06-1362-304/3003, dated March 2013.
- Golder. 2011. Spring 2011 Site Reconnaissance – East Riverbank of the South Saskatchewan River. Report prepared for the City of Saskatoon, Report Number 11-1362-0057/1000, dated October 2011.
- Golder. 2013a. Assessment of Slope Instability at 200 Block, 11th Street East, Saskatoon. Report prepared for the City of Saskatoon, Report Number 11-1362-0057/5000, dated May 2013.
- Golder. 2013b. Spring 2012 Site Reconnaissance – East Riverbank of the South Saskatchewan River. Report prepared for the City of Saskatoon, Report Number 11-1362-0057/2000, dated March 2013.
- Ground Engineering Ltd. 1976. Geotechnical Investigation 216, 218 and 220 Saskatchewan Crescent, Saskatoon, Saskatchewan. Report prepared for Saskatchewan Housing Corporation, Job No. GS-033, dated April 9, 1976.
- Ground Engineering Ltd. 1977. Geotechnical Site Investigation Proposed Housing Complex, Saskatchewan Crescent. Report prepared for Saskatchewan Housing Corporation, Job No. GS-033, dated July 4, 1977.
- Hamilton, J.J. and Tao, S.S. 1977. Impact of urban development on groundwater in glacial deposits. In Proceedings of the 30th Canadian Geotechnical Conference, Saskatoon, Saskatchewan. Canadian Geotechnical Society.



- Haug, M.D., Sauer, E.K, and Fredlund, D.G. 1977. Retrogressive Slope Failures at Beaver Creek, South of Saskatoon, Saskatchewan, Canada. Canadian Geotechnical Journal, 14: 228-301.
- Ireland, James. 2000. Overview of Slope Instability and Monitoring Equipment for the East River bank within the City of Saskatoon (draft). File # 0181-3.
- Meewasin Valley Authority. 2004. Policies and Guidelines Conservation Zone.
<http://meewasin.com/development/application-form/policy/>.
- PMEL (P. Machibroda Engineering Ltd.) 1981. Geotechnical Investigation, Proposed Apartment Building, Saskatchewan Crescent, Saskatoon, Saskatchewan. Report prepared for Saskatchewan Housing Corporation, PMEL File No. S81-335, dated June 17, 1981.
- PMEL. 1994. Geotechnical Investigation Q1A/Q2A Transmission Line Tower No. 11 Relocation St. Henry Avenue Saskatoon Saskatchewan. Dated May 11, 1994.
- PMEL. 1997. Geotechnical Investigation and Slope Stability Study, Proposed Residential Development, 237-11th Street East, Saskatoon, Saskatchewan. Report prepared for Kindrachuck Agrey Architects Ltd., PMEL File No. S97-2778, dated September 15, 1997.
- PMEL. 2003a. Geotechnical Investigation and Slope Stability Study, Proposed Garage, 306 Saskatchewan Crescent East, Saskatoon, Saskatchewan, Report prepared for Orko Developments Ltd., PMEL File No. S03-4869, dated September 11, 2003.
- PMEL. 2003b. Geotechnical Investigation and Slope Stability Study, Proposed Residence, 313-11th Street East, Saskatoon, Saskatchewan. Report prepared for James D. Zimmer Architect, PMEL File No. S03-4925, dated October 31, 2003.
- PMEL. 2006. Geotechnical Investigation and Slope Stability Study, Proposed Condominium 316 - Saskatchewan Crescent East, Saskatoon, SK. Report prepared for Ehrenburg Homes Ltd., PMEL File NO. S06-5722, dated July 14, 2006.
- PMEL. 2007. Geotechnical Investigation and Slope Stability Study, Proposed Residences, 221 & 225 - 11th Street East, Saskatoon, SK, PMEL File No. S07-6078. Report prepared for North Ridge Development Corp, dated June 12, 2007.
- PMEL. 2008. Proposed Commercial/Residential Development 328 Saskatchewan Crescent East, Saskatoon, SK. Prepared for Think Enterprises, PMEL File No. S08-6500, dated July 8, 2008.
- PMEL. 2009. Supplementary Comments and Visual Review and Groundwater Monitoring Results, Proposed Condominium, 316-Saskatchewan Crescent East, Saskatoon, Saskatchewan. Report prepared for Ehrenburg Homes Ltd., PMEL File No. S09-5722.1, dated November 16, 2009.
- Sauer E.K. 1975. Urban Fringe Development and Slope Instability in Southern Saskatchewan. Canadian Geotechnical Journal, 12: 106-118.
- SRC (Saskatchewan Research Council). Precipitation Data. Purchased January 23, 2014.



CHERRY LANE GEOTECHNICAL INVESTIGATION AND EVALUATION

WSA (Water Security Agency of Saskatchewan). 2013. Spring Runoff Outlook: Based on Conditions as of March 5, 2013.

Weir, H. No date. Historical Report of Riverbank Slides.



APPENDIX A

Information and Limitations of this Report

IMPORTANT INFORMATION AND LIMITATIONS OF THIS REPORT

Standard of Care: Golder Associates Ltd. (Golder) has prepared this report in a manner consistent with that level of care and skill ordinarily exercised by members of the engineering and science professions currently practising under similar conditions in the jurisdiction in which the services are provided, subject to the time limits and physical constraints applicable to this report. No other warranty, expressed or implied is made.

Basis and Use of the Report: This report has been prepared for the specific site, design objective, development and purpose described to Golder by the Client. The factual data, interpretations and recommendations pertain to a specific project as described in this report and are not applicable to any other project or site location. Any change of site conditions, purpose, development plans or if the project is not initiated within eighteen months of the date of the report may alter the validity of the report. Golder can not be responsible for use of this report, or portions thereof, unless Golder is requested to review and, if necessary, revise the report.

The information, recommendations and opinions expressed in this report are for the sole benefit of the Client. No other party may use or rely on this report or any portion thereof without Golder's express written consent. If the report was prepared to be included for a specific permit application process, then upon the reasonable request of the client, Golder may authorize in writing the use of this report by the regulatory agency as an Approved User for the specific and identified purpose of the applicable permit review process. Any other use of this report by others is prohibited and is without responsibility to Golder. The report, all plans, data, drawings and other documents as well as all electronic media prepared by Golder are considered its professional work product and shall remain the copyright property of Golder, who authorizes only the Client and Approved Users to make copies of the report, but only in such quantities as are reasonably necessary for the use of the report by those parties. The Client and Approved Users may not give, lend, sell, or otherwise make available the report or any portion thereof to any other party without the express written permission of Golder. The Client acknowledges that electronic media is susceptible to unauthorized modification, deterioration and incompatibility and therefore the Client can not rely upon the electronic media versions of Golder's report or other work products.

The report is of a summary nature and is not intended to stand alone without reference to the instructions given to Golder by the Client, communications between Golder and the Client, and to any other reports prepared by Golder for the Client relative to the specific site described in the report. In order to properly understand the suggestions, recommendations and opinions expressed in this report, reference must be made to the whole of the report. Golder can not be responsible for use of portions of the report without reference to the entire report.

Unless otherwise stated, the suggestions, recommendations and opinions given in this report are intended only for the guidance of the Client in the design of the specific project. The extent and detail of investigations, including the number of test holes, necessary to determine all of the relevant conditions which may affect construction costs would normally be greater than has been carried out for design purposes. Contractors bidding on, or undertaking the work, should rely on their own investigations, as well as their own interpretations of the factual data presented in the report, as to how subsurface conditions may affect their work, including but not limited to proposed construction techniques, schedule, safety and equipment capabilities.

Soil, Rock and Groundwater Conditions: Classification and identification of soils, rocks, and geologic units have been based on commonly accepted methods employed in the practice of geotechnical engineering and related disciplines. Classification and identification of the type and condition of these materials or units involves judgment, and boundaries between different soil, rock or geologic types or units may be transitional rather than abrupt. Accordingly, Golder does not warrant or guarantee the exactness of the descriptions.

IMPORTANT INFORMATION AND LIMITATIONS OF THIS REPORT (cont'd)

Special risks occur whenever engineering or related disciplines are applied to identify subsurface conditions and even a comprehensive investigation, sampling and testing program may fail to detect all or certain subsurface conditions. The environmental, geologic, geotechnical, geochemical and hydrogeologic conditions that Golder interprets to exist between and beyond sampling points may differ from those that actually exist. In addition to soil variability, fill of variable physical and chemical composition can be present over portions of the site or on adjacent properties. **The professional services retained for this project include only the geotechnical aspects of the subsurface conditions at the site, unless otherwise specifically stated and identified in the report.** The presence or implication(s) of possible surface and/or subsurface contamination resulting from previous activities or uses of the site and/or resulting from the introduction onto the site of materials from off-site sources are outside the terms of reference for this project and have not been investigated or addressed.

Soil and groundwater conditions shown in the factual data and described in the report are the observed conditions at the time of their determination or measurement. Unless otherwise noted, those conditions form the basis of the recommendations in the report. Groundwater conditions may vary between and beyond reported locations and can be affected by annual, seasonal and meteorological conditions. The condition of the soil, rock and groundwater may be significantly altered by construction activities (traffic, excavation, groundwater level lowering, pile driving, blasting, etc.) on the site or on adjacent sites. Excavation may expose the soils to changes due to wetting, drying or frost. Unless otherwise indicated the soil must be protected from these changes during construction.

Sample Disposal: Golder will dispose of all uncontaminated soil and/or rock samples 90 days following issue of this report or, upon written request of the Client, will store uncontaminated samples and materials at the Client's expense. In the event that actual contaminated soils, fills or groundwater are encountered or are inferred to be present, all contaminated samples shall remain the property and responsibility of the Client for proper disposal.

Follow-Up and Construction Services: All details of the design were not known at the time of submission of Golder's report. Golder should be retained to review the final design, project plans and documents prior to construction, to confirm that they are consistent with the intent of Golder's report.

During construction, Golder should be retained to perform sufficient and timely observations of encountered conditions to confirm and document that the subsurface conditions do not materially differ from those interpreted conditions considered in the preparation of Golder's report and to confirm and document that construction activities do not adversely affect the suggestions, recommendations and opinions contained in Golder's report. Adequate field review, observation and testing during construction are necessary for Golder to be able to provide letters of assurance, in accordance with the requirements of many regulatory authorities. In cases where this recommendation is not followed, Golder's responsibility is limited to interpreting accurately the information encountered at the borehole locations, at the time of their initial determination or measurement during the preparation of the Report.

Changed Conditions and Drainage: Where conditions encountered at the site differ significantly from those anticipated in this report, either due to natural variability of subsurface conditions or construction activities, it is a condition of this report that Golder be notified of any changes and be provided with an opportunity to review or revise the recommendations within this report. Recognition of changed soil and rock conditions requires experience and it is recommended that Golder be employed to visit the site with sufficient frequency to detect if conditions have changed significantly.

Drainage of subsurface water is commonly required either for temporary or permanent installations for the project. Improper design or construction of drainage or dewatering can have serious consequences. Golder takes no responsibility for the effects of drainage unless specifically involved in the detailed design and construction monitoring of the system.



APPENDIX B

Aerial Photographs



APPENDIX B
Aerial Photographs



Figure B.1. Aerial Photograph, 1939



Figure B.2. Aerial Photograph, 1958



APPENDIX B
Aerial Photographs



Figure B.3. Aerial Photograph, 1961



Figure B.4. Aerial Photograph, 1970



APPENDIX B
Aerial Photographs



Figure B.5. Aerial Photograph, 1974



Figure B.6. Aerial Photograph, 1977



APPENDIX B
Aerial Photographs



Figure B.7. Aerial Photograph, 1987



Figure B.8. Aerial Photograph, 1997



APPENDIX B
Aerial Photographs



Figure B.9. Aerial Photograph, 2001




Figure B.10. Aerial Photograph, 2006



APPENDIX B
Aerial Photographs



Figure B.11. Aerial Photograph, 2011



APPENDIX C

Field Inspection Photographs



Photo C.1. Looking East at Deflection of Curb and Fence Line along Cherry Lane (Nov 5, 2006)



Photo C.2. Looking East at Deflection of Curb and Fence Line along Cherry Lane (May 27, 2010)



Photo C.3. Looking East at Deflection of Curb and Fence Line along Cherry Lane (April 26, 2012)



Photo C.4. Looking West at Toe of Upper Slope (April 26, 2012)



Photo C.5. Headscarp in the Backyard of 233-235 11th St. E. (June 21, 2012)



Photo C.6. Bulging Toe of Slide on Cherry Lane (June 21, 2012)



Photo C.7. Bulging Toe of Slide below Cherry Lane (June 21, 2012)



Photo C.8. Cracking Behind Retaining Wall in Backyard of 237-239 11th St. E. (June 21, 2012)



Photo C.9. Retaining Wall in Backyard of 237-239 11th St. E. (June 21, 2012)



Photo C.10. Looking East at Tension Cracking along Cherry Lane (June 21, 2013)



Photo C.11. Cracking along Headscarp of East Failure (June 21, 2012)



Photo C.12. Looking East at Headscarp of East Failure in Backyard of 305 11th St. E.; Approx. 90 cm Drop (June 24, 2013)



Photo C.13. Headscarp of East Failure in Backyard of 303 11th St. E.; Approx. 60 cm Drop (June 24, 2013)



Photo C.14. Looking East at Bulging Toe of Slide above Retaining Wall behind 306 Sask. Cres. E. (June 24, 2013)



Photo C.15. Looking East at Severe Cracking across Cherry Lane, Pavement; Approx. 50 cm Drop (June 24, 2013)



Photo C.16. Looking East at Scarp & Tension Cracking on Cherry Lane (June 24, 2013)



Photo C.17. Retaining Wall in Backyard of 237-239 11th St. E. (June 4, 2013)




Photo C.18. Retaining Wall in Backyard of 237-239 11th St. E. (June 20, 2013)



Photo C.19. Retaining Wall in Backyard of 237-239 11th St. E. (June 24, 2013)



Photo C.20. Looking East at Drop in Pavement behind 305 11th St. E.; Approx 53 cm Drop (June 4, 2013)



Photo C.21. Looking East at Public Works Filling Cracks and Regrading Lane (June 5, 2013)



Photo C.22. Looking West at Erosion along Cherry Lane (June 6, 2013)



Photo C.23. Looking West at Berm Along North Edge of Cherry Lane, behind 306 Sask. Cres. E. (July 7, 2013)



Photo C.24. Looking Northeast at Trench being Excavated Adjacent to Wall between 230 & 306 Sask. Cres. E. (July 7, 2013)



Photo C.25. Looking Northeast at Concrete Retaining Wall between 230 & 306 Sask. Cres. E. (July 7, 2013)



Photo C.26. Looking North at Concrete Retaining Wall between 230 & 306 Sask. Cres. E. (July 7, 2013)



Photo C.27. Looking East at New Tension Cracking Forming on Regraded Lane (July 7, 2013)



Photo C.28. Looking North at Partially Filled Trench (July 17, 2013)




Photo C.29. Looking East at Above Ground Driantage System Installed on Cherry Lane (September 18, 2013)



APPENDIX D

Topographic Survey Plan



KEYPLAN
Scale: 1:2500


CONTROL POINTS				
POINT	NAD 83 (CSRS)		UTM ZONE 13	
	NORTHING (m)	EASTING (m)	ORTHOMETRIC ELEVATION (m) HTv2.0	DESCRIPTION
CP-1	5,775,701.84	385,897.84	477.97	24" REBAR WITH PLASTIC CAP
CP-2	5,775,680.32	386,022.25	478.99	24" REBAR WITH PLASTIC CAP
CP-3	5,775,693.72	386,071.10	479.49	24" REBAR WITH PLASTIC CAP
CP-4	5,775,692.40	385,951.67	477.95	GPS CONTROL POINT
TP-4	5,775,565.50	386,118.76	499.32	X IN CONCRETE
TP-5	5,775,549.79	386,001.87	498.05	X IN NORTH RIM CATCH BASIN
TP-7	5,775,566.48	385,909.52	491.32	X IN SOUTH RIM MANHOLE
TP-8	5,775,560.37	385,809.26	484.62	X IN WEST RIM MANHOLE
D1-008	5,775,775.85	386,467.62	499.033	CONTROL TABLET

STAND PIPES (PIEZOMETERS) and SLOPE INDICATORS					
POINT	NAD 83 (CSRS)		UTM ZONE 13		GROUND ELEVATION (m)
	NORTHING (m)	EASTING (m)	ORTHOMETRIC ELEVATION (m) HTv2.0	DESCRIPTION	
44	5,775,674.76	386,061.60	480.88	COS-13-003 (SP)	480.343
102	5,775,620.13	386,037.21	489.00	PIEZOMETER (SP)	488.597
103	5,775,627.80	386,037.09	488.65	PIEZOMETER (SP)	487.852
104	5,775,626.17	386,029.80	487.78	PIEZOMETER (SP)	487.340
105	5,775,621.04	386,023.51	488.17	PIEZOMETER (SP)	487.843
110	5,775,629.91	386,023.30	487.32	PIEZOMETER (SP)	486.554
111	5,775,637.71	386,047.56	486.00	COS-13-005 (SP)	485.408
112	5,775,600.60	386,028.65	493.75	PIEZOMETER (SP)	492.734
117	5,775,609.14	386,050.90	492.39	PIEZOMETER (SP)	491.388
127	5,775,573.48	385,959.11	495.34	COS-13-007 (SP)	494.799

STAND PIPES (PIEZOMETERS) and SLOPE INDICATORS					
POINT	NAD 83 (CSRS)		UTM ZONE 13		GROUND ELEVATION (m)
	NORTHING (m)	EASTING (m)	ORTHOMETRIC ELEVATION (m) HTv2.0	DESCRIPTION	
118	5,775,604.97	386,050.63	491.61	COS-13-004 (SI)	491.738
119	5,775,616.97	386,010.94	488.09	11-0057-BH1 (SI)	488.207
120*	5,775,621.52	385,986.89	486.16	11-0057-BH2 (SI)	486.157
121	5,775,622.14	385,959.83	483.97	11-0057-BH3 (SI)	484.035
128	5,775,572.72	385,959.21	494.62	COS-13-006 (SI)	494.767
130	5,775,567.41	386,043.54	498.37	COS-13-002 (SI)	498.483
131	5,775,616.67	386,038.94	489.23	COS-13-001 (SI)	489.339

* Could not locate PVC pipe in metal collar. Elevation to north rim of collar.

Elevations are to North Rim of PVC pipe and to typical ground beside said pipe.



Note by Golder:
Subsequent to this survey, Golder discovered that the surveyed location of this borehole was incorrect. The borehole location was resurveyed by Golder. The correct coordinates are:
Northing: 5775631.30 m
Easting: 386078.85 m
Orthometric Elevation: 494.39 masl
Ground Elevation: 494.48 masl

- NOTES**
- TOPOGRAPHIC SURVEY CONDUCTED TO PROVIDE THE OVERALL GEOMETRY OF THE SLOPE IN AREA OF INTEREST. SURVEY DOES NOT PURPORT TO ILLUSTRATE ALL SITE DETAIL. CERTAIN AREAS CONTAIN LESS TOPOGRAPHIC DETAIL DUE TO SCOPE LIMITATIONS OR SAFETY ISSUES OF WORKING IN PROXIMITY TO COMPROMISED STRUCTURES.
 - SPOT ELEVATIONS AND BREAKLINE INFORMATION RESIDE ON LAYERS "TOPO-ELEV" AND "TOPO-BREAKLINES" OF ASSOCIATED PROJECT CAD FILE.
 - MEASUREMENTS AND ELEVATIONS ARE IN METERS AND DECIMALS THEREOF.
 - ELEVATIONS ARE BASED ON COS BENCHMARK D1-008 (ORTHOMETRIC ELEV. 499.033).
 - HORIZONTAL COORDINATES ARE DERIVED FROM PRECISE POINT POSITIONING.
 - CONTOUR INTERVALS ARE 0.50 METERS.
 - BACKGROUND PARCEL INFORMATION IS DERIVED FROM THE GeoSask BASE.
 - DATA PICKUP BETWEEN HOUSES IS SPARSE AND CONTOURS ARE INTERPOLATED BASED ON DATA ACQUIRED.

LEGEND

- CONTROL POINTS ARE SHOWN THUS Δ
- STANDARD IRON POSTS ARE SHOWN THUS ◆
- PIEZOMETERS ARE SHOWN THUS PZ
- MANHOLES ARE SHOWN THUS S
- CATCHBASINS ARE SHOWN THUS □
- BUILDINGS ARE SHOWN THUS []
- C OF ROAD IS SHOWN THUS —
- EDGE OF ASPHALT ROAD IS SHOWN THUS - - -
- EDGE OF SIDEWALK IS SHOWN THUS - - -
- POWERLINES AND POWERPOLES ARE SHOWN THUS — OH —
- RETAINING WALLS ARE SHOWN THUS - - -

TOPOGRAPHIC SURVEY
SHOWING Surface Features of the
200 & 300 Blocks of Saskatchewan Crescent & 11th Street
in
S.W. Sec. 28 Twp. 36 - Rge. 5 - W3rd Mer.
Saskatoon, Saskatchewan

Drawn By: kgb	Date: July 31, 2013	Drawing Name: S13152Topo-UTM.dwg	Scale: 1:500	Prepared by: Meridian Surveys Ltd.
Checked By: gar	Date: July 31, 2013	File No.: S13152	Rev: 1	

REVISIONS

NO.	DATE	REVISION	REV. BY	CHD. BY	DES. ENG.
1	Sept. 4, 2013	Added Piezometers and slope indicators.	kgb	mp	



APPENDIX E


Records of Boreholes



METHOD OF SOIL CLASSIFICATION

The Golder Associates Ltd. Soil Classification System is based on the Unified Soil Classification System (USCS)

Organic or Inorganic	Soil Group	Type of Soil	Gradation or Plasticity	$Cu = \frac{D_{60}}{D_{10}}$	$Cc = \frac{(D_{30})^2}{D_{10} \times D_{60}}$	Organic Content	USCS Group Symbol	Group Name				
INORGANIC (Organic Content $\leq 30\%$ by mass)	COARSE-GRAINED SOILS ($>50\%$ by mass is larger than 0.075 mm)	GRAVELS ($>50\%$ by mass of coarse fraction is larger than 4.75 mm)	Poorly Graded	<4	≤ 1 or ≥ 3	$\leq 30\%$	GP	GRAVEL				
			Well Graded	≥ 4	1 to 3		GW	GRAVEL				
			Below A Line	n/a			GM	SILTY GRAVEL				
			Above A Line	n/a			GC	CLAYEY GRAVEL				
		SANDS ($\geq 50\%$ by mass of coarse fraction is smaller than 4.75 mm)	Poorly Graded	<6	≤ 1 or ≥ 3		SP	SAND				
			Well Graded	≥ 6	1 to 3		SW	SAND				
			Below A Line	n/a			SM	SILTY SAND				
			Above A Line	n/a			SC	CLAYEY SAND				
Organic or Inorganic	Soil Group	Type of Soil	Laboratory Tests	Field Indicators					Organic Content	USCS Group Symbol	Primary Name	
				Dilatancy	Dry Strength	Shine Test	Thread Diameter	Toughness (of 3 mm thread)				
INORGANIC (Organic Content $\leq 30\%$ by mass)	FINE-GRAINED SOILS ($\geq 50\%$ by mass is smaller than 0.075 mm)	SILTS (Non-Plastic or PL and LL plot below A-Line on Plasticity Chart below)	Liquid Limit <50	Rapid	None	None	>6 mm	N/A (can't roll 3 mm thread)	$<5\%$	ML	SILT	
				Slow	None to Low	Dull	3mm to 6 mm	None to low	$<5\%$	ML	CLAYEY SILT	
			Liquid Limit ≥ 50	Slow to very slow	Low to medium	Dull to slight	3mm to 6 mm	Low	5% to 30%	OL	ORGANIC SILT	
				Slow to very slow	Low to medium	Slight	3mm to 6 mm	Low to medium	$<5\%$	MH	CLAYEY SILT	
			CLAYS (PI and LL plot above A-Line on Plasticity Chart below)	Liquid Limit <30	None	Low to medium	Slight to shiny	~ 3 mm	Low to medium	0% to 30%	CL	SILTY CLAY
					None	Medium to high	Slight to shiny	1 mm to 3 mm	Medium	(see Note 2)	CI	SILTY CLAY
		None			High	Shiny	<1 mm	High	(see Note 2)	CH	CLAY	
		HIGHLY ORGANIC SOILS (Organic Content $>30\%$ by mass)	Peat and mineral soil mixtures							30% to 75%	PT	SILTY PEAT, SANDY PEAT
										75% to 100%		PEAT



Note 1 – Fine grained materials with PI and LL that plot in this area are named (ML) SILT with slight plasticity. Fine-grained materials which are non-plastic (i.e. a PL cannot be measured) are named SILT.
 Note 2 – For soils with $<5\%$ organic content, include the descriptor “trace organics” for soils with between 5% and 30% organic content include the prefix “organic” before the Primary name.

Dual Symbol — A dual symbol is two symbols separated by a hyphen, for example, GP-GM, SW-SC and CL-ML. For non-cohesive soils, the dual symbols must be used when the soil has between 5% and 12% fines (i.e. to identify transitional material between “clean” and “dirty” sand or gravel. For cohesive soils, the dual symbol must be used when the liquid limit and plasticity index values plot in the CL-ML area of the plasticity chart (see Plasticity Chart at left).

Borderline Symbol — A borderline symbol is two symbols separated by a slash, for example, CL/CI, GM/SM, CL/ML. A borderline symbol should be used to indicate that the soil has been identified as having properties that are on the transition between similar materials. In addition, a borderline symbol may be used to indicate a range of similar soil types within a stratum.





ABBREVIATIONS AND TERMS USED ON RECORDS OF BOREHOLES AND TEST PITS

PARTICLE SIZES OF CONSTITUENTS

Soil Constituent	Particle Size Description	Millimetres	Inches (US Std. Sieve Size)
BOULDERS	Not Applicable	>300	>12
COBBLES	Not Applicable	75 to 300	3 to 12
GRAVEL	Coarse	19 to 75	0.75 to 3
	Fine	4.75 to 19	(4) to 0.75
SAND	Coarse	2.00 to 4.75	(10) to (4)
	Medium	0.425 to 2.00	(40) to (10)
	Fine	0.075 to 0.425	(200) to (40)
SILT/CLAY	Classified by plasticity	<0.075	< (200)

MODIFIERS FOR SECONDARY AND MINOR CONSTITUENTS

Percentage by Mass	Modifier
>35	Use 'and' to combine major constituents (i.e., SAND and GRAVEL, SAND and CLAY)
> 12 to 35	Primary soil name prefixed with "gravelly, sandy, SILTY, CLAYEY" as applicable
> 5 to 12	some
≤ 5	trace

PENETRATION RESISTANCE

Standard Penetration Resistance (SPT), N:

The number of blows by a 63.5 kg (140 lb) hammer dropped 760 mm (30 in.) required to drive a 50 mm (2 in.) split-spoon sampler for a distance of 300 mm (12 in.).

Cone Penetration Test (CPT)

An electronic cone penetrometer with a 60° conical tip and a project end area of 10 cm² pushed through ground at a penetration rate of 2 cm/s. Measurements of tip resistance (q_t), porewater pressure (u) and sleeve frictions are recorded electronically at 25 mm penetration intervals.

Dynamic Cone Penetration Resistance (DCPT); N_d:

The number of blows by a 63.5 kg (140 lb) hammer dropped 760 mm (30 in.) to drive uncased a 50 mm (2 in.) diameter, 60° cone attached to "A" size drill rods for a distance of 300 mm (12 in.).

- PH:** Sampler advanced by hydraulic pressure
PM: Sampler advanced by manual pressure
WH: Sampler advanced by static weight of hammer
WR: Sampler advanced by weight of sampler and rod

SAMPLES

AS	Auger sample
BS	Block sample
CS	Chunk sample
DO or DP	Seamless open ended, driven or pushed tube sampler – note size
DS	Denison type sample
FS	Foil sample
RC	Rock core
SC	Soil core
SS	Split spoon sampler – note size
ST	Slotted tube
TO	Thin-walled, open – note size
TP	Thin-walled, piston – note size
WS	Wash sample

SOIL TESTS

w	water content
PL, w _p	plastic limit
LL, w _L	liquid limit
C	consolidation (oedometer) test
CHEM	chemical analysis (refer to text)
CID	consolidated isotropically drained triaxial test ¹
CIU	consolidated isotropically undrained triaxial test with porewater pressure measurement ¹
D _r	relative density (specific gravity, G _s)
DS	direct shear test
GS	specific gravity
M	sieve analysis for particle size
MH	combined sieve and hydrometer (H) analysis
MPC	Modified Proctor compaction test
SPC	Standard Proctor compaction test
OC	organic content test
SO ₄	concentration of water-soluble sulphates
UC	unconfined compression test
UU	unconsolidated undrained triaxial test
V (FV)	field vane (LV-laboratory vane test)
γ	unit weight

1. Tests which are anisotropically consolidated prior to shear are shown as CAD, CAU.

NON-COHESIVE (COHESIONLESS) SOILS

Compactness²

Term	SPT 'N' (blows/0.3m) ¹
Very Loose	0 - 4
Loose	4 to 10
Compact	10 to 30
Dense	30 to 50
Very Dense	>50

1. SPT 'N' in accordance with ASTM D1586, uncorrected for overburden pressure effects.
 2. Definition of compactness descriptions based on SPT 'N' ranges from Terzaghi and Peck (1967) and correspond to typical average N₆₀ values.

Field Moisture Condition

Term	Description
Dry	Soil flows freely through fingers.
Moist	Soils are darker than in the dry condition and may feel cool.
Wet	As moist, but with free water forming on hands when handled.

COHESIVE SOILS

Consistency

Term	Undrained Shear Strength (kPa)	SPT 'N' ¹ (blows/0.3m)
Very Soft	<12	0 to 2
Soft	12 to 25	2 to 4
Firm	25 to 50	4 to 8
Stiff	50 to 100	8 to 15
Very Stiff	100 to 200	15 to 30
Hard	>200	>30

1. SPT 'N' in accordance with ASTM D1586, uncorrected for overburden pressure effects; approximate only.

Water Content

Term	Description
w < PL	Material is estimated to be drier than the Plastic Limit.
w ~ PL	Material is estimated to be close to the Plastic Limit.
w > PL	Material is estimated to be wetter than the Plastic Limit.



LIST OF SYMBOLS

Unless otherwise stated, the symbols employed in the report are as follows:

I. GENERAL

π	3.1416
$\ln x$	natural logarithm of x
$\log_{10} x$	x or log x, logarithm of x to base 10
g	acceleration due to gravity
t	time

II. STRESS AND STRAIN

γ	shear strain
Δ	change in, e.g. in stress: $\Delta \sigma$
ε	linear strain
ε_v	volumetric strain
η	coefficient of viscosity
ν	Poisson's ratio
σ	total stress
σ'	effective stress ($\sigma' = \sigma - u$)
σ'_{vo}	initial effective overburden stress
$\sigma_1, \sigma_2, \sigma_3$	principal stress (major, intermediate, minor)
σ_{oct}	mean stress or octahedral stress = $(\sigma_1 + \sigma_2 + \sigma_3)/3$
τ	shear stress
u	porewater pressure
E	modulus of deformation
G	shear modulus of deformation
K	bulk modulus of compressibility

III. SOIL PROPERTIES

(a) Index Properties

$\rho(\gamma)$	bulk density (bulk unit weight)*
$\rho_d(\gamma_d)$	dry density (dry unit weight)
$\rho_w(\gamma_w)$	density (unit weight) of water
$\rho_s(\gamma_s)$	density (unit weight) of solid particles
γ'	unit weight of submerged soil ($\gamma' = \gamma - \gamma_w$)
D_R	relative density (specific gravity) of solid particles ($D_R = \rho_s / \rho_w$) (formerly G_s)
e	void ratio
n	porosity
S	degree of saturation

(a) Index Properties (continued)

w	water content
w_l or LL	liquid limit
w_p or PL	plastic limit
I_p or PI	plasticity index = $(w_l - w_p)$
w_s	shrinkage limit
I_L	liquidity index = $(w - w_p) / I_p$
I_C	consistency index = $(w_l - w) / I_p$
e_{max}	void ratio in loosest state
e_{min}	void ratio in densest state
I_D	density index = $(e_{max} - e) / (e_{max} - e_{min})$ (formerly relative density)

(b) Hydraulic Properties

h	hydraulic head or potential
q	rate of flow
v	velocity of flow
i	hydraulic gradient
k	hydraulic conductivity (coefficient of permeability)
j	seepage force per unit volume

(c) Consolidation (one-dimensional)

C_c	compression index (normally consolidated range)
C_r	recompression index (over-consolidated range)
C_s	swelling index
C_α	secondary compression index
m_v	coefficient of volume change
C_v	coefficient of consolidation (vertical direction)
C_h	coefficient of consolidation (horizontal direction)
T_v	time factor (vertical direction)
U	degree of consolidation
σ'_p	pre-consolidation stress
OCR	over-consolidation ratio = σ'_p / σ'_{vo}

(d) Shear Strength

τ_p, τ_r	peak and residual shear strength
ϕ'	effective angle of internal friction
δ	angle of interface friction
μ	coefficient of friction = $\tan \delta$
c'	effective cohesion
c_u, s_u	undrained shear strength ($\phi = 0$ analysis)
p	mean total stress $(\sigma_1 + \sigma_3)/2$
p'	mean effective stress $(\sigma'_1 + \sigma'_3)/2$
q	$(\sigma_1 - \sigma_3)/2$ or $(\sigma'_1 - \sigma'_3)/2$
q_u	compressive strength $(\sigma_1 - \sigma_3)$
S_t	sensitivity

* Density symbol is ρ . Unit weight symbol is γ where $\gamma = \rho g$ (i.e. mass density multiplied by acceleration due to gravity)

Notes: 1
2

$$\tau = c' + \sigma' \tan \phi'$$

$$\text{shear strength} = (\text{compressive strength})/2$$



LITHOLOGICAL AND GEOTECHNICAL ROCK DESCRIPTION TERMINOLOGY

WEATHERINGS STATE

Fresh: no visible sign of weathering

Faintly weathered: weathering limited to the surface of major discontinuities.

Slightly weathered: penetrative weathering developed on open discontinuity surfaces but only slight weathering of rock material.

Moderately weathered: weathering extends throughout the rock mass but the rock material is not friable.

Highly weathered: weathering extends throughout rock mass and the rock material is partly friable.

Completely weathered: rock is wholly decomposed and in a friable condition but the rock and structure are preserved.

BEDDING THICKNESS

<u>Description</u>	<u>Bedding Plane Spacing</u>
Very thickly bedded	Greater than 2 m
Thickly bedded	0.6 m to 2 m
Medium bedded	0.2 m to 0.6 m
Thinly bedded	60 mm to 0.2 m
Very thinly bedded	20 mm to 60 mm
Laminated	6 mm to 20 mm
Thinly laminated	Less than 6 mm

JOINT OR FOLIATION SPACING

<u>Description</u>	<u>Spacing</u>
Very wide	Greater than 3 m
Wide	1 m to 3 m
Moderately close	0.3 m to 1 m
Close	50 mm to 300 mm
Very close	Less than 50 mm

GRAIN SIZE

<u>Term</u>	<u>Size*</u>
Very Coarse Grained	Greater than 60 mm
Coarse Grained	2 mm to 60 mm
Medium Grained	60 microns to 2 mm
Fine Grained	2 microns to 60 microns
Very Fine Grained	Less than 2 microns

Note: * Grains greater than 60 microns diameter are visible to the naked eye.

CORE CONDITION

Total Core Recovery (TCR)

The percentage of solid drill core recovered regardless of quality or length, measured relative to the length of the total core run.

Solid Core Recovery (SCR)

The percentage of solid drill core, regardless of length, recovered at full diameter, measured relative to the length of the total core run.

Rock Quality Designation (RQD)

The percentage of solid drill core, greater than 100 mm length, recovered at full diameter, measured relative to the length of the total core run. RQD varied from 0% for completely broken core to 100% for core in solid sticks.

DISCONTINUITY DATA

Fracture Index

A count of the number of discontinuities (physical separations) in the rock core, including both naturally occurring fractures and mechanically induced breaks caused by drilling.

Dip with Respect to Core Axis

The angle of the discontinuity relative to the axis (length) of the core. In a vertical borehole a discontinuity with a 90° angle is horizontal.

Description and Notes

An abbreviation description of the discontinuities, whether naturally occurring separations such as fractures, bedding planes and foliation planes or mechanically induced features caused by drilling such as ground or shattered core and mechanically separated bedding or foliation surfaces. Additional information concerning the nature of fracture surfaces and infillings are also noted.

Abbreviations

JN Joint	PL Planar
FLT Fault	CU Curved
SH Shear	UN Undulating
VN Vein	IR Irregular
FR Fracture	K Slickensided
SY Stylolite	PO Polished
BD Bedding	SM Smooth
FO Foliation	SR Slightly Rough
CO Contact	RO Rough
AXJ Axial Joint	VR Very Rough
KV Karstic Void	
MB Mechanical Break	



APPENDIX E
Record of Borehole Logs

HISTORICAL BOREHOLE LOGS
TH 101, TH 101A, TH 102, TH103, TH 104, TH 105 (GE76)

Ground Engineering Ltd. Apr. 9, 1976. Geotechnical Investigation 216, 218 and 220 Saskatchewan Crescent

1/2 BH 101

JOB NO. GS-033
 LOCATION 216 - 220 Saskatchewan Crescent
SASKATOON, Saskatchewan
 TEST HOLE REFERENCE _____
 E LOGGED BY: _____ DATE _____
 SP. COND. WATER _____ mmhoes/cm. at _____ °C
 SP. COND. MUD _____ mmhoes/cm. at _____ °C
 SP _____ mv/cm. R _____ ohms/cm.

BOREHOLE NO. 101 DATE February 10, 1976
 SURFACE ELEVATION 1554.3 City Datum
 VERTICAL SCALE 1" = 20'
 DRILLED BY Hayter Drilling Co.
 DRILLER _____
 INTERPRETATION & SAMPLE DESCRIPTION BY:
GROUND ENGINEERING LTD.

GROUND ENGINEERING LTD.
 CIVIL AND GEOTECHNICAL ENGINEERS
 REGINA SASKATOON
BOREHOLE TEST REPORT

SHEET _____ OF _____

SHEAR STRENGTH K.S.F.


POCKET PEN 1.0 UNCONFINED 2.0 LAB VANE 4.0

▲ FIELD UNIT WEIGHT P.C.F. 3.0 115 120


MOISTURE CONTENT % 80 85 90 95 100 105 110 115 120

Nw ○ Pw | Lw →

ELEVATION	POTENTIAL	STRATIGRAPHIC SYMBOL	SAMPLE TYPE	RESISTIVITY	DEPTH	DESCRIPTION
			Bag			CLAY - silty, sandy - highly organic - becoming sandy @ 15'
			Bag			- pale olive, oxidized
			Bag			- massive, Fe stains
			Bag		20'6"	- boulders @ 20'
			Bag			SAND - coarse grained
			Bag		26'0"	- well graded
			Bag			TILL - clayey with fine sand lenses @ 58'
			Bag			- grey
			Bag			- unoxidized
			Bag			- pebbles
			Bag			- boulders @ 27', 38'6"
			Bag			40'6", 60'6", 66'6"
			Bag			and 72'0"
			Bag			- hard
			Bag			- massive
			Bag			
			Bag			
			Bag			
			Bag			
			Bag		100'0"	GRAVEL - poorly graded
			Bag		105'0"	- 1" diameter maximum size
			Bag			CLAY SHALE - grey, unoxidized
			Bag			- hard becoming softer with depth
			Bag			- massive
			Bag			- non calcareous




2/a
BH 701



160'0" END OF HOLE

NOTES: 4-3/4" diameter rotary
drill used.
Sloughing between 100 &
105'.
Bag samples taken from
S700 to S720 inclusive.




TEST HOLE LOG

DATE February 10, 1976

HOLE NO. 101A

SAMPLE DATA
WEIGHT HAMMER
HEIGHT DROP


ELEV. COLLAR
ELEV. GROUND 1554.3 (City Datum)
CO-ORD. LOCATION



DESCRIPTION OF MATERIAL

DEPTH ELEV.	NO TYPE	UNIF PI
10' 44.3		
20' 34.3		
30' 24.3	S721 Sy	CL 15.2
	S722 Sy	
40' 14.3	S723 Sy	CL 19.5
	S724 Sy	
50' 04.3		
	S725 Sy	
60' 494.3	S726 Sy	CL 22.0

CLAY - silty, sandy
 - highly organic becoming sandy @ 15'
 - pale olive
 - oxidized
 - massive
 - Fe stains
 - boulder @ 20'
 20'6" SAND - coarse grained
 - well graded
 26'0" TILL - clayey
 - unoxidized
 - hard & moist becoming extremely hard & dry @ 60'
 - pebbles
 - boulders encountered @ 30', 35' and 58'
 - massive
 62'0" END OF HOLE



NOTES: 4-3/4" diameter rotary drill used.

GROUND ENGINEERING LTD.
 GEOTECHNICAL ENGINEERS/Soil Mechanics & Foundations

PROPOSED HOUSING DEVELOPMENT
 216 - 220 SASKATCHEWAN CRESCENT
 LOCATION
 SASKATOON, Saskatchewan

JOB NO. GS-033

LOCATION 216 - 220 Saskatchewan Crescent

SASKATOON, Saskatchewan

TEST HOLE REFERENCE _____

E LOGGED BY: _____ DATE _____

SP. COND. WATER _____ mmhoes/cm. at _____ °C

SP. COND. MUD _____ mmhoes/cm. at _____ °C

SP 10 _____ mv/cm. R 10 _____ ohms/cm.

BOREHOLE NO. 102 DATE February 9, 1976

SURFACE ELEVATION 1615.3 City Datum


VERTICAL SCALE 1" = 20'

DRILLED BY Hayter Drilling Co.

DRILLER _____

INTERPRETATION & SAMPLE DESCRIPTION BY:

GROUND ENGINEERING LTD.



GROUND ENGINEERING LTD.

CIVIL AND GEOTECHNICAL ENGINEERS
REGINA SASKATOON


BOREHOLE TEST REPORT

SHEET _____ OF _____


SHEAR STRENGTH K.S.F.		POCKET PEN		UNCONFINED		LAB VANE	
80	85	90	95	100	105	110	115
10	20	30	40	50	60	70	80
FIELD UNIT WEIGHT P.C.F.		MOISTURE CONTENT %				Lw	
110	115	120	80	90			

ELEVATION	POTENTIAL	STRATIGRAPHIC SYMBOL	SAMPLE TYPE	RESISTIVITY	DEPTH	DESCRIPTION	P.I. & UNIFIED
		[Symbol]	Bag			CLAY - pale olive & oxidized with Fe stains becoming unoxidized @ 30' - massive - hard	
		[Symbol]	Bag				
		[Symbol]	Bag				
		[Symbol]	Bag				
		[Symbol]	Bag				
		[Symbol]	Bag				
		[Symbol]	Bag		56'0"	TILL - silty clay, grey - unoxidized, massive - stiff & dry - pebbles	
		[Symbol]	Bag				
		[Symbol]	Bag				
		[Symbol]	Bag		85'0"	SAND - coarse grained to fine grained, well graded to poorly graded - clean	
		[Symbol]	Bag		88'0"		
		[Symbol]	Bag				
		[Symbol]	Bag		95'0"	TILL - as above	
		[Symbol]	Bag		97'0"	SAND - as above	
		[Symbol]	Bag				
		[Symbol]	Bag			TILL - clayey, grey, - unoxidized - massive, hard - numerous pebbles & boulders	
		[Symbol]	Bag				

212
BH 102



150'0" SAND - medium to coarse grained
- poorly graded to medium graded,
- grey, unoxidized
162'0" GRAVEL
171'0" CLAY SHALE - grey, unoxidized
- massive, hard
- non calcareous
196'0" END OF HOLE



TEST HOLE LOG

DATE February 9, 1976

HOLE NO. 103

SAMPLE DATA				SYMBOL	ELEV. COLLAR		SHEAR STRENGTH KIPS/SQ. FT.							
WEIGHT HAMMER					ELEV. GROUND 1554.7 (City Datum)		<input type="checkbox"/> UNCONFINED <input type="checkbox"/> POCKET PEN. <input type="checkbox"/> LAB. VANE ▲ DRY DENSITY LBS./CU. FT.							
HEIGHT DROP					CO-ORD. LOCATION		PLASTIC LIMIT	WATER CONTENT	LIQUID LIMIT					
DEPTH ELEV.	NO. TYPE	UNIF. PI	RE-COVERY	DESCRIPTION OF MATERIAL					10	30	50	70	90%	
				0'6"	TOPSOIL									
				4'0"	CLAY - silty with some organic material									
				7'0"	SAND - silty - medium brown - oxidized - non-plastic - moist									
10'	S750	CL-ML												
44.7	Bag	6.9												
	S751			0.10	CLAY - silty and sandy - olive brown becoming olive grey @ 20' - oxidized - low plastic									
	Bag													
20'	S752	CL		0.04										
34.7	Bag	10.8												
	S753	CL			22'0"									
	Bag	25.1												
30'	S754	CL		0.04										
24.7	Bag	17.3			30'0"									
					TILL - silty clay - grey - oxidized becoming unoxidized @ 24' - very soft becoming stiff & moist @ 25' & very stiff @ 30' - pebbles									

NOTES: Hole terminated @ 30'0"
6" diameter continuous flight auger used. Water seepage.

GROUND ENGINEERING LTD.
 GEOTECHNICAL ENGINEERS/Soil Mechanics & Foundations

PROJECT: PROPOSED HOUSING DEVELOPMENT
 216 - 220 SASKATCHEWAN CRESCENT
 LOCATION: SASKATOON, Saskatchewan

DATE February 9, 1976

TEST HOLE LOG

HOLE NO. 104

SAMPLE DATA				SYMBOL	ELEV. COLLAR	SHEAR STRENGTH KIPS/SQ. FT. UNCONFINED <input type="checkbox"/> POCKET PEN. <input type="checkbox"/> LAB. VANE <input type="checkbox"/>				
WEIGHT HAMMER					ELEV. GROUND 1553.2 (City Datum)	▲ DRY DENSITY LBS./CU. FT. 80 90 100 110 120				
HEIGHT DROP					CO-ORD. LOCATION 6'W & 6'S of NE lot corner	PLASTIC LIMIT	WATER CONTENT	LIQUID LIMIT		
DEPTH ELEV.	NO. TYPE	UNIF. PI	RE-COVERY	DESCRIPTION OF MATERIAL		10	30	50	70	90%
	S755 Bag				1'0" TOPSOIL					
10'	S756 Bag				CLAY - silty and sandy with sand seams - olive brown - oxidized - dry becoming moist then soft & saturated @ 15'					
43.2	S757 Bag				- massive - Fe stains					
20'	S758 Bag				21'0" SAND - medium to coarse grained					
33.2	S759 Bag				23'0" - poorly to medium graded - pale olive - wet					
30'	S761 Bag	CL 17.0			30'0" TILL - clayey - grey - unoxidized - soft & wet becoming firm & moist @ 30' - pebbles					
23.2	S760 Bag	CL 18.4								

NOTES: Hole terminated @ 30'0"
6" diameter continuous flight auger used.
Water seepage @ 14'
Water level @ 17'

GROUND ENGINEERING LTD.
GEOTECHNICAL ENGINEERS/Soil Mechanics & Foundations

PROPOSED HOUSING PROJECT
216 - 220 SASKATCHEWAN CRESCENT
LOCATION
SASKATOON, SASKATCHEWAN

TEST HOLE LOG

DATE February 9, 1976

HOLE NO. 105

SAMPLE DATA			SYMBOL	ELEV. COLLAR		SHEAR STRENGTH KIPS/SQ. FT.			
WEIGHT HAMMER				ELEV. GROUND 1556.3 (City Datum)		■ UNCONFINED	□ POCKET PEN	□ LAB. VANE	
HEIGHT DROP				CO-ORD. LOCATION		▲ DRY DENSITY LBS./CU. FT.			
DEPTH ELEV.	NO. TYPE	UNIF. P.I.		DESCRIPTION OF MATERIAL		PLASTIC LIMIT		WATER CONTENT	LIQUID LIMIT
			10			30	50	70	90%
	S762 CL-ML Bag	4.8	1'0"	TOPSOIL	CLAY - silty with some organic material - pale olive becoming olive @ 10' - oxidized - dry - massive - frost to 3'				
10' 46.3	S763 Bag	0.10	11'0"	TILL	- silty clay - grey-brown becoming grey and unoxidized @ 20' - low plastic - very stiff & moist becoming hard & dry @ 20' (Floral) - massive - few pebbles - Fe stains - boulders @ 25'				
20' 36.3	S764 CL Bag	25.4	25'0"						
	S765 Sy								
	S766 CL Bag	20.0							
	S767 Sy								
	S768 CL Sy	20.4							

NOTES: Hole terminated @ 25'0"
6" diameter continuous flight auger used.
Water level @ 19'

GROUND ENGINEERING LTD.
GEOTECHNICAL ENGINEERS/Soil Mechanics & Foundations

PROJECT: **PROPOSED HOUSING PROJECT**
216 - 220 SASKATCHEWAN CRESCENT
LOCATION: **SASKATOON, Saskatchewan**



APPENDIX E
Record of Borehole Logs

HISTORICAL BOREHOLE LOGS
TH 201, TH 202, TH203, TH 204 (GE77)

Ground Engineering Ltd. July 4, 1977. Geotechnical Site Investigation Proposed Housing Complex, Saskatchewan Crescent

TEST HOLE LOG

DATE 77/06/07

HOLE NO. 201

SAMPLE DATA				SYMBOL	ELEV. COLLAR		SHEAR STRENGTH KIPS SQ FT <input type="checkbox"/> UNCONFINED <input type="checkbox"/> POCKET PEN <input type="checkbox"/> LAB VANE 0.2 0.6 1.0 1.4 1.8 ▲ DRY DENSITY LBS CU FT 80 90 100 110 120						
WEIGHT HAMMER					ELEV. GROUND		PLASTIC LIMIT WATER CONTENT LIQUID LIMIT ────────────┬───────────┬───────────▶ 10 30 50 70 90%						
HEIGHT DROP					CO-ORD. LOCATION								
DEPTH ELEV.	NO TYPE	UNIF PI	% SO.		DESCRIPTION OF MATERIAL								
	S42			Bags	2'6"	TOPSOIL - clay, silty, organic CLAY - low plasticity - very silty, organic to 10' - stratified, laminated - moist, firm, becoming stiff - light olive brown to olive grey, oxidized							
	Bag												
5	S43												
48	Bag												
	S44												
	Bag												
10	S45												
43	Bag												
	S46					13'0"		SILT - trace of sand - well graded fine sand layer 13'-13½' - poorly graded fine, silty gravel layer 19-20½' - olive grey, oxidized - wet, soft, stratified - sloughing					
	S47												
15	S48												
38	Bag												
	S49												
	Bag												
20	S50												
33	Bag				20'6"	TILL - clay, silty, fine gravel - dark olive grey, oxidized becoming very dark grey, unoxidized at 23' - wet, firm, becoming moist, hard - massive - shale fragments, Fe stains							
	S51												
	Bag												
25	S52												
28	Bag												
	S53												
	Bag												
30	S54												
23	Bag												
	S55												
	Bag												
35	S56												
18	Bag					END OF HOLE							

NOTES: - Mobile Model B52 continuous flight auger used, 6" diameter
 - sloughing at 16'

GROUND ENGINEERING LTD.
 GEOTECHNICAL ENGINEERS/Soil Mechanics & Foundations

PROJECT PROPOSED HOUSING PROJECT
 222 - 224 SASKATCHEWAN CRESCENT
 LOCATION SASKATOON, SASKATCHEWAN

DATE 77/06/07

TEST HOLE LOG

HOLE NO. 202

SAMPLE DATA				SYMBOL	ELEV. COLLAR	SHEAR STRENGTH KIPS/SO FT UNCONFINED <input type="checkbox"/> POCKET PEN <input type="checkbox"/> LAB VANE <input type="checkbox"/>		
WEIGHT HAMMER					ELEV. GROUND	DRY DENSITY LBS CU FT 80 90 100 110 120		
HEIGHT DROP					CO-ORD. LOCATION	PLASTIC LIMIT	WATER CONTENT	LIQUID LIMIT
DEPTH ELEV.	NO TYPE		% SO.		DESCRIPTION OF MATERIAL			
	S57 Bag			2'6"	TOPSOIL - clay, silty, organic			
5	S58 Bag				CLAY - very silty, low plasticity - light olive brown to olive, oxidized - stratified, laminated, soft, moist - organic to 10'			
50	S59 Bag	6						
10								
45								
				13'0"	TILL - clay, silty, frequent fine gravel, low plasticity			
15	S60 Sy				- olive brown to dark olive grey, oxidized, becoming very dark grey, unoxidized at 23' - massive, moist, stiff becoming very stiff - Fe stains, shale fragments below 23' - layer of fine, brown gravel, sandy 21'-23', saturated, sloughing			
40	S61 Bag							
20	S62 Bag	Bag						
35	S63 Sy	Sy						
25	S64 Bag							
30	S65 Bag							
30				30'0"	END OF HOLE			
25								

NOTES: - Mobile Model B52 Continuous Flight Auger used, 6" diameter
 - sloughing 21-23', water level at 18' 2 hours after completion

GROUND ENGINEERING LTD.
 GEOTECHNICAL ENGINEERS/Soil Mechanics & Foundations
 243

PROJECT PROPOSED HOUSING PROJECT
 222 - 224 SASKATCHEWAN CRESCENT
 LOCATION SASKATOON, SASKATCHEWAN

TEST HOLE LOG

DATE 77/06/07

HOLE NO. 203

SAMPLE DATA				SYMBOL	ELEV. COLLAR		SHEAR STRENGTH KIPS SQ FT				
WEIGHT HAMMER					ELEV. GROUND <u>1557.4 City Datum</u>		<input type="checkbox"/> UNCONFINED <input type="checkbox"/> POCKET PEN <input type="checkbox"/> LAB VANE 0.2 0.6 1.0 1.4 1.8				
HEIGHT DROP					CO-ORD. LOCATION		▲ DRY DENSITY LBS CU FT 80 90 100 110 120				
DEPTH ELEV.	NO TYPE	UNIF PI	% SO.		DESCRIPTION OF MATERIAL		PLASTIC LIMIT WATER CONTENT LIQUID LIMIT 10 30 50 70 90%				
	S64			[Symbol]	TOPSOIL - clay, silty, organic						
5	S65			[Symbol]	2'0" CLAY - very silty, low plasticity, organic - stratified, dry, stiff - dark greyish brown, oxidized						
52	S66			[Symbol]	6'6" TILL - clay, silty, low plasticity frequent fine gravel - massive, nuggetty to 9' - dark greyish brown, oxidized becoming very dark grey, unoxidized at 11'						
10	S67			[Symbol]	11'0" - dry, stiff - shale stones from 11', Fe stains, gypsum						
47	S68			[Symbol]							
15	S69			[Symbol]	20'0" END OF HOLE						
42	S70			[Symbol]							
20	S71			[Symbol]							

NOTES: - Mobile Model B52 continuous flight auger used, 6" diameter
- hole dry

GROUND ENGINEERING LTD.
 GEOTECHNICAL ENGINEERS/Soil Mechanics & Foundations
 244

PROJECT PROPOSED HOUSING PROJECT
 222 - 224 SASKATCHEWAN CRESCENT
 LOCATION
 SASKATOON, SASKATCHEWAN

TEST HOLE LOG

DATE 77/06/07

HOLE NO. 204

SAMPLE DATA				SYMBOL	ELEV. COLLAR	<input checked="" type="checkbox"/> UNCONFINED SHEAR STRENGTH KIPS SQ FT 0.2 0.5 1.0 1.4 1.8 <input type="checkbox"/> POCKET PEN <input checked="" type="checkbox"/> LAB VANE ▲ DRY DENSITY LBS CU FT 80 90 100 110 120	
WEIGHT HAMMER					ELEV. GROUND	PLASTIC LIMIT WATER CONTENT LIQUID LIMIT ----- ----- ----- ----- ----- 10 30 50 70 90%	
HEIGHT DROP					CO-ORD. LOCATION	DESCRIPTION OF MATERIAL	
DEPTH ELEV.	NO TYPE	UNIF PT	% SO.				
				1'0"	TOPSOIL - clay, organic		
	S76				CLAY - very silty, moist - sand layer at 13'; silty - water bearing sand layer @ 18', sloughing - olive grey, oxidized		
5 49	S77						
	S78						
10 44	S79						
	S80						
15 39	S81			19'0"	TILL - clayey, silty, low plasticity frequent gravel. - 19 - 21½' gravel, fine, silty, water bearing - very dark grey, unoxidized - moist, stiff, massive		
	S82						
20 34	S83						
	S84						
25 29	S85						
	S86			30'0"	Z END OF HOLE NOTES: - Mobile Model B52 Continuous flight auger used, 6" diameter - sloughing to 17', water level at 16' on completion		
30 24							

GROUND ENGINEERING LTD.
 GEOTECHNICAL ENGINEERS/Soil Mechanics & Foundations
 245

PROJECT PROPOSED HOUSING PROJECT
 222-224 SASKATCHEWAN CRESCENT
 LOCATION
 SASKATOON, Saskatchewan




HISTORICAL BOREHOLE LOGS
TH 301 (PMEL81)

P. Machibroda Engineering Ltd. June 17, 1981. Geotechnical Investigation Proposed Apartment Building
Saskatchewan Crescent, Saskatoon, Saskatchewan


TEST HOLE 301

ELEV. 476.9 m (CITY DATUM)

SO_d U $\bar{\sigma}_d$ Pw Lw w



LEGEND:



COMBINATION OF ABOVE SHOWN WITH PREDOMINANT SOIL TYPE IN HEAVY LINE AND MODIFYING SOIL TYPE IN LIGHT LINE.

$\bar{\sigma}_d$ DRY DENSITY (kg/m³)

w WATER CONTENT (PERCENT OF DRY SOIL WT)

Lw LIQUID LIMIT

Pw PLASTIC LIMIT

U UNCONFINED COMPRESSIVE STRENGTH (k Pa)

SO_d SULPHATE CONTENT (PERCENT OF DRY SOIL)

TR TRACE

* SULPHATE CONTENT WATER SAMPLE (PPM)

v RECORDED WATER LEVEL

N NUMBER OF BLOWS TO ADVANCE A 51 mm O.D. SPLIT SAMPLER 30 cm INTO THE SOIL USING A 63.5 kg HAMMER DROPPING FREELY A DISTANCE OF 76 cm (475 J PER BLOW).

LIMITATIONS:

THE FIELD DRILL LOG IS A SUMMARY OF FIELD CONDITIONS ENCOUNTERED AT A SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THE SPECIFIC LOCATION OF ANY TEST HOLE.

P. MACHIBRODA ENGINEERING LTD.



2331 MILLAR AVENUE
SASKATOON, SASK.

CONSULTING
ENGINEERS

FIELD DRILL LOGS AND SOIL TEST RESULTS

PROJECT:

PROPOSED APARTMENT BUILDING
SASKATOON, SASKATCHEWAN

LOCATION:

200 BLOCK SASKATCHEWAN CRES.
SASKATOON, SASKATCHEWAN

SCALE: 1:50

DRAWING NUMBER:

DATE: JUNE 17, 1981

581-335-2




HISTORICAL BOREHOLE LOGS
TH 101, TH102, TH 103, TH 104, TH 105, TH 106, TH 107, P201, P202
(CLIF83)

Clifton Associates Ltd. Aug. 17, 1983. Geotechnical Studies Proposed Park Terrace Condominiums 222 Saskatchewan Crescent East Saskatoon, SK.

TEST HOLE LOG

DATE <u>83/07/28</u>	GROUND ELEV. <u>485.57 m (Geodetic)</u>	TEST HOLE NO. 102
DRILL <u>Brat 22</u>	LOCATION _____	SHEAR STRENGTH - kPa <input type="checkbox"/> UNCONF. <input type="checkbox"/> POCKET PEN. <input checked="" type="checkbox"/> LAB VANE 50 100 150 200
LOGGED BY <u>Dave Williamson</u>		



	Clifton Associates Ltd.	PROJECT <u>PARK TERRACE CONDOMINIUMS</u>
	CONSULTING GEOTECHNICAL ENGINEERS REGINA SASKATOON	LOCATION <u>Saskatoon, Saskatchewan</u>
		PROJECT NO. <u>S145</u> PAGE NO. _____

TEST HOLE LOG

DATE 83/07/28

GROUND ELEV. 480.82 m (Geodetic)


TEST HOLE NO. 105

DRILL Brat 22

LOCATION _____

LOGGED BY Dave Williamson

SHEAR STRENGTH - kPa
 UNCONF. POCKET PEN. LAB VANE
 50 100 150 200



Clifton Associates Ltd.
 CONSULTING GEOTECHNICAL ENGINEERS
 REGINA SASKATOON

PROJECT PARK TERRACE CONDOMINIUMS
 LOCATION Saskatoon, Saskatchewan
 PROJECT NO. S145 PAGE NO. _____

TEST HOLE LOG

DATE <u>83/07/28</u>	GROUND ELEV. <u>481.95 m (Geodetic)</u>	TEST HOLE NO. <u>106</u>
DRILL <u>Brat 22</u>	LOCATION _____	
LOGGED BY <u>Dave Williamson</u>	_____	SHEAR STRENGTH - kPa <input checked="" type="checkbox"/> UNCONF. <input type="checkbox"/> POCKET PEN. <input checked="" type="checkbox"/> LAB VANE 50 100 150 200

DEPTH m	SYMBOL	DESCRIPTION OF MATERIALS	SAMPLE	USC	PLASTIC LIMIT	WATER CONTENT	LIQUID LIMIT		
1		CLAY - silty, with organics - black (10YR2/1), oxidized - moist - disturbed (Fill)	S1	U	10	30	50		
1.4 m									
2		TILL - medium plastic silty sandy clay matrix - light olive brown (2.5y5/4), oxidized - becoming olive brown (2.5y4/4), with depth - moist - stiff to very stiff - brittle - heavy Fe stains	S2	U	10	30	50		
3			S3	U	10	30	50		
4			S4	U	10	30	50		
4.5 m E.O.H.									
5		NOTES: 1). Drilled using 125 mm diameter continuous flight, solid stem augers.							
					1300	1500	1700	1900	2100
					▲ DRY DENSITY - kg/m ³				



Clifton Associates Ltd.

CONSULTING GEOTECHNICAL ENGINEERS
REGINA SASKATOON

PROJECT PARK TERRACE CONDOMINIUMS

LOCATION Saskatoon, Saskatchewan

PROJECT NO. S145 PAGE NO. _____

TEST HOLE LOG

DATE <u>83/07/28</u>	GROUND ELEV. <u>497.254 m (Geodetic)</u>	TEST HOLE NO. <u>107</u>
DRILL <u>Brat 22</u>	LOCATION _____	SHEAR STRENGTH - kPa <input type="checkbox"/> UNCONF. <input type="checkbox"/> POCKET PEN. <input checked="" type="checkbox"/> LAB VANE
LOGGED BY <u>Dave Williamson</u>		

DEPTH m	SYMBOL	DESCRIPTION OF MATERIALS	SAMPLE	USC	SHEAR STRENGTH - kPa					
					PLASTIC LIMIT	WATER CONTENT			LIQUID LIMIT	
					10	50	100	150	200	90%
1	+	0.1 m TOFSOIL <i>SILT</i> - with silty clay lumps and fine sand - dark brown (10YR3/3), oxidized, becoming light grey (2.5Y7/2) below 0.8 m - heavy organics to 0.8 m - damp								
2	+									
3	+									
4	.	3.9 m <i>SAND</i> - fine grained, silty - light yellowish brown (2.5Y6/4), oxidized - damp								
5	~	4.8 m <i>CLAY</i> - highly plastic - olive (5Y4/3), oxidized - moist, stiff - laminated - organic odour - Fe stains								
6	-	6.0 m E.O.H. <u>NOTES:</u> 1). Drilled using 125 mm diameter, continuous flight, solid stem augers.								
										1300 1500 1700 1900 2100 ▲ DRY DENSITY - kg/m ³



Clifton Associates Ltd.
CONSULTING GEOTECHNICAL ENGINEERS
REGINA SASKATOON

PROJECT PARK TERRACE CONDOMINIUMS
 LOCATION Saskatoon, Saskatchewan
 PROJECT NO. S145 PAGE NO. _____

PIEZOMETER CONSTRUCTION DETAILS

DEPTH m	PIEZOMETER DETAIL	SYMBOL	SOIL DESCRIPTION	ELEV. m	PIEZOMETER NO. <u>P101</u> TEST HOLE NO. <u>101</u>																							
0		④		486.44	LOCATION _____																							
1		③	CLAY - fill - silty	486.36	TOP PIPE ELEV. <u>486.44</u> GROUND ELEV. <u>486.36</u> BASE SCREEN ELEV. <u>483.05</u> PIPE TYPE <u>38 mm PVC Schedule 80</u> SCREEN <u>51 mm PVC Johnson 10 slot</u>																							
2		②	CLAY - medium to highly plastic		TEST HOLE DIA. <u>125 mm</u> INST. DATE <u>July 28, 1983</u> TECHNICIAN <u>D.W. Williamson</u> CONTRACTOR <u>Anderson Drilling</u> DRILL <u>Brat 22 Continuous Flight</u>																							
3		①	TILL - oxidized	483.90	WATER LEVELS DATE TIME DEPTH-m ELEV.-m																							
4			- unoxidized		UPON COMPLETION																							
5					<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">83/07/28</td> <td style="width: 20%;">1545</td> <td style="width: 20%;">----</td> <td style="width: 20%;">----</td> </tr> <tr> <td colspan="4" style="text-align: center;">ADDITIONAL READINGS</td> </tr> <tr> <td>83/08/02</td> <td>0915</td> <td>2.04</td> <td>484.40</td> </tr> <tr> <td>83/08/09</td> <td>1355</td> <td>2.13</td> <td>484.31</td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table>	83/07/28	1545	----	----	ADDITIONAL READINGS				83/08/02	0915	2.04	484.40	83/08/09	1355	2.13	484.31							
83/07/28	1545	----	----																									
ADDITIONAL READINGS																												
83/08/02	0915	2.04	484.40																									
83/08/09	1355	2.13	484.31																									
6			GRAVEL	480.36	REMARKS <u>Construction Materials</u> <u>1. Auger Cuttings</u> <u>2. 12-20 Silica Sand</u> <u>3. Bentonite Pellets</u> <u>4. Auger Cuttings</u> <u>All elevations referenced to Geodetic Datum.</u>																							
					DRAWN BY <u>GJB</u> APPROVED BY _____																							



Clifton Associates Ltd.

CONSULTING GEOTECHNICAL ENGINEERS
REGINA SASKATOON

CLIENT Starport Investments Ltd.
PROJECT Park Terrace Condominiums
LOCATION Saskatoon, Saskatchewan
DATE 83/08/09 PROJECT NO. S145

PIEZOMETER CONSTRUCTION DETAILS

DEPTH m	PIEZOMETER DETAIL	SYMBOL	SOIL DESCRIPTION	ELEV. m	PIEZOMETER NO. <u>P102</u> TEST HOLE NO. <u>102</u>
				486.28	LOCATION _____
0	④	③	CLAY - fill - silty	485.57	TOP PIPE ELEV. <u>486.28 m</u>
			TOPSOIL		GROUND ELEV. <u>485.57 m</u>
1			TILL		BASE SCREEN ELEV. <u>480.35 m</u>
			CLAY - highly plastic		PIPE TYPE <u>38 mm PVC Schedule 80</u>
2			TILL - oxidized		SCREEN <u>51 mm PVC Johnson 10 slot</u>
	②		- unoxidized		TEST HOLE DIA. <u>125 mm</u>
3			- sandy silt from 3.9 to 4.2 m		INST. DATE <u>July 28, 1983</u>
					TECHNICIAN <u>D. W. Williamson</u>
4					CONTRACTOR <u>Anderson Drilling</u>
					DRILL <u>Brat 22 Continuous Flight</u>
5				481.20	WATER LEVELS
					DATE TIME DEPTH-m ELEV.-m
6	①			480.35	UPON COMPLETION
				480.28	<u>83/07/28</u> <u>1800</u> <u>3.37</u> <u>482.91</u>
					ADDITIONAL READINGS
					<u>83/08/02</u> <u>0920</u> <u>3.60</u> <u>482.68</u>
					<u>83/08/09</u> <u>1350</u> <u>3.63</u> <u>482.65</u>
					REMARKS <u>Construction Materials</u>
					<u>1. Auger Cuttings</u>
					<u>2. 12-20 Silica Sand</u>
					<u>3. Bentonite Pellets</u>
					<u>4. Auger Cuttings</u>
					<u>All elevations referenced to Geodetic Datum</u>
					DRAWN BY <u>GJB</u>
					APPROVED BY _____



Clifton Associates Ltd.

CONSULTING GEOTECHNICAL ENGINEERS
REGINA SASKATOON

CLIENT Starport Investments Ltd.

PROJECT Park Terrace Condominiums

LOCATION Saskatoon, Saskatchewan

DATE 83/08/09

PROJECT NO. S145

PIEZOMETER CONSTRUCTION DETAILS

DEPTH m	PIEZOMETER DETAIL	SYMBOL	SOIL DESCRIPTION	ELEV. m	PIEZOMETER NO. <u>P201</u> TEST HOLE NO. _____																								
					LOCATION <u>237 - 11th Street East</u>																								
0				497.21	TOP PIPE ELEV. <u>497.21 m</u>																								
2					GROUND ELEV. <u>497.27 m</u>																								
4						BASE SCREEN ELEV. <u>483.79 m</u>																							
6						PIPE TYPE <u>51 mm PVC Schedule 80</u>																							
8						SCREEN <u>51 mm PVC slotted with circular saw</u>																							
10						TEST HOLE DIA. <u>410 mm</u>																							
12						INST. DATE <u>July 22, 1983</u>																							
14						TECHNICIAN <u>Gerry Berube</u>																							
16						CONTRACTOR _____																							
						DRILL _____																							
					WATER LEVELS																								
					DATE TIME DEPTH-m ELEV.-m																								
					UPON COMPLETION																								
					ADDITIONAL READINGS																								
					<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">83/07/25</td> <td style="width: 15%;">1020</td> <td style="width: 15%;">11.63</td> <td style="width: 45%;">485.58</td> </tr> <tr> <td>83/08/09</td> <td>1610</td> <td>11.65</td> <td>485.56</td> </tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> </table>	83/07/25	1020	11.63	485.58	83/08/09	1610	11.65	485.56																
83/07/25	1020	11.63	485.58																										
83/08/09	1610	11.65	485.56																										
					REMARKS _____																								
					<i>Construction Materials</i>																								
					1. <i>Natural slough</i>																								
					2. <i>Concrete Sand</i>																								
					3. <i>Bentonite Pellets</i>																								
					4. <i>Sand Bentonite (10% Bentonite) mixture</i>																								
					5. <i>Cuttings</i>																								
					<i>Water depths referenced to top of pipe.</i>																								
					<i>Screen wrapped with filter cloth.</i>																								
					DRAWN BY <u>GJB</u>																								
					APPROVED BY _____																								



Clifton Associates Ltd.
CONSULTING GEOTECHNICAL ENGINEERS
REGINA SASKATOON

CLIENT Starport Investments Ltd.
PROJECT PARK TERRACE CONDOMINIUMS
LOCATION Saskatoon, Saskatchewan
DATE 83/07/25 PROJECT NO. S145



APPENDIX E
Record of Borehole Logs

HISTORICAL BOREHOLE LOGS
SI1, SI2, SI3, P801G, P802G, P803G (GAL85)

Golder Associates Ltd. May 1985. Progress Report No. 1 Slope Monitoring Program, Park Terrace Condominiums, 222 Saskatchewan Crescent East, Saskatoon, Saskatchewan


INSTRUMENTATION NEST NO. I SLOPE MONITORING PROGRAM

FIGURE SM I

PARK TERRACE CONDOMINIUMS

SASKATOON, SASK.

LOCATION — IN CHERRY LANE NEAR EAST PROPERTY LINE. (SEE LOCATION PLAN.)



SCALE — 1 : 75

DATE OF INSTALLATION

SLOPE INDICATOR SI I — APRIL 2, 1985.

PIEZOMETER P80IG — MAY 7, 1985.

Date MAY 16 / 85.
Project 852-6010

Golder Associates
201

Drawn N.E.
Chkd [Signature]


INSTRUMENTATION NEST NO. 2 SLOPE MONITORING PROGRAM

FIGURE SM 2

PARK TERRACE CONDOMINIUMS

SASKATOON, SASK.

LOCATION - CHERRY LANE NEAR WEST PROPERTY LINE (SEE LOCATION PLAN.)



SCALE - 1:75

DATE OF INSTALLATION

SLOPE INDICATOR SI 2 - APRIL 2, 1985.

PIEZOMETER P802G - MAY 7, 1985.

Date MAY 21/85.
Project 852-6010

Golder Associates

Drawn N.E.
Chkd [Signature]


INSTRUMENTATION NEST NO. 3 SLOPE MONITORING PROGRAM

FIGURE SM 3

PARK TERRACE CONDOMINIUMS

SASKATOON, SASK.

LOCATION - TOP OF SLOPE NEAR ELEVENTH STREET.



DATE OF INSTALLATION

SLOPE INDICATOR SI 3-APRIL 2, 1985.

PIEZOMETER P803G - MAY 7, 1985.

SCALE - 1 : 75

Date MAY. 21/85
Project 852-6010

Golder Associates

Drawn N.E.
Chkd AM



APPENDIX E
Record of Borehole Logs

HISTORICAL BOREHOLE LOGS
TH 97-01, TH 97-02, TH 97-03, TH 97-04 (PMEL97)

P. Machibroda Engineering Ltd. Sept. 15, 1997. Geotechnical Investigation and Slope Stability Study Proposed Residential Development, 237-11th Street East, Saskatoon, Saskatchewan


TEST HOLE 97-1

DEPTH (m)

PIEZO. ELEV. = 87.63 m

ELEV: 87.73 m


N U D Pw Lw w



ASPHALT CONCRETE BASE COURSE
FILL, Clay, silty, some sand, firm, medium plastic, dark brown.
TOPSOIL- silty, moist, black, rootlets, organics.
CLAY, silty, firm, medium to highly plastic, moist, olive brown, oxidized, iron stained.
GLACIAL TILL- Clay, silty, some sand, trace gravel, firm to stiff, medium plastic, olive brown, oxidized, iron stained, gypsum crystals,
 -wet, sand lenses at 3.0 m.
SILT, some sand, non to low plastic, moist, grey.
GLACIAL TILL- Clay, silty, some sand, trace gravel, stiff, low plastic, moist, grey.
 -boulder at 5.2 m.

NOTE:
 1) Auger refusal at 5.2 m.

LEGEND:



pp....POCKET PENETROMETER (kg/cm²)
 w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
 Lw....LIQUID LIMIT
 Pw....PLASTIC LIMIT
 D.....DRY DENSITY (kg/m³)
 U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
 N.....STANDARD PENETRATION TEST
 SO....SULPHATE CONTENT (PERCENT OF DRY SOIL)
 TR....TRACE
 *.....SULPHATE CONTENT WATER SAMPL (ppm)
 ▼.....RECORDED WATER LEVEL



LIMITATIONS:THE FIELD DRILL LOG IS A SUMMARY OF THE FIELD CONDITIONS ENCOUNTERED AT A SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND IN TIME, MAY CHANGE AT THE SPECIFIC TEST HOLE LOCATION

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
 SLOPE STABILITY STUDY
 237-11TH STREET EAST

LOCATION:
 SASKATOON, SK


DATE DRILLED: AUG 5, 1997
DRAWING NUMBER: S97-2778-2

TEST HOLE 97-2


DEPTH (m)

PIEZO = 99.85 m

N U D Pw Lw w ELEV: 99.14 m



LEGEND:



pp....POCKET PENETROMETER (kg/cm²)
 w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
 Lw....LIQUID LIMIT
 Pw....PLASTIC LIMIT
 D.....DRY DENSITY (kg/m³)
 U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
 N.....STANDARD PENETRATION TEST
 SO....SULPHATE CONTENT (PERCENT OF DRY SOIL)
 TR....TRACE
 *.....SULPHATE CONTENT WATER SAMPLE (ppm)
 ▼.....RECORDED WATER LEVEL



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE FIELD CONDITIONS ENCOUNTERED AT A SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND IN TIME, MAY CHANGE AT THE SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
 SLOPE STABILITY STUDY
 237-11TH STREET EAST

LOCATION:
 SASKATOON, SK

DATE DRILLED: AUG 5, 1997
DRAWING NUMBER: S97-2778-3

PIEZO. ELEV. = 100.09 m


PAGE 1 OF 2

TEST HOLE 97-3

DEPTH (m)

N U D Pw Lw w ELEV: 99.33 m

LEGEND:



- pp....POCKET PENETROMETER (kg/cm²)
- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw....LIQUID LIMIT
- Pw....PLASTIC LIMIT
- D.....DRY DENSITY (kg/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- N.....STANDARD PENETRATION TEST
- SO....SULPHATE CONTENT (PERCENT OF DRY SOIL)
- TR....TRACE
- *.....SULPHATE CONTENT WATER SAMPLE (ppm)
- ▼.....RECORDED WATER LEVEL
- SHELBY TUBE
- ⊠ SPLIT SPOON
- CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE FIELD CONDITIONS ENCOUNTERED AT A SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND IN TIME, MAY CHANGE AT THE SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.




FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
SLOPE STABILITY STUDY
237-11TH STREET EAST

LOCATION:
SASKATOON, SK

DATE DRILLED: AUG 5, 1997
DRAWING NUMBER: S97-2778-4



TEST HOLE 97-3

DEPTH (m)

DEPTH (m)	N	U	D	Pw	Lw	w
12		pp				
12.26			1454			30.3
12.88.8						
13						
13.2						
14						
15						
15.3						
16						
15.8						
17						
18						
19						
20						
21						
22						
23						

CLAY, some silt, firm, highly plastic, moist, grey, oxides.

GLACIAL TILL- Clay, silty, some sand, trace gravel, firm, medium plastic, moist, grey, unoxidized.

SAND PACKED ANNULUS

50 mm diam. SCH 40, PVC RISER PIPE

50 mm diam. MACHINE SLOTTED SCH 40 PVC WELL SCREEN


-sand silty, some clay below 14.9 m.
 -seepage at 15.0 m.
 -cobbles below 15.0 m.
 -sloughed to 15.7 m immediately after drilling.

-cobbles/boulders at 17.0 m.

NOTE:

1. Auger refusal at 17.0 m.
2. Test Hole sloughed to 15.7 m immediately after drilling.

LEGEND:



pp....POCKET PENETROMETER (kg/cm²)

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw....LIQUID LIMIT

Pw....PLASTIC LIMIT

D.....DRY DENSITY (kg/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

N.....STANDARD PENETRATION TEST

SO....SULPHATE CONTENT (PERCENT OF DRY SOIL)

TR....TRACE

*.....SULPHATE CONTENT WATER SAMPLE (ppm)

▼.....RECORDED WATER LEVEL



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE FIELD CONDITIONS ENCOUNTERED AT A SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND IN TIME, MAY CHANGE AT THE SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
 SLOPE STABILITY STUDY
 237-11TH STREET EAST

LOCATION:
 SASKATOON, SK


DATE DRILLED: AUG 5, 1997
DRAWING NUMBER: S97-2778-4A

TEST HOLE 97-4


DEPTH (m)

PIEZO. ELEV. = 97.22 m

N U D Pw Lw w ELEV: 96.66 m



LEGEND:



pp....POCKET PENETROMETER (kg/cm²)

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw....LIQUID LIMIT

Pw....PLASTIC LIMIT

D.....DRY DENSITY (kg/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

N.....STANDARD PENETRATION TEST

SO....SULPHATE CONTENT (PERCENT OF DRY SOIL)

TR....TRACE

*.....SULPHATE CONTENT WATER SAMPLE (ppm)

▼.....RECORDED WATER LEVEL



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE FIELD CONDITIONS ENCOUNTERED AT A SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND IN TIME, MAY CHANGE AT THE SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
SLOPE STABILITY STUDY
237-11TH STREET EAST

LOCATION:
SASKATOON, SK


DATE DRILLED:
AUG 5, 1997

DRAWING NUMBER:
S97-2778-5

TEST HOLE 97-4

DEPTH (m)

N U D Pw Lw w



GLACIAL TILL-Clay, silty, some sand, trace gravel, stiff, low to medium plastic, moist, grey.
 -seepage at 12.0 m.
 -cobbles below 12.5 m.
 -soft below 12.8 m.

-hard medium plastic below 13.5 m.


51.8 m
97-03-04

50 mm diam.
SCH 40, PVC
RISER PIPE

SAND PACKED
ANNULUS

50 mm diam.
MACHINE SLOTTED
SCH 40 PVC WELL
SCREEN

LEGEND:



pp....POCKET PENETROMETER (kg/cm²)

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw....LIQUID LIMIT

Pw....PLASTIC LIMIT

D.....DRY DENSITY (kg/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

N.....STANDARD PENETRATION TEST

SO....SULPHATE CONTENT (PERCENT OF DRY SOIL)

TR....TRACE

*.....SULPHATE CONTENT WATER SAMPL (ppm)

▼.....RECORDED WATER LEVEL



LIMITATIONS:THE FIELD DRILL LOG IS A SUMMARY OF THE FIELD CONDITIONS ENCOUNTERED AT A SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND IN TIME, MAY CHANGE AT THE SPECIFIC TEST HOLE LOCATION

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
SLOPE STABILITY STUDY
237-11TH STREET EAST

LOCATION:
SASKATOON, SK

DATE DRILLED: AUG 5, 1997
DRAWING NUMBER: S97-2778-5A



HISTORICAL BOREHOLE LOGS
TH03-1, TH 03-2, TH 03-3, TH 03-101, TH 03-101A, TH 03-102, TH 03-103
(PMEL03A)


P. Machibroda Engineering Ltd. September 11, 2003. Geotechnical Investigation and Slope Stability Study
Proposed Garage, 306 Saskatchewan Crescent East, Saskatoon, Saskatchewan, PMEL File No. S03-4869

PIEZO. ELEV.= 481.9 m


TEST HOLE 03-1

DEPTH (m)

N U γ_w Pw Lw w ELEV: 482.0 m



LEGEND:



pp....POCKET PENETROMETER (kg/cm²)

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw....LIQUID LIMIT

Pw....PLASTIC LIMIT

γ_wWET UNIT WEIGHT (kN/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

N.....STANDARD PENETRATION TEST

SO₄ ...SULPHATE CONTENT (PERCENT OF DRY SOIL)

I.A.D....IMMEDIATELY AFTER DRILLING

∇...RECORDED WATER LEVEL TEST HOLE (I.A.D.)

∇.....RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:

306 SASK CRESCENT EAST

LOCATION:

SASKATOON, SK

DATE DRILLED:

JULY 3/03

DRAWING NUMBER:


SO3-4869-2

PIEZO. ELEV.= 487.8 m

TEST HOLE 03-2


DEPTH (m)

N U γ_w Pw Lw w ELEV: 487.4 m



NOTE:
1. Test Hole open to 4.4 m and dry I.A.D.

LEGEND:



pp....POCKET PENETROMETER (kg/cm²)
w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
Lw....LIQUID LIMIT
Pw....PLASTIC LIMIT
 γ_wWET UNIT WEIGHT (kN/m³)
U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
N.....STANDARD PENETRATION TEST
SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)
I.A.D....IMMEDIATELY AFTER DRILLING
▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)
▽.....RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS


PROJECT: 306 SASK CRESCENT EAST	
LOCATION: SASKATOON, SK	
DATE DRILLED: JULY 3/03	DRAWING NUMBER: S03-4869-3

PIEZO. ELEV.= 481.9 m


TEST HOLE 03-3

DEPTH (m)

N U γ_w Pw Lw w ELEV: 482.0 m



LEGEND:



- pp....POCKET PENETROMETER (kg/cm²)
- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw....LIQUID LIMIT
- Pw....PLASTIC LIMIT
- γ_wWET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- N.....STANDARD PENETRATION TEST
- SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)
- I.A.D....IMMEDIATELY AFTER DRILLING
- ▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)
- ▼.....RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.




FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT: 306 SASK CRESCENT EAST	
LOCATION: SASKATOON, SK	
DATE DRILLED: JULY 3/03	DRAWING NUMBER: S03-4869-4


TEST HOLE 03-101

DEPTH (m)

N U γ_w Pw Lw w ELEV: 498.4 m



LEGEND:



- pp....POCKET PENETROMETER (kg/cm²)
- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw....LIQUID LIMIT
- Pw....PLASTIC LIMIT
- γ_wWET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- N.....STANDARD PENETRATION TEST
- SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)
- I.A.D....IMMEDIATELY AFTER DRILLING
- ▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)
- ▼.....RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
PROPOSED GARAGE
306 SASKATCHEWAN CRESCENT


LOCATION:
SASKATOON, SK

DATE DRILLED: AUG 14/03
DRAWING NUMBER: S03-4869-5

TEST HOLE 03-101

DEPTH (m)

N U γ_w Pw Lw w ELEV: 498.4 m



GLACIAL TILL, silt and sand, some clay, trace gravel, stiff, low plastic, moist, grey.


-very stiff below 12.8 m.

-hard below 13.8 m.

-broke auger at 23.1 m.

NOTE:
1. Test Hole sloughed to 5.2 m I.A.D.

LEGEND:



pp....POCKET PENETROMETER (kg/cm²)

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw....LIQUID LIMIT

Pw....PLASTIC LIMIT

γ_wWET UNIT WEIGHT (kN/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

N.....STANDARD PENETRATION TEST

SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)

I.A.D....IMMEDIATELY AFTER DRILLING

▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)

▽.....RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
PROPOSED GARAGE
306 SASKATCHEWAN CRESCENT

LOCATION:
SASKATOON, SK

DATE DRILLED:
AUG 14/03


DRAWING NUMBER:
S03-4869-5A

PIEZO. ELEV.= 498.2 m

TEST HOLE 03-101A

DEPTH (m)

N U γ_w Pw Lw w ELEV: 498.4 m



ASPHALT CONCRETE (25 mm) FILL, gravel and sand, some silt, moist, brown.
CLAY, some silt, firm, highly plastic, moist, brown.
SAND, some silt, medium dense, poorly graded, fine grained, moist, brown.
CLAY, some silt, stiff, highly plastic, moist, brown.
 -silt lense 3.2 m.
 -silty, trace seepage, sloughing below 4.7 m.
SILT, sandy, soft, low plastic, wet, brown, seepage, sloughing.

NOTE:
 1. Test Hole sloughed to 5.2 m I.A.D.

LEGEND:

TOPSOIL	GRAVEL	SAND	SILT	CLAY	GLACIAL FILL	FILL

pp....POCKET PENETROMETER (kg/cm²)
 w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
 Lw....LIQUID LIMIT
 Pw....PLASTIC LIMIT
 γ_wWET UNIT WEIGHT (kN/m³)
 U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
 N.....STANDARD PENETRATION TEST
 SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)
 I.A.D....IMMEDIATELY AFTER DRILLING
 ▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)
 ▽.....RECORDED WATER LEVEL (PIEZO)

SHELBY TUBE	SPLIT SPOON	CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
 PROPOSED GARAGE
 306 SASKATCHEWAN CRESCENT

LOCATION:
 SASKATOON, SK


DATE DRILLED: AUG 14/03	DRAWING NUMBER: S03-4869-6
-----------------------------------	--------------------------------------

PIEZO. ELEV.= 479.4 m


TEST HOLE 03-102

DEPTH (m)

N U γ_w Pw Lw w ELEV: 479.6 m



LEGEND:



pp....POCKET PENETROMETER (kg/cm²)

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw....LIQUID LIMIT

Pw....PLASTIC LIMIT

γ_wWET UNIT WEIGHT (kN/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

N.....STANDARD PENETRATION TEST

SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)

I.A.D....IMMEDIATELY AFTER DRILLING

▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)

▼.....RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
PROPOSED GARAGE
306 SASKATCHEWAN CRESCENT

LOCATION:
SASKATOON, SK

DATE DRILLED:
AUG 15/03


DRAWING NUMBER:
S03-4869-7

PIEZO. ELEV.= 488.1 m


TEST HOLE 03-103

DEPTH (m)

N U γ_w Pw Lw w ELEV: 488.3 m



LEGEND:



pp....POCKET PENETROMETER (kg/cm²)

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw....LIQUID LIMIT

Pw....PLASTIC LIMIT

γ_wWET UNIT WEIGHT (kN/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

N.....STANDARD PENETRATION TEST

SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)

I.A.D....IMMEDIATELY AFTER DRILLING

▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)

▼.....RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
PROPOSED GARAGE
306 SASKATCHEWAN CRESCENT

LOCATION:
SASKATOON, SK

DATE DRILLED:
AUG 15/03


DRAWING NUMBER:
S03-4869-8

PIEZO. ELEV.= 488.1 m

TEST HOLE 03-103

DEPTH (m)


N U γ_w Pw Lw w ELEV: 488.3 m



GLACIAL TILL, silt and sand, some clay, trace gravel, hard, low plastic, moist, grey.

NOTE:
1. Test Hole open to 15.3 m I.A.D.

LEGEND:



pp....POCKET PENETROMETER (kg/cm²)

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw....LIQUID LIMIT

Pw....PLASTIC LIMIT

γ_wWET UNIT WEIGHT (kN/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

N.....STANDARD PENETRATION TEST

SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)

I.A.D....IMMEDIATELY AFTER DRILLING

▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)

▼.....RECORDED WATER LEVEL (PIEZO)



SHELBY TUBE



SPLIT SPOON



CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
PROPOSED GARAGE
306 SASKATCHEWAN CRESCENT

LOCATION:
SASKATOON, SK

DATE DRILLED:
AUG 15/03

DRAWING NUMBER:
S03-4869-8A



APPENDIX E
Record of Borehole Logs

HISTORICAL BOREHOLE LOGS
TH03-1, TH 03-2, TH 03-3, TH 03-4, TH 03-5 (PMEL03B)


P. Machibroda Engineering Ltd. October 31, 2003. Geotechnical Investigation and Slope Stability Study
Proposed Residence, 313-11th Street East, Saskatoon, Saskatchewan, PMEL File No. S03-4925

PIEZO. ELEV.= 499.6 m


TEST HOLE 03-1

DEPTH (m)

N U γ_w Pw Lw w ELEV: 498.7 m



LEGEND:



- pp....POCKET PENETROMETER (kg/cm²)
- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw....LIQUID LIMIT
- Pw....PLASTIC LIMIT
- γ_wWET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- N.....STANDARD PENETRATION TEST
- SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)
- I.A.D....IMMEDIATELY AFTER DRILLING
- ▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)
- ▼.....RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:

SLOPE STABILITY STUDY

LOCATION:

313 - 11TH STREET, SASKATOON, SK

DATE DRILLED:

OCTOBER 7/03

DRAWING NUMBER:

S03-4925-2


NOTE:

1. Test Hole open to 12.0 m and dry I.A.D.


GLACIAL TILL, silt, sandy, some clay, trace gravel, stiff, medium plastic, moist, grey.

TEST HOLE 03-2

DEPTH (m)



LEGEND:



pp....POCKET PENETROMETER (kg/cm²)

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw....LIQUID LIMIT

Pw....PLASTIC LIMIT

γ_wWET UNIT WEIGHT (kN/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

N.....STANDARD PENETRATION TEST

SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)

I.A.D....IMMEDIATELY AFTER DRILLING

▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)

▼.....RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:

SLOPE STABILITY STUDY

LOCATION:

313 - 11TH STREET, SASKATOON, SK

DATE DRILLED:

OCTOBER 7/03

DRAWING NUMBER:

S03-4925-3

TEST HOLE 03-2

DEPTH (m)

N U γ_w Pw Lw w ELEV: 497.8 m

12									
13									
14									
15									
16									
17									
18									
19									
20									
21									
22									
23									

PP
50 mm diam.
MACHINE SLOTTED
SCH 40 PVC WELL
SCREEN

SAND PACKED
ANNULUS


18 22 13.1

CLAY, some silt, stiff, highly plastic, moist, grey, gypsum crystals, oxide stained.

GLACIAL TILL, silt, sandy, some clay, trace gravel, stiff, low plastic, moist, grey.

NOTE:
1. Test Hole open to 13.5 m and dry I.A.D.

LEGEND:



pp....POCKET PENETROMETER (kg/cm²)

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw....LIQUID LIMIT

Pw....PLASTIC LIMIT

γ_wWET UNIT WEIGHT (kN/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

N.....STANDARD PENETRATION TEST

SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)

I.A.D....IMMEDIATELY AFTER DRILLING

∇...RECORDED WATER LEVEL TEST HOLE (I.A.D.)

∇.....RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
SLOPE STABILITY STUDY


LOCATION:
313 - 11TH STREET, SASKATOON, SK

DATE DRILLED: OCTOBER 7/03
DRAWING NUMBER: S03-4925-3A


TEST HOLE 03-3

DEPTH (m)

N U γ_w Pw Lw w ELEV: 497.6 m



LEGEND:



pp....POCKET PENETROMETER (kg/cm²)

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw....LIQUID LIMIT

Pw....PLASTIC LIMIT

γ_wWET UNIT WEIGHT (kN/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

N.....STANDARD PENETRATION TEST

SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)

I.A.D....IMMEDIATELY AFTER DRILLING

∇...RECORDED WATER LEVEL TEST HOLE (I.A.D.)

∇.....RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:

SLOPE STABILITY STUDY

LOCATION:

313 - 11TH STREET, SASKATOON, SK

DATE DRILLED:

OCTOBER 7/03

DRAWING NUMBER:

S03-4925-4


CONTINUED ON NEXT PAGE

485.8 m
2003/10/23

TEST HOLE 03-3

DEPTH
(m)

N U γ_w Pw Lw w ELEV: 497.6 m




CLAY, some silt, stiff, highly plastic, moist, olive brown.
GLACIAL TILL, silt, sandy, some clay, trace gravel, stiff, medium plastic, moist, grey.

-very stiff to hard below 14.3 m.
 -trace seepage at 15.5 m.
 -hard below 16.0 m.

NOTE:
 1. Auger refusal at 19.0 m on boulder.
 2. Test Hole sloughed to 16.4 m I.A.D.

LEGEND:



pp....POCKET PENETROMETER (kg/cm²)
 w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
 Lw....LIQUID LIMIT
 Pw....PLASTIC LIMIT
 γ_wWET UNIT WEIGHT (kN/m³)
 U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
 N.....STANDARD PENETRATION TEST
 SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)
 I.A.D....IMMEDIATELY AFTER DRILLING
 ▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)
 ▼.....RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
 SLOPE STABILITY STUDY

LOCATION:
 313 - 11TH STREET, SASKATOON, SK

DATE DRILLED: OCTOBER 7/03
DRAWING NUMBER: S03-4925-4A

TEST HOLE 03-4

DEPTH (m)

N U γ_w Pw Lw w ELEV: 493.4 m

DEPTH (m)	N	U	γ_w	Pw	Lw	w	Notes
0		pp					
17.3							FILL, sand, gravelly, some silt, trace clay, dense, well graded, fine to coarse grained, damp, brown.
26.6							CLAY, silty, stiff, low to medium plastic, moist, brown. -highly plastic below 650 mm. -silt lense at 1.3 m.
16.3							SILT, some clay, trace sand, stiff, low plastic, moist, light olive brown.
16.9							
14.4							
19 30 27.3							-soft, wet, seepage, sloughing below 7.3 m.
31.7							CLAY, silty, firm, low to medium plastic, moist, olive brown. -highly plastic, stiff, grey below 9.1 m.
19 69 30.8							
10.2							GLACIAL TILL, silt, sandy, some clay, trace gravel, very stiff, medium plastic, moist, grey. -cobbles/boulders at 12.0 m.

LEGEND:

- TOPSOIL
- GRAVEL
- SAND
- SILT
- CLAY
- GLACIAL
- FILL

pp....POCKET PENETROMETER (kg/cm²)
w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
Lw....LIQUID LIMIT
Pw....PLASTIC LIMIT
 γ_wWET UNIT WEIGHT (kN/m³)
U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
N.....STANDARD PENETRATION TEST
SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)
I.A.D....IMMEDIATELY AFTER DRILLING
▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)
▼.....RECORDED WATER LEVEL (PIEZO)

■ SHELBY TUBE
⊗ SPLIT SPOON
◻ CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.


FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
SLOPE STABILITY STUDY

LOCATION:
313 - 11TH STREET, SASKATOON, SK

DATE DRILLED: OCTOBER 7/03
DRAWING NUMBER: S03-4925-5

NOTE:
1. Test Hole sloughed to 11.8 m and dry I.A.D.



LEGEND:

TOPSOIL	GRAVEL	SAND	SILT	CLAY	GLACIAL TILL	FILL

- pp....POCKET PENETROMETER (kg/cm²)
 - w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
 - Lw....LIQUID LIMIT
 - Pw....PLASTIC LIMIT
 - γ_wWET UNIT WEIGHT (kN/m³)
 - U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
 - N.....STANDARD PENETRATION TEST
 - SO₄...SULPHATE CONTENT (PERCENT OF DRY SOIL)
 - I.A.D....IMMEDIATELY AFTER DRILLING
 - ▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)
 - ▼.....RECORDED WATER LEVEL (PIEZO)
- | | | |
|-------------|-------------|----------|
| | | |
| SHELBY TUBE | SPLIT SPOON | CUTTINGS |

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.



FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
 SLOPE STABILITY STUDY

LOCATION:
 313 - 11TH STREET, SASKATOON, SK

DATE DRILLED: OCTOBER 7/03	DRAWING NUMBER: S03-4925-6
--------------------------------------	--------------------------------------




APPENDIX E
Record of Borehole Logs

HISTORICAL BOREHOLE LOGS
TH 1, TH 2, TH 3, TH 4, TH 5, TH 6 (AMEC05)

AMEC Earth & Environmental. July 27, 2005. Revised Slope Stability Assessment Proposed Condominium Development, 316 Saskatchewan Crescent, Saskatoon, Saskatchewan

Project: PROPOSED CONDOMINIUM DEVELOPMENT
306 SASKATCHEWAN CRESCENT
SASKATOON, SASKATCHEWAN

Elevation(m): 479.50
Date Drilled: 12/10/93
Drill Method: CME 75 cont. hollow stem auger



Sample Type:

☐ DISTURBED
■ SHELBY


⊗ SPT SAMPLE
▨ CONT.SAMPLER

▩ CORE
▤ NO RECOVERY

FIGURE A4

Project: PROPOSED CONDOMINIUM DEVELOPMENT
306 SASKATCHEWAN CRESCENT
SASKATOON, SASKATCHEWAN

Elevation(m): 480.53
Date Drilled: 12/10/93
Drill Method: CME 75 cont. hollow stem auger



Sample Type:

☐ DISTURBED
■ SHELBY

⊗ SPT SAMPLE
▨ CONT. SAMPLER


▬ CORE
▤ NO RECOVERY

FIGURE A5

Sheet 1 of 1

Project: PROPOSED CONDOMINIUM DEVELOPMENT
 306 SASKATCHEWAN CRESCENT
 SASKATOON, SASKATCHEWAN

Elevation(m): 494.36
 Date Drilled: 12/10/93
 Drill Method: CME 75 cont. hollow stem auger



Sample Type:

□ DISTURBED

■ SHELBY

⊠ SPT SAMPLE

▨ CONT. SAMPLER

▩ CORE

▤ NO RECOVERY

FIGURE A6


Sheet 1 of 1

Project: PROPOSED CONDOMINIUM DEVELOPMENT
 306 SASKATCHEWAN CRESCENT
 SASKATOON, SASKATCHEWAN

Elevation(m): 488.67

Date Drilled: 13/10/93

Drill Method: CME 75 cont. hollow stem auger



Sample Type:

▨ DISTURBED

⊠ SPT SAMPLE

▣ CORE

■ SHELBY

▨ CONT. SAMPLER


▨ NO RECOVERY

FIGURE A7

Sheet 1 of 1

Project: PROPOSED CONDOMINIUM DEVELOPMENT
306 SASKATCHEWAN CRESCENT
SASKATOON, SASKATCHEWAN

Elevation(m): 485.18
Date Drilled: 14/10/93
Drill Method: Hand auger



Sample Type:

- DISTURBED
- SPT SAMPLE
- CORE
- SHELBY
- CONT.SAMPLER
- NO RECOVERY

FIGURE A8

Project: PROPOSED CONDOMINIUM DEVELOPMENT
 306 SASKATCHEWAN CRESCENT
 SASKATOON, SASKATCHEWAN

Elevation(m): 486.23
 Date Drilled: 14/10/93
 Drill Method: Hand auger

DEPTH (m)	SAMPLE TYPE	U. S. C	DESCRIPTION	TEST DATA				OTHER TESTS	DEPTH (m)
				POCKET PEN. (kPa)		STD. PEN.	UNCON. COMP STR. (kPa)		
1.0			TOPSOIL (190 mm) silty, moist, black, fibrous	▲ 100 200 300 400					
			SILT sandy, damp, low plastic, light brown, clayey, organics	PL — MC — LI 20 40 60 80					
			CLAY TILL damp, low plastic, brown, oxides, few rootlets						
			End of test hole at 1.5 m on cobble or boulder						

Sample Type:

DISTURBED
 SHELBY

SPT SAMPLE
 CONT. SAMPLER

CORE
 NO RECOVERY


FIGURE A9

Sheet 1 of 1



HISTORICAL BOREHOLE LOGS
TH 06-1, TH 06-2 (PMEL06)

P. Machibroda Engineering Ltd. July 14, 2006. Geotechnical Investigation and Slope Stability Study Proposed Condominium 316 - Saskatchewan Crescent East, Saskatoon, SK



LEGEND:

TOPSOIL	GRAVEL	SAND	SILT	CLAY	GLACIAL TILL	FILL

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
 Lw...LIQUID LIMIT
 Pw...PLASTIC LIMIT
 γ_w ...WET UNIT WEIGHT (kN/m³)
 U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
 pp...POCKET PENETROMETER (kg/cm²)
 N.....STANDARD PENETRATION TEST (ROPE-CATHEAD & DONUT HAMMER) (50/125mm = BLOWS/SAMPLER PENETRATION)
 SO₄.....SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
 P200...% PASSING No. 200 SIEVE
 I.A.D.....IMMEDIATELY AFTER DRILLING
 ▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)
 ▼...RECORDED WATER LEVEL (PIEZO)

SHELBY TUBE	SPLIT SPOON	CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.


P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT: PROPOSED CONDOMINIUM DEVELOPMENT

LOCATION: SASKATOON, SK

DATE DRILLED: MAR 17/06	DRAWING NUMBER: S06-5722-3
--------------------------------	-----------------------------------



LEGEND:

TOPSOIL	GRAVEL	SAND	SILT	CLAY	GLACIAL TILL	FILL

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
 Lw...LIQUID LIMIT
 Pw...PLASTIC LIMIT
 γ_w ...WET UNIT WEIGHT (kN/m³)
 U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
 pp...POCKET PENETROMETER (kg/cm²)
 N.....STANDARD PENETRATION TEST (ROPE-CATHEAD & DONUT HAMMER) (50/125mm = BLOWS/SAMPLER PENETRATION)
 SO₄.....SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
 P200...% PASSING No. 200 SIEVE
 I.A.D.....IMMEDIATELY AFTER DRILLING
 ▽...RECORDED WATER LEVEL TEST HOLE (I.A.D.)
 ▼...RECORDED WATER LEVEL (PIEZO)

SHELBY TUBE	SPLIT SPOON	CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT: PROPOSED CONDOMINIUM DEVELOPMENT

LOCATION: SASKATOON, SK


DATE DRILLED: MAR 17/06	DRAWING NUMBER: S06-5722-4
--------------------------------	-----------------------------------



HISTORICAL BOREHOLE LOGS
TH07-01, TH 07-02, TH 07-03, TH 07-04, TH 07-5 (PMEL07)

P. Machibroda Engineering Ltd. June 12, 2007. Geotechnical Investigation and Slope Stability Study Proposed Residences, 221 & 225 - 11th Street East, Saskatoon, SK

LEGEND:



w.....WATER CONTENT
(PERCENT OF DRY SOIL WEIGHT)

Lw...LIQUID LIMIT

Pw...PLASTIC LIMIT

γ_w ...WET UNIT WEIGHT (kN/m³)

U.....UNCONFINED COMPRESSIVE
STRENGTH (kPa)

pp...POCKET PENETROMETER (kg/cm²)

N.....STANDARD PENETRATION TEST
(ROPE-CATHEAD & DONUT HAMMER)
(50/125 = BLOWS/SAMPLER
PENETRATION [mm])

SO₄.....SULPHATE CONTENT
(PERCENT OF DRY SOIL WEIGHT)

P200...% PASSING No. 200 SIEVE

I.A.D.....IMMEDIATELY AFTER DRILLING

▽...RECORDED WATER LEVEL
(TEST HOLE I.A.D.)

▼...RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



**P. MACHIBRODA
ENGINEERING
LTD.**

**FIELD DRILL LOG
AND
SOIL TEST RESULTS**

PROJECT:

PROPOSED RESIDENCE

LOCATION:

221 & 225 - 11th STREET EAST
SASKATOON, SK

NORTHING:


EASTING:

DATE DRILLED:

MAY 1/07

DRAWING NUMBER:


S07-6078-2



11th STREET

CONTINUED ON NEXT PAGE

LEGEND:




- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (ROPE-CATHEAD & DONUT HAMMER) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ∇...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ▼...RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

TEST HOLE 07-1

DEPTH (m)



NOTE:
1. Test Hole sloughed to 11.8 m I.A.D.

11th STREET



**P. MACHIBRODA
ENGINEERING
LTD.**

**FIELD DRILL LOG
AND
SOIL TEST RESULTS**

PROJECT:

PROPOSED RESIDENCE

LOCATION:

221 & 225 - 11th STREET EAST
SASKATOON, SK

NORTHING:

EASTING:

DATE DRILLED:

MAY 1/07

DRAWING NUMBER:


S07-6078-2A

TEST HOLE 07-2

DEPTH (m)

ROADBOX


ELEV: 489.4 m



TOPSOIL, organic, brown, rootlets.
SILT, some clay, firm, low to medium plastic, moist, brown.
SAND, silty, compact, poorly graded, fine grained, moist, brown.
 -trace seepage, sloughing below 2.6 m.
CLAY, some silt, stiff, medium plastic, moist, brown, oxide stained.
GLACIAL TILL, clay, silty, some sand, trace gravel, stiff, medium plastic, moist, brown, oxide stained, gypsum crystals.
GLACIAL TILL, sand, silty, some clay, trace gravel, dense, poorly graded, fine to medium grained, moist, brown, oxide stained.

NOTE:
1. Test Hole sloughed to 7.1 m and dry I.A.D.

11th STREET



w....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
 Lw...LIQUID LIMIT
 Pw...PLASTIC LIMIT
 γ_w ...WET UNIT WEIGHT (kN/m³)
 U....UNCONFINED COMPRESSIVE STRENGTH (kPa)
 pp...POCKET PENETROMETER (kg/cm²)
 N....STANDARD PENETRATION TEST (ROPE-CATHEAD & DONUT HAMMER) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
 SO₄.....SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
 P200...% PASSING No. 200 SIEVE
 I.A.D.....IMMEDIATELY AFTER DRILLING
 ▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
 ▼...RECORDED WATER LEVEL (PIEZO)
 ■ SHELBY TUBE ⊠ SPLIT SPOON ◻ CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
PROPOSED RESIDENCE

LOCATION:
221 & 225 - 11th STREET EAST
SASKATOON, SK

NORTHING: **EASTING:**


DATE DRILLED: **DRAWING NUMBER:**
MAY 3/07 S07-6078-3

PIEZO. ELEV.= 481.0 m

TEST HOLE 07-3

DEPTH (m)


N U γ_w Pw Lw w ELEV: 481.1 m



NOTE:
1. Test Hole sloughed to 7.2 m and dry I.A.D.

CHERRY LANE

LEGEND:



- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (ROPE-CATHEAD & DONUT HAMMER) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ▼...RECORDED WATER LEVEL (PIEZO)
- SHELBY TUBE
- ⊗ SPLIT SPOON
- ▤ CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:

PROPOSED RESIDENCE

LOCATION:

221 & 225 - 11th STREET EAST
SASKATOON, SK

NORTHING:

EASTING:

DATE DRILLED:
MAY 10/07

DRAWING NUMBER:
S07-6078-4


PIEZO. ELEV.= 478.4 m

TEST HOLE 07-4

DEPTH (m)

ROADBOX

N U γ_w Pw Lw w ELEV: 478.5 m



ASPHALT CONCRETE, (100 mm).
FILL, gravel, sandy, some silt,
 dense, well graded, fine to coarse
 grained, moist, brown.


SAND AND SILT, compact to dense,
 poorly graded, fine grained, moist,
 brown.

—some silt below 2.7 m.
 —wet, seepage, sloughing below
 3.0 m.

SAND AND GRAVEL, some silt,
 dense, well graded, fine to coarse
 grained, wet, brown, seepage,
 sloughing.

GLACIAL TILL, clay, some silt,
 some sand, trace gravel, hard,
 medium plastic, moist, grey.

LEGEND:



- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (ROPE-CATHEAD & DONUT HAMMER) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄.....SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ▼...RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
 PROPOSED RESIDENCE

LOCATION:
 221 & 225 - 11th STREET EAST
 SASKATOON, SK

NORTHING: **EASTING:**

DATE DRILLED: **DRAWING NUMBER:**
 MAY 3/07 S07-6078-5

NOTE:
 1. Test Hole sloughed to 5.0 m I.A.D.

SASKATCHEWAN CRESCENT


TEST HOLE 07-5

TOPSOIL	FILL	GRAVEL	SAND	SILT	CLAY	GLACIAL TILL

DEPTH (m)

ROADBOX

N U γ_w Pw Lw w ELEV: 493.3 m



- w....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (ROPE-CATHEAD & DONUT HAMMER) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ▼...RECORDED WATER LEVEL (PIEZO)
- SHELBY TUBE
- SPLIT SPOON
- CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
PROPOSED RESIDENCE

LOCATION:
221 & 225 - 11th STREET EAST
SASKATOON, SK

NORTHING: **EASTING:**

DATE DRILLED: **DRAWING NUMBER:**


MAY 2/07 S07-6078-6

11th STREET

CONTINUED ON NEXT PAGE

TEST HOLE 07-5

LEGEND:



- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (ROPE-CATHEAD & DONUT HAMMER) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄.....SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ▼...RECORDED WATER LEVEL (PIEZO)
- SHELBY TUBE
- ⊠ SPLIT SPOON
- CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



**P. MACHIBRODA
ENGINEERING
LTD.**

**FIELD DRILL LOG
AND
SOIL TEST RESULTS**


PROJECT:
PROPOSED RESIDENCE

LOCATION:
221 & 225 - 11th STREET EAST
SASKATOON, SK

NORTHING: **EASTING:**

DATE DRILLED: **DRAWING NUMBER:**
MAY 2/07 S07-6078-6A

DEPTH (m)



NOTE:
1. Test Hole sloughed to 11.8 m I.A.D.

11th STREET



APPENDIX E
Record of Borehole Logs

HISTORICAL BOREHOLE LOGS
TH08-01, TH 08-02, TH 08-03, TH 08-04 (PMEL08)

P. Machibroda Engineering Ltd. July 8, 2008. Proposed Commercial/Residential Development 328 Saskatchewan Crescent East, Saskatoon, SK

PIEZO. ELEV.= 480.4 m


TEST HOLE 08-1

DEPTH (m)

ROAD BOX

N U γ_w Pw Lw w ELEV: 480.4 m

LEGEND:



w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw...LIQUID LIMIT

Pw...PLASTIC LIMIT

γ_w ...WET UNIT WEIGHT (kN/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

pp...POCKET PENETROMETER (kg/cm²)

N.....STANDARD PENETRATION TEST (SAFETY HAMMER w/AUTOMATIC TRIP) (50/125 = BLOWS/SAMPLER PENETRATION [mm])

SO₄SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)

P200...% PASSING No. 200 SIEVE

I.A.D.....IMMEDIATELY AFTER DRILLING

▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)

▼...RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:

PROPOSED COMMERCIAL / RESIDENTIAL DEVELOPMENT

LOCATION:

328 SASKATCHEWAN CRESCENT SASKATOON, SK

NORTHING:


EASTING:

DATE DRILLED:

MAY 26/08

DRAWING NUMBER:

S08-6500-2




NOTE:
1. Test Hole, sloughed to 7.5 m I.A.D.

PIEZO. ELEV.= 485.9 m

TEST HOLE 08-2

LEGEND:




DEPTH (m)

ROAD BOX

N U γ_w Pw Lw w

ELEV: 486.1 m



- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (SAFETY HAMMER w/AUTOMATIC TRIP) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄.....SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ▼...RECORDED WATER LEVEL (PIEZO)
- SHELBY TUBE
- ⊠ SPLIT SPOON
- CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
PROPOSED COMMERCIAL / RESIDENTIAL DEVELOPMENT


LOCATION:
328 SASKATCHEWAN CRESCENT
SASKATOON, SK

NORTHING: **EASTING:**

DATE DRILLED: **DRAWING NUMBER:**
MAY 23/08 S08-6500-3


TEST HOLE 08-3

LEGEND:



DEPTH (m)

N U γ_w Pw Lw w ELEV: 497.4 m



- w....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (SAFETY HAMMER w/AUTOMATIC TRIP) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄.....SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ∇...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ▼...RECORDED WATER LEVEL (PIEZO)
- SHELBY TUBE
- ⊠ SPLIT SPOON
- ◻ CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
PROPOSED COMMERCIAL / RESIDENTIAL DEVELOPMENT


LOCATION:
325 SASKATCHEWAN CRESCENT
SASKATOON, SK

NORTHING: **EASTING:**

DATE DRILLED: **DRAWING NUMBER:**
MAY 22/08 S08-6500-4

TEST HOLE 08-3

LEGEND:



- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (SAFETY HAMMER w/AUTOMATIC TRIP) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ▼...RECORDED WATER LEVEL (PIEZO)
- SHELBY TUBE
- SPLIT SPOON
- CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS


PROJECT:
PROPOSED COMMERCIAL / RESIDENTIAL DEVELOPMENT

LOCATION:
328 SASKATCHEWAN CRESCENT
SASKATOON, SK

NORTHING: **EASTING:**


DATE DRILLED: **DRAWING NUMBER:**
MAY 22/08 S08-6500-4A

DEPTH (m)



TEST HOLE 08-4

LEGEND:



DEPTH (m)

N U γ_w Pw Lw w ELEV: 494.4 m

w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw...LIQUID LIMIT

Pw...PLASTIC LIMIT

γ_w ...WET UNIT WEIGHT (kN/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

pp...POCKET PENETROMETER (kg/cm²)

N.....STANDARD PENETRATION TEST (SAFETY HAMMER w/AUTOMATIC TRIP) (50/125 = BLOWS/SAMPLER PENETRATION [mm])

SO₄SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)

P200...% PASSING No. 200 SIEVE

I.A.D.....IMMEDIATELY AFTER DRILLING

▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)

▼...RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:

PROPOSED COMMERCIAL / RESIDENTIAL DEVELOPMENT

LOCATION:

328 SASKATCHEWAN CRESCENT SASKATOON, SK

NORTHING:


EASTING:

DATE DRILLED:

MAY 26/08


DRAWING NUMBER:

S08-6500-5



CONTINUED ON NEXT PAGE

LEGEND:



- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (SAFETY HAMMER w/AUTOMATIC TRIP) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ▼...RECORDED WATER LEVEL (PIEZO)
- SHELBY TUBE
- ⊠ SPLIT SPOON
- ◻ CUTTINGS

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



**P. MACHIBRODA
ENGINEERING
LTD.**

**FIELD DRILL LOG
AND
SOIL TEST RESULTS**


PROJECT:
PROPOSED COMMERCIAL /
RESIDENTIAL DEVELOPMENT

LOCATION:
328 SASKATCHEWAN CRESCENT
SASKATOON, SK

NORTHING: **EASTING:**

DATE DRILLED: **DRAWING NUMBER:**
MAY 26/08 S08-6500-5A

TEST HOLE 08-4



NOTE:
1. Test Hole sloughed to 11.1 m I.A.D.



HISTORICAL BOREHOLE LOGS
11-0057-BH1, 11-0057-BH2, 11-0057-BH3 (GAL12)

Golder Associates Ltd. May 2013. Assessment of Slope Instability at 200 Block, 11th Street East.

PROJECT: 11-1362-0057.5000

RECORD OF BOREHOLE: 11-0057-BH1

SHEET 1 OF 1

LOCATION: Cherry Lane N 5775616.80 E 386010.50

BORING DATE: 23/6/12

DATUM: City Datum

DRILL RIG: Acker MP-5

DRILLING CONTRACTOR: Paddock Drilling Ltd.

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH Cu, kPa		WATER CONTENT PERCENT		WATER CONTENT PERCENT			
								20	40	60	80	10 ⁻⁶	10 ⁻⁵		
0		GROUND SURFACE		488.30											
		ASPHALT PAVEMENT		488.10											Flushmount
		SAND and GRAVEL, well graded, angular, some silt, medium brown, dry (GRANULAR BASE)		487.84											
		(ML) CLAYEY SILT, trace fine sand, medium brown, (FILL), w>PL, soft		487.08	1-1	AS								PP= 0.25	
		(CI) SILTY CLAY, medium brown, w>PL, soft to firm		487.08	1-2	AS								PP= 0.5	
		(CH) CLAY, medium brown, w>PL, firm		485.86	1-3	AS								PP= 1.0	
		(CH) CLAY, medium brown, w>PL, firm		2.44	1-4	AS									
		(CI) SILTY CLAY, some sand and gravel, medium brown, (TILL), w~PL, stiff		484.64	1-5	AS								PP= 0.75 MH	Slope Indicator in Grout
		(CI) SILTY CLAY, some sand and gravel, medium brown, (TILL), w~PL, stiff		3.66	1-6	AS								PP= 1.25	
		(CI) SILTY CLAY, some sand and gravel, medium brown, (TILL), w~PL, stiff		484.64	1-7	AS								PP= 1.25	
		(ML) sandy SILT, some fine gravel, medium grey, (TILL), w<PL, very stiff		481.90	1-8	AS								PP= 3.0	
		(SM) SILTY SAND, fine grained, medium brown, wet		481.29											
		END OF BOREHOLE = 7.62m		480.68											Slough
				7.62											

BOREHOLE 11-1362-0057-5000-BOREHOLES.GPJ GAL-SASK.GDT 1/10/12

DEPTH SCALE

1 : 50



LOGGED: CSF

CHECKED: HV

PROJECT: 11-1362-0057.5000

RECORD OF BOREHOLE: 11-0057-BH1P

SHEET 1 OF 1

LOCATION: Cherry Lane N 5775616.80 E 386010.50

BORING DATE: 23/6/12

DATUM: City Datum

DRILL RIG: Acker MP-5

DRILLING CONTRACTOR: Paddock Drilling Ltd.

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS		
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH				WATER CONTENT PERCENT					
								20 40 60 80		nat V. + Q - rem V. ⊕ U - ⊙		10 ⁻⁶ 10 ⁻⁵ 10 ⁻⁴ 10 ⁻³				Wp W WI	
0	Acker MP-5 Power Auger Boring Solid Stem Augers	GROUND SURFACE		488.30													
		ASPHALT PAVEMENT		488.10													
		SAND and GRAVEL, well graded, angular, some silt, medium brown, dry (GRANULAR BASE)		487.84													
		(ML) CLAYEY SILT, trace fine sand, medium brown, (FILL), w>PL, soft		487.08													
1		(CI) SILTY CLAY, medium brown, w>PL, soft to firm		485.86	1.22	1P-1	TO								Grout		
2		(CH) CLAY, medium brown, w>PL, firm		484.64	2.44	1P-2	TO										
3				484.64	3.66	1P-3	TO										
4	END OF BOREHOLE = 3.66m																
5	NOTE: Borehole was drilled 0.3m west of borehole 11-0057-BH1. Soil description derived from the adjacent borehole.																
6																	
7																	
8																	
9																	
10																	

BOREHOLE 11-1362-0057-5000-BOREHOLES.GPJ GAL-SASK.GDT 1/10/12

DEPTH SCALE
1 : 50



LOGGED: CSF
CHECKED: HV

PROJECT: 11-1362-0057.5000

RECORD OF BOREHOLE: 11-0057-BH2

SHEET 1 OF 1

LOCATION: Cherry Lane N 5775620.20 E 385980.90

BORING DATE: 23/6/12

DATUM: City Datum

DRILL RIG: Acker MP-5

DRILLING CONTRACTOR: Paddock Drilling Ltd.

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS			
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH Cu, kPa		nat V. rem V.		WATER CONTENT PERCENT				Wp	W	Wi
								20	40	60	80	+	Q - U -					
0	Acker MP-5 Power Auger Boring Solid Stem Augers	GROUND SURFACE		485.90														
		ASPHALT PAVEMENT		485.67													Flushmount	
		ORGANIC SILT, black, wet, soft		485.23														
1		(CI) SILTY CLAY, trace fine sand, medium brown, w>PL, firm		485.14	0.76	2-1	AS										PP= 0.5	
		- stiff				2-2	AS										PP= 0.75	
2						2-3	AS										PP= 1.5	
		(CH) CLAY, medium brown, w>PL, firm		483.46	2.44	2-4	AS										PP= 0.5	
3		(CI) SILTY CLAY, some sand and gravel, medium brown, (TILL), w~PL, very stiff		483.00	2.90	2-5	AS										Slope Indicator in Grout	
		(ML) sandy SILT, some fine gravel, medium brown, (TILL), w<PL, very stiff		482.24	3.66	2-6	AS										PP= 3.0	
4						2-7	AS										PP= 3.0	
5		END OF BOREHOLE = 5.21m		480.69	5.21													

BOREHOLE 11-1362-0057-5000-BOREHOLES.GPJ GAL-SASK.GDT 1/10/12

DEPTH SCALE

1 : 50



LOGGED: CSF

CHECKED: HV

PROJECT: 11-1362-0057.5000

RECORD OF BOREHOLE: 11-0057-BH2P

SHEET 1 OF 1

LOCATION: Cherry Lane N 5775620.20 E 385980.90

BORING DATE: 23/6/12

DATUM: City Datum

DRILL RIG: Acker MP-5

DRILLING CONTRACTOR: Paddock Drilling Ltd.

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH Cu, kPa		WATER CONTENT PERCENT		WATER CONTENT PERCENT			
								20	40	60	80	nat V. +	rem V. ⊕		
0	Acker MP-5 Power Auger Boring Solid Stem Augers	GROUND SURFACE		485.90											
		ASPHALT PAVEMENT		0.00											
		ORGANIC SILT, black, wet, soft		0.23											
1		(CI) SILTY CLAY, trace fine sand, medium brown, w>PL, firm		0.76											
2		- stiff				2P-1	TO								
		(CH) CLAY, medium brown, w>PL, firm		2.44		2P-2	TO								
3	(CI) SILTY CLAY, some sand and gravel, medium brown, (TILL), w~PL, very stiff		2.90		2P-3	TO									
	END OF BOREHOLE = 3.45m		3.45												
4	NOTE: Borehole was drilled 0.3m west of borehole 11-0057-BH2. Soil description derived from the adjacent borehole.														
5															
6															
7															
8															
9															
10															

BOREHOLE 11-1362-0057-5000-BOREHOLES.GPJ GAL-SASK.GDT 1/10/12

DEPTH SCALE

1 : 50



LOGGED: CSF

CHECKED: HV

PROJECT: 11-1362-0057.5000

RECORD OF BOREHOLE: 11-0057-BH3

SHEET 1 OF 1

LOCATION: Cherry Lane N 5775622.30 E 385959.40

BORING DATE: 23/6/12

DATUM: City Datum

DRILL RIG: Acker MP-5

DRILLING CONTRACTOR: Paddock Drilling Ltd.

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES			DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH				WATER CONTENT PERCENT					
								20 40 60 80		nat V. + Q - rem V. ⊕ U - ⊙		10 ⁻⁶ 10 ⁻⁵ 10 ⁻⁴ 10 ⁻³		Wp WI			
0	Acker MP-5 Power Auger Boring Solid Stem Augers	GROUND SURFACE		484.10													
		ASPHALT PAVEMENT		0.08													
		SAND and GRAVEL, well graded, angular, some silt, medium brown, moist (GRANULAR BASE)		0.13													Flushmount
1		(CL) sandy SILTY CLAY, some gravel, medium brown, (Possibly FILL), w>PL			3-1	AS											Grout
					3-2	AS											VW11984
					3-3	AS											Slope Indicator in Grout
2		(SC) CLAYEY SAND, fine grained, some silt, medium brown, moist		482.58	1.52												
				3-4	AS												
				3-5	AS												
3		(SM) SILTY SAND, fine grained, some to trace gravel, light brown, very moist		481.66	2.44												
				480.29	3.81												
4		END OF BOREHOLE = 3.81m															

BOREHOLE 11-1362-0057-5000-BOREHOLES.GPJ GAL-SASK.GDT 1/10/12

DEPTH SCALE

1 : 50



LOGGED: CSF

CHECKED: HV




HISTORICAL BOREHOLE LOGS
TH 13-1, 13-2, 13-3, 13-4, 13-5, 13-6 AND CPT 13-1 (PMEL13)

P. Machibroda Engineering Ltd. July 18, 2013. Slope Instability 230/306 Saskatchewan Crescent Saskatoon, SK. Drawing No S13-8517-1 to 7,


PIEZO. ELEV.= 99.0 m

TEST HOLE 13-1

DEPTH (m)



LEGEND:



- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (SAFETY HAMMER w/AUTOMATIC TRIP) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ∇...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ∇...RECORDED WATER LEVEL (PIEZO)

LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
SLOPE INSTABILITY

LOCATION:
230/306 SASKATCHEWAN CRESCENT
SASKATOON, SK


NORTHING: **EASTING:**

DATE DRILLED: JUL 17/13 **DRAWING NUMBER:** S13-8517-2


PIEZO. ELEV.= 99.5 m

TEST HOLE 13-2

DEPTH (m)



LEGEND:



- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (SAFETY HAMMER w/AUTOMATIC TRIP) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ▼...RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

NOTE:
1. Test Hole sloughed to 5.8 m I.A.D.



P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:

SLOPE INSTABILITY

LOCATION:

230/306 SASKATCHEWAN CRESCENT SASKATOON, SK

NORTHING:

EASTING:

DATE DRILLED:

JUL 17/13


DRAWING NUMBER:

S13-8517-3

PIEZO. ELEV.= 99.9 m


TEST HOLE 13-3

DEPTH (m)



NOTE:
1. Test Hole sloughed to 5.9 m I.A.D.

LEGEND:



- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (SAFETY HAMMER w/AUTOMATIC TRIP) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ∇...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ∇...RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
SLOPE INSTABILITY

LOCATION:
230/306 SASKATCHEWAN CRESCENT
SASKATOON, SK


NORTHING: **EASTING:**

DATE DRILLED: JUL 17/13 **DRAWING NUMBER:** S13-8517-4

PIEZO. ELEV.= 100.3 m


TEST HOLE 13-4

DEPTH (m)



NOTE:
1. Test Hole sloughed to 6.5 m I.A.D.

LEGEND:



- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (SAFETY HAMMER w/AUTOMATIC TRIP) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ▼...RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:

SLOPE INSTABILITY

LOCATION:

230/306 SASKATCHEWAN CRESCENT SASKATOON, SK

NORTHING:

EASTING:

DATE DRILLED:

JUL 17/13


DRAWING NUMBER:

S13-8517-5

PIEZO. ELEV.= 103.6 m


TEST HOLE 13-5

DEPTH (m)



NOTE:
1. Test Hole open to 9.0 m and dry I.A.D.

LEGEND:



- w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)
- Lw...LIQUID LIMIT
- Pw...PLASTIC LIMIT
- γ_w ...WET UNIT WEIGHT (kN/m³)
- U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)
- pp...POCKET PENETROMETER (kg/cm²)
- N.....STANDARD PENETRATION TEST (SAFETY HAMMER w/AUTOMATIC TRIP) (50/125 = BLOWS/SAMPLER PENETRATION [mm])
- SO₄SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)
- P200...% PASSING No. 200 SIEVE
- I.A.D.....IMMEDIATELY AFTER DRILLING
- ▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)
- ▼...RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.

P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:
SLOPE INSTABILITY

LOCATION:
230/306 SASKATCHEWAN CRESCENT
SASKATOON, SK

NORTHING: **EASTING:**


DATE DRILLED: JUL 18/13 **DRAWING NUMBER:** S13-8517-6

PIEZO. ELEV.= 104.9 m

TEST HOLE 13-6


DEPTH (m)

N U γ_w Pw Lw w ELEV: 104.0 m



NOTE:
1. Test Hole open to 8.7 m I.A.D.

LEGEND:



w.....WATER CONTENT (PERCENT OF DRY SOIL WEIGHT)

Lw...LIQUID LIMIT

Pw...PLASTIC LIMIT

γ_w ...WET UNIT WEIGHT (kN/m³)

U.....UNCONFINED COMPRESSIVE STRENGTH (kPa)

pp...POCKET PENETROMETER (kg/cm²)

N.....STANDARD PENETRATION TEST (SAFETY HAMMER w/AUTOMATIC TRIP) (50/125 = BLOWS/SAMPLER PENETRATION [mm])

SO₄SULPHATE CONTENT (PERCENT OF DRY SOIL WEIGHT)

P200...% PASSING No. 200 SIEVE

I.A.D.....IMMEDIATELY AFTER DRILLING

▽...RECORDED WATER LEVEL (TEST HOLE I.A.D.)

▽...RECORDED WATER LEVEL (PIEZO)



LIMITATIONS: THE FIELD DRILL LOG IS A SUMMARY OF THE SUBSURFACE CONDITIONS ENCOUNTERED AT THE SPECIFIC TEST HOLE LOCATION AT THE TIME OF TEST DRILLING. SUBSURFACE CONDITIONS MAY VARY AT OTHER LOCATIONS OF THIS SITE AND, IN TIME, MAY CHANGE AT THIS SPECIFIC TEST HOLE LOCATION.



P. MACHIBRODA ENGINEERING LTD.

FIELD DRILL LOG AND SOIL TEST RESULTS

PROJECT:

SLOPE INSTABILITY

LOCATION:

230/306 SASKATCHEWAN CRESCENT SASKATOON, SK

NORTHING:

EASTING:

DATE DRILLED:

JUL 18/13

DRAWING NUMBER:


S13-8517-7



P. Machibroda Engineering Ltd.
 806-48th Street East
 Saskatoon, Saskatchewan S7K 4A2
 www.machibroda.com

CPT: 13-1
 Total depth: 5.81 m, Date: 18/07/2013
 Surface Elevation: 0.00 m
 Coords: X:0.00, Y:0.00
 Cone Type: 15 cm²
 Cone Operator: PMEL

Project: Slope Stability Assessment
Location: 230/306 Saskatchewan Crescent East, Saskatoon, Saskatchewan





APPENDIX E
Record of Borehole Logs

2013 BOREHOLE LOGS

**COS-13-001, COS-13-001B, COS-13-002, COS-13-003, COS-13-004,
COS 13-005, COS-13-006, COS-13-007 (GAL13)**

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES			DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH				WATER CONTENT PERCENT					
								20 40 60 80		nat V. + Q - rem V. ⊕ U - ○		10 ⁻⁶ 10 ⁻⁵ 10 ⁻⁴ 10 ⁻³		Wp ----- W ----- Wi			
0		GROUND SURFACE		489.34													
		ASPHALT		489.03													
		(ML) CLAYEY SILT, some fine grained sand, brown, some black mottling, w>PL, very soft		0.30	001-1	AS										PP>0	
1				488.12													
		(CL) SILTY CLAY, low plasticity, trace fine grained gravel, brown/black, trace iron staining, trace gypsum/weathered gypsum, some organics, w>PL, soft to firm		1.22	001-2	AS											
2																	
		-plasticity increases with depth			001-3	AS										PP=1	
3				486.29													
		(CI) SILTY CLAY, medium-high plasticity, trace fine grained gravel, brown, trace gypsum		3.05												PP=0.75	
4					001-4	AS											
					001-5	AS										PP>0	
5				484.46													
		(CH) CLAY, high plasticity, some silt, brown, trace sand, trace gypsum, w>PL, soft to very soft		4.88	001-6	AS										SG MH	
6					001-7	AS										FP=0.75-1	
7				482.79												PP=1.5	
		(CL) SILTY CLAY, some fine grained gravel, grey, (TILL), w~PL, stiff to very stiff		6.55	001-8	AS											
8				481.41													
		(SM) SILTY SAND, trace gravel, fine to medium grained, grey, wet		7.92	001-9	AS										MH	
		(CL) SILTY CLAY, some sand, some gravel, fine to coarse grained, grey, (TILL), w~PL		8.23													
		END OF BOREHOLE = 9.4m			001-10	AS											
9		Notes: 1. Upon completion of drilling, the borehole was backfilled with bentonite chips to the ground surface.		479.89													
10				9.45													

SK SOIL 11-1362-0057-5100 BOREHOLES.GPJ GAL-SASK.GDT 05/05/14

07/26/13



PROJECT: Cherry Lane Slope Remediation

RECORD OF BOREHOLE: COS-13-001B

SHEET 1 OF 1

LOCATION: N 5775616.7 E 386038.9

BORING DATE: 07/26/13

DATUM: NAD83

DRILL RIG: CME

DRILLING CONTRACTOR: Boss Drilling

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES			DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH				WATER CONTENT PERCENT					
								Cu, kPa		nat V. rem V.		+		Q - U -			Wp
0	150mm Dia. Solid Stem Auger Continuous Flight	GROUND SURFACE		489.34													
		No Classification		0.00													
1																	
2																	
3																	
4																	
5																	
5.18			(CH) CLAY, high plasticity, some silt, brown, trace gypsum, w>PL, firm to soft		484.16												
5.18					5.18	001B-1	TO										
6																	
6.55				482.79	001B-2	TO											
6.55		(CL) SILTY CLAY and SAND, fine to coarse, some fine grained gravel, grey, (TILL), w~PL, stiff		6.55													
7				482.18	001B-3	TO											
7.16				482.18													
7.16		No Classification		7.16													
9.14				480.20													
9.14		END OF BOREHOLE = 9.1m		9.14													
10		Notes: 1. Additional Lab testing * indicates Dry Density in kg/m ³															

SK SOIL 11-1362-0057-5100 BOREHOLES.GPJ GAL-SASK.GDT 05/05/14

DEPTH SCALE

1 : 50



LOGGED: LM

CHECKED: LDN

PROJECT: Cherry Lane Slope Remediation

RECORD OF BOREHOLE: COS-13-002

SHEET 1 OF 2

LOCATION: N 5775616.7 E 386038.9

BORING DATE: 07/25/13

DATUM: NAD83

DRILL RIG: CME

DRILLING CONTRACTOR: Boss Drilling

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS		
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH Cu, kPa				WATER CONTENT PERCENT					
								20	40	60	80	nat V. rem V.	+ Q - U -			Wp	W
0		GROUND SURFACE		498.48													
		TOPSOIL		498.33	002-1	AS											
		FILL, (SC) CLAYEY SILT, fine, dark brown, some organics, non-cohesive, dry (SM) SILTY SAND, fine, some clay, low plasticity, brown, some organics, non-cohesive, dry (CL) SILTY CLAY, low plastic, brown, some iron staining, some white staining, cohesive, w~PL, hard		498.18	002-2	AS											
				0.30	002-3	AS											
				497.87	0.61												
1					002-4	AS								PP=4.5			
					002-5	AS								PP=1.5			
2																	
		-some fine grained sand at approximately 2.4m -becomes stiff at approximately 2.4m			002-6	AS											
3				495.44													
		(Cl) SILTY CLAY, medium plastic, trace sand, fine, trace/some iron staining, trace/some white staining, cohesive, w>PL, stiff to very stiff		3.05	002-7	AS								PP=3			
					002-8	AS											
4																	
					002-9	AS											
5																	
					002-10	AS								PP=0.25			
6																	
					002-11	AS											
7																	
					002-12	AS											
8																	
					002-13	AS								PP=0			
9																	
10				488.73													
		(CL) sandy, SILTY CLAY, fine grained, brown, wet, very soft		9.75													

CONTINUED NEXT PAGE

SK SOIL 11-1362-0057-5100 BOREHOLES.GPJ GAL-SASK.GDT 05/05/14

DEPTH SCALE

1 : 50



LOGGED: LM

CHECKED: LDN

PROJECT: Cherry Lane Slope Remediation

RECORD OF BOREHOLE: COS-13-002

SHEET 2 OF 2

LOCATION: N 5775616.7 E 386038.9

BORING DATE: 07/25/13

DATUM: NAD83

DRILL RIG: CME

DRILLING CONTRACTOR: Boss Drilling

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH Cu, kPa		WATER CONTENT PERCENT		HYDRAULIC CONDUCTIVITY				
								20	40	60	80	10 ⁻⁶	10 ⁻⁵			10 ⁻⁴
10	150mm Dia. Solid Stem Auger Continuous Flight	<i>CONTINUED FROM PREVIOUS PAGE</i> (CL) sandy, SILTY CLAY, fine grained, brown, wet, very soft (<i>continued</i>)		488.12												
		(CL) SILTY CLAY, low plasticity, some sand, fine, brown, cohesive, w>PL, soft to very soft	10.36	002-14	AS										PP=0.5	
11			(CI) SILTY CLAY, medium plastic, brown, cohesive, w>PL, firm to stiff	487.21											PP=1.0	
			-becomes grey at approximately 12m	11.28	002-15	AS									PP=1.5	
12					002-16	AS									PP=1	
13			(CH) CLAY, some silt, high plasticity, grey, cohesive, w>PL, stiff	485.38											PP=2	VW25400 Slope Indicator in Grout
14		(CL) SILTY CLAY, some gravel, fine-coarse, grey, (TILL), cohesive, w>PL, stiff	13.11	002-17	AS									SG		
15			484.46											PP=1		
16			14.02	002-18	AS									PP=2.5	VW25399	
17		END OF BOREHOLE = 16.8m	481.72													
			16.76													

SK SOIL 11-1362-0057-5100 BOREHOLES.GPJ GAL-SASK.GDT 05/05/14

DEPTH SCALE

1 : 50



LOGGED: LM

CHECKED: LDN

PROJECT: Cherry Lane Slope Remediation

RECORD OF BOREHOLE: COS-13-003

SHEET 1 OF 1

LOCATION: N 5775674.7 E 386061.6

BORING DATE: 07/26/13

DATUM: NAD83

DRILL RIG: CME

DRILLING CONTRACTOR: Boss Drilling

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		HYDRAULIC CONDUCTIVITY, k, cm/s		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	SHEAR STRENGTH Cu, kPa		WATER CONTENT PERCENT			
							20	40	60			80
0	150mm Dia. Solid Stem Auger Continuous Flight	GROUND SURFACE		480.34							TOC=0.5mags	
		FILL, (CL) SILTY CLAY and SAND, well graded, some gravel, fine to coarse grained, black, w-PL, stiff to very stiff		0.00	003-1	AS						
1		(CL) SILTY CLAY, low plasticity, some gravel, fine to coarse grained, brown, trace iron staining, trace gypsum and weathered gypsum, trace petrified wood, trace coal, w-PL, stiff to very stiff		479.43	003-2	AS					PP=2	
		(GW) GRAVEL, dry		478.82								
		(CL) SILTY CLAY, low plasticity, some gravel, fine to coarse grained, brown, trace iron staining, trace gypsum and weathered gypsum, trace petrified wood, trace coal, w-PL, stiff to very stiff		478.67								Bentonite
2				1.68	003-3	AS						
3												
4					003-4	AS						
5			(CH) CLAY, high plasticity, trace gravel, fine to coarse grained, brown, trace iron staining, some weathered gypsum, some coal, w-PL, stiff to very stiff		475.47	003-5	AS					
			(SM) SILTY SAND, brown, trace iron staining, wet		4.88							
6				474.86	003-6	AS					Sand	
				5.49	003-7	TO						
7												
8		(GW) GRAVEL, well graded, fine to coarse grained, brown, very wet		473.03	003-8	AS					07/26/13	
				7.32								
9		(CL) SILTY CLAY, some gravel, fine grained, (TILL), w>PL, firm to stiff		471.50	003-9	AS						
				8.84								
10		END OF BOREHOLE = 9.1m		471.20							Screen	
				9.14								

SK SOIL 11-1362-0057-5100 BOREHOLES.GPJ GAL-SASK.GDT 05/05/14

DEPTH SCALE

1 : 50



LOGGED: LM

CHECKED: LDN

PROJECT: Cherry Lane Slope Remediation

RECORD OF BOREHOLE: COS-13-004

SHEET 1 OF 2

LOCATION: N 5775605.0 E 386050.6

BORING DATE: 08/19/13

DATUM: NAD83

DRILL RIG: M4CT

DRILLING CONTRACTOR: Mobile Augers and Research Ltd.

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS		
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m				WATER CONTENT PERCENT						
							20	40	60	80	Wp	W	Wi				
0	150mm Dia. Solid Stem Auger Continuous Flight	GROUND SURFACE		491.74													
		TOPSOIL, clayey, some fine-medium grained sand, some fine gravel, some organics, dark brown/black (CL) SILTY CLAY, low plasticity, trace fine grained sand, light brown, some rust staining, some organics, trace weathered gypsum, cohesive, w>PL, very soft to soft		0.00	004-1	AS											
				491.43													
				0.30	004-2	AS										MH	
1																	
2																	
3																	
4																	
5		(CH) CLAY, high plasticity, some silt, brown/black mottling, some rust staining, cohesive, w>PL, stiff		487.32													
				4.42	004-5	DO											
6		(CI) SILTY CLAY, medium plastic, brown, cohesive, w>PL, stiff		486.56													
				5.18	004-6	AS											
7																	
8																	
9		(CL-ML) SILTY CLAY/CLAYEY SILT and fine to medium grained sand, some gravel, trace cobbles, grey, cohesive, (TILL), w~PL, very stiff		483.05													
				8.69	004-9	TO											
10																	

CONTINUED NEXT PAGE

SK SOIL 11-1362-0057-5100 BOREHOLES.GPJ GAL-SASK.GDT 05/05/14

DEPTH SCALE

1 : 50



LOGGED: LM

CHECKED: LDN

08/19/13

PROJECT: Cherry Lane Slope Remediation

RECORD OF BOREHOLE: COS-13-004

SHEET 2 OF 2

LOCATION: N 5775605.0 E 386050.6

BORING DATE: 08/19/13

DATUM: NAD83

DRILL RIG: M4CT

DRILLING CONTRACTOR: Mobile Augers and Research Ltd.

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES			DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH Cu, kPa				WATER CONTENT PERCENT					
								20	40	60	80	nat V. +	rem V. ⊕	Q - ●			U - ○
10	Continuous Flight	<p><i>CONTINUED FROM PREVIOUS PAGE</i> (CL-ML) SILTY CLAY/CLAYEY SILT and fine to medium grained sand, some gravel, trace cobbles, grey, cohesive, (TILL), w~PL, very stiff (<i>continued</i>)</p>		480.71												VW25397 Slope Indicator in Grout	
11		END OF BOREHOLE = 11.02m		11.02													
12																	
13																	
14																	
15																	
16																	
17																	
18																	
19																	
20																	

SK SOIL 11-1362-0057-5100 BOREHOLES.GPJ GAL-SASK.GDT 05/05/14

DEPTH SCALE

1 : 50



LOGGED: LM

CHECKED: LDN

PROJECT: Cherry Lane Slope Remediation
 LOCATION: N 5775637.7 E 386047.6

RECORD OF BOREHOLE: COS-13-005

SHEET 1 OF 2
 DATUM: NAD83

BORING DATE: 08/20/13
 DRILL RIG: M10
 DRILLING CONTRACTOR: Mobile Augers and Research Ltd.

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE			SAMPLES			DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH Cu, kPa		WATER CONTENT PERCENT						
								20	40	60	80	nat V. +	rem V. ⊕			Q - ●
0	150mm Dia. Solid Stem Auger Continuous Flight	GROUND SURFACE		494.48												
		(SM) SILTY SAND, fine grained, light brown, trace organics, non-cohesive, moist, loose		0.00	005-1	AS									MH	
1							12									
						005-2	DO									
2							19									
						005-3	DO									
3																
4			(SC) CLAYEY SAND, fine grained, light brown with black and white seams, cohesive, dry, compact		490.82 3.66	005-4	DO									
5															Slope Indicator in Grout	
6			(CI) SILTY CLAY, sand seams, brown, w~PL		488.99 5.49	005-5	TO		+						PP=3.75	
					005-6	TO								PP>4.5		
7		(SM) SILTY SAND, some clay, light brown, cohesive, dry-moist, compact		487.77 6.71	005-7	TO									VW25926	
8		(CI) SILTY CLAY, medium plastic, trace sand, brown, cohesive, w~PL		486.86 7.62	005-8	TO								MH		
					005-9	TO								SG		
9																
10		(ML) SANDY, CLAYEY SILT, fine grained, brown, moist, compact		485.34 9.14	005-10	TO								MH		
					005-11	TO										
		CONTINUED NEXT PAGE														

SK SOIL 11-1362-0057-5100 BOREHOLES.GPJ GAL-SASK.GDT 05/05/14

DEPTH SCALE
 1 : 50



LOGGED: LM
 CHECKED: LDN

PROJECT: Cherry Lane Slope Remediation

RECORD OF BOREHOLE: COS-13-005

SHEET 2 OF 2

LOCATION: N 5775637.7 E 386047.6

BORING DATE: 08/20/13

DATUM: NAD83

DRILL RIG: M10

DRILLING CONTRACTOR: Mobile Augers and Research Ltd.

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH Cu, kPa		WATER CONTENT PERCENT		WATER CONTENT PERCENT			
								20	40	60	80	10 ⁻⁶	10 ⁻⁵		
10	150mm Dia. Solid Stem Auger Continuous Flight	<i>CONTINUED FROM PREVIOUS PAGE</i> (ML) SANDY, CLAYEY SILT, fine grained, brown, moist, compact <i>(continued)</i>													
				483.81	005-11	TO									
				10.67	005-12	TO									
11			(CI) SILTY CLAY, medium plastic, fine grained, grey and brown laminated, w~PL, very stiff												
					005-13	TO									
12			482.14	005-14	TO										
			12.34												
13		(CI) SILTY CLAY, medium plastic, some sand, grey, w>PL, (TILL)													
14				005-15	DO	64									
15			479.16												
			15.32												
16		END OF BOREHOLE = 15.32m													
17															
18															
19															
20															

SK SOIL 11-1362-0057-5100 BOREHOLES.GPJ GAL-SASK.GDT 05/05/14

DEPTH SCALE

1 : 50



LOGGED: LM

CHECKED: LDN

PROJECT: Cherry Lane Slope Remediation

RECORD OF BOREHOLE: COS-13-006

SHEET 1 OF 2

LOCATION: N 5775572.7 E 385959.2

BORING DATE: 08/21/13

DATUM: NAD83

DRILL RIG: M10

DRILLING CONTRACTOR: Mobile Augers and Research Ltd.

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH Cu, kPa		WATER CONTENT PERCENT		WATER CONTENT PERCENT			
								20	40	60	80	nat V. +	rem V. ⊕		
0		GROUND SURFACE		494.77											
		FILL (CL) SILTY CLAY, low plasticity, sandy, some organics, black and brown, cohesive, w<PL		0.00											
		(CI-CL) SILTY CLAY, low to medium plastic, trace sand, brown, some white staining, some iron staining, cohesive, w~PL, very soft to stiff		494.46	006-1	AS									
				0.30											
1					006-2	AS									
2		(CH) CLAY, high plasticity, brown, some iron staining, cohesive, w~PL, very stiff		492.94	006-3	AS									
				1.83	006-4	AS									
3					006-5	AS									
4		-some white staining and gypsum crystals below 3.4m													
5					006-6	AS									
6					006-7	AS									
7					006-8	AS									
8					006-9	AS									
9		(CI) SILTY CLAY, medium plasticity, trace sand, cohesive, w>PL, firm to stiff		486.23	006-10	AS									MH
				8.53											
10															

CONTINUED NEXT PAGE

SK SOIL 11-1362-0057-5100 BOREHOLES.GPJ GAL-SASK.GDT 05/05/14

DEPTH SCALE

1 : 50



LOGGED: LM

CHECKED: LDN

PROJECT: Cherry Lane Slope Remediation

RECORD OF BOREHOLE: COS-13-006

SHEET 2 OF 2

LOCATION: N 5775572.7 E 385959.2

BORING DATE: 08/21/13

DATUM: NAD83

DRILL RIG: M10

DRILLING CONTRACTOR: Mobile Augers and Research Ltd.

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH Cu, kPa		WATER CONTENT PERCENT		WATER CONTENT PERCENT				
								20	40	60	80	10 ⁻⁶	10 ⁻⁵			10 ⁻⁴
10	150mm Dia. Solid Stem Auger Continuous Flight	<i>CONTINUED FROM PREVIOUS PAGE</i>														
		(CI) SILTY CLAY, medium plasticity, trace sand, cohesive, w>PL, firm to stiff (continued)			006-11	AS										VW26018
				484.25												
		(CL) SILTY CLAY, low plasticity, some fine gravel and sand, trace coarse gravel, grey, (TILL), cohesive, w~PL, stiff		10.52												
11					006-12	AS										Slope Indicator in Grout
				482.57												
		(SM) SILTY SAND, some fine grained gravel, grey, non-cohesive, wet		482.42	006-13	AS										
		(CL) SILTY CLAY, low plasticity, some fine gravel and sand, trace coarse gravel, grey, (TILL), cohesive, w~PL, stiff		12.34												
13			(SM) SILTY SAND, some fine grained gravel, grey, non-cohesive, wet	481.66												
				13.11	006-14	AS										VW25398
			(CL) SILTY CLAY, low plasticity, some fine gravel and sand, trace coarse gravel, grey, (TILL), cohesive, w~PL, stiff	481.36												
				13.41												
14			END OF BOREHOLE = 14.33m	480.44												
				14.33												

SK SOIL 11-1362-0057-5100 BOREHOLES.GPJ GAL-SASK.GDT 05/05/14

DEPTH SCALE

1 : 50



LOGGED: LM

CHECKED: LDN

PROJECT: Cherry Lane Slope Remediation

RECORD OF BOREHOLE: COS-13-007

SHEET 1 OF 1

LOCATION: N 5775573.5 E 385959.1

BORING DATE: 08/21/13

DATUM: NAD83

DRILL RIG: M10

DRILLING CONTRACTOR: Mobile Augers and Research Ltd.

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES			DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION AND GROUNDWATER OBSERVATIONS	
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH Cu, kPa				WATER CONTENT PERCENT					
								20	40	60	80	nat V. rem V.	+ Q - U	Wp			W
0	150mm Dia. Solid Stem Auger Continuous Flight	GROUND SURFACE		494.80													
		FILL (CL) SILTY CLAY, low plasticity, sandy, some organics, black and brown, w<PL		0.00													
		(CI-CL) SILTY CLAY, low to medium plasticity, trace sand, brown, some white staining, some iron staining, cohesive, w~PL, very soft to stiff		0.30													
2		(CH) CLAY, high plasticity, brown, some iron staining, cohesive, w~PL, very stiff with some soft spots		1.83													Bentonite
3		-some white staining and gypsum crystals below 3.4m															
4																	Sand
5																	Screen
5.59		END OF BOREHOLE = 5.59m		5.59													

SK SOIL 11-1362-0057-5100 BOREHOLES.GPJ GAL-SASK.GDT 05/05/14

DEPTH SCALE

1 : 50



LOGGED: LM

CHECKED: LDN




APPENDIX F

Monitoring Data




F.1. SLOPE INCLINOMETER PLOTS

AGRA Earth & Environmental Limited - Saskatoon, SK




COS#12 - EAST RIVER BANK, Inclinometer SI-84ICL
Cherry Lane (West Casing)

AMEC Earth & Environmental - Saskatoon, SK



- 22-Aug-85
- 29-Oct-86
- 3-Nov-87
- 19-Oct-87
- 11-Oct-89
- 16-Nov-90
- 21-Nov-91
- 25-May-92
- 30-Nov-99
- 27-Oct-00
- 12-Oct-01
- 24-Oct-02
- 10-Oct-03
- 19-Nov-04
- 13-Oct-05

Note: Casing in need of repair since 2005



COS #11 - EAST RIVER BANK, Inclinometer 85-511 Cherry Lane (East Casing)



Earth & Environmental
A Division of AMEC Americas Limited

COS#11 – EAST RIVER BANK – 85-511
CUMULATIVE DEFLECTION

SOUTH SASKATCHEWAN RIVER
SASKATOON, SASKATCHEWAN

CITY OF SASKATOON
2008 EAST RIVER BANK MONITORING PROGRAM

Drawn: EM


Scale: As Shown

Date: Nov/08

Proj. No: SX0258510

Figure: 33

AMEC Earth & Environmental - Saskatoon, SK



Earth & Environmental
 A Division of AMEC Americas Limited

Drawn by: EM Scale: As Shown



CITY OF SASKATOON
2008 EAST RIVER BANK MONITORING PROGRAM

Date: Nov/08 Proj. No: SX0258510 Figure: 34

COS#11 - EAST RIVER BANK - 85-511
DISPLACEMENT TIME - A-DIRECTION
SOUTH SASKATCHEWAN RIVER
SASKATOON, SASKATCHEWAN

Borehole : BH1
Project : 11-1362-0057 Cherry Lane
Location : Lane - 241 11th St E
Northing : 5775616.8
Easting : 386010.5
Collar :


Spiral Correction : N/A
Collar Elevation : 488.1 meters
Borehole Total Depth : 7.0 meters
A+ Groove Azimuth :
Base Reading : 2012 Jun 25 08:55
Applied Azimuth : 0.0 degrees




Borehole : BH1
Project : 11-1362-0057 Cherry Lane
Location : Lane - 241 11th St E
Northing : 5775616.8
Easting : 386010.5
Collar :

Spiral Correction : N/A
Collar Elevation : 488.1 meters
Borehole Total Depth : 7.0 meters
A+ Groove Azimuth :
Base Reading : 2012 Jun 25 08:55
Applied Azimuth : 0.0 degrees

Axis - A





Axis - B



Borehole : BH 2
Project : 11-1362-0057 Cherry Lane
Location : Lane - 233 11th St E.
Northing : 5775623.7
Easting : 385980.0
Collar :


Spiral Correction : N/A
Collar Elevation : 485.7 meters
Borehole Total Depth : 4.5 meters
A+ Groove Azimuth :
Base Reading : 2012 Jun 25 09:39
Applied Azimuth : 0.0 degrees




Borehole : BH 2
Project : 11-1362-0057 Cherry Lane
Location : Lane - 233 11th St E.
Northing : 5775623.7
Easting : 385980.0
Collar :

Spiral Correction : N/A
Collar Elevation : 485.7 meters
Borehole Total Depth : 4.5 meters
A+ Groove Azimuth :
Base Reading : 2012 Jun 25 09:39
Applied Azimuth : 0.0 degrees

Axis - A




Axis - B



Borehole : BH 2
Project : 11-1362-0057 Cherry Lane
Location : Lane - 233 11th St E.
Northing : 5775623.7
Easting : 385980.0
Collar :
Collar Elev : 485.7 meters



Spiral Correction : N/A
Movement Depth : 2.0 - 3.5 meters
Borehole Total Depth : 4.5 meters
A+ Groove Azimuth :
Latest Reading : 2012 Jun 26 09:02
Initial Reading : 2012 Jun 25 09:39
Applied Azimuth : 0.0 degrees

Time Plot : 2.0 - 3.5 meters





Borehole : BH 3
Project : 11-1362-0057 Cherry Lane
Location : Lane - 231 11th St E.
Northing : 5775623.7
Easting : 385980.0
Collar :

Spiral Correction : N/A
Collar Elevation : 484.0 meters
Borehole Total Depth : 3.5 meters
A+ Groove Azimuth :
Base Reading : 2012 Jun 25 10:17
Applied Azimuth : 0.0 degrees



Borehole : BH 3
Project : 11-1362-0057 Cherry Lane
Location : Lane - 231 11th St E.
Northing : 5775623.7
Easting : 385980.0
Collar :

Spiral Correction : N/A
Collar Elevation : 484.0 meters
Borehole Total Depth : 3.5 meters
A+ Groove Azimuth :
Base Reading : 2012 Jun 25 10:17
Applied Azimuth : 0.0 degrees



Borehole : BH 3
Project : 11-1362-0057 Cherry Lane
Location : Lane - 231 11th St E.
Northing : 5775623.7
Easting : 385980.0
Collar :
Collar Elev : 484.0 meters



Spiral Correction : N/A
Movement Depth : 0.5 - 1.5 meters
Borehole Total Depth : 3.5 meters
A+ Groove Azimuth :
Latest Reading : 2013 Oct 30 10:49
Initial Reading : 2012 Jun 25 10:17
Applied Azimuth : 0.0 degrees

Time Plot : 0.5 - 1.5 meters



Borehole : COS-13-001B
Project : 11-1362-0057 Cherry Lane
Location : Lane - 306 SK. Cres. E.
Northing : 5775616.67
Easting : 386038.94
Collar : -0.109


Spiral Correction : N/A
Collar Elevation : 489.2 meters
Borehole Total Depth : 7.5 meters
A+ Groove Azimuth :
Base Reading : 2013 Jul 27 15:17
Applied Azimuth : 0.0 degrees




Borehole : COS-13-001B
Project : 11-1362-0057 Cherry Lane
Location : Lane - 306 SK. Cres. E.
Northing : 5775616.67
Easting : 386038.94
Collar : -0.109

Spiral Correction : N/A
Collar Elevation : 489.2 meters
Borehole Total Depth : 7.5 meters
A+ Groove Azimuth :
Base Reading : 2013 Jul 27 15:17
Applied Azimuth : 0.0 degrees

Axis - A




Axis - B



Borehole : COS-13-001B
Project : 11-1362-0057 Cherry Lane
Location : Lane - 306 SK. Cres. E.
Northing : 5775616.67
Easting : 386038.94
Collar : -0.109
Collar Elev : 489.2 meters



Spiral Correction : N/A
Movement Depth : 4.5 - 6.5 meters
Borehole Total Depth : 7.5 meters
A+ Groove Azimuth :
Latest Reading : 2013 Aug 28 08:05
Initial Reading : 2013 Jul 27 15:17
Applied Azimuth : 0.0 degrees

Time Plot : 4.5 - 6.5 meters





Borehole : COS-13-002
Project : 11-1362-0057 Cherry Lane
Location : 307 11th St. E. (Front)
Northing : 5775567.41
Easting : 386043.54
Collar : -0.113

Spiral Correction : N/A
Collar Elevation : 498.4 meters
Borehole Total Depth : 15.5 meters
A+ Groove Azimuth :
Base Reading : 2013 Jul 30 16:18
Applied Azimuth : 0.0 degrees





Borehole : COS-13-002
Project : 11-1362-0057 Cherry Lane
Location : 307 11th St. E. (Front)
Northing : 5775567.41
Easting : 386043.54
Collar : -0.113

Spiral Correction : N/A
Collar Elevation : 498.4 meters
Borehole Total Depth : 15.5 meters
A+ Groove Azimuth :
Base Reading : 2013 Jul 30 16:18
Applied Azimuth : 0.0 degrees





Borehole : COS-13-004
Project : 11-1362-0057 Cherry Lane
Location : 307 11th. St. E. (back)
Northing : 5775604.97
Easting : 386050.63
Collar : -0.677

Spiral Correction : N/A
Collar Elevation : 491.6 meters
Borehole Total Depth : 10.0 meters
A+ Groove Azimuth :
Base Reading : 2013 Aug 28 08:30
Applied Azimuth : 0.0 degrees



Borehole : COS-13-004
Project : 11-1362-0057 Cherry Lane
Location : 307 11th. St. E. (back)
Northing : 5775604.97
Easting : 386050.63
Collar : -0.677


Spiral Correction : N/A
Collar Elevation : 491.6 meters
Borehole Total Depth : 10.0 meters
A+ Groove Azimuth :
Base Reading : 2013 Aug 28 08:30
Applied Azimuth : 0.0 degrees




Borehole : COS-13-005
Project : 11-1362-0057 Cherry Lane
Location : 316 Sask. Cres. E.
Northing : 5775631.299
Easting : 386078.8467
Collar : -0.1

Spiral Correction : N/A
Collar Elevation : 494.4 meters
Borehole Total Depth : 14.5 meters
A+ Groove Azimuth :
Base Reading : 2013 Aug 28 09:11
Applied Azimuth : 0.0 degrees

Axis - A




Axis - B




Borehole : COS-13-005
Project : 11-1362-0057 Cherry Lane
Location : 316 Sask. Cres. E.
Northing : 5775631.299
Easting : 386078.8467
Collar : -0.1

Spiral Correction : N/A
Collar Elevation : 494.4 meters
Borehole Total Depth : 14.5 meters
A+ Groove Azimuth :
Base Reading : 2013 Aug 28 09:11
Applied Azimuth : 0.0 degrees

Axis - A



Axis - B





Borehole : COS-13-006
Project : 11-1362-0057 Cherry Lane
Location : 231 11th St. E.
Northing : 5775572.72
Easting : 385959.21
Collar : -0.147

Spiral Correction : N/A
Collar Elevation : 494.6 meters
Borehole Total Depth : 13.0 meters
A+ Groove Azimuth :
Base Reading : 2013 Aug 28 13:13
Applied Azimuth : 0.0 degrees

Axis - A

Axis - B





Borehole : COS-13-006
Project : 11-1362-0057 Cherry Lane
Location : 231 11th St. E.
Northing : 5775572.72
Easting : 385959.21
Collar : -0.147

Spiral Correction : N/A
Collar Elevation : 494.6 meters
Borehole Total Depth : 13.0 meters
A+ Groove Azimuth :
Base Reading : 2013 Aug 28 13:13
Applied Azimuth : 0.0 degrees

Axis - A

Axis - B





F.2. TELL-TALE CRACK MONITORS PHOTOS




Photo F.1: Crack Meter Located on the Retaining Wall Behind 306 Sask. Cres. E. (CM1) (Aug 12, 2013)



Photo F.2: Crack Meter Located on the Retaining Wall Behind 306 Sask. Cres. E. (CM1) (Sept 18, 2013)



Photo F.3: Crack Meter Located on the East Face of the Retaining Wall Between 230 & 306 Sask. Cres. E. (CM2) (Aug 12, 2013)



Photo F.4: Crack Meter Located on the East Face of the Retaining Wall Between 230 & 306 Sask. Cres. E. (CM2) (Sept 18, 2013)



Photo F.5: Crack Meter Located on the West Face of the Retaining Wall Between 230 & 306 Sask. Cres. E. (CM3) (Aug 12, 2013)



Photo F.6: Crack Meter Located on the West Face of the Retaining Wall Between 230 & 306 Sask. Cres. E. (CM3) (Sept 18, 2013)



F.3. SETTLEMENT POINT DATA

Cherry Lane - Settlement Point Data

Point ID	Description	Elevation (masl)			Settlement (mm)	
		29-Aug-13	18-Sep-13	28-Nov-13	18-Sep-13	28-Nov-13
PT03	BM2 - Sask. Cres./sidewalk	480.12	480.12	480.12	-2.15	-5.98
PT04	306 Sask. Cres. (NE corner)	479.95	479.95	479.95	-0.50	-3.17
PT05	306 Sask. Cres. (NW corner)	479.52	479.52	479.52	-0.35	-3.27
PT06	230 Sask. Cres. (NE corner)	479.60	479.60	479.60	-0.60	-4.26
PT07	230 Sask. Cres. (E side)	479.71	479.71	479.71	-1.24	-4.33
PT08	306 Sask. Cres. (SW corner)	481.70	481.70	481.69	-1.47	-5.71
PT09	306 Sask. Cres. (SE corner)	482.40	482.39	482.39	-1.01	-3.99
PT10	230 Sask. Cres. (SE corner)	487.62	487.62	487.62	-0.38	-3.99
PT11	230 Sask. Cres. (SW corner)	487.85	487.85	487.85	-0.22	-2.77
PT12	311/313 - 11th St. (NW corner)	494.82	494.82	494.82	0.07	-0.55
PT13	311/313 - 11th St. (drive-way)	495.48	495.48	495.48	-0.36	-1.47
PT14	BM3 - Apt. 328 Sask. Cres. (SW corner)	496.41	496.41	496.41	0.00	0.00
PT15	Apt. 328 Sask. Cres. (NW corner)	494.56	494.56	494.56	0.03	0.20
PT16	311/313 - 11th St. (SE corner)	499.14	499.14	499.14	-1.62	-0.56
PT17	311/313 - 11th St. (SW corner)	499.19	499.19	499.19	-1.85	-1.19
PT18	309 - 11th St. (NW corner)	496.60	496.60	496.60	-0.63	-0.19
PT19	307 - 11th St. (back deck)	496.72	496.72	496.72	-0.46	0.53
PT20	305 - 11th St. (NE corner)	497.06	497.06	497.06	-0.50	-0.54
PT21	305 - 11th St. (SE corner)	498.84	498.84	498.84	-0.31	4.00
PT22	303 - 11th St. (SW corner)	498.28	498.28	498.28	1.38	0.02
PT23	233/235 - 11th St. (drive-way)	497.13	497.13	497.12	-0.61	-3.80
PT24	233/235 - 11th St. (NW corner)	492.74	492.74	492.74	0.01	-1.86
PT25	233/235 - 11th St. (N side)	492.80	492.80	492.80	1.48	-0.43
PT26	237/239 - 11th St. (NW side)	494.85	494.85	494.85	0.74	-1.21
PT27	237/239 - 11th St. (NE side)	494.89	494.89	494.89	1.90	0.71
PT28	241 - 11th St. (NW corner)	495.83	495.84	495.83	1.87	1.44
PT29	237/239 - 11th St. (E side)	497.83	497.84	497.84	1.47	0.76
PT30	241 - 11th St. (NE corner)	495.41	495.41	495.41	2.14	0.53
PT31	303 - 11th St. (NE corner)	494.42	494.42	494.42	1.77	1.08



APPENDIX G

Laboratory Test Results

GENERAL TESTING RESULTS

Project #: 11-1362-0057

Phase : 5000

Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK

Tested by: S.H.

Date: July 4, 2012

Sample Identification				Laboratory Test Results									
Borehole #	Sample #	Depth (m)	Sample Type	Water Content (%)	Plastic Limit	Liquid Limit	Plasticity Index	% Passing #200	SHT Group Index	ASTM Group Index	Dry Density (Kg/m ³)	Pocket Penetrometer (kPa)	Lab Vane (kPa)
11-0057-BH1	BH1-1	0.61-0.91	AS	36.2									
11-0057-BH1	BH1-2	1.22-1.52	AS	37.0									
11-0057-BH1	BH1-3	2.13-2.44	AS	33.9	20	39	19						
11-0057-BH1	BH1-4	2.44-2.74	AS	36.1									
11-0057-BH1	BH1-5	3.35-3.66	AS	36.3	22	62	40						
11-0057-BH1	BH1-6	3.96-4.27	AS	14.5									
11-0057-BH1	BH1-7	4.88-5.18	AS	15.7									
11-0057-BH1	BH1-8	6.40-6.71	AS	8.3									
11-0057-BH1P	BH1P-1	1.52-2.13	TO	34.6	21	43	22				1371		
11-0057-BH1P	BH1P-2	2.44-3.05	TO	31.1									
11-0057-BH1P	BH1P-3	3.05	TO	35.0	21	50	29				1405		
11-0057-BH2	BH2-1	0.91-1.22	AS	33.0									
11-0057-BH2	BH2-2	1.22-1.52	AS	31.8	24	55	31						
11-0057-BH2	BH2-3	1.83-2.13	AS	31.7									
11-0057-BH2	BH2-4	2.44-2.74	AS	30.4	25	48	23						
11-0057-BH2	BH2-5	3.35-3.66	AS	12.9	12	18	6						
11-0057-BH2	BH2-6	3.66-3.96	AS	9.1									
11-0057-BH2	BH2-7	4.57-4.88	AS	14.9									
11-0057-BH2P	BH2P-1	1.52-2.13	TO	34.9									
11-0057-BH2P	BH2P-2	2.44	TO	34.5	27	72	45				1415		
11-0057-BH2P	BH2P-3	2.74-3.35	TO	10.9									
11-0057-BH3	BH3-1	0.61-0.91	AS	22.2									
11-0057-BH3	BH3-2	1.22-1.52	AS	24.3	17	31	14						
11-0057-BH3	BH3-3	1.83-2.13	AS	28.4	18	28	10						
11-0057-BH3	BH3-4	2.44-3.05	AS	15.9									
11-0057-BH3	BH3-5	3.66-3.96	AS	13.6									

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.B. / P.E.
 Borehole #: 11-0057-BH1 Sample #: BH1-5
 Source:
 Date Sample Received: June 25, 2012

Phase: 5000
 Date: July 3, 2012

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	100
0.425	99
0.250	99
0.150	98
0.075	97
0.032	94
0.024	89
0.017	84
0.013	77
0.010	69
0.007	58
0.005	50
0.004	44
0.003	39
0.002	35
0.001	33

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.B. / P.E.
 Borehole #: 11-0057-BH1P Sample #: BH1P-1
 Source:
 Date Sample Received: June 25, 2012

Phase: 5000
 Date: July 3, 2012

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	100
0.425	100
0.250	100
0.150	100
0.075	97
0.038	72
0.028	63
0.021	53
0.015	46
0.011	44
0.008	40
0.006	37
0.004	34
0.003	31
0.002	28
0.001	26

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.B. / P.E.
 Borehole #: 11-0057-BH1P Sample #: BH1P-3
 Source:
 Date Sample Received: June 25, 2012

Phase: 5000
 Date: July 3, 2012

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	100
0.425	100
0.250	99
0.150	99
0.075	99
0.031	93
0.023	90
0.016	85
0.012	80
0.009	73
0.007	63
0.005	54
0.004	46
0.003	41
0.002	37
0.001	33

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.B. / P.E.
 Borehole #: 11-0057-BH2P Sample #: BH2P-2
 Source:
 Date Sample Received: June 25, 2012

Phase: 5000
 Date: July 3, 2012

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	100
0.425	100
0.250	100
0.150	99
0.075	99
0.033	96
0.023	94
0.017	91
0.012	86
0.009	81
0.007	75
0.005	70
0.004	65
0.003	58
0.002	52
0.001	48

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.B. / P.E.
 Borehole #: 11-0057-BH3 Sample #: BH3-3
 Source:
 Date Sample Received: June 25, 2012

Phase: 5000
 Date: July 3, 2012

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	99
0.425	99
0.250	99
0.150	94
0.075	61
0.043	42
0.032	33
0.023	27
0.017	23
0.012	22
0.008	21
0.006	19
0.004	17
0.003	15
0.002	14
0.001	13

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST-SUMMARY

Project #: 11-1362-0057

Phase: 5000



Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK

Tested By: D.B.

Date: July 24, 2012

Sample	Normal Stress	Shear Stress	
	(kPa)	Peak (kPa)	Residual (kPa)
11-0057-BH1P BH1P-3	50	23	11
	100	63	48
	200	114	40

	Peak	Residual
Friction angle (degrees):	30.0	11.4
cohesion (kPa):	0	0



Comments:



The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057 Phase: 5000
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested By: D.B. Date: July 24, 2012
 Sample: 11-0057-BH1P BH1P-3

Effective Stress:	50	kPa	Peak Shear Stress:	23	kPa
			Residual Shear Stress	11	kPa
Sample Data:			Comments:		
Sample Length:	60.0	mm			
Initial Height:	20.0	mm			
Initial Water Content:	33.7	%			
Initial Dry Density:	1372	kg/m ³			
Final Water Content:	42.7	%			





The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057	Phase: 5000
Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK	
Tested By: D.B.	Date: July 24, 2012
Sample: 11-0057-BH1P BH1P-3	

Effective Stress: 100 kPa	Peak Shear Stress: 63 kPa
	Residual Shear Stress: 48 kPa
Sample Data:	Comments:
Sample Length: 60.0 mm	
Initial Height: 20.0 mm	
Initial Water Content: 34.4 %	
Initial Dry Density: 1416 kg/m ³	
Final Water Content: 34.2 %	





The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057	Phase: 5000
Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK	
Tested By: D.B.	Date: July 24, 2012
Sample: 11-0057-BH1P BH1P-3	

Effective Stress: 200 kPa	Peak Shear Stress: 114 kPa
	Residual Shear Stress: 40 kPa
Sample Data:	Comments:
Sample Length: 60.0 mm	
Initial Height: 20.0 mm	
Initial Water Content: 33.2 %	
Initial Dry Density: 1386 kg/m ³	
Final Water Content: 35.8 %	



The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST-SUMMARY

Project #: 11-1362-0057

Phase: 5000



Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK

Tested By: D.B.

Date: July 12, 2012

Sample	Normal Stress	Shear Stress	
	(kPa)	Peak (kPa)	Residual (kPa)
11-0057-BH2P BH2P-2	50	35	15
	100	68	63
	200	103	82

	Peak	Residual
Friction angle (degrees):	23.7	22.0
cohesion (kPa):	18	0



Comments:



The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057	Phase: 5000
Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK	
Tested By: D.B.	Date: July 12, 2012
Sample: 11-0057-BH2P BH2P-2	

Effective Stress: 50 kPa	Peak Shear Stress: 35 kPa
	Residual Shear Stress: 15 kPa
Sample Data:	Comments:
Sample Length: 60.0 mm	
Initial Height: 20.0 mm	
Initial Water Content: 34.8 %	
Initial Dry Density: 1346 kg/m ³	
Final Water Content: 40.3 %	





The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057	Phase: 5000
Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK	
Tested By: D.B.	Date: July 12, 2012
Sample: 11-0057-BH2P BH2P-2	

Effective Stress: 100 kPa	Peak Shear Stress: 68 kPa	Residual Shear Stress: 63 kPa
Sample Data:	Comments:	
Sample Length: 60.0 mm		
Initial Height: 20.0 mm		
Initial Water Content: 36.6 %		
Initial Dry Density: 1336 kg/m ³		
Final Water Content: 38.3 %		





The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057	Phase: 5000
Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK	
Tested By: D.B.	Date: July 12, 2012
Sample: 11-0057-BH2P BH2P-2	

Effective Stress: 200 kPa	Peak Shear Stress: 103 kPa
	Residual Shear Stress: 82 kPa
Sample Data:	Comments:
Sample Length: 60.0 mm	
Initial Height: 20.0 mm	
Initial Water Content: 34.4 %	
Initial Dry Density: 1359 kg/m ³	
Final Water Content: 36.3 %	



The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.

GENERAL TESTING RESULTS

Project #: 11-1362-0057

Phase: 5100

Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK

Tested by: S.E. / J.F. / S.J.B.

Date: August 15, 2013

Sample Identification				Laboratory Test Results									
Borehole #	Sample #	Depth (m)	Sample Type	Water Content (%)	Plastic Limit	Liquid Limit	Plasticity Index	% Passing #200	ASTM Group Index	Specific Gravity	Dry Density (Kg/m ³)	Pocket Penetrometer (kPa)	Lab Vane (kPa)
COS-13-001	001-1	0.61-0.91	AS	27.9									
COS-13-001	001-2	1.22-1.52	AS	37.4									
COS-13-001	001-3	2.44-2.74	AS	37.5									
COS-13-001	001-4	3.66-3.96	AS	34.7									
COS-13-001	001-5	4.27-4.57	AS	36.0									
COS-13-001	001-6	4.88-5.18	AS	33.9	18	56	38			2.63			
COS-13-001	001-7	5.79-6.10	AS	37.6									
COS-13-001	001-8	6.71-7.01	AS	12.1									
COS-13-001	001-9	7.92-8.23	AS	14.8									
COS-13-001	001-10	8.53-8.84	AS	9.7									
COS-13-001B	001B-1	5.18-5.87	TO	35.0									
COS-13-001B	001B-2	5.87-6.55	TO	32.1									
COS-13-001B	001B-3	6.55-7.24	TO	11.0	11	23	12				2057		
COS-13-002	002-1	0.00-0.15	AS	15.3									
COS-13-002	002-2	0.15-0.30	AS	14.0									
COS-13-002	002-3	0.30-0.61	AS	14.2									
COS-13-002	002-4	0.91-1.22	AS	25.9									
COS-13-002	002-5	1.52-1.83	AS	23.1									
COS-13-002	002-6	2.44-2.74	AS	30.1									
COS-13-002	002-7	3.35-3.66	AS	31.3									
COS-13-002	002-8	4.27-4.57	AS	32.2									
COS-13-002	002-9	5.49-5.79	AS	30.7									
COS-13-002	002-10	6.71-7.01	AS	32.1									
COS-13-002	002-11	7.62-7.92	AS	33.0									
COS-13-002	002-12	8.53-8.84	AS	30.2									
COS-13-002	002-13	9.75-10.06	AS	27.8									
COS-13-002	002-14	10.36-10.67	AS	32.5									
COS-13-002	002-15	11.58-11.89	AS	30.8									
COS-13-002	002-16	12.19-12.50	AS	33.7									
COS-13-002	002-17	13.11-13.41	AS	32.7	21	69	48			2.63			
COS-13-002	002-18	14.33-14.63	AS	15.4									
COS-13-002	002-19	16.15-16.46	AS	12.0									
COS-13-003	003-1	0.46-0.61	AS	18.4									
COS-13-003	003-2	0.91-1.22	AS	26.3									
COS-13-003	003-3	2.13-2.44	AS	20.7									
COS-13-003	003-4	3.96-4.27	AS	25.8									

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GENERAL TESTING RESULTS

Project #: 11-1362-0057

Phase: 5100

Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK

Tested by: S.E. / J.F. / S.J.B.

Date: August 15, 2013

Sample Identification				Laboratory Test Results									
Borehole #	Sample #	Depth (m)	Sample Type	Water Content (%)	Plastic Limit	Liquid Limit	Plasticity Index	% Passing #200	ASTM Group Index	Specific Gravity	Dry Density (Kg/m ³)	Pocket Penetrometer (kPa)	Lab Vane (kPa)
COS-13-003	003-5	4.88-5.03	AS	32.3	19	57	38						
COS-13-003	003-6	5.49-5.79	AS	24.0									
COS-13-003	003-7	5.79-6.48	TO	24.2									
COS-13-003	003-8	7.32-7.62	AS	14.5									
COS-13-003	003-9	8.84-9.14	AS	17.7									

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.

GENERAL TESTING RESULTS

Project #: 11-1362-0057

Phase: 5100 / 4000

Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK

Tested by: S.E. / W.C.

Date: September 6, 2013

Sample Identification				Laboratory Test Results									
Borehole #	Sample #	Depth (m)	Sample Type	Water Content (%)	Plastic Limit	Liquid Limit	Plasticity Index	% Passing #200	ASTM Group Index	Specific Gravity	Dry Density (Kg/m ³)	Pocket Penetrometer (kPa)	Lab Vane (kPa)
COS-13-004	004-1	0.00-0.15	AS	11.2									
COS-13-004	004-2	0.30-0.61	AS	32.5									
COS-13-004	004-3	1.22-1.37	DO	33.4									
COS-13-004	004-4	2.59-2.90	DO	33.4									
COS-13-004	004-5	4.42-4.72	DO	33.6	24	74	50						
COS-13-004	004-6	5.18-5.49	AS	31.6									
COS-13-004	004-7	5.79-6.10	TO	30.1						2.61	1699	72	80
COS-13-004	004-8	7.01-7.62	TO	33.7	21	46	25					120	99
COS-13-004	004-9	8.53-9.14	TO	27.2								168	188
COS-13-004	004-10	9.30-9.60	AS	10.2									
COS-13-004	004-11	9.75-10.06	AS	10.8	12	19	7						
COS-13-005	005-1	0.00-0.30	AS	8.9									
COS-13-005	005-2	1.07-1.22	DO	8.2									
COS-13-005	005-3	2.59-2.74	DO	7.5									
COS-13-005	005-4	4.11-4.27	DO	11.5	15	35	20						
COS-13-005	005-5	5.33-5.94	TO	23.2	20	49	29					180	91
COS-13-005	005-6	6.10-6.71	TO	8.4								>200	203
COS-13-005	005-7	6.86-7.47	TO	8.0									
COS-13-005	005-8	7.62-8.23	TO	29.5	22	38	16						
COS-13-005	005-9	8.38-8.99	TO	23.9						2.59	1306		
COS-13-005	005-10	9.14-9.75	TO	28.2	25	32	7						
COS-13-005	005-11	9.91-10.52	TO	33.0									
COS-13-005	005-12	10.67-11.28	TO	28.7	21	33	12						
COS-13-005	005-13	11.43-12.04	TO	29.3	19	34	15						
COS-13-005	005-14	12.19-12.34	TO	29.4	14	40	26						
COS-13-005	005-15	13.72-14.02	DO	9.0									
COS-13-006	006-1	0.15-0.30	AS	17.2									
COS-13-006	006-2	1.07-1.22	AS	28.7									
COS-13-006	006-3	1.83-1.98	AS	25.3	22	65	43						
COS-13-006	006-4	2.29-2.44	AS	24.6									
COS-13-006	006-5	2.90-3.05	AS	30.6									
COS-13-006	006-6	4.72-4.88	AS	29.6									
COS-13-006	006-7	5.33-5.49	AS	29.1									
COS-13-006	006-8	6.25-6.40	AS	34.0	23	72	49						
COS-13-006	006-9	7.62-7.77	AS	33.8									
COS-13-006	006-10	8.69-8.84	AS	29.5	13	41	28						

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GENERAL TESTING RESULTS

Project #: 11-1362-0057

Phase: 5100 / 4000

Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK

Tested by: S.E. / W.C.

Date: September 6, 2013

Sample Identification				Laboratory Test Results									
Borehole #	Sample #	Depth (m)	Sample Type	Water Content (%)	Plastic Limit	Liquid Limit	Plasticity Index	% Passing #200	ASTM Group Index	Specific Gravity	Dry Density (Kg/m ³)	Pocket Penetrometer (kPa)	Lab Vane (kPa)
COS-13-006	006-11	10.06-10.21	AS	34.8									
COS-13-006	006-12	11.58-11.73	AS	13.0									
COS-13-006	006-13	12.19-12.34	AS	11.8									
COS-13-006	006-14	13.11-13.26	AS	10.3									

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, :
 Tested by: S.H. / S.B.
 Borehole #: COS-13-001 Sample #: 001-6
 Source:
 Date Sample Received: July 29, 2013

Phase: 5100
 Date: August 9, 2013

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	99
0.425	99
0.250	98
0.150	98
0.075	97
0.029	96
0.021	92
0.015	84
0.011	76
0.008	68
0.006	63
0.004	55
0.003	52
0.002	46
0.001	41

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, :
 Tested by: S.H. / S.B.
 Borehole #: COS-13-001 Sample #: 001-9
 Source:
 Date Sample Received: July 29, 2013

Phase: 5100
 Date: August 9, 2013

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	99
2.00	98
0.850	96
0.425	91
0.250	85
0.150	70
0.075	49
0.043	31
0.031	27
0.023	22
0.015	20
0.012	18
0.008	16
0.006	13
0.004	10
0.003	9.3
0.002	8.5
0.001	7.1

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, :
 Tested by: S.J.B. / S.B.
 Borehole #: CP-13-001B Sample #: 001B-3
 Source:
 Date Sample Received: July 29, 2013

Phase: 5100
 Date: August 10, 2013

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	98
2.00	94
0.850	90
0.425	84
0.250	75
0.150	65
0.075	54
0.041	48
0.030	43
0.022	39
0.016	35
0.011	31
0.008	28
0.006	25
0.004	22
0.003	21
0.002	18
0.001	15

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, :
 Tested by: S.J.B. / S.B.
 Borehole #: COS-13-002 Sample #: 002-13
 Source:
 Date Sample Received: July 29, 2013

Phase: 5100
 Date: August 10, 2013

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	100
0.425	100
0.250	100
0.150	100
0.075	82
0.044	52
0.032	38
0.023	32
0.017	28
0.012	27
0.009	24
0.006	22
0.004	20
0.003	19
0.002	17
0.001	14

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422

(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.E.
 Borehole #: COS-13-004 Sample #: 004-11
 Source:
 Date Sample Received: September 3, 2013

Phase: 5100 / 4000
 Date: September 16, 2013

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	98
4.75	97
2.00	95
0.850	90
0.425	84
0.250	74
0.150	61
0.075	48
0.048	27
0.034	26
0.024	25
0.017	24
0.013	23
0.009	21
0.006	19
0.005	16
0.003	13
0.002	12
0.001	9.5

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422

(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.E.
 Borehole #: COS-13-004 Sample #: 004-2
 Source:
 Date Sample Received: September 3, 2013

Phase: 5100 / 4000
 Date: September 16, 2013

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	100
0.425	100
0.250	99
0.150	99
0.075	99
0.042	70
0.030	62
0.022	56
0.016	51
0.012	46
0.008	42
0.006	38
0.004	36
0.003	33
0.002	31
0.001	25

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.E.
 Borehole #: COS-13-005 Sample #: 005-1
 Source:
 Date Sample Received: September 3, 2013

Phase: 5100 / 4000
 Date: September 16, 2013

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	100
0.425	100
0.250	100
0.150	67
0.075	34
0.050	18
0.036	17
0.025	16
0.018	15
0.013	15
0.009	14
0.007	14
0.005	13
0.003	12
0.002	11
0.001	10

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.E.
 Borehole #: COS-13-005 Sample #: 005-10
 Source:
 Date Sample Received: September 3, 2013

Phase: 5100 / 4000
 Date: September 16, 2013

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	100
0.425	97
0.250	97
0.150	97
0.075	86
0.048	38
0.035	34
0.025	33
0.018	29
0.013	27
0.009	24
0.007	23
0.005	21
0.003	19
0.002	18
0.001	15

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.E.
 Borehole #: COS-13-005 Sample #: 005-11
 Source:
 Date Sample Received: September 3, 2013

Phase: 5100 / 4000
 Date: September 16, 2013

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	100
0.425	100
0.250	100
0.150	100
0.075	88
0.045	43
0.032	35
0.023	29
0.017	26
0.012	24
0.009	23
0.006	21
0.004	19
0.003	16
0.002	15
0.001	12

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.E.
 Borehole #: COS-13-005 Sample #: 005-12
 Source:
 Date Sample Received: September 3, 2013

Phase: 5100 / 4000
 Date: September 16, 2013

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	100
0.425	100
0.250	100
0.150	99
0.075	93
0.041	56
0.030	46
0.022	36
0.016	32
0.012	29
0.009	27
0.006	25
0.004	23
0.003	20
0.002	19
0.001	17

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.E.
 Borehole #: COS-13-005 Sample #: 005-8
 Source:
 Date Sample Received: September 3, 2013

Phase: 5100 / 4000
 Date: September 16, 2013

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	100
0.425	100
0.250	100
0.150	100
0.075	99
0.041	78
0.031	63
0.023	52
0.017	44
0.012	39
0.009	37
0.006	34
0.005	29
0.003	28
0.002	25
0.001	20

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.E.
 Borehole #: COS-13-006 Sample #: 006-10
 Source:
 Date Sample Received: September 3, 2013

Phase: 5100 / 4000
 Date: September 16, 2013

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	100
2.00	100
0.850	100
0.425	100
0.250	100
0.150	100
0.075	99
0.037	98
0.027	93
0.020	80
0.015	68
0.012	58
0.009	49
0.006	44
0.004	40
0.003	36
0.002	33
0.001	29

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



GRAIN SIZE ANALYSIS - ASTM D422
(Mechanical & Hydrometer)


Project #: 11-1362-0057
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested by: S.E.
 Borehole #: COS-13-006 Sample #: 006-13
 Source:
 Date Sample Received: September 3, 2013

Phase: 5100 / 4000
 Date: September 16, 2013

Grain Size Analysis Results:

Opening (mm)	Percent Passing (%)
152	100
76	100
38	100
19	100
9.5	100
4.75	98
2.00	95
0.850	90
0.425	83
0.250	68
0.150	52
0.075	41
0.047	36
0.034	32
0.025	28
0.018	23
0.013	20
0.009	17
0.007	14
0.005	12
0.003	11
0.002	9.6
0.001	7.4

Graphical Analysis



BOULDERS	COBBLES	GRAVEL		SAND			SILT / CLAY
		Coarse	Fine	Coarse	Medium	Fine	

Comments:

The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.





CONSOLIDATED DRAINED DIRECT SHEAR TEST-SUMMARY

Project #: 11-1362-0057 Phase: 5100
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation Saskatoon, SK
 Tested By: B.Y. / D.B. Date: August 29, 2013

Sample	Normal Stress		
	(kPa)	Peak (kPa)	Residual (kPa)
COS-13-001B 001B-1	50	35	30
	100	65	44
	200	111	75

	Peak	Residual
Friction angle (degrees):	26.6	21.7
cohesion (kPa):	12	0



Comments:



The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057	Phase: 5100
Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation Saskatoon, SK	
Tested By: B.Y. / D.B.	Date: August 29, 2013
Sample: COS-13-001B 001B-1 (REDO#2)	

Effective Stress: 50 kPa	Peak Shear Stress: 35 kPa
	Residual Shear Stress: 30 kPa
Sample Data:	Comments:
Sample Length: 60.0 mm	
Initial Height: 20.0 mm	
Initial Water Content: 35.4 %	
Initial Dry Density: 1319 kg/m ³	
Final Water Content: 42.6 %	





The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057 Phase: 5100
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation Saskatoon, SK
 Tested By: B.Y. / D.B. Date: August 29, 2013
 Sample: COS-13-001B 001B-1

Effective Stress:	100	kPa	Peak Shear Stress:	65	kPa
			Residual Shear Stress	44	kPa
Sample Data:			Comments:		
Sample Length:	60.0	mm			
Initial Height:	20.0	mm			
Initial Water Content:	35.0	%			
Initial Dry Density:	1349	kg/m ³			
Final Water Content:	40.5	%			





The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057 Phase: 5100
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation Saskatoon, SK
 Tested By: B.Y. / D.B. Date: August 29, 2013
 Sample: COS-13-001B 001B-1

Effective Stress:	200	kPa	Peak Shear Stress:	111	kPa
			Residual Shear Stress	75	kPa
Sample Data:			Comments:		
Sample Length:	60.0	mm			
Initial Height:	20.0	mm			
Initial Water Content:	36.4	%			
Initial Dry Density:	1337	kg/m ³			
Final Water Content:	35.0	%			





The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.

CONSOLIDATED DRAINED DIRECT SHEAR TEST-SUMMARY

Project #: 11-1362-0057	Phase: 5100 / 4000
Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK	
Tested By: B.Y. / D.B.	Date: November 10, 2013

Sample	Normal Stress		Shear Stress	
	(kPa)	(kPa)	Peak (kPa)	Residual (kPa)
COS-13-004 004-8 7.01-7.62 m depth	75	47	13	
	125	70	27	
	200	80	40	

Friction angle (degrees):	Peak 14.2	Residual 11.4
cohesion (kPa):	32	0



Comments:



The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057	Phase: 5100 / 4000
Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK	
Tested By: B.Y. / D.B.	Date: November 10, 2013
Sample: COS-13-004 004-8 7.01-7.62 m depth	

Effective Stress: 75 kPa	Peak Shear Stress: 47 kPa	Residual Shear Stress: 13 kPa
Sample Data:	Comments:	
Sample Length: 60.0 mm		
Initial Height: 20.0 mm		
Initial Water Content: 36.8 %		
Initial Dry Density: 1329 kg/m ³		
Final Water Content: 43.6 %		





The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057	Phase: 5100 / 4000
Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK	
Tested By: B.Y. / D.B.	Date: November 10, 2013
Sample: COS-13-004 004-8 7.01-7.62 m depth	

Effective Stress: 125 kPa	Peak Shear Stress: 70 kPa
	Residual Shear Stress: 27 kPa
Sample Data:	Comments:
Sample Length: 60.0 mm	
Initial Height: 20.0 mm	
Initial Water Content: 35.0 %	
Initial Dry Density: 1368 kg/m ³	
Final Water Content: 38.6 %	





The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057 Phase: 5100 / 4000
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested By: B.Y. / D.B. Date: November 10, 2013
 Sample: COS-13-004 004-8 7.01-7.62 m depth

Effective Stress:	200	kPa	Peak Shear Stress:	80	kPa
			Residual Shear Stress	40	kPa
Sample Data:			Comments:		
Sample Length:	60.0	mm			
Initial Height:	20.0	mm			
Initial Water Content:	36.8	%			
Initial Dry Density:	1356	kg/m ³			
Final Water Content:	39.0	%			



The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.





CONSOLIDATED DRAINED DIRECT SHEAR TEST-SUMMARY

Project #: 11-1362-0057	Phase: 5100 / 4000
Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK	
Tested By: B.Y. / D.B.	Date: October 22, 2013

Sample	Normal Stress (kPa)	Shear Stress Peak (kPa)	Shear Stress Residual (kPa)
COS-13-005 005-13 11.43-12.04 m depth	50	41	31
	100	77	68
	200	126	118

	Peak	Residual
Friction angle (degrees):	31.3	31.3
cohesion (kPa):	9	0



Comments:



The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057 Phase: 5100 / 4000
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested By: B.Y. / D.B. Date: October 22, 2013
 Sample: COS-13-005 005-13 11.43-12.04 m depth

Effective Stress:	50	kPa	Peak Shear Stress:	41	kPa
			Residual Shear Stress	31	kPa
Sample Data:			Comments:		
Sample Length:	60.0	mm			
Initial Height:	20.0	mm			
Initial Water Content:	26.2	%			
Initial Dry Density:	1512	kg/m ³			
Final Water Content:	30.9	%			





The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057 Phase: 5100 / 4000
 Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK
 Tested By: B.Y. / D.B. Date: October 22, 2013
 Sample: COS-13-005 005-13 11.43-12.04 m depth

Effective Stress:	100	kPa	Peak Shear Stress:	77	kPa
			Residual Shear Stress	68	kPa
Sample Data:			Comments:		
Sample Length:	60.0	mm			
Initial Height:	20.0	mm			
Initial Water Content:	27.2	%			
Initial Dry Density:	1507	kg/m ³			
Final Water Content:	30.2	%			





The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



CONSOLIDATED DRAINED DIRECT SHEAR TEST

Project #: 11-1362-0057	Phase: 5100 / 4000
Short Title: COS East Riverbank / Cherry Lane - Geotech Investigation / Saskatoon, SK	
Tested By: B.Y. / D.B.	Date: October 22, 2013
Sample: COS-13-005 005-13 11.43-12.04 m depth	

Effective Stress: 200 kPa	Peak Shear Stress: 126 kPa	Residual Shear Stress: 118 kPa
Sample Data:	Comments:	
Sample Length: 60.0 mm		
Initial Height: 20.0 mm		
Initial Water Content: 26.4 %		
Initial Dry Density: 1507 kg/m ³		
Final Water Content: 28.5 %		



The testing services reported herein have been performed in accordance with the indicated recognized standard, or in accordance with local industry practice. This report is for the sole use of the designated client. This report constitutes a testing service only and does not represent any results interpretation or opinion regarding specification compliance or material suitability. Engineering interpretation can be provided by Golder Associates Ltd. upon request.



APPENDIX H

Cost Estimates for Conceptual Remediation Options

Conceptual Option	Description	Estimated Cost	Engineering (5-10%)	Monitoring (5%)	Contingency (50%)	Estimated Total Cost	Estimate Assumption (Average Dimensions)	Estimate Basis
1	Do Nothing							
2A	Dewatering - 11th St	\$ 1,760,000	\$ 180,000	\$ 90,000	\$ 880,000	\$ 2,910,000	150 m long x 10 m deep	COS 17th Street (2013) ~\$325K for drainage trench and street repairs, 80 m long x 4 m deep
2B	Dewatering - Cherry Lane	\$ 880,000	\$ 90,000	\$ 50,000	\$ 440,000	\$ 1,460,000	150 m long x 5 m deep	COS 17th Street (2013) ~\$325K for drainage trench and street repairs, 80 m long x 4 m deep
3	Slope Re-grading w/ drainage	\$ 4,000,000	\$ 200,000	\$ 200,000	\$ 2,000,000	\$ 6,400,000	135 m long x 40 m ²	COS 17th Street (2013) ~\$880K for selective site demolition, 2 drainage trenches, landscaping, excavation, 80 m long x 4 m deep x 15 m wide. Does not include purchase or demolition of residential property
4A	Shear Zone Modification - CSM w/ drainage	\$ 5,810,000	\$ 300,000	\$ 300,000	\$ 2,905,000	\$ 9,315,000	10 m long x 6 m deep x 4 m wide; 50 m long x 5 m deep x 13 m wide; 60 m long x 7 m deep x 4 m wide	CSM Slurry Wall ~\$250/m ² or \$2.5M/km (0.9 m wide trench), assume cement cost is 1.8:1 for bentonite, not including platform construction. COS 17th Street (2013) ~\$580K selective site demo, drainage systems and landscaping.
4B	Shear Zone Modification - Shear Key w/drainage	\$ 6,520,000	\$ 330,000	\$ 330,000	\$ 3,260,000	\$ 10,440,000	10 m long x 6 m deep x 4 m wide; 50 m long x 5 m deep x 13 m wide; 60 m long x 7 m deep x 4 m wide	Cosmo Park (2009) ~\$2M for shear key construction, 150 m long x 5 m deep x 6 m wide, assume 7% inflation. COS 17th Street (2013) ~\$500K for 2 drainage systems. Assume \$1.35M for temporary shoring

As a global, employee-owned organisation with over 50 years of experience, Golder Associates is driven by our purpose to engineer earth's development while preserving earth's integrity. We deliver solutions that help our clients achieve their sustainable development goals by providing a wide range of independent consulting, design and construction services in our specialist areas of earth, environment and energy.

For more information, visit golder.com

Africa	+ 27 11 254 4800
Asia	+ 86 21 6258 5522
Australasia	+ 61 3 8862 3500
Europe	+ 356 21 42 30 20
North America	+ 1 800 275 3281
South America	+ 56 2 2616 2000

solutions@golder.com
www.golder.com

Golder Associates Ltd.
1721 8th Street East
Saskatoon, Saskatchewan, Canada S7H 0T4
Canada
T: +1 (306) 665 7989

