

SECTION 'A-A'

NOTES:

1. USE ROUND TOP IN PARKING LOTS, LANES OR DRIVEWAYS

MATERIAL SPECIFICATIONS:

(ALL SPECIFICATIONS & STANDARDS REFER TO LATEST EDITION)

- CEMENT: SULPHATE RESISTANT TYPE: TYPE HS (TYPE 50) TO CSA A3001 OR TYPE V TO ASTM C150 CONCRETE COMPRESSIVE STRENGTH: 30 MPa AT 28 DAYS
- AIR CONTENT: 4 TO 7% EXCEPT WHERE NO-SLUMP CONCRETE IS USED
- CONCRETE CLEAR COVER: 30mm MIN
- REINFORCING STEEL: DEFORMED BARS TO CSA G30.18, fy = 400 MPa REINFORCING STEEL TO BE SLANTED WHERE NECESSARY TO ACCOMMODATE SLAB THICKNESS

L	PLAN DESCRIPTION/REVISION	DATE	BY	6:4	APPROVALS
1	ORIGINAL STANDARD DRAWING	2020-JAN-30	DLH	Saskatoon	SIGNATURE SIGNATURE
				CATCH BASIN PRECAST SLAB TOP TYPE K-3	NAME FOR ZOZO FEB 2 0 2020 DATE SIGNED SCALES: HOR. N.T.S. VERT. N.T.S. PLAN NO. 102-0010-028r001