

BUILDING & DEVELOPMENT PERMIT APPLICATION EXTERIOR INSULATION AND FINISH SYSTEM (EIFS) REQUEST

Project Address:			
Builder Name:		Builder Address:	
SYSTEM DESIGN	New Construction □ Retrofit □ Manufacturer	Is the supporting wall thermally insulated? Yes □ No □ R or RSI value	NO
	Manufacturer's system name Does the EIFS system comply with CAN/ULC-S716 1, 2 & 3? Yes No CCMC Listing or Report #	Substrate Material : Glass matt gypsum Plywood OSB Other Thickness	CONSTRUCTION
LOCATION	Walls to have EFIS applied North	Insulation board R or RSI value per inch Thickness of EIFS insulation board Does the EIFS panel have a drainage cavity at least 10mm (3/8 in) deep and an open area not less than 13% of the panel? Yes	SYSTEM COMPONENTS
NOTES	It is the responsibility of the contractor to incorporate all accessories and follow the methods specified by the manufacturer and Subsection 9.27.14 of the 2020 NBC. This includes, but is not limited to: water protection barrier (WPB), clearances from heat emitting devices, and placement of expansion joints, reinforcing mesh, closed cell backer rods, flashings, and wall cavity water drainage. * EIFS that do not comply to CAN/ULC-S716.1, 2 & 3, do not have a drainage cavity, do not have a substrate of the minimum tested thickness, or are mechanically fastened are required to be designed and sealed by a design professional liscenced to consult in Saskatchewan.		

Updated: December 2023 Page 1 of 1